



MOLD KILLING PRIMER

Kills Existing Mold, Mildew, and Odor Causing Bacteria

Paint directly over existing mold, mildew, odor causing bacteria and any other fungal organisms*

**KEEP OUT OF REACH OF CHILDREN
DANGER**

Binds chalky siding, masonry, & metal

Great for use under wallcovering

FIRST AID	
IF IN EYES:	• Hold eye open and rinse slowly and gently with water for 15-20 minutes. • Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. • Call poison control center or doctor for treatment advice.
IF INHALED:	• Move person to fresh air. • If person is not breathing, call 911 or an ambulance, and then give artificial respiration, preferably mouth-to-mouth, if possible. • Call a poison control center or doctor for further treatment advice.
IF ON SKIN:	• Take off contaminated clothing. • Rinse skin immediately with plenty of water for 15-20 minutes. • Call a poison control center or doctor for treatment advice.
IF SWALLOWED:	• Call a poison control center or doctor immediately for treatment advice. • Have person sip a glass of water if able to swallow. • Do not induce vomiting unless told to do so by a poison control center or doctor. • Do not give anything by mouth to an unconscious person.

Active Ingredients:
3-iodo-2-propynylbutylcarbamate 0.0063%
Inert Ingredients 99.9937%
TOTAL 100.0000%
This contains 63 ppm of 3-iodo-2-propynylbutylcarbamate per gallon.
EPA Reg. No. 87469-1-69587 E PA Est. No. 69587-NJ-002

**Fungicidal
Protective Coating**

BEFORE

AFTER

**INTERIOR/EXTERIOR
DANGER:** Read carefully other cautions on back panel

Water-Base • White

ONE GALLON (3.78 L)

ZINSSER® Mold Killing Primer is a water-based fungicidal protective coating that can be used to paint over and kill all existing mold, mildew, moss, fungi, odor causing bacteria and any other fungal organisms*. The Mold Killing Primer contains an EPA registered antimicrobial to prevent the growth of mold, mildew and other fungal organisms on the paint film. The Mold Killing Primer also aides in covering residual microbiological and fungal stains. See Product Data and Material Safety Data Sheets before application at www.rustoleum.com, www.zinsser.com.

The Mold Killing Primer is for use on non-porous interior and exterior, residential, commercial, and industrial applications and can be applied in factories, warehouses, storage facilities, refrigerated storage facilities, office buildings, residential living, schools, hospitals, veterinary care facilities, elderly care facilities, prisons and correction facilities, wash houses, restaurants, fitness centers and locker rooms, attics, basements, window frames, bathrooms, wall cavities, base-boards, sub-floors and table tops. Mold Killing Primer can be used with any topcoat.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Check with all local, state and federal regulations prior to using or working or using this product. Fix the source of any moisture problems prior to remediation. Do not attempt to salvage damaged or structurally unsound building materials. Consult a qualified professional to perform a thorough inspection and supply work specifications appropriate to the project.

Surface Preparation & Application: *For applications that have existing wet, slimy, heavy soiled, gross filth, overgrowth or loose material on the substrate a pre-cleaning step is required. Physically or mechanically remove gross filth, heavy soil, overgrowth or loose material before application and ensure the substrate is free of slime or excessive moisture to ensure long-term adhesion and product performance. If mold or mildew needs to be removed prior to application remove with a mildew remover that is EPA registered and let dry. Eye, skin and NOISH approved respiratory protection is highly recommended. Patch surface irregularities with appropriate patching compounds.

The Mold Killing Primer is a ready to use product, do not thin, do not dilute and do not mix with water or other chemicals or other paints. Mix thoroughly. Do not apply when air or surface temperature is below 50°F (10°C) or when drying conditions are poor. Use adequate ventilation during application.

Use a brush, roller, or airless sprayer to apply. (Follow spray equipment manufacturer's instructions; for airless spraying use 0.17 tip at 2000 – 2500 P.S.I.) Coverage dependant on substrate porosity and surface smoothness.

Dry to the touch in 30 minutes; can be recoated in 1 hour. Full adhesion and hardness develops in 7 days.

Mold, Mildew, Fungi, Moss and Odor Causing Bacteria Control: The Mold Killing Primer will kill all existing mold, mildew and fungal organisms. Apply the Mold Killing Primer generously and uniformly, ensuring that the surface is completely coated. Allow to air dry.

COVERAGE: 400 – 450 sq ft per gallon. Coverage rates may vary depending on the surface smoothness.

Limitations: Not for application to floors or decks or to surfaces subject to immersion or prolonged contact with water.

KEEP PRODUCT FROM FREEZING

CLEANUP: Clean all tools and drippings with warm soapy water before coating dries.

Health & Safety: If spilled, contain spilled material and remove with inert absorbent.

Dispose of absorbent, container and unused product in accordance with all current Federal, state and local regulations.

The information and data contained herein are correct to the best of our knowledge and tests. We recommend that adequate tests be made by the purchaser to determine if a product is suitable for the intended purpose of use.

Lead Paint:

CAUTIONS:

MAY CONTAIN CRYSTALLINE SILICA. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use any other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear NOISH approved respiratory protection and/or leave area. Adequate ventilation is required when sanding or abrading the dry film. If adequate ventilation cannot be provided wear a NOISH approved particulate respirator. Follow respirator manufacturer's instructions for use. Do not transfer contents to other containers for storage.

ATTENTION: Before sanding, scraping or otherwise distributing old paint (pre-1978 housing) contact the U.S. EPA/Lead Hotline (800-424-LEAD 800-424-LEAD) for LEAD HAZARD information published in their "Protect Your Family From Lead In Your Home" Brochure and the Lead Pre-Renovation Education Rule. Lead exposure can cause serious health problems, especially in children and pregnant women. Visit www.epa.gov/lead.

Shelf Life: 1 year. STORE ABOVE 50°F; KEEP FROM FREEZING.

EPA Reg. No. 87469-1-69587 EPA Est. No. 69587-NJ-002
Less than 100 grams/ Liter V.O.C.

Distributed by
RUST-OLEUM®
CORPORATION
11 Hawthorn Pkwy., Vernon Hills, IL 60061

© 2013 Rust-Oleum Corporation Made in USA 774 277491 0813

An **RPM** Company

zinsser.com

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage and disposal.

Pesticide Storage: Store in original, tightly closed containers below 30°C (86°F) and above 0°C (32°F) in a secure area inaccessible to children and away from food or feed.

Pesticide Disposal: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

For Residential Use

Container Handling: Nonrefillable container. Do not reuse or refill this container. Securely wrap original container in several layers of newspaper and discard in trash or offer for recycling if available.

Nonresidential Use (Containers larger than 5 gallons)

Container Disposal: Nonrefillable container. Do not reuse or refill this container. Triple rinse or pressure rinse container (or equivalent) promptly after emptying. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Dispose of rinsate as pesticide waste. Repeat this procedure two more times. Then offer for recycling if available or puncture and dispose of in a sanitary landfill, or by incineration.

In case of emergency call 800-535-5053. Have the product container/label with you when calling Poison Control Center, doctor or going for treatment.

PRECAUTIONARY STATEMENTS

HAZARDOUS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes irreversible eye damage. Do not get in eyes or on clothing. Wear protective goggles or face shield. Harmful if swallowed, absorbed through the skin or inhaled. Avoid breathing spray mist. Wash hands thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. Remove contaminated clothing and wash clothes before reuse. When applying with a sprayer, wear a dust/mist filtering respirator (MSHA/NIOSH approved number prefix TC-21C) or a NIOSH approved respirator with any R,P,N, or HE filter.

USER SAFETY REQUIREMENTS

Users must wash hands before eating, drinking, chewing gum, using tobacco or using the toilet. Users must remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users must remove personal protective equipment immediately after handling this product. Wash outside of gloves before removing. As soon as possible wash thoroughly.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other water unless in accord with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

LIMITED WARRANTY: This product will perform as claimed if applied according to our directions. The directions apply to most applications, but may not cover special conditions, applications, techniques and/or surfaces. If you have questions, check with your dealer or contact Rust-Oleum Corporation, Vernon Hills IL. Warranty is limited to replacement or refunded value of product actually used if such product proves defective within two years of manufacture. No other warranty is expressed or implied.

276049 MOLD KILLING PRIMER

