



**ZINSSER® ROLL-A-TEX  
SAND TEXTURE ADDITIVE**

**DESCRIPTION AND USES**

Zinsser® Roll-A-Tex Sand Texture Additive is an extremely fine mineral compound that when added to paint will cover small cracks, hide tape joints, and will create a sand finish texture.

**PERFORMANCE CHARACTERISTICS**

- Create a sand finish texture to walls and ceilings
- Excellent for hiding cracks and tape joints
- Covers small cracks and hides patched surfaces
- Gives a fresh look to old plaster
- Works in all paints and varnishes
- Provides a durable, washable, texture coating

**PRODUCTS**

SKU	DESCRIPTION
22616	1-Pound Package
57068	8-Pound Package

**PRODUCT APPLICATION**

**INSTRUCTIONS FOR USE**

Apply only when air, material, and surface temperatures are between 50-90°F (10-32°C) and the relative humidity is below 85%. In a clean, separate container, add 4 ounces of Roll-A-Tex Additive to one quart of paint. More or less may be added for a rougher or finer surface. Mix thoroughly using a slotted paint paddle or mechanical agitator to ensure the additive is incorporated. Let the mixture sit for at least 30 minutes before applying. Stir occasionally to ensure good distribution of the mix. Use a 3/8" to 3/4" nap roller cover and follow the paint manufacturer's directions for application.

**CLEAN-UP**

Follow paint manufacturer's directions for clean up and disposal.

**PHYSICAL PROPERTIES**

		ROLL-A-TEX SAND TEXTURE ADDITIVE
<b>Composition</b>		Pumice, Crystalline Silica
<b>Weight</b>	<b>Per Gallon</b>	20.3 lbs.
<b>Solids</b>	<b>By Weight</b>	100%
	<b>By Volume</b>	100%
<b>Volatile Organic Compounds</b>		0 g/l
<b>Practical Coverage</b>		Will depend on the method of application and surface type
<b>Shelf Life</b>		5 years
<b>Flash Point</b>		>200°F (93°C)
<b>Safety Information</b>		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.