



**PAINTER'S TOUCH®  
2X ULTRA COVER® SATIN SPRAYS**

**DESCRIPTION AND USES**

Rust-Oleum® Painter's Touch® 2X Ultra Cover® Satin Sprays contain technology that provides twice the coverage on wood, metal, most plastic, wicker and more when compared to other matching colors of Rust-Oleum general purpose paints: Painter's Touch, SPRAY N GO, Quick Color and Touch 'n tone. It covers surfaces with less spray passes, allowing projects to be completed faster and easier. Any angle spray feature allows you to spray in any direction, even upside down. Fast Drying.

**TIP:** Some plastics made of polyethylene such as plastic storage containers are manufactured in a way that may hinder maximum paint adhesion. Test paint in a hidden area first.

**PRODUCTS**

SKU	DESCRIPTION (Aerosol)
334080	Satin Wildflower Blue
249063	Satin Sweet Pea
334079	Satin Summer Squash
249065	Satin Strawflower
249066	Satin Slate Blue
249068	Satin Paprika
334077	Satin Oregano
334076	Satin Nutmeg
334075	Satin Moss Green
249072	Satin Leafy Green
334073	Satin Ivory Silk
334072	Satin Hunt Club Green
334071	Satin Heirloom White
334070	Satin Green Apple
334069	Satin Granite
334068	Satin French Lilac
334067	Satin Fossil
334066	Satin Espresso
334063	Satin Colonial Red
334062	Satin Claret Wine
334061	Satin Cinnamon
334059	Satin Aqua
346950	Satin Blossom White
346951	Satin Canyon Black
334091	Satin Midnight Blue
334086	Satin Stone Gray
346953	Satin London Gray
334065	Satin Eden
257419	Satin Aubergine
334074	Satin Lagoon

**PRODUCTS (cont.)**

SKU	DESCRIPTION (Aerosol)
334064	Satin Dark Walnut
334081	Satin Lemon Grass
334058	Satin Aluminum
263149	Satin Fire Orange
334083	Satin Warm Carmel
334085	Satin Oasis Blue
334084	Satin Poppy Red
334087	Satin Magenta
334092	Satin Smokey Beige
299887	Satin Vintage Blush
334088	Satin French Blue
334089	Satin Rustic Orange
334093	Satin Ink Blue
334095	Satin Seaside
334094	Satin Apple Red
334090	Satin Vintage Teal
329201	Satin Silver Lilac
350373	Satin Charcoal Gray
350372	Satin Deep Forest
366993	Satin Harvest Peach
383200	Satin Seaweed
383201	Satin Eucalyptus
383202	Satin Iris
389904	Satin Fuzzy Peach
389905	Satin Tulip Fields
389906	Satin Sweet Mano

**PRODUCT APPLICATION**

**SURFACE PREPARATION**

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Previously coated surfaces must be sound and in good condition. Smooth, hard, or glossy finishes should be scarified by sanding to create a surface profile.

**WARNING!** If you scrape, sand or remove old paint from any surface, you may release lead paint dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).



# PAINTER'S TOUCH®

## 2X ULTRA COVER® SATIN SPRAYS

### PRODUCT APPLICATION (cont.)

#### PRIMING

Use of Painter's Touch 2X Ultra Cover primer provides superior adhesion and hiding and is especially recommended for bare wood and metal. The following primers are recommended:

249058	White Primer
249086	Red Primer
249088	Gray Primer
249846	Flat Black Primer

#### APPLICATION

Use outdoors or in a well ventilated area such as an open garage. Use when temperature is between 50-90°F (10-32°C) and humidity is below 65% to ensure proper drying. Do not use on objects that may exceed 200°F (93°C) surface temperature. Do not apply to galvanized steel. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

Shake can vigorously for one minute after mixing ball begins to rattle. If mixing ball fails to rattle, DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold can upright 10-16" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply 2 or more light coats a few minutes apart to avoid drips and runs. **Do not use near open flame.**

#### DRY & RECOAT

Dry and recoat times are based on 70°F and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 20 minutes, to handle in 1 hour, and is fully dry in 24 hours. Apply a second coat or clear coat within 1 hour or after 48 hours. Apply clear in 2-3 light coats a few minutes apart.

**NOTE:** On plastic maximum paint adhesion and durability is achieved in 5-7 days.

#### CLEAN-UP

When finished spraying, wipe off tip before storing. Clean up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

#### CLOGGING

If valve clogs, twist and pull off spray tip and rinse it in a solvent such as mineral spirits. Do not stick pin or other object into the stem.

	<b>TECHNICAL DATA</b>	<b>PT2X-02</b>
	<b>PAINTER'S TOUCH®</b> <b>2X ULTRA COVER® SATIN SPRAYS</b>	

**PHYSICAL PROPERTIES**

		2X ULTRA COVER SATIN SPRAYS
<b>Resin Type</b>		Acrylic Modified Alkyd, Alkyd
<b>Pigment Type</b>		Varies with color
<b>Solvents</b>		Acetone, n-Butyl Acetate, Naptha, Xylene
<b>MIR</b>		Max 0.95
<b>Fill Weight</b>		12 oz.
<b>Recommended Dry Film Thickness (DFT) per Coat</b>		1.0-2.0 mils (25-50μ)
<b>Practical Coverage at Recommended DFT (assume 15% material loss)</b>		8-12 sq. ft./can (0.74-1.11 m <sup>2</sup> /can)
<b>Dry Times at 70°F (21°C) and 50% Relative Humidity</b>	<b>Touch</b>	20 minutes
	<b>Handle</b>	1 hour
	<b>Recoat</b>	Within 1 hour or after 48 hours
<b>Dry Heat Resistance</b>		200°F (93°C)
<b>Shelf Life</b>		5 years
<b>Flash Point</b>		-156°F (-104°C)
<b>Safety Information</b>		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.