



# ROCKSOLID® COMPOSITE DECK REFRESH

## DESCRIPTION AND USES

RockSolid® Composite Deck Refresh is an exceptional water-base exterior stain and sealer designed to refresh the color and restore the finish on faded composite wood decks. It provides protection against water damage, UV graying and mildew. It is easy to use, dries fast and cleans up quickly with water.

Use on wood capped composite decks. Follow specific manufacturer's recommendation before applying to any composite decking. Not recommended for plastic capped composite decks. Be sure to choose the tone that best matches the original composite deck color. (Deck Refresh is not recommended for color changes). Final color will be dependent on age, type and condition of the deck.

## PRODUCT FEATURES

- One coat application
- Protects against UV damage
- Resists mold & mildew growth
- Provides superior water repellency with NeverWet® properties
- Covers up to 300 square feet
- 3 Year Performance Guarantee

## PRODUCTS

SKU	DESCRIPTION
350007	Gray Tone
350058	Cedar Tone
350059	Redwood Tone
350060	Brown Tone

## PRODUCT APPLICATION

### SURFACE PREPARATION

Failure to follow this preparation method may result in poor adhesion and possible coating failure. If the composite deck has previously applied coatings such as paint, stain or sealer remove/strip prior to starting. Check the composite deck for loose or extremely damaged boards and make necessary repairs prior to starting the project.

**WARNING!** If you scrape, sand or remove old paint from any surface, you may release lead paint dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## PRODUCT APPLICATION (cont.)

### SURFACE PREPARATION (cont.)

Clean the composite deck surface with RockSolid Composite Deck Cleaner or RockSolid Deck & Patio Cleaner and treat any deep stains with RockSolid Composite Deck Stain Remover. After cleaning allow the deck surface to completely dry, then conduct a splash test on the composite deck to confirm water absorption before applying this product. To conduct the test, splash a few drops of water on multiple areas of the composite deck and watch for water absorption. If the water is not absorbed within a few minutes, a barrier exists, and should be removed before staining can begin. Make sure the entire composite wood surface is dry and free of dust, dirt and debris. Cover all surrounding areas not intended to be coated.

### APPLICATION

DO NOT APPLY IF RAIN IS EXPECTED WITHIN 24 HOURS OF APPLICATION. Apply when surface and air temperature is between 50-90°F and humidity is below 65% and will remain between 50-90°F for at least 6 hours after application.

**NOTE:** Test RockSolid Composite Deck Refresh in an inconspicuous area first.

Thoroughly stir the material before and during application. When using more than one container, combine all containers to ensure color consistency. Using either a 3/8" nap roller, short nap stain pad, synthetic paint brush or a pump-style sprayer saturate and apply generously in a consistent pattern. If using a pump-style sprayer back brushing with a synthetic paint brush is recommended. Work to a wet edge at all times. Avoid rolling back into coated areas where drying has begun. To minimize lapping, always work from end to end on a few boards at a time, and maintain a wet edge. On horizontal surfaces, coat board ends and all 4 sides whenever possible to protect against moisture absorption. Clean up drips or spatters with water IMMEDIATELY, as dried coating is very difficult to remove.

Allow to dry 24 hours before light foot traffic and 48 hours before replacing furniture. If surface is tacky or soft, extend drying time before putting heavy objects back in place. Full cure to a hard finish will take approximately 7 days. Avoid dragging furniture across surface. On newly coated surfaces, allow 7 days for coating to cure before washing.

### CLEAN UP

Use mild soap and water to remove drips and spatters as soon as possible.

 <p><b>RUST-OLEUM</b> <b>ROCKSOLID</b> THE WORLD'S TOUGHEST COATINGS™</p>	<b>TECHNICAL DATA</b>	<b>RSD-65</b>
<b>ROCKSOLID® COMPOSITE DECK REFRESH</b>		

### PHYSICAL PROPERTIES

		COMPOSITE DECK REFRESH
<b>Resin Type</b>		Acrylic Copolymer
<b>Pigment</b>		Varies with color
<b>Solvent</b>		Water
<b>Weight</b>	<b>Per Gallon</b>	8.4-8.5 lbs.
	<b>Per Liter</b>	1.0 kg
<b>Solids</b>	<b>By Weight</b>	11.7-11.8%
	<b>By Volume</b>	10.1-10.2%
<b>Volatile Organic Compounds</b>		55 g/l
<b>Recommended Dry Film Thickness (DFT) Per Coat</b>		0.5-1.0 mil
<b>Practical Coverage at Recommended DFT (assumes 15% material loss)</b>		Up to 300 sq. ft./kit
<b>Dry Times @ 77° F (25°C) and 50% Relative Humidity</b>	<b>Touch</b>	1 hour
	<b>Recoat</b>	3-4 hours
	<b>Full Cure</b>	7 days
<b>Flash Point</b>		>200°F (93°C)
<b>WARNING!</b>		PROTECT FROM FREEZING
<b>Shelf Life</b>		3 years
<b>Safety Information</b>		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation  
11 Hawthorn Parkway  
Vernon Hills, Illinois 60061

Phone: 800-373-6333  
[www.rustoleum.com/rocksolid](http://www.rustoleum.com/rocksolid)

Form: ARJ-1819  
Rev.: 080421