



**ZINSSER® SMARTCOAT® ADVANCED
PAINT & PRIMER IN ONE**

DESCRIPTION AND USES

Paint Smart with Zinsser® SmartCoat® Advanced Paint & Primer in One Interior Wall Paint. An intelligent formula that makes painting simple. Ultra-smooth coverage, superior adhesion and exceptional washability all in one user-friendly formula.

PRODUCTS

FLAT

SKU	SIZE	DESCRIPTION
357555	Quart	White/Pastel
357567	Gallon	White/Pastel
357579	5 Gallon Pail	White/Pastel
357556	Quart	Midtone
357568	Gallon	Midtone
357580	5 Gallon Pail	Midtone
357557	Quart	Accent
357569	Gallon	Accent

EGGSHELL

SKU	SIZE	DESCRIPTION
357552	8 oz.	White/Pastel
357558	Quart	White/Pastel
357570	Gallon	White/Pastel
357581	5 Gallon Pail	White/Pastel
357553	8 oz.	Midtone
357559	Quart	Midtone
357571	Gallon	Midtone
357582	5 Gallon Pail	Midtone
357554	8 oz.	Accent
357560	Quart	Accent
357572	Gallon	Accent

SATIN

SKU	SIZE	DESCRIPTION
357561	Quart	White/Pastel
357573	Gallon	White/Pastel
357583	5 Gallon Pail	White/Pastel
357562	Quart	Midtone
357574	Gallon	Midtone
357584	5 Gallon Pail	Midtone
357563	Quart	Accent
357575	Gallon	Accent

PRODUCTS (cont.)

SEMI-GLOSS

SKU	SIZE	DESCRIPTION
357564	Quart	White/Pastel
357576	Gallon	White/Pastel
357585	5 Gallon Pail	White/Pastel
357565	Quart	Midtone
357577	Gallon	Midtone
357586	5 Gallon Pail	Midtone
357566	Quart	Accent
357578	Gallon	Accent

IMPORTANT: SmartCoat Advanced Paint & Primer in One Interior Wall Paint must be tinted at the purchase location before use.

TINT BASE MAXIMUM COLORANT

8 Oz.	Quart	1-Gallon	5-Gallon	DESCRIPTION
.25 oz.	1 oz.	4 oz.	20 oz.	White/Pastel
.50 oz.	2 oz.	8 oz.	40 oz.	Midtone
.75 oz.	3 oz.	12 oz.	-----	Accent

PRODUCT APPLICATION

READ ALL DIRECTIONS BEFORE BEGINNING PROJECT

SURFACE PREPARATION

Surface must be free of any dust, grease, oil, stains, rust or any other contaminants. Sand glossy surfaces before painting and wash walls if necessary. Fill in any cracks or holes to ensure a smooth surface. Drywall joint compound must dry for two days. New drywall and bare wood should be primed before painting. Allow new plaster to cure for 30 days before painting. We recommended the use of Zinsser Bulls Eye 1-2-3® Primer to protect new drywall, painting over contrasting colors, bare woods and metals or where paint adhesion could propose a problem.

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.



ZINSSER® SMARTCOAT® ADVANCED PAINT & PRIMER IN ONE

PRODUCT APPLICATION (cont.)

COVERAGE/WHERE TO USE

Coverages varies depending on surface texture, porosity, and application method. Dark colors may require multiple coats. Ideal for interior walls, trim, windows, and doors. Surfaces - Drywall, masonry and wood.

NOTE: Do not use on floors.

APPLICATION

Stir well before use. Intermix cans of the same color and product to ensure color consistency. Apply using a high quality 3/8"-1/2" nap roller or a high quality brush. If using an airless sprayer, follow manufacturer's instructions for use, and use a .013"-.017" tip at 1800-2300 psi, adjusting as needed. Apply using even strokes, moving from dry to wet areas, keeping a wet edge. Two coats are required for new or uncoated surfaces. Some colors may require additional coats. Thinning is not recommended.

DRY AND RECOAT TIMES

Based on 77°F (25°C) <50% humidity, dries to the touch in one hour. May be recoated after four hours. Allow more time to dry at cooler temperatures or in high humidity.

CLEAN-UP

Clean hands, tools, spills and splatters with soap and warm water.

DISPOSAL

To dispose of empty containers and unused product, contact your local environmental regulatory agency.

MAINTENANCE CARE

Do not place objects on painted surfaces until thoroughly dry. Freshly painted surfaces may be washed after 30 days. Clean with mild, non-oily soap and water.



**ZINSSER® SMARTCOAT® ADVANCED
PAINT & PRIMER IN ONE**

PHYSICAL PROPERTIES

		SMARTCOAT ADVANCED PAINT & PRIMER IN ONE
Resin Type		Styrene Acrylic
Pigment Type		Varies by color
Solvents		Water, Glycol Ethers
Weight	Per Gallon	10.1-11.5 lbs.
	Per Liter	1.2-1.4 kg
Solids	By Weight	51.2-57.8%
	By Volume	40.1-42.8%
Volatile Organic Compounds		<50 g/l (lbs./gal.)
Recommended Dry Film Thickness (DFT) per Coat		1.5-2.0 mils (37.5-50µ)
Wet Film to Achieve DFT (unthinned material)		2.5-5.0 mils (62.5-175µ)
Practical Coverage at Recommended DFT (assumes 15% material loss)		8 oz. up to 25 sq. ft. Quart up to 100 sq. ft. Gallon up to 400 sq. ft. 5 Gallon Pail up to 2,000 sq. ft. Varies depending on porosity and type of surface
Dry Times at 77°F (25°C) and 50% Relative Humidity	Touch	1 hour
	Recoat	4 hours
	Full Cure	7-10 days
Shelf Life		3 years
Flash Point		>200°F (93°C)
Storage		PROTECT FROM FREEZING
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.