



RUST-OLEUM® AUTOMOTIVE TRIM & BUMPER PAINT

DESCRIPTION AND USES

Rust-Oleum® Trim & Bumper Paint is designed to renew and restore the OEM finishes found on many vehicles. Trim & Bumper Paint is ideal for metal trim, moldings, rearview mirror covers, and rub strips. Rust-Oleum® Trim & Bumper Paint features an advanced spray system that allows you to spray at any angle, even upside down for those hard to reach areas. A comfort spray tip with a wider finger pad reduces fatigue caused by continuous spraying.

PRODUCTS

SKU	DESCRIPTION (Aerosol)
251574	Matte Black
260861	Charcoal Gray

PRODUCT APPLICATION

SURFACE PREPARATION

Remove all dirt, wax, and grease from the surface with Rust-Oleum® Wax & Tar Remover. Wash the area with a mild soap and water solution, fresh with fresh water, and dry with a clean cloth.

PRIMING

To improve adhesion, apply a Rust-Oleum Primer first. Recommended primers include 249321 Primer Sealer or any of the sandable primers (249419 Red, 252472 Light Gray, or 249415 Gray).

PRODUCT APPLICATION (cont.)

APPLICATION

Use outdoors or in a well ventilated area such as an open garage. Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 85% to ensure proper drying. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold can 12-16" from the surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. For best results, apply 2-3 light coats a few minutes apart. Do not use near open flame.

DRY & RECOAT


Dry and recoat times are based on 70°F and 50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 20 minutes, to handle in 1 hour and fully dry in 24 hours. Apply a second coat within 1 hour or after 24 hours.

CLEAN-UP

Wipe off tip when finished. Clean-up wet paint with xylene or mineral spirits or xylene. Properly discard empty container. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

	TECHNICAL DATA	ATO-02
	RUST-OLEUM® AUTOMOTIVE TRIM & BUMPER PAINT	

PHYSICAL PROPERTIES

TRIM & BUMPER PAINT		
Resin Type	Modified Alkyd	
Pigment Type	Carbon Black	
Solvents	Acetone, Aliphatic and Aromatic Hydrocarbons	
MIR	1.70 Max	
Fill Weight	11 ounces	
Recommended Dry Film Thickness (DFT) Per Coat	1.0-2.0 mils (25-50μ)	
Practical Coverage at Recommended DFT	10-15 sq. ft./can (1.1-1.7 m ² /can)	
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	20 minutes
	Handle	1 hour
	Recoat	Within 1 hour or after 24 hours
Shelf Life	5 years	
Flash Point	-156°F (-104°C)	
Safety Information	For additional information, see SDS	

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.