



PROJECT DETAILS			
BEST FOR	Garages, Basements, Workshops, Laundry Rooms, Mud Rooms and More	WALK-ON READY	8-10 Hours
SUBSTRATES	Concrete, Wood, Tile	DRIVE READY	24 Hours
KIT COVERAGE	Metallic System - Up to 100-250 Sq. Ft. Pearlescent System - Up to 200-250 Sq. Ft. Marble System - Up to 200-250 Sq. Ft.	# COATS NEEDED	1 Coat
# GARAGE	Varies by System	APPLY WHEN TEMPERATURE IS	BETWEEN 40°-90° F

UNIVERSAL BASE

FLOOR COATING KIT

RUST-OLEUM CORPORATION
11 Hawthorn Pkwy, Vernon Hills, IL 60061

MADE IN THE USA

SATISFACTION GUARANTEED
If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-800-765-4474 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.

rustoleum.com
1-866-765-4474

Category: Floor Coating
VOC: <1 g/L (0.01 lbs/gal)
*Formulated without addition of VOC containing solvent.
U.S. PATENT NUMBERS 8,381,860 B2

©2016 Rust-Oleum Corporation
59893 0516

UNIVERSAL BASE 282941

8 99201 00200 1

GREEN BUILDING
VERIFIED

SAFETY INFORMATION

BEFORE OPENING THE PACKAGE, READ ALL WARNING LABELS AND DATA SHEETS. FOLLOW ALL PRECAUTIONS. KEEP OUT OF REACH OF CHILDREN AND ANIMALS. DO NOT TAKE INTERNALLY.

DANGER!
CONTAINS: POLYCURAMINE RESIN, PROPRIETARY RESIN BLEND, EPOXY RESIN, POLYETHERAMINE BENZYL ALCOHOL, NONYMPHENDOL, HMPHOL, UNWASHED OR INGESTED CAUSES SKIN AND EYE IRRITATION. MAY CAUSE ALLERGIC REACTIONS. MAY CAUSE RESPIRATORY IRRITATION. AVOID BREATHING DUSTS OR FUMES. USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING DUSTS OR FUMES. IF YOU EXPERIENCE EYE IRRITATION, HEADACHE OR DIZZINESS, WEAR AN APPROPRIATE PROTECTIVE RESPIRATOR AND STOP WORK IMMEDIATELY. IF YOU EXPERIENCE EYE IRRITATION, HEADACHE OR DIZZINESS, WEAR AN APPROPRIATE PROTECTIVE RESPIRATOR AND STOP WORK IMMEDIATELY. IF YOU EXPERIENCE EYE IRRITATION, HEADACHE OR DIZZINESS, WEAR AN APPROPRIATE PROTECTIVE RESPIRATOR AND STOP WORK IMMEDIATELY. IF YOU EXPERIENCE EYE IRRITATION, HEADACHE OR DIZZINESS, WEAR AN APPROPRIATE PROTECTIVE RESPIRATOR AND STOP WORK IMMEDIATELY.

FIRST AID:
EYE CONTACT: IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 20 MINUTES AND GET MEDICAL ATTENTION.

SKIN CONTACT: IN CASE OF SKIN CONTACT, WASH THOROUGHLY WITH SOAP AND WATER. WASH CLOTHING BEFORE REUSE. THOROUGHLY CLEAN OR DESTROY CONTAMINATED CLOTHES.

INHALATION: IF AFFECTED BY INHALATION OF VAPOR OR SPRAY, MOVE TO FRESH AIR. IF BREATHING DIFFICULTY PERSISTS OR WORSE, LATER, CONSULT A PHYSICIAN AND HAVE LABEL INFORMATION AVAILABLE.

INGESTION: IF SWALLOWED, GET MEDICAL ATTENTION IMMEDIATELY. DO NOT INDUCE VOMITING. IF BREATHING DIFFICULTY PERSISTS OR WORSE, LATER, CONSULT A PHYSICIAN AND HAVE LABEL INFORMATION AVAILABLE.

PROPOSITION 65 - WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

EMERGENCY TELEPHONE: 1-800-424-7200

INFORMACIÓN DE SEGURIDAD

ANTES DE ABRIR EL ENVASE, LEA TODAS LAS ETIQUETAS DE ADVERTENCIA Y LAS FICHAS DE DATOS DE SEGURIDAD Y PRECAUCIONES. MANTÉNGALO FUERA DEL ALCANCE DE LOS NIÑOS Y DE LOS ANIMALES. NO LO TOMES INTERIAMENTE.

¡PELIGRO!
CONTIENE: RESINA POLYCURAMINE, COMBINACIÓN PATENTADA DE RESINAS, PEGAMENTO DE ALCOHOL DE BENCIL, ALCOHOL, NONYMPHENDOL, HMPHOL, POLYETHERAMINE, BENCIL ALCOHOL, NOYMPHENDOL, HMPHOL. SI SE INGESTA O SE INHALA SIN PRECAUCIONES, CAUSA IRRITACIÓN. PUEDE CAUSAR REACCIONES ALÉRGICAS. PUEDE CAUSAR IRRITACIÓN RESPIRATORIA. EVITE RESPIRAR POLVOS O HUMOS. ÚSELO ÚNICAMENTE CON VENTILACIÓN ADECUADA. SI EXPERIMENTA IRRITACIÓN OCULAR, DOLOR DE CABEZA O VERTIGEROS, USE UN RESPIRADOR ADECUADO Y DETÉNTESE DE TRABAJAR INMEDIATAMENTE. SI EXPERIMENTA IRRITACIÓN OCULAR, DOLOR DE CABEZA O VERTIGEROS, USE UN RESPIRADOR ADECUADO Y DETÉNTESE DE TRABAJAR INMEDIATAMENTE. SI EXPERIMENTA IRRITACIÓN OCULAR, DOLOR DE CABEZA O VERTIGEROS, USE UN RESPIRADOR ADECUADO Y DETÉNTESE DE TRABAJAR INMEDIATAMENTE.

PRIMEROS AUXILIOS:
CONTACTO CON LOS OJOS: EN CASO DE CONTACTO CON LOS OJOS, ENJUAGUE ABUNDANTE CON AGUA CORRIENTE DURANTE AL MENOS 20 MINUTOS. BUSQUE ATENCIÓN MÉDICA.

CONTACTO CON LA PIEL: EN CASO DE CONTACTO CON LA PIEL, LÁVESE ABUNDANTE CON AGUA Y JABÓN. SI SE PRESENTA DERMATITIS, USAR LA PIEL CONTAMINADA DEBE DESTRUIRSE. LOS ROPAJES CONTAMINADOS DEBE DESTRUIRSE.

INHALACIÓN: EN CASO DE QUE SE HAYAN VAPORES, POLVOS, BOSQUE ARE, PRESIÓN SUJETO AL TUBO PARA RESPIRACIÓN PROTECTORA DE SE PREVENIR EL LEGADO. CONSULTA CON UN MÉDICO Y LLEVE CONSIGO LA INFORMACIÓN DE LA ETIQUETA.

INGESTIÓN: EN CASO DE INGESTIÓN, BUSQUE ATENCIÓN MÉDICA INMEDIATAMENTE. NO INDUCIR EL VÓMITO. BUSQUE ATENCIÓN MÉDICA INMEDIATAMENTE.

CONTACTO CON LA PIEL: EN CASO DE CONTACTO CON LA PIEL, LÁVESE ABUNDANTE CON AGUA Y JABÓN. SI SE PRESENTA DERMATITIS, USAR LA PIEL CONTAMINADA DEBE DESTRUIRSE. LOS ROPAJES CONTAMINADOS DEBE DESTRUIRSE.

INHALACIÓN: EN CASO DE QUE SE HAYAN VAPORES, POLVOS, BOSQUE ARE, PRESIÓN SUJETO AL TUBO PARA RESPIRACIÓN PROTECTORA DE SE PREVENIR EL LEGADO. CONSULTA CON UN MÉDICO Y LLEVE CONSIGO LA INFORMACIÓN DE LA ETIQUETA.

INGESTIÓN: EN CASO DE INGESTIÓN, BUSQUE ATENCIÓN MÉDICA INMEDIATAMENTE. NO INDUCIR EL VÓMITO. BUSQUE ATENCIÓN MÉDICA INMEDIATAMENTE.

PROPOSICIÓN 65 - ADVERTENCIA: ESTE PRODUCTO SE CONOCIO QUE EL EPOXI RESINA FORMA UNA SUSTANCIA QUE CAUSA CÁNCER Y DEFECTOS DE REPRODUCCIÓN. LEA ATENTAMENTE LAS ADVERTENCIAS ADICIONALES EN LA PARTE POSTERIOR.

TELÉFONO DE EMERGENCIA: 1-800-424-7200

SYSTEM REQUIREMENTS

ADDITIVE	OTHER SUPPLIES NEEDED	BASE	COVERAGE / KIT
METALLIC ADDITIVE	MICROFIBER ROLLER	UNIVERSAL BASE	UP TO 100 - 125 SQ. FT.
PEARLESCENT ADDITIVE	MICROFIBER ROLLER		UP TO 200 - 250 SQ. FT.
MARBLE ADDITIVE	MARBLE ROLLER & TRAY KIT		UP TO 200 - 250 SQ. FT.

UNIVERSAL BASE


FLOOR COATING KIT

POLYCURAMINE® INNOVATION

The revolutionary RockSolid Polycuramine® combines key attributes from multiple chemistries into one. This creates a durable, self-leveling, fast curing, extreme high gloss coating system, that can be completed in one day.

20X STRONGER THAN EPOXY

POLYCURAMINE® TECHNOLOGY



PENETRATES AND ATTACHES TO CONCRETE ON A MOLECULAR LEVEL FORMING MULTIPLE BONDING POINTS

SELF-LEVELING

FLEXES & MOVES WITH THE CONCRETE TO PREVENT CRACKING OR PEELING

TRUSTED QUALITY SINCE 1921



THE WORLD'S TOUGHEST COATINGS™

UNIVERSAL BASE

FLOOR COATING KIT

INDUSTRIAL-GRADE POLYCURAMINE®

EASY AS 1-2-3

1 CHOOSE ADDITIVE: MARBLE, PEARLESCENT OR METALLIC

2 SELECT A ROLLER / TRAY

3 UNIVERSAL BASE COAT

KIT INCLUDES:



OTHER SUPPLIES NEEDED:

- ADDITIVE
 - ROLLER & TRAY
 - ROLLER FRAME
 - EXTENSION POLE
 - STIFF BRISTLED BROOM OR SCRUB BRUSH
 - 3" PAINT BRUSH
 - MIXING BUCKETS
- OPTIONAL:
- ANTI-SKID ADDITIVE
 - HEAVY-DUTY DEGREASER
 - CONCRETE PATCH AND REPAIR
 - PADDLE MIXER, DRILL

FORMULATED FOR GARAGE & INTERIOR

TRUSTED QUALITY SINCE 1921



THE WORLD'S TOUGHEST COATINGS™



METALLIC

SILVER BULLET SHOWN*

UNIVERSAL BASE

FLOOR COATING KIT

INDUSTRIAL-GRADE POLYCURAMINE®

20X STRONGER THAN EPOXY

DRIVE & WALK ON 24 HOURS

FOR USE WITH ADDITIVES

PEARLESCENT

CABINET SHOWN*

MARBLE

STONE OBSSIDIAN SHOWN*

NO HOT TIRE PICKUP | CHEMICAL RESISTANT | EXTREME HIGH GLOSS

*ADDITIVES SOLD SEPARATELY
NET WEIGHT: 6.3 LBS (2858 g)
1 POLYCURAMINE POUCH - 70 FL OZ
1 CONCRETE ETCH - 1 LBS

*See side for coverage details and system requirements
DANGER! VAPOR HARMFUL AND CAUSES EYE AND SKIN BURNS. READ CAREFULLY OTHER CAUTIONS ON BACK PANEL.
PELIGRO! VAPOR DAÑINO Y CAUSA QUEMADURAS EN LA PIEL Y LOS OJOS.
LEA ATENTAMENTE LAS ADVERTENCIAS ADICIONALES EN LA PARTE POSTERIOR.

GREAT FOR GARAGES & INTERIOR LIVING SPACES



STONE OBSSIDIAN

SILVER BULLET

CABINET

UNIVERSAL BASE

FLOOR COATING KIT

INDUSTRIAL-GRADE POLYCURAMINE®



EASY MIX BURST POUCH!

FEATURES & BENEFITS

DRIVE ON 24 HOURS	20X STRONGER THAN EPOXY
NO HOT TIRE PICK UP	EXTREME HIGH GLOSS
CHEMICAL RESISTANT	SELF-LEVELING AND BUILDABLE
ECO SAFE	LOW ODOR AND ZERO VOC*

EASY MIX BURST POUCH

VISIT [RUSTOLEUM.COM/ROCKSOLID](http://rustoleum.com/rocksolid) FOR INSTRUCTIONAL VIDEOS, FAQs AND TIPS & TECHNIQUES