



**METALLIC
ADDITIVE**

FOR USE WITH UNIVERSAL BASE FLOOR COATING



**METALLIC
ADDITIVE**


FOR USE WITH UNIVERSAL BASE FLOOR COATING




CHERRY BOMB

CONTAINS: 1 METALLIC POWDER

COVERS UP TO: 100-125 SQ. FT.*



RockSolid Metallic floor coatings add a gleaming and lustrous finish to your garage or interior living spaces. Add style and durability to your home with RockSolid Metallic Floor Coatings.



EASY APPLICATION

1 PREPARE SURFACE



- Scrub heavily-soiled areas with Rust-Oleum Cleaner & Degreaser (sold separately)
- Etch entire floor with concrete etch
- Rinse thoroughly & allow to dry completely

2 BURST-SHAKE-POUR



- Roll side A of RockSolid Universal Base (sold separately) pouch toward side B
- Burst and mix the two parts. Shake well for 2-3 minutes
- Cut off one corner and pour contents into mixing bucket

3 MIX IN METALLIC POWDER



- Add metallic tint to bucket
- Mix with paddle mixer & drill or stir stick for 1-2 minutes

4 APPLY COATING



- Trim outer edges
- Apply coating in 4' x 4' sections with RockSolid Microfiber roller (sold separately)

VISIT RUSTOLEUM.COM/ROCKSOLID
FOR INSTRUCTIONAL VIDEOS, FAQs AND TIPS & TECHNIQUES

PROJECT DETAILS

BEST FOR	> Garages, Basements, Workshops, Laundry Rooms, Mud Rooms and More	DRIVE READY	> 24 Hours
SUBSTRATES	> Concrete, Wood, Tile *see instructions for proper surface preparation	# COATS NEEDED	> 1 Coat
KIT COVERAGE*	> Up to 100-125 Sq. Ft.	APPLY WHEN TEMPERATURE IS	> BETWEEN 40°-90° F
WALK-ON READY	> 8-10 Hours	SYSTEM REQUIREMENTS	> RockSolid Universal Base Floor Coating Kit RockSolid Microfiber Roller Cover

*WHEN COMBINED WITH ROCKSOLID UNIVERSAL BASE FLOOR COATING

SAFETY INFORMATION

BEFORE OPENING THE PACKAGE, READ ALL WARNING LABELS AND DATA SHEETS. FOLLOW ALL PRECAUTIONS. KEEP OUT OF REACH OF CHILDREN AND ANIMALS

FIRST AID:

INHALATION: MILD BRONCHIAL IRRITATION MAY OCCUR. INGESTION: LARGE QUANTITIES MAY CAUSE IRRITATION TO MOUTH, THROAT AND GASTROINTESTINAL TRACT RESULTING IN NAUSEA AND VOMITING.

EMERGENCY TELEPHONE:
1-800-424-9300

PROPOSITION 65 - WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

INFORMACIÓN DE SEGURIDAD

ANTES DE ABRIR EL ENVASE, LEA TODAS LAS ETIQUETAS DE ADVERTENCIA Y LAS FICHAS TÉCNICAS. TOME TODAS LAS PRECAUCIONES.

MANTENGA EL PRODUCTO FUERA DEL ALCANCE DE LOS NIÑOS Y DE LOS ANIMALES

PRIMEROS AUXILIOS:

INHALACIÓN: SE PUEDE PRODUCIR UNA IRRITACIÓN BRONQUIAL LEVE. INGESTIÓN: LA INGESTIÓN DE GRANDES CANTIDADES DEL PRODUCTO PUEDE CAUSAR IRRITACIÓN DE LA BOCA, DE LA GARGANTA Y DEL TRACTO GÁSTRICO-INTestinal, LO QUE, A SU VEZ, PUEDE PROVOCAR NÁUSEAS Y VÓMITOS. EN CASO DE INGESTIÓN, BEBA AGUA Y OBTENGA ATENCIÓN MÉDICA. NO INDUZCA EL VÓMITO.

TELÉFONO DE EMERGENCIA: 1-800-424-9300

PROPOSICIÓN 65 - ADVERTENCIA: ESTE PRODUCTO ES CONOCIDO EN EL ESTADO DE CALIFORNIA COMO CAUSANTE DE CÁNCER Y DEFECTOS DE NACIMIENTO U OTROS DAÑOS REPRODUCTIVOS.



SATISFACTION GUARANTEED

If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-866-765-4474 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.

rustoleum.com
1-866-765-4474

© 2016 Rust-Oleum Corporation
Made in USA 59955 0516

CHERRY BOMB 60070



TRUSTED QUALITY SINCE 1921

RUST-OLEUM

ROCKSOLID

THE WORLD'S TOUGHEST COATINGS

METALLIC
ADDITIVE

FOR USE WITH UNIVERSAL BASE FLOOR COATING

TRUSTED QUALITY SINCE 1921

RUST-OLEUM

ROCKSOLID

THE WORLD'S TOUGHEST COATINGS

METALLIC
ADDITIVE

FOR USE WITH UNIVERSAL BASE FLOOR COATING



COPPER POT

CONTAINS: 1 METALLIC POWDER

NET WT 2 OZ

COVERS UP TO: 100-125 SQ. FT.*



RockSolid Metallic floor coatings add a gleaming and lustrous finish to your garage or interior living spaces. Add style and durability to your home with RockSolid Metallic Floor Coatings.



EASY APPLICATION

1 PREPARE SURFACE



- Scrub heavily-soiled areas with Rust-Oleum Cleaner & Degreaser (sold separately)
- Etch entire floor with concrete etch
- Rinse thoroughly & allow to dry completely

2 BURST-SHAKE-POUR



- Roll side A of RockSolid Universal Base (sold separately) pouch toward side B
- Burst and mix the two parts. Shake well for 2-3 minutes
- Cut off one corner and pour contents into mixing bucket

3 MIX IN METALLIC POWDER



- Add metallic tint to bucket
- Mix with paddle mixer & drill or stir stick for 1-2 minutes

4 APPLY COATING



- Trim outer edges
- Apply coating in 4' x 4' sections with RockSolid Microfiber roller (sold separately)

VISIT RUSTOLEUM.COM/ROCKSOLID
FOR INSTRUCTIONAL VIDEOS, FAQs AND TIPS & TECHNIQUES

PROJECT DETAILS

BEST FOR	Garages, Basements, Workshops, Laundry Rooms, Mud Rooms and More	DRIVE READY	> 24 Hours
SUBSTRATES	Concrete, Wood, Tile *see instructions for proper surface preparation	# COATS NEEDED	> 1 Coat
KIT COVERAGE*	> Up to 100-125 Sq. Ft.	APPLY WHEN TEMPERATURE IS	> BETWEEN 40°-90° F
WALK-ON READY	> 8-10 Hours	SYSTEM REQUIREMENTS	> RockSolid Universal Base Floor Coating Kit RockSolid Microfiber Roller Cover

*WHEN COMBINED WITH ROCKSOLID UNIVERSAL BASE FLOOR COATING

SAFETY INFORMATION

BEFORE OPENING THE PACKAGE, READ ALL WARNING LABELS AND DATA SHEETS. FOLLOW ALL PRECAUTIONS. KEEP OUT OF REACH OF CHILDREN AND ANIMALS.
FIRST AID:
INHALATION: MILD BRONCHIAL IRRITATION MAY OCCUR. INGESTION: LARGE QUANTITIES MAY CAUSE IRRITATION TO MOUTH, THROAT AND GASTROINTESTINAL TRACT RESULTING IN NAUSEA AND VOMITING.
EMERGENCY TELEPHONE: 1-800-424-9300
PROPOSITION 65 - WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

INFORMACIÓN DE SEGURIDAD

ANTES DE ABIR EL ENVASE, LEA TODAS LAS ETIQUETAS DE ADVERTENCIA Y LAS FICHAS TÉCNICAS. TOME TODAS LAS PRECAUCIONES. MANTENGA EL PRODUCTO FUERA DEL ALCANCE DE LOS NIÑOS Y DE LOS ANIMALES.
PRIMEROS AUXILIOS:
INHALACIÓN: SE PUEDE PRODUCIR UNA IRRITACIÓN BRONQUIAL LEVE. INGESTIÓN: LA INGESTIÓN DE GRANDES CANTIDADES DEL PRODUCTO PUEDE CAUSAR IRRITACIÓN DE LA BOCA, DE LA GARGANTA Y DEL TRACTO GASTRO-INTESTINAL, LO QUE A SU VEZ, PUEDE PROVOCAR NAÚSEAS Y VÓMITOS. EN CASO DE INGESTIÓN, BEBA AGUA Y OBTENGA ATENCIÓN MÉDICA. NO INDUZCA EL VÓMITO.
TELÉFONO DE EMERGENCIA: 1-800-424-9300
PROPOSICIÓN 65 - ADVERTENCIA: ESTE PRODUCTO ES CONOCIDO EN EL ESTADO DE CALIFORNIA COMO CAUSANTE DE CÁNCER Y DEFECTOS DE NACIMIENTO O U OTROS DAÑOS REPRODUCTIVOS.

RUST-OLEUM
CORPORATION
11 Hawthorn Place, Vernon Hills, IL 60061

SATISFACTION GUARANTEED

If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-866-765-4474 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.

rustoleum.com
1-866-765-4474

©2016 Rust-Oleum Corporation
Made in USA 59954 0516

COPPER POT 60071



TRUSTED QUALITY SINCE 1921

RUST-OLEUM®

ROCKSOLID®

THE WORLD'S TOUGHEST COATINGS™

METALLIC
ADDITIVE

FOR USE WITH UNIVERSAL BASE FLOOR COATING

TRUSTED QUALITY SINCE 1921

RUST-OLEUM®

ROCKSOLID®

THE WORLD'S TOUGHEST COATINGS™

METALLIC
ADDITIVE

FOR USE WITH UNIVERSAL BASE FLOOR COATING



EARTH BROWN

CONTAINS: 1 METALLIC POWDER

NET WT 2 OZ

COVERS UP TO: 100-125 SQ. FT.*



RockSolid Metallic floor coatings add a gleaming and lustrous finish to your garage or interior living spaces. Add style and durability to your home with RockSolid Metallic Floor Coatings.



EASY APPLICATION

1 PREPARE SURFACE



- Scrub heavily soiled areas with Rust-Oleum Cleaner & Degreaser (sold separately)
- Etch entire floor with concrete etch
- Rinse thoroughly & allow to dry completely

2 BURST-SHAKE-POUR



- Roll side A of RockSolid Universal Base (sold separately) pouch toward side B
- Burst and mix the two parts. Shake well for 2-3 minutes
- Cut off one corner and pour contents into mixing bucket

3 MIX IN METALLIC POWDER



- Add metallic tint to bucket
- Mix with paddle mixer & drill or stir stick for 1-2 minutes

4 APPLY COATING



- Trim outer edges
- Apply coating in 4' x 4' sections with RockSolid Microfiber roller (sold separately)

VISIT RUSTOLEUM.COM/ROCKSOLID

FOR INSTRUCTIONAL VIDEOS, FAQs AND TIPS & TECHNIQUES

PROJECT DETAILS

BEST FOR	Garages, Basements, Workshops, Laundry Rooms, Mud Rooms and More	DRIVE READY	> 24 Hours
SUBSTRATES	Concrete, Wood, Tile *see instructions for proper surface preparation	# COATS NEEDED	> 1 Coat
KIT COVERAGE*	> Up to 100-125 Sq. Ft	APPLY WHEN TEMPERATURE IS	> BETWEEN 40°-90° F
WALK-ON READY	> 8-10 Hours	SYSTEM REQUIREMENTS	> RockSolid Universal Base Floor Coating Kit RockSolid Microfiber Roller Cover

*WHEN COMBINED WITH ROCKSOLID UNIVERSAL BASE FLOOR COATING

SAFETY INFORMATION

BEFORE OPENING THE PACKAGE, READ ALL WARNING LABELS AND DATA SHEETS. FOLLOW ALL PRECAUTIONS. KEEP OUT OF REACH OF CHILDREN AND ANIMALS

FIRST AID:

INHALATION: MILD BRONCHIAL IRRITATION MAY OCCUR. INGESTION: LARGE QUANTITIES MAY CAUSE IRRITATION TO MOUTH, THROAT AND GASTROINTESTINAL TRACT RESULTING IN NAUSEA AND VOMITING.

EMERGENCY TELEPHONE:
1-800-424-9300

PROPOSITION 65 - WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

INFORMACIÓN DE SEGURIDAD

ANTES DE ABRIR EL ENVASE, LEA TODAS LAS ETIQUETAS DE ADVERTENCIA Y LAS FICHAS TÉCNICAS. TOME TODAS LAS PRECAUCIONES.

MANTENGA EL PRODUCTO FUERA DEL ALCANCE DE LOS NIÑOS Y DE LOS ANIMALES

PRIMEROS AUXILIOS:

INHALACIÓN: SE PUEDE PRODUCIR UNA IRRITACIÓN BRONQUIAL LIGERA. INGESTIÓN: LA INGESTIÓN DE GRANDES CANTIDADES DEL PRODUCTO PUEDE CAUSAR IRRITACIÓN DE LA BOCA, DE LA GARGANTA Y DEL TRACTO GASTRO-INTESTINAL, LO QUE A SU VEZ PUEDE PROVOCAR NAÚSEAS Y VÓMITOS. EN CASO DE INGESTIÓN, BEBA AGUA Y OBTENGA ATENCIÓN MÉDICA. NO INDUzca EL VÓMITO.

TELÉFONO DE EMERGENCIA: 1-800-424-9300

PROPOSICIÓN 65 - ADVERTENCIA: ESTE PRODUCTO ES CONOCIDO EN EL ESTADO DE CALIFORNIA COMO CAUSANTE DE CÁNCER Y DEFECTOS DE NACIMIENTO U OTROS DAÑOS REPRODUCTIVOS.

RUST-OLEUM
CORPORATION

11 Hawthorn Place, Vernon Hills, IL 60061

SATISFACTION GUARANTEED

If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-866-765-4474 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.

rustoleum.com

1-866-765-4474

©2016 Rust-Oleum Corporation
Made in USA 5953 0516

EARTH BROWN 60072



TRUSTED QUALITY SINCE 1921

ROCKSOLID

THE WORLD'S TOUGHEST COATINGS

METALLIC
ADDITIVE

FOR USE WITH UNIVERSAL BASE FLOOR COATING

TRUSTED QUALITY SINCE 1921

ROCKSOLID

THE WORLD'S TOUGHEST COATINGS

METALLIC
ADDITIVE

FOR USE WITH UNIVERSAL BASE FLOOR COATING



SILVER BULLET

CONTAINS: 1 METALLIC POWDER

NET WT 2 OZ

COVERS UP TO: 100-125 SQ. FT.*



RockSolid Metallic floor coatings add a gleaming and lustrous finish to your garage or interior living spaces. Add style and durability to your home with RockSolid Metallic Floor Coatings.



EASY APPLICATION

1 PREPARE SURFACE



- Scrub heavily soiled areas with Rust-Oleum Cleaner & Degreaser (sold separately)
- Etch entire floor with concrete etch
- Rinse thoroughly & allow to dry completely

2 BURST-SHAKE-POUR



- Roll side A of RockSolid Universal Base (sold separately) pouch towards side B
- Burst and mix the two parts. Shake well for 2-3 minutes
- Cut off one corner and pour contents into mixing bucket

3 MIX IN METALLIC POWDER



- Add metallic tint to bucket
- Mix with paddle mixer & drill or stir stick for 1-2 minutes

4 APPLY COATING



- Trim outer edges
- Apply coating in 4' x 4' sections with RockSolid Microfiber roller (sold separately)

VISIT RUSTOLEUM.COM/ROCKSOLID
FOR INSTRUCTIONAL VIDEOS, FAQs AND TIPS & TECHNIQUES

PROJECT DETAILS

BEST FOR	Garages, Basements, Workshops, Laundry Rooms, Mud Rooms and More	DRIVE READY	> 24 Hours
SUBSTRATES	Concrete, Wood, Tile *see instructions for proper surface preparation	# COATS NEEDED	> 1 Coat
KIT COVERAGE*	> Up to 100-125 Sq. Ft.	APPLY WHEN TEMPERATURE IS	> BETWEEN 40°-90° F
WALK-ON READY	> 8-10 Hours	SYSTEM REQUIREMENTS	> RockSolid Universal Base Floor Coating Kit RockSolid Microfiber Roller Cover

*WHEN COMBINED WITH ROCKSOLID UNIVERSAL BASE FLOOR COATING

SAFETY INFORMATION

BEFORE OPENING THE PACKAGE, READ ALL WARNING LABELS AND DATA SHEETS. FOLLOW ALL PRECAUTIONS. KEEP OUT OF REACH OF CHILDREN AND ANIMALS.
FIRST AID:
INHALATION: MILD BRONCHIAL IRRITATION MAY OCCUR. INGESTION: LARGE QUANTITIES MAY CAUSE IRRITATION TO MOUTH, THROAT AND GASTROINTESTINAL TRACT RESULTING IN NAUSEA AND VOMITING.
EMERGENCY TELEPHONE: 1-800-424-9300
PROPOSITION 65 - WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

INFORMACIÓN DE SEGURIDAD

ANTES DE ABRIR EL ENVASE, LEA TODAS LAS ETIQUETAS DE ADVERTENCIA Y LAS FICHAS TÉCNICAS. TOQUE TODAS LAS PRECAUCIONES. MANTENGA EL PRODUCTO FUERA DEL ALCANCE DE LOS NIÑOS Y DE LOS ANIMALES.
PRIMEROS AUXILIOS:
INHALACIÓN: SE PUEDE PRODUCIR UNA IRRITACIÓN BRONQUIAL LEVE. INGESTIÓN: LA INGESTIÓN DE GRANDES CANTIDADES DEL PRODUCTO PUEDE CAUSAR IRRITACIÓN DE LA BOCA, DE LA GARGANTA Y DEL TRACTO GASTRO-INTESTINAL, LO QUE A SU VEZ, PUEDE PROVOCAR NAÚSEAS Y VÓMITOS. EN CASO DE INGESTIÓN, BEBA AGUA Y OBTENGA ATENCIÓN MÉDICA. NO INDUzca EL VÓMITO.
TELÉFONO DE EMERGENCIA: 1-800-424-9300
PROPOSICIÓN 65 - ADVERTENCIA: ESTE PRODUCTO ES CONOCIDO EN EL ESTADO DE CALIFORNIA COMO CAUSANTE DE CÁNCER Y DEFECTOS DE NACIMIENTO O UOTROS DAÑOS REPRODUCTIVOS.

RUSTOLEUM
CORPORATION
11 Hawthorn Place, Vernon Hills, IL 60061

SATISFACTION GUARANTEED

If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-866-765-4474 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.

rustoleum.com
1-866-765-4474

©2016 Rust-Oleum Corporation
Made in USA 59956 0516

SILVER BULLET 60073

