NO INK OR COATING

•TRUSTED QUALITY SINCE 1921•
RUST-OLEUM®
ROCKSOLID®
THE WORLD'S TOUGHEST COATINGS™

METALLIC
FLOOR COATING KIT

EASY MIX BURST POUCH!
METALLIC TINT IN POUCH

KIT INCLUDES:
- INSTRUCTIONS
- CONCRETE ETCH
- 3/8" NAP WROLLER
- POLYCURAMINE BURST POUCH

OTHER SUPPLIES NEEDED:
- ☐ ROLLER FRAME
- ☐ EXTENSION POLE
- ☐ STIFF BRISTLED BROOM OR SCRUB BRUSH
- ☐ 3" PAINT BRUSH

OPTIONAL:
- ☐ ANTI-SKID ADDITIVE
- ☐ HEAVY-DUTY DEGREASER
- ☐ CONCRETE PATCH AND REPAIR

RUST-OLEUM® ROCKSOLID® THE WORLD'S TOUGHEST COATINGS™

IT'S THAT TOUGH!

PROJECT DETAILS

BEST FOR	Garages, Basements, Workshops, Laundry Rooms, Mud Rooms and More	WALK-ON READY	8-10 Hours
SUBSTRATES	Concrete, Wood, & Tile See instructions for proper surface preparation	DRIVE READY	1 Day
KIT COVERAGE	Up to 100-125 Sq. Ft	# COATS NEEDED	1 Coat
# GARAGE	2 kits needed for one car garage	APPLY WHEN TEMPERATURE IS	BETWEEN 40°- 90° F

METALLIC
FLOOR COATING KIT

RUST-OLEUM CORPORATION
11 Hawthorn Pkwy., Vernon Hills, IL 60061
888-683-5667 rustoleum.com/garage
Made in USA

Limited Warranty: Rust-Oleum Corporation guarantees product performance when the product is applied according to the label directions. If you are dissatisfied with this product, your sole and exclusive remedy is either a refund of the original purchase price or a replacement with a product of equal value. We do not guarantee the product against factors beyond our control, such as damage to the product by others, poor condition of the substrate, inadequate surface preparation, structural defects, improper application, etc. We will not be responsible for labor or the cost of labor for removal or application of any product or replacement of any surface.

rustoleum.com/garage
1-866-765-4474

Category: Floor Coating
VOC < 1 g/L (0.01 lbs/gal)
*Formulated without addition of VOC containing solvent.
*Formulado sin añadir solvente que contenga COV.
U.S. PATENT NUMBER 8,985,323

©2026 Rust-Oleum Corporation
366696 0620

SILVER BULLET 286893

SAFETY INFORMATION

Before opening the package, read all warning labels and data sheets. Follow all precautions.
KEEP OUT OF REACH OF CHILDREN AND ANIMALS.
Do not take internally.
DANGER!
CONTAINS: Polycuramine Resin, Proprietary Resin Blend, Polyethoxamine, Benzyl Alcohol, Neopentyl Glycol Diglycidyl Ether, 1-Octen-3-ol, Trifluoromethylbenzene, 4-Nonylphenol, Branched, Isophorone Diamine
WARNING: IF INHALED OR ABSORBED, CAUSES SKIN AND EYE BURNS. MAY CAUSE ALLERGIC SKIN REACTION. MAY CAUSE RESPIRATORY IRRITATION, ASTHMA, OR BREATHING DIFFICULTIES IF INHALED.
USE ONLY WITH ADEQUATE VENTILATION.
AVOID BREATHING VAPORS. ENSURE FRESH AIR ENTRY DURING APPLICATION AND DRYING. KEEP AWAY FROM SPARKS, FLAMES, AND HOT SURFACES. DO NOT SMOKE WHILE USING THIS PRODUCT. USE ONLY IN WELL-VENTILATED AREAS. IF VENTILATION IS INSUFFICIENT, WEAR A SUITABLE RESPIRATOR. WASH HANDS THOROUGHLY AFTER HANDLING. DO NOT EAT OR DRINK WHEN USING THIS PRODUCT.
FIRST AID:
Eye Contact: In case of eye contact, flush immediately with plenty of water for at least 20 minutes and get medical attention.
Skin Contact: In case of skin contact, wash thoroughly with soap and water. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation: If affected by inhalation of vapor or spray mist, remove to fresh air. If breathing difficulty persists or occurs later, consult a physician and have label information available.
Ingestion: If swallowed, get medical attention immediately. Do not induce vomiting. Get medical attention immediately.
⚠ WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov.
Phone: 1-800-424-9300

INFORMACIÓN DE SEGURIDAD

Antes de abrir el envase, lealodas las etiquetas de advertencia y las fichas técnicas. Tome todas las precauciones.
MANTENGASE FUERA DEL ALCANCE DE LOS NIÑOS Y DE LOS ANIMALES. No lo ingiera.
¡ADVERTENCIA!
CONTIENE: Resina Policuramina®, Mezcla de Resina Patentada, Polietoxamina, Alcohol Bencílico, Éter Diglicidílico de Neopentil Glicol, 1-Octen-3-ol, Trifluorometilbenceno, 4-Nonilfenol Ramificado, Isoforona diamina
¡ADVERTENCIA! AL INHALARSE O ABSORBERSE, CAUSA QUEMADURAS EN LA PIEL Y LOS OJOS. PUEDE CAUSAR REACCIÓN ALÉRGICA CUTÁNEA. PUEDE CAUSAR IRRITACIÓN RESPIRATORIA, ASMA O DIFICULTADES PARA RESPIRAR SI SE INHALA.
USAR SOLO CON VENTILACIÓN ADECUADA.
EVITAR LA INHALACIÓN DE VAPORES. ASEGURE EL INGRESO DE AIRE FRESCO DURANTE LA APLICACIÓN Y EL SECADO. MANTENGA ALEJADO DE CHISPAS, LLAMAS Y SUPERFICIES CALIENTES. NO FUME MIENTRAS USA ESTE PRODUCTO. USE SOLO EN ÁREAS BIEN VENTILADAS. SI LA VENTILACIÓN ES INSUFICIENTE, USE UN RESPIRADOR ADECUADO. LÁVESE LAS MANOS BIEN DESPUÉS DE MANIPULAR. NO COMA NI BEBA MIENTRAS USA ESTE PRODUCTO.
PRIMEROS AUXILIOS:
Contacto Con Los Ojos: En caso de contacto con los ojos, enjuague de inmediato con abundante agua durante al menos 20 minutos y obtenga atención médica.
Contacto Con La Piel: En caso de contacto con la piel, lave cuidadosamente con agua y jabón. Lave la ropa antes de volver a usarla. Limpie cuidadosamente o destruya los zapatos contaminados.
Inhalación: En caso de que se inhalen vapores o niebla, busque aire fresco. Si la dificultad para respirar persiste o se presenta luego, consulte un médico y lleve consigo la información de la etiqueta.
Ingestión: En caso de ingestión, busque atención médica inmediatamente. No induzca el vómito. Busque atención médica inmediatamente.
⚠ ADVERTENCIA! Cáncer y daños reproductivos - www.P65warnings.ca.gov.
Teléfono De Emergencias: 1-800-424-9300

GREAT FOR GARAGES & INTERIOR LIVING SPACES



NO PEEL PROMISE

100-125 SQ. FT.
2 KITS NEEDED FOR 1 CAR GARAGE

•TRUSTED QUALITY SINCE 1921•
RUST-OLEUM®
ROCKSOLID®
THE WORLD'S TOUGHEST COATINGS™

METALLIC
FLOOR COATING KIT

20X STRONGER THAN EPOXY
DRIVE ON IN 1 DAY

INDUSTRIAL-GRADE POLYCURAMINE®

- *No Hot Tire Pick-Up*
- *Superior Impact & Chemical Resistance*
- *Limited Lifetime Warranty*
- *Showroom Quality Finish*

EXTREME HIGH GLOSS

2.5 QTS (80 FL OZ/2.37L)
KIT INCLUDES: POLYCURAMINE POUCH, CONCRETE ETCH, ROLLER, INSTRUCTION SHEET (ENGLISH/ESPANOL)

SILVER BULLET
HIGH GLOSS

KIT COVERS: UP TO 100-125 SQ. FT.
2 KITS NEEDED FOR 1 CAR GARAGE

DANGER! VAPOR HARMFUL AND CAUSES EYE AND SKIN BURNS. READ CAREFULLY OTHER CAUTIONS ON BACK PANEL.
¡PELIGRO! VAPOR DAÑINO Y CAUSA QUEMADURAS EN LA PIEL Y LOS OJOS. LEA ATENTAMENTE LAS ADVERTENCIAS ADICIONALES EN LA PARTE POSTERIOR.

EASY MIX BURST POUCH!
METALLIC TINT IN POUCH

BURST	SHAKE	POUR
TIGHTLY ROLL POUCH UNTIL SEAL BURSTS ALLOWING CONTENTS TO MIX	MIX CONTENTS BY SHAKING POUCH BACK AND FORTH AND SQUEEZING THE EDGES AND CORNERS FOR 2-3 MINUTES	CUT CORNER & POUR FOLLOW APPLICATION INSTRUCTIONS INCLUDED IN KIT

METALLIC
FLOOR COATING KIT

EASY 3-STEP APPLICATION

1 PREPARE SURFACE



- Clean and degrease entire floor
- Etch entire floor with concrete etch (included)
- Rinse thoroughly & allow to dry completely

2 BURST-SHAKE-POUR

- Roll side A of pouch toward side B to burst and mix the two components
- Mix contents by shaking pouch back and forth and squeezing the edges and corners for 2-3 minutes
- Cut off one corner and pour out a ribbon onto the floor

3 APPLY COATING

- Trim outer edges
- Apply coating in 4' x 4' sections with roller (included)

VISIT RUSTOLEUM.COM/GARAGE FOR INSTRUCTIONAL VIDEOS, FAQS AND TIPS & TECHNIQUES

POLYCURAMINE® TECHNOLOGY



20X STRONGER THAN EPOXY

FEATURES & BENEFITS
DRIVE ON IN 1 DAY
NO HOT TIRE PICK UP
CHEMICAL RESISTANT
EASY MIX BURST POUCH WITH METALLIC TINT IN POUCH
20X STRONGER THAN EPOXY
EXTREME HIGH GLOSS
SELF-LEVELING & BUILDABLE
LOW ODOR & LOW VOC

NO INK OR COATING

NO INK OR COATING