



• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®

P R O F E S S I O N A L

ROCKSOLID®

THE WORLD'S TOUGHEST COATINGS™

**PRO
SERIES**

COVERS
1000
SQUARE FEET

INDUSTRIAL FLOOR COATING

INDUSTRIAL-GRADE POLYCURAMINE®



20X
STRONGER
THAN EPOXY
DRIVE ON
24 HOURS

DARK GRAY

NET CONTENTS:
4 POLYCURAMINE
POUCHES - 90 FL OZ

**LOW ODOR &
VOC FREE***

**IMPACT &
CHEMICAL RESISTANT**

**EXTREME
HIGH GLOSS**

DANGER! VAPOR HARMFUL AND CAUSES EYE AND SKIN BURNS. READ CAREFULLY OTHER CAUTIONS ON BACK PANEL.
PELIGRO! VAPOR DAÑINO Y CAUSA QUEMADURAS EN LA PIEL Y LOS OJOS. LEA ATENTAMENTE LAS ADVERTENCIAS ADICIONALES EN LA PARTE POSTERIOR.

PROJECT DETAILS

BEST FOR	>	Commercial Areas, Workshops, Garages, Basements	WALK-ON READY	>	8-10 Hours
SUBSTRATES	>	Concrete, Wood, & Tile *see instructions for proper surface preparation	RETURN TO SERVICE	>	24 Hours
KIT COVERAGE	>	Up to 1000 Sq. Ft	# COATS NEEDED	>	1 Coat
APPLICATOR	>	3/8" nap roller *see instructions for squeegee application	APPLY WHEN TEMPERATURE IS	>	BETWEEN 40°-90° F

EASY 3-STEP APPLICATION

1 - PREPARE SURFACE



- Scrub heavily-soiled areas with Rust-Oleum Cleaner & Degreaser (sold separately)
- Etch entire floor with Rust-Oleum Clean & Etch (sold separately), and rinse thoroughly & allow to dry completely
- Diamond grind as an alternate method to etching

2 - BURST-SHAKE-POUR



- Roll side A of pouch toward side B to burst and mix the two components
- Mix contents by shaking pouch back and forth and squeezing the edges and corners for 2-3 minutes
- Cut off one corner and pour out a ribbon of RockSolid Professional directly onto the floor

3 - APPLY COATING



- Trim outer edges
- Apply coating with a roller (see instructions for squeegee application)
- If desired, broadcast RockSolid Professional Decorative Chips and apply RockSolid Clear Topcoat (sold separately)



11 Hawthorn Pkwy., Vernon Hills, IL 60061
800-481-4785 | rustoleum.com/rocksolid
 Made in USA | Hecho en E.U.A.
 ©2017 Rust-Oleum Corporation 76063B 0517

SATISFACTION GUARANTEED

If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-866-765-4474 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.

Category: Floor Coating
 VOC < 1 g/L (0.01 lbs/gal)

*Formulated without addition of VOC containing solvent.

*Formulado sin añadir solvente que contenga COV.

U.S. PATENT NUMBER 8,381,903 B2

DARK GRAY 322760



SAFETY INFORMATION

BEFORE OPENING THE PACKAGE, READ ALL WARNING LABELS AND DATA SHEETS. FOLLOW ALL PRECAUTIONS.

KEEP OUT OF REACH OF CHILDREN AND ANIMALS.
 DO NOT TAKE INTERNALLY.

DANGER! CONTAINS: POLYCURAMINE® RESIN, PROPRIETARY RESIN BLEND, TITANIUM DIOXIDE PIGMENT, 3-AMINOMETHYL-3, 5,5-TRIMETHYLCYCLOXYLAMINE, POLYETHERAMINE, BENZYL ALCOHOL. HARMFUL IF INHALED OR INGESTED. CAUSES EYE AND SKIN BURNS. MAY CAUSE ALLERGIC REACTIONS. MAY CAUSE RESPIRATORY IRRITATION, ASTHMA, OR BREATHING DIFFICULTIES IF INHALED. **USE ONLY WITH ADEQUATE VENTILATION.** AVOID BREATHING VAPORS. ENSURE FRESH AIR ENTRY DURING APPLICATION AND DRYING. KEEP AWAY FROM HEAT, SPARKS AND FLAME. VAPOR MAY CAUSE FLASH FIRE. DO NOT SMOKE. IF YOU EXPERIENCE EYE WATERING, HEADACHE OR DIZZINESS, WEAR AN APPROPRIATE, PROPERLY FITTED RESPIRATOR (NIOSH APPROVED) DURING AND AFTER APPLICATION. WEAR PROTECTIVE EYE AND HAND WEAR. WASH THOROUGHLY AFTER HANDLING.

FIRST AID:

EYE CONTACT: IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 20 MINUTES AND GET MEDICAL ATTENTION.

SKIN CONTACT: IN CASE OF SKIN CONTACT, WASH THOROUGHLY WITH SOAP AND WATER. WASH CLOTHING BEFORE REUSE. THOROUGHLY CLEAN OR DESTROY CONTAMINATED SHOES.

INHALATION: IF AFFECTED BY INHALATION OF VAPOR OR SPRAY MIST, REMOVE TO FRESH AIR. IF BREATHING DIFFICULTY PERSISTS OR OCCURS LATER, CONSULT A PHYSICIAN AND HAVE LABEL INFORMATION AVAILABLE.

INGESTION: IF SWALLOWED, GET MEDICAL ATTENTION IMMEDIATELY. DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.

⚠ WARNING: CANCER AND REPRODUCTIVE HARM - WWW.P65WARNINGS.CA.GOV.

EMERGENCY TELEPHONE: 1-800-424-9300

INFORMACIÓN DE SEGURIDAD

ANTES DE ABRIR EL ENVASE, LEA TODAS LAS ETIQUETAS DE ADVERTENCIA Y LAS FICHAS TÉCNICAS. TOMÉ TODAS LAS PRECAUCIONES.

MANTENGA EL PRODUCTO FUERA DEL ALCANCE DE LOS NIÑOS Y DE LOS ANIMALES. NO LO INGERA.

¡ADVERTENCIA! CONTIENE: RESINA POLYCURAMINE®, COMBINACIÓN PATENTADA DE RESINAS, PIGMENTO DE DIOXIDO DE TITANIO, 3-AMINOMETIL-3, 5,5-TRIMETILCICLOXILAMINA, POLIETERAMINA, ALCOHOL DE BENCÍLO. SU INHALACIÓN O SU INGESTA SON PERJUDICIALES. CAUSA IRRITACIÓN CUTÁNEA Y OCULAR. PUEDE CAUSAR REACCIONES ALÉRGICAS. EN CASO DE QUE SE INHALE EL PRODUCTO, PUEDE CAUSAR IRRITACIÓN DEL SISTEMA RESPIRATORIO, ASMA O DIFICULTADES PARA RESPIRAR. **USAR SOLO CON VENTILACIÓN ADECUADA.** EVITAR LA INHALACIÓN DE VAPORES. ASEGURE EL INGRESO DE AIRE FRESCO DURANTE LA APLICACIÓN Y SECADO. MANTENGA EL PRODUCTO ALEJADO DEL CALOR, DE LAS CHISPAS Y DE LAS LLAMAS. LOS VAPORES PUEDEN CAUSAR COMBUSTIÓN INSTANTÁNEA. NO FUME. SI EXPERIMENTA LAGRIMO DE LOS OJOS, DOLOR DE CABEZA O MAREOS, UTILICE UN RESPIRADOR APROPIADO, CON UN AJUSTE ADECUADO (APROBADO POR NIOSH) DURANTE Y DESPUÉS DE LA APLICACIÓN. UTILICE PROTECCIÓN ADECUADA PARA LOS OJOS Y MANOS. LÁVESE BIEN DESPUÉS DE MANIPULAR.

PRIMEROS AUXILIOS:

CONTACTO CON LOS OJOS: EN CASO DE CONTACTO CON LOS OJOS, ENJUAGUE DE INMEDIATO CON ABUNDANTE AGUA DURANTE AL MENOS 20 MINUTOS Y OBTENGA ATENCIÓN MÉDICA.

CONTACTO CON LA PIEL: EN CASO DE CONTACTO CON LA PIEL, LAVE CUIDADOSAMENTE CON AGUA Y JABÓN. LAVE LA ROPA ANTES DE VOLVER A USARLA. LIMPIE CUIDADOSAMENTE O DESTRUYA LOS ZAPATOS CONTAMINADOS.

INHALACIÓN: EN CASO DE QUE SE INHALEN VAPORES O ROCIÓ, BUSQUE AIRE FRESCO. SI LA DIFICULTAD PARA RESPIRAR PERSISTE O SI SE PRESENTA LUEGO, CONSULTE CON UN MÉDICO Y LLEVE CONSIGO LA INFORMACIÓN DE LA ETIQUETA.

INGESTIÓN: EN CASO DE INGESTIÓN, BUSQUE ATENCIÓN MÉDICA INMEDIATAMENTE. NO INDUZCA EL VÓMITO. BUSQUE ATENCIÓN MÉDICA INMEDIATAMENTE.

⚠ ADVERTENCIA: CÁNCER Y DAÑOS REPRODUCTIVOS - WWW.P65WARNINGS.CA.GOV.

TÉLEFONO DE EMERGENCIA: 1-800-424-9300



• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®

P R O F E S S I O N A L

ROCKSOLID®

THE WORLD'S TOUGHEST COATINGS™

**PRO
SERIES**

COVERS
1000
SQUARE FEET

INDUSTRIAL FLOOR COATING

INDUSTRIAL-GRADE POLYCURAMINE®



20X
STRONGER
THAN EPOXY

**DRIVE ON
24 HOURS**

GRAY

NET CONTENTS:
4 POLYCURAMINE
POUCHES - 90 FL OZ

LOW ODOR &
VOC FREE*

IMPACT &
CHEMICAL RESISTANT

EXTREME
HIGH GLOSS

DANGER! VAPOR HARMFUL AND CAUSES EYE AND SKIN BURNS. READ CAREFULLY OTHER CAUTIONS ON BACK PANEL.
PELIGRO! VAPOR DAÑINO Y CAUSA QUEMADURAS EN LA PIEL Y LOS OJOS. LEA ATENTAMENTE LAS ADVERTENCIAS ADICIONALES EN LA PARTE POSTERIOR.

PROJECT DETAILS

BEST FOR	>	Commercial Areas, Workshops, Garages, Basements	WALK-ON READY	>	8-10 Hours
SUBSTRATES	>	Concrete, Wood, & Tile *see instructions for proper surface preparation	RETURN TO SERVICE	>	24 Hours
KIT COVERAGE	>	Up to 1000 Sq. Ft	# COATS NEEDED	>	1 Coat
APPLICATOR	>	3/8" nap roller *see instructions for squeegee application	APPLY WHEN TEMPERATURE IS	>	BETWEEN 40°-90° F

EASY 3-STEP APPLICATION

1 - PREPARE SURFACE



- Scrub heavily-soiled areas with Rust-Oleum Cleaner & Degreaser (sold separately)
- Etch entire floor with Rust-Oleum Clean & Etch (sold separately), and rinse thoroughly & allow to dry completely
- Diamond grind as an alternate method to etching

2 - BURST-SHAKE-POUR



- Roll side A of pouch toward side B to burst and mix the two components
- Mix contents by shaking pouch back and forth and squeezing the edges and corners for 2-3 minutes
- Cut off one corner and pour out a ribbon of RockSolid Professional directly onto the floor

3 - APPLY COATING



- Trim outer edges
- Apply coating with a roller (see instructions for squeegee application)
- If desired, broadcast RockSolid Professional Decorative Chips and apply RockSolid Clear Topcoat (sold separately)



CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061

800-481-4785 | rustoleum.com/rocksolid

Made in USA | Hecho en E.U.A.

©2017 Rust-Oleum Corporation 76061B 0517

SATISFACTION GUARANTEED

If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-866-765-4474 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.

Category: Floor Coating
VOC < 1 g/L (0.01 lbs/gal)

*Formulated without addition of VOC containing solvent.

*Formulado sin añadir solvente que contenga COV.

U.S. PATENT NUMBER 8,381,903 B2

GRAY 322759



SAFETY INFORMATION

BEFORE OPENING THE PACKAGE, READ ALL WARNING LABELS AND DATA SHEETS. FOLLOW ALL PRECAUTIONS.

KEEP OUT OF REACH OF CHILDREN AND ANIMALS.
DO NOT TAKE INTERNALLY.

DANGER! CONTAINS: POLYURAMINE® RESIN, PROPRIETARY RESIN BLEND, TITANIUM DIOXIDE PIGMENT, 3-AMINOMETHYL-3, 5,5-TRIMETHYLCYCLOXYLAMINE, POLYETHERAMINE, BENZYL ALCOHOL. HARMFUL IF INHALED OR INGESTED. CAUSES EYE AND SKIN BURNS. MAY CAUSE ALLERGIC REACTIONS. MAY CAUSE RESPIRATORY IRRITATION, ASTHMA, OR BREATHING DIFFICULTIES IF INHALED. **USE ONLY WITH ADEQUATE VENTILATION.** AVOID BREATHING VAPORS. ENSURE FRESH AIR ENTRY DURING APPLICATION AND DRYING. KEEP AWAY FROM HEAT, SPARKS AND FLAME. VAPOR MAY CAUSE FLASH FIRE. DO NOT SMOKE. IF YOU EXPERIENCE EYE WATERING, HEADACHE OR DIZZINESS, WEAR AN APPROPRIATE, PROPERLY FITTED RESPIRATOR (NIOSH APPROVED) DURING AND AFTER APPLICATION. WEAR PROTECTIVE EYE AND HAND WEAR. WASH THOROUGHLY AFTER HANDLING.

FIRST AID:

EYE CONTACT: IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 20 MINUTES AND GET MEDICAL ATTENTION.

SKIN CONTACT: IN CASE OF SKIN CONTACT, WASH THOROUGHLY WITH SOAP AND WATER. WASH CLOTHING BEFORE REUSE. THOROUGHLY CLEAN OR DESTROY CONTAMINATED SHOES.

INHALATION: IF AFFECTED BY INHALATION OF VAPOR OR SPRAY MIST, REMOVE TO FRESH AIR. IF BREATHING DIFFICULTY PERSISTS OR OCCURS LATER, CONSULT A PHYSICIAN AND HAVE LABEL INFORMATION AVAILABLE.

INGESTION: IF SWALLOWED, GET MEDICAL ATTENTION IMMEDIATELY. DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.

⚠ WARNING: CANCER AND REPRODUCTIVE HARM - WWW.P65WARNINGS.CA.GOV.

EMERGENCY TELEPHONE: 1-800-424-9300

INFORMACIÓN DE SEGURIDAD

ANTES DE ABRIR EL ENVASE, LEA TODAS LAS ETIQUETAS DE ADVERTENCIA Y LAS FICHAS TÉCNICAS. TOMÉ TODAS LAS PRECAUCIONES.

MANTENGA EL PRODUCTO FUERA DEL ALCANCE DE LOS NIÑOS Y DE LOS ANIMALES. NO LO INGERA.

¡ADVERTENCIA! CONTIENE: RESINA POLYURAMINE® COMBINACIÓN PATENTADA DE RESINAS, PIGMENTO DE DIOXIDO DE TITANIO, 3-AMINOMETIL-3, 5, 5-TRIMETILCICLOXILAMINA, POLIETERAMINA, ALCOHOL DE BENCILICO. SU INHALACION O SU INGESTA SON PERJUDICIALES. CAUSA IRRITACION CUTANEA Y OCULAR. PUEDE CAUSAR REACCIONES ALERGICAS. EN CASO DE QUE SE INHALE EL PRODUCTO, PUEDE CAUSAR IRRITACION DEL SISTEMA RESPIRATORIO, ASMA O DIFICULTADES PARA RESPIRAR. **USAR SOLO CON VENTILACION ADECUADA.** EVITAR LA INHALACION DE VAPORES. ASEGURE EL INGRESO DE AIRE FRESCO DURANTE LA APLICACION Y SECADO. MANTENGA EL PRODUCTO ALEJADO DEL CALOR, DE LAS CHISPAS Y DE LAS LLAMAS. LOS VAPORES PUEDEN CAUSAR COMBUSTION INSTANTANEA. NO FUME. SI EXPERIMENTA LAGRIMO DE LOS OJOS, DOLOR DE CABEZA O MAREOS, UTILICE UN RESPIRADOR APROPIADO, CON UN AJUSTE ADECUADO (APROBADO POR NIOSH) DURANTE Y DESPUES DE LA APLICACION. UTILICE PROTECCION ADECUADA PARA LOS OJOS Y MANOS. LAVESE BIEN DESPUES DE MANIPULAR.

PRIMEROS AUXILIOS:

CONTACTO CON LOS OJOS: EN CASO DE CONTACTO CON LOS OJOS, ENJUAGUE DE INMEDIATO CON ABUNDANTE AGUA DURANTE AL MENOS 20 MINUTOS Y OBTENGA ATENCION MEDICA.

CONTACTO CON LA PIEL: EN CASO DE CONTACTO CON LA PIEL, LAVE CUIDADOSAMENTE CON AGUA Y JABÓN. LAVE LA ROPA ANTES DE VOLVER A USARLA. LIMPIE CUIDADOSAMENTE O DESTRUYA LOS ZAPATOS CONTAMINADOS.

INHALACION: EN CASO DE QUE SE INHALEN VAPORES O ROCIO, BUSQUE AIRE FRESCO. SI LA DIFICULTAD PARA RESPIRAR PERSISTE O SI SE PRESENTA LUEGO, CONSULTE CON UN MEDICO Y LLEVE CONSIGO LA INFORMACION DE LA ETIQUETA.

INGESTION: EN CASO DE INGESTION, BUSQUE ATENCION MEDICA INMEDIATAMENTE. NO INDUZCA EL VÓMITO. BUSQUE ATENCION MEDICA INMEDIATAMENTE.

⚠ ADVERTENCIA: CANCER Y DAÑOS REPRODUCTIVOS - WWW.P65WARNINGS.CA.GOV.

TELÉFONO DE EMERGENCIA: 1-800-424-9300



• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®

P R O F E S S I O N A L

ROCKSOLID®

THE WORLD'S TOUGHEST COATINGS™

**P R O
S E R I E S**

COVERS
1000
SQUARE FEET

INDUSTRIAL FLOOR COATING

INDUSTRIAL-GRADE POLYCURAMINE®



20X
STRONGER
THAN EPOXY

**DRIVE ON
24 HOURS**

MOCHA

NET CONTENTS:
4 POLYCURAMINE
POUCHES - 90 FL OZ

**LOW ODOR &
VOC FREE***

**IMPACT &
CHEMICAL RESISTANT**

**EXTREME
HIGH GLOSS**

DANGER! VAPOR HARMFUL AND CAUSES EYE AND SKIN BURNS. READ CAREFULLY OTHER CAUTIONS ON BACK PANEL.
PELIGRO! VAPOR DAÑINO Y CAUSA QUEMADURAS EN LA PIEL Y LOS OJOS. LEA ATENTAMENTE LAS ADVERTENCIAS ADICIONALES EN LA PARTE POSTERIOR.

PROJECT DETAILS

BEST FOR	>	Commercial Areas, Workshops, Garages, Basements	WALK-ON READY	>	8-10 Hours
SUBSTRATES	>	Concrete, Wood, & Tile *see instructions for proper surface preparation	RETURN TO SERVICE	>	24 Hours
KIT COVERAGE	>	Up to 1000 Sq. Ft	# COATS NEEDED	>	1 Coat
APPLICATOR	>	3/8" nap roller *see instructions for squeegee application	APPLY WHEN TEMPERATURE IS	>	BETWEEN 40°-90° F

EASY 3-STEP APPLICATION

1 - PREPARE SURFACE



- Scrub heavily-soiled areas with Rust-Oleum Cleaner & Degreaser (sold separately)
- Etch entire floor with Rust-Oleum Clean & Etch (sold separately), and rinse thoroughly & allow to dry completely
- Diamond grind as an alternate method to etching

2 - BURST-SHAKE-POUR



- Roll side A of pouch toward side B to burst and mix the two components
- Mix contents by shaking pouch back and forth and squeezing the edges and corners for 2-3 minutes
- Cut off one corner and pour out a ribbon of RockSolid Professional directly onto the floor

3 - APPLY COATING



- Trim outer edges
- Apply coating with a roller (see instructions for squeegee application)
- If desired, broadcast RockSolid Professional Decorative Chips and apply RockSolid Clear Topcoat (sold separately)



CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061

800-481-4785 | rustoleum.com/rocksolid

Made in USA | Hecho en E.U.A.

©2017 Rust-Oleum Corporation 76065B 0517

SATISFACTION GUARANTEED

If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-866-765-4474 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.

Category: Floor Coating
VOC < 1 g/L (0.01 lbs/gal)

*Formulated without addition of VOC containing solvent.

*Formulado sin añadir solvente que contenga COV.

U.S. PATENT NUMBER 8,381,903 B2

MOCHA 322761



0 20066 37100 5



SAFETY INFORMATION

BEFORE OPENING THE PACKAGE, READ ALL WARNING LABELS AND DATA SHEETS. FOLLOW ALL PRECAUTIONS.

KEEP OUT OF REACH OF CHILDREN AND ANIMALS.
DO NOT TAKE INTERNALLY.

DANGER! CONTAINS: POLYURAMINE® RESIN, PROPRIETARY RESIN BLEND, TITANIUM DIOXIDE PIGMENT, 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOXYLAMINE, POLYETHERAMINE, BENZYL ALCOHOL. HARMFUL IF INHALED OR INGESTED. CAUSES EYE AND SKIN BURNS. MAY CAUSE ALLERGIC REACTIONS. MAY CAUSE RESPIRATORY IRRITATION, ASTHMA, OR BREATHING DIFFICULTIES IF INHALED. **USE ONLY WITH ADEQUATE VENTILATION.** AVOID BREATHING VAPORS. ENSURE FRESH AIR ENTRY DURING APPLICATION AND DRYING. KEEP AWAY FROM HEAT, SPARKS AND FLAME. VAPOR MAY CAUSE FLASH FIRE. DO NOT SMOKE. IF YOU EXPERIENCE EYE WATERING, HEADACHE OR DIZZINESS, WEAR AN APPROPRIATE, PROPERLY FITTED RESPIRATOR (NIOSH APPROVED) DURING AND AFTER APPLICATION. WEAR PROTECTIVE EYE AND HAND WEAR. WASH THOROUGHLY AFTER HANDLING.

FIRST AID:

EYE CONTACT: IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 20 MINUTES AND GET MEDICAL ATTENTION.

SKIN CONTACT: IN CASE OF SKIN CONTACT, WASH THOROUGHLY WITH SOAP AND WATER. WASH CLOTHING BEFORE REUSE. THOROUGHLY CLEAN OR DESTROY CONTAMINATED SHOES.

INHALATION: IF AFFECTED BY INHALATION OF VAPOR OR SPRAY MIST, REMOVE TO FRESH AIR. IF BREATHING DIFFICULTY PERSISTS OR OCCURS LATER, CONSULT A PHYSICIAN AND HAVE LABEL INFORMATION AVAILABLE.

INGESTION: IF SWALLOWED, GET MEDICAL ATTENTION IMMEDIATELY. DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.

⚠ **WARNING:** CANCER AND REPRODUCTIVE HARM - WWW.P65WARNINGS.CA.GOV.

EMERGENCY TELEPHONE: 1-800-424-9300

INFORMACIÓN DE SEGURIDAD

ANTES DE ABRIR EL ENVASE, LEA TODAS LAS ETIQUETAS DE ADVERTENCIA Y LAS FICHAS TÉCNICAS. TOME TODAS LAS PRECAUCIONES.

MANTENGA EL PRODUCTO FUERA DEL ALCANCE DE LOS NIÑOS Y DE LOS ANIMALES. NO LO INGERA.

ADVERTENCIA: CONTIENE: RESINA POLYURAMINE® COMBINACIÓN PATENTADA DE RESINAS, PIGMENTO DE DIOXIDO DE TITANIO, 3-AMINOMETIL-3,5,5-TRIMETILÓCLOXILAMINA, POLIETERAMINA, ALCOHOL DE BENCÍLICO. SU INHALACIÓN O SU INGESTA SON PERJUDICIALES. CAUSA IRRITACIÓN CUTÁNEA Y OCULAR. PUEDE CAUSAR REACCIONES ALÉRGICAS. EN CASO DE QUE SE INHALE EL PRODUCTO, PUEDE CAUSAR IRRITACIÓN DEL SISTEMA RESPIRATORIO. ASMA O DIFICULTADES PARA RESPIRAR. **USAR SOLO CON VENTILACIÓN ADECUADA.** EVITAR LA INHALACIÓN DE VAPORES. ASEGURE EL INGRESO DE AIRE FRESCO DURANTE LA APLICACIÓN Y SECADO. MANTENGA EL PRODUCTO ALEJADO DEL CALOR, DE LAS CHISPAS Y DE LAS LLAMAS. LOS VAPORES PUEDEN CAUSAR COMBUSTIÓN INSTANTÁNEA. NO FUME. SI EXPERIMENTA LAGRIMO DE LOS OJOS, DOLOR DE CABEZA O MAREOS, UTILICE UN RESPIRADOR APROPIADO, CON UN AJUSTE ADECUADO (APROBADO POR NIOSH) DURANTE Y DESPUÉS DE LA APLICACIÓN. UTILICE PROTECCIÓN ADECUADA PARA LOS OJOS Y MANOS. LÁVESE BIEN DESPUÉS DE MANIPULAR.

PRIMEROS AUXILIOS:

CONTACTO CON LOS OJOS: EN CASO DE CONTACTO CON LOS OJOS, ENJUAGUE DE INMEDIATO CON ABUNDANTE AGUA DURANTE AL MENOS 20 MINUTOS Y OBTENGA ATENCIÓN MÉDICA.

CONTACTO CON LA PIEL: EN CASO DE CONTACTO CON LA PIEL, LÁVE CUIDADOSAMENTE CON AGUA Y JABÓN. LÁVE LA ROPA ANTES DE VOLVER A USARLA. LIMPIE CUIDADOSAMENTE O DESTROYA LOS ZAPATOS CONTAMINADOS.

INHALACIÓN: EN CASO DE QUE SE INHALEN VAPORES O ROCÍO, BUSQUE AIRE FRESCO. SI LA DIFICULTAD PARA RESPIRAR PERSISTE O SI SE PRESENTA LUEGO, CONSULTE CON UN MÉDICO Y LLEVE CONSIGO LA INFORMACIÓN DE LA ETIQUETA.

INGESTIÓN: EN CASO DE INGESTIÓN, BUSQUE ATENCIÓN MÉDICA INMEDIATAMENTE. NO INDUzca EL VÓMITO. BUSQUE ATENCIÓN MÉDICA INMEDIATAMENTE.

⚠ **ADVERTENCIA:** CÁNCER Y DAÑOS REPRODUCTIVOS - WWW.P65WARNINGS.CA.GOV.

TÉLEFONO DE EMERGENCIA: 1-800-424-9300