WORKS GREAT ON MANY SURFACES!

With TESTORS® COLOR SHIFT paint, projects take on multiple colors at once depending on the light or angle. Great for any craft or hobby project. For use on interior surfaces.

Preparation: Clean with soap and water, rinse and let dry.

Directions: For best results, apply over a black colored surface or a black basecoat to create a color shift effect. Shake well, Using a point brush or sponge opplicator, apply 1 or 2 light even costs, a fer wrimingt spatial hiddesant Shimmer over other colored basecoats for different effects. Dries to the touch in 30 minutes and to house in 1.5 hours. Fully dry in 24 hours.

Painting Conditions: Can be used indoors. Use when temperature is between 50 °F and 90 °F and humidity is below 85% to ensure proper drying. Do not apply to surfaces that, when heated, exceed 200 °F. Caution: Protect from freezing.



Made in USA | Hecho en E.U.A. ©2020 Rust-Oleum Corporation 358745 1220



Contains: Glycol ethers. May cause skin imitation. Avoid contact with eyes and skin. Wash thoroughly differ handling. Use with adequate ventilation. [RIS Alb: In case of eye contact, immediately flash eyes with jetherly of water for at least 15 minutes and get medical attention immediately. for skin, wesh thoroughly with scop and water. If svallowed, do not induce vorniting. KEEP OUT OF THE REACH OF CHUDREN. CONFORMS TO ASTIM D-4236. For emergency health information, call your Poison Control Center 1-800/227-1226.

MARNING: Cancer – www.P65Warnings.ca.gov.

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-800-837-8677 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.

WORKS GREAT ON MANY SURFACES!

With TESTORS® COLOR SHIFT paint, projects take on multiple colors at once depending on the light or angle. Great for any craft or hobby project. For use on interior surfaces.

Preparation: Clean with soap and water, rinse and let dry.

Directions: For best results, apply over a block colored surface or a block basecoat ho create a color shift effect. Shake well, Using a point brush or sponge applicator, apply 1 or 2 light even costs, a few minutes apart. Tiny the Indexemt Shimmer over other colored basecoats for different effects. Dries to the touch in 30 minutes and to house in 1.5 hours. Fully dry in 24 hours.

Painting Conditions: Can be used indoors. Use when temperature is between 50 °F and 90 °F and humidity is below 85% to ensure proper drying. Do not apply to surfaces that, when heated, exceed 200 °F. Caution: Protect from freezina.



. TRUSTED QUALITY SINCE 1921. **RUST-OLEUM®** Inagine color shift COLOB SHIFT **TOP COAT - ACRYLIC** PURPLE SUNRISE CAUTION MAY DAUSE EVE IRITATION, Reference the American NET WT 4 fl oz (177 mL)

Contains: Glycol ethers. May cause skin initiation. Avoid contact with eyes and skin. Wash thoroughly after handling. Use with adequate ventilation. FIRST AUC: In case of eye contact, immediately flash eyes with plenty of water for at least 15 minutes and get medical attention immediately. for skin, wash thoroughly with soop and water. If souldweed, do not induce vorniting. KEPP OUT OF THE REACH OF CHILDREN. CONFORMS TO ASTIM D-4236. For emergency headth information, call your Poison Control Center 1-800-222-1222.

MARNING: Cancer – www.P65Warnings.ca.gov.

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-800-837-8677 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.

WORKS GREAT ON MANY SURFACES

When TESTORS® COLOR SHIFT BLACK is applied as a basecoat for the color shift colors, the final result shows projects taking on a color changing effect depending on the light or gnale.

Preparation: Clean with soap and water, rinse and let dry.

Directions: Shake the bottle. Pour paint into a cup. stir. then apply 1 coat to the surface or object using a paint brush or sponge applicator.

Painting Conditions: Can be used indoors. Use when temperature is between 50 °F and 90 °F and humidity is below 85% to ensure proper drying. Do not apply to surfaces that, when heated, exceed 200 °F. Protect from freezing.





Made in USA | Hecho en E II A ©2020 Rust-Oleum Corporation 358749 1220

• TRUSTED QUALITY SINCE 1921 • **RUST-OLEUM®**

Inagine States

Contains: Glycol ethers. May cause skin irritation. Avoid contact with eves and skin. Wash thoroughly after handling. Use with adequate ventilation. FIRST AID: In case of eye contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately: for skin, wash thoroughly with soap and water. If swallowed, do not induce vomiting. KEEP OUT OF THE REACH OF CHILDREN. CONFORMS TO ASTM D-4236 For emergency health information, call your Poison Control Center 1-800-222-1222

WARNING: Cancer – www.P65Warninas.ca.aov.

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-800-837-8677 for a product replacement or a full refund of the purchase price. Refer to product number and batch code.

color \mathbf{shift} COLOB SHIFT BASECOAT - ACRYLIC GLOSS BLACK CAUTION! MAY CAUSE EYE IRRITATION. Refer to side/back panel.

NET WT 4 fl oz (177 mL)