



# RUST-OLEUM® CHALKED CLEAR PROTECTIVE TOPCOAT

## DESCRIPTION AND USES

Rust-Oleum® Chalked Clear Protective Topcoat enhances any Chalked Ultra Matte paint finish and adds protection to the surface. The clear topcoat can be applied to maintain and enhance any Chalked project. Easier application and more durability compared to traditional furniture waxes. **For interior use only.**

## PRODUCT

SKU	DESCRIPTION (Quart)
287722	Chalked Clear

## PRODUCT APPLICATION

### READ ALL DIRECTIONS BEFORE BEGNNING PROJECT

Use when temperature is between 50°F (10°C) and 90°F (32°C) and humidity is below 85% to ensure proper drying.

### SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with soap and water and let dry. Remove loose paint and rust with a wire brush or sandpaper. To enhance adhesion, lightly sand glossy or porous surfaces. Remove any wax by lightly wiping the surface with mineral spirits.

**WARNING!** If you scrape, sand or remove old paint from any surface, you may release lead paint dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## PRODUCT APPLICATION (cont.)

### APPLICATION

Apply only when air and surface temperatures are between 50-90°F (10-32°C) and humidity is below 85% to ensure proper drying. Stir thoroughly. Do not shake the can. Thinning is not required. Avoid painting in direct sunlight or on hot surfaces.

Use a high quality synthetic brush. Roller application is not recommended. Avoid excessive brushing as this will reduce film thickness and protection. Wait for the base coat to dry for at least 8 hours before applying the Clear Protective Topcoat. Use light even brush strokes to ensure even flow and the smoothest finish. Apply 1-2 even coats. Wait 2 hours between each coat.

### DRY & RECOAT

Dry and recoat times are based on 70°F (21°C) and 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in 30 minutes, to handle in 1 hour and is fully dry in 4 hours. It can be recoated after 2 hours.

### CLEAN-UP

Clean brush and other application tools immediately with soap and water.

<small>TRUSTED QUALITY SINCE 1921</small> <b>RUST-OLEUM®</b> <i>Chalked</i>	<b>TECHNICAL DATA</b>	<b>CHD-03</b>
<b>RUST-OLEUM® CHALKED CLEAR PROTECTIVE TOPCOAT</b>		

**PHYSICAL PROPERTIES**

		CHALKED CLEAR PROTECTIVE TOPCOAT
<b>Resin Type</b>		Acrylic Urethane
<b>Pigment Type</b>		NA
<b>Solvents</b>		Water, Glycol Ethers
<b>Weight</b>	<b>Per Gallon</b>	8.5 lbs.
	<b>Per Liter</b>	1.02 kg
<b>Solids</b>	<b>By Weight</b>	30.5%
	<b>By Volume</b>	28.8%
<b>Volatile Organic Compounds</b>		<250 g/l
<b>Recommended Dry Film Thickness (DFT) per Coat</b>		1.0-2.0 mils 25-50µ
<b>Wet Film to Achieve DFT (Unthinned material)</b>		4.0-6.0 mils (100-150µ)
<b>Practical Coverage at Recommended DFT (assume 15% material loss)</b>		110-150 sq.ft./qt. (9.7-13.2 m <sup>2</sup> /l)
<b>Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity</b>	<b>Touch</b>	30 minutes
	<b>Handle</b>	1-2 hour
	<b>Recoat</b>	2hour
<b>Shelf Life</b>		3 years
<b>Flash Point</b>		>200°F (93°C)
<b>Safety Information</b>		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.