



RUST-OLEUM® SPECIALTY CAMOUFLAGE SPRAYS

DESCRIPTION AND USES

Rust-Oleum® Specialty Camouflage Sprays are designed to provide a non-reflective finish on hunting and sporting equipment. Various colors can be combined in a variety of patterns to blend with any terrain. Camouflage Sprays are suitable for use on vehicles, tree stands, decoys, blinds, boats and equipment.

TIP: Some plastics made of polyethylene such as plastic storage containers are manufactured in a way that may hinder maximum paint adhesion. Test paint in a hidden area first. Not for use on galvanized metal.

PRODUCTS

SKU	DESCRIPTION (Flat)
1916830	Black
1917830	Khaki
1918830	Earth Brown
1919830	Deep Forest Green
1920830	Army Green
263653	Sand

PRODUCT APPLICATION

Use outdoors or in a well ventilated area. Use when temperature is between 50-90°F (10-32°C) and humidity is below 65% to ensure proper drying. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

SURFACE PREPARATION

ALL SURFACES: Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Mold and mildew must be cleaned with a chlorinated cleaner or bleach solution. Rinse with fresh water and allow to thoroughly dry.

STEEL: Scrape and wire brush or power tool clean to remove loose rust, scale, and deteriorated coatings. Use 7569838 Red Primer for sound rusted or clean metal before application of a finish coat.

PREVIOUSLY COATED: Previously coated surfaces must be sound and in good condition. Smooth, hard, or glossy surfaces should be scarified by sanding to create a surface profile.

PRODUCT APPLICATION (cont.)

SURFACE PREPARATION (cont.)

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead paint dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold can upright 12-16" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying.

Apply a base coat of one color first. Then use leaves and twigs as stencils. Apply a base coat of color. Lay the leaves and twigs randomly over the object you are painting. Spray over the items using three or more colors. **Do not use near open flame.**

DRY & RECOAT

Dry and recoat times are based on 70°F (21°C) and 50% relative humidity. Dries to the touch in 20 minutes, to handle in 1 hour and can be recoated within 1 hour or after 24 hours. It is fully dry in 24 hours. Note: On plastic, maximum paint adhesion and durability is achieved in 5-7 days.

CLEAN-UP

Wipe off tip before storing. Clean up wet paint with xylene or mineral spirits. Throw away empty can in trash pick-up. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.



**RUST-OLEUM® SPECIALTY
CAMOUFLAGE SPRAYS**

PHYSICAL PROPERTIES

		SPECIALTY CAMOUFLAGE SPRAYS
Resin Type		Acrylic Modified Alkyd
Pigments		Varies with color
Solvents		Acetone, Toluene, Xylene
Fill Weight		12 ounces
MIR		0.80 Max
Practical Coverage at Recommended DFT (assumes 15% material loss)		Approximately 6.0-7.0 sq.ft./can (0.55-0.65 m ² /can)
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	20 minutes
	Handle	1 hour
	Recoat	Within 1 hour or after 24 hours
Dry Heat Resistance		200°F (93°C)
Shelf Life		5 years
Flash Point		-156°F (-104°C)
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.