



RUST-OLEUM® SPECIALTY POLISHED METALLIC

DESCRIPTION AND USES

Rust-Oleum® Specialty Polished Metallics are a premium spray paint that create a bright reflective finish and deliver high shine on surfaces made of metal, plastic, glass, ceramic and more. Great for use on interior and exterior surfaces. Works best on smooth, unscratched surfaces.

PRODUCTS

SKU	DESCRIPTION (Aerosol)
365136	Rose Gold
365137	Champagne
365138	Copper
365139	Gunmetal Gray

PRODUCT APPLICATION

READ ALL DIRECTIONS BEFORE BEGINNING PROJECT

SURFACE PREPARATION

Clean surfaces with soap and water, rinse and let dry.

PRIMING

Use of a Rust-Oleum lacquer as a primer provides superior adhesion and a smooth surface for painting. Do not use a matte or enamel primer. The coating will wrinkle.

PRODUCT APPLICATION (cont.)

APPLICATION

Do not apply to a rough or matte surface. Shake can vigorously for one minute after mixing ball begins to rattle. Shake often during use. If mixing ball fails to rattle, DO NOT STRIKE CAN. Contact Rust-Oleum.

Hold can upright 10-16" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply 2 or more light coats a few minutes apart.

DRY TIMES

Dry and recoat times are based on 70°F (21°C) – 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in 20 minutes and to handle in 1 hour. Fully dry in 24 hours. May recoat at anytime. Apply a clear top coat for maximum durability.

CLEAN UP

Wipe off tip before storing. Clean up wet paint with xylol or acetone. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

CLOGGING

If valve clogs, twist and pull off spray tip and rinse it in a solvent such as acetone. Do not stick pin or other object into the stem.



**RUST-OLEUM® SPECIALTY
POLISHED METALLIC**

PHYSICAL PROPERTIES

		POLISHED METALLIC
Resin Type		CAB
Pigment Type		Shading paste
Solvents		Acetone, MAK
MIR		0.95 Max
Fill Weight		10 oz.
Practical Coverage (assume 15% material loss)		Approximately 8 sq.ft./can
Dry Times at 77°F (25°C) and 50% Relative Humidity	Touch	10 minutes
	Handle	15 minutes
	Recoat	Anytime
	Full Cure	30 minutes
Shelf Life		3 years
Flash Point		-141°F
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

