



STOPS RUST® ENAMEL SPRAYS

DESCRIPTION AND USES

Rust-Oleum® Stops Rust® Enamel Sprays are designed to provide a durable protective coating with excellent rust prevention, and excellent resistance to abrasion, fading, chipping, and dulling. These sprays apply easily, provide excellent coverage and dry fast to a tough attractive finish. Rust-Oleum Stops Rust Enamel Sprays are ideal for ferrous, non-ferrous metal and wood surfaces. It features a comfort tip with a wider finger pad to reduce fatigue caused by continuous spraying and an any-angle tip which allows you to spray at any angle. Not for use on galvanized metal.

PRODUCTS

SKU	DESCRIPTION (12 Ounce Aerosol)
7776830	Flat Black
7790830	Flat White
214085	Flat Brown
312821	Flat Red Rock
366346	Flat Smoke Gray
241238	Satin Dark Taupe
276271	Satin French Beige
7772830	Satin Putty
7777830	Satin Black
248633	Satin Indigo
276270	Satin Sapphire
350337	Satin Vintage Teal
7758830	Satin Almond
7774830	Satin Chestnut Brown
241239	Satin Dark Brown
7767830	Satin Redwood
312819	Satin Coastal Gray
350418	Satin Parisian Gray
7749830	Satin Dark Hunter Green
7732830	Satin Hunter Green
7720830	Satin Sage
7737830	Satin Spruce Green
300115	Satin Classic Navy
248632	Satin America Red
248635	Satin Cabernet
347023	Satin Fire Red
7760830	Satin Heritage Red
7793830	Satin Shell White
7791830	Satin White
365143	Satin Driftwood
365144	Satin Citrus Yellow
365145	Satin Peaceful Blue
371671	Satin Brick Red
371673	Satin Canyon Green
7797830	Semi-Gloss White
7798830	Semi-Gloss Black
7754830	Semi-Gloss Anodized Bronze
7722830	Gloss Harbor Blue

PRODUCTS (cont.)

SKU	DESCRIPTION (12 Ounce Aerosol)
7723830	Gloss Navy
7724830	Gloss Sail Blue
7727830	Gloss Royal Blue
7731830	Gloss Grass Green
7733830	Gloss Dark Hunter Green
7738830	Gloss Hunter Green
7747830	Gloss Sunburst Yellow
7762830	Gloss Sunrise Red
7763830	Gloss Carnival Red
7765830	Gloss Regal Red
7768830	Gloss Burgundy
7770830	Gloss Almond
7771830	Gloss Sand
7775830	Gloss Leather Brown
7779830	Gloss Black
7783830	Gloss Pewter Gray
7784830	Gloss Charcoal Gray
7786830	Gloss Smoke Gray
7789830	Gloss Canvas White
7792830	Gloss White
7794830	Gloss Antique White
214084	Gloss Orange
214086	Gloss Charleston Green
248567	Gloss Merlot
248568	Gloss Cherry
248569	Gloss Emerald Green
248630	Gloss French Roast
249032	Gloss Khaki
250702	Gloss Pure White
262661	Gloss Dark Walnut
267112	Gloss Kona Brown
269292	Gloss Maui Blue
277239	Gloss Lagoon
284678	Gloss Light Turquoise
298537	Gloss Tuscan Sun
312817	Gloss Cambridge Stone
312818	Gloss Deep Slate
350419	Gloss Candy Pink
350420	Gloss Purple
347024	Gloss Cobalt Blue
347026	Gloss Poppy Pink
347027	Gloss Deep Mint
347025	Gloss Willow Green
353010	Gloss Island Coral
320263	Gloss Seaside
365146	Gloss Laurel Green
371669	Gloss Arctic White
371670	Gloss Ink Black



**STOPS RUST®
ENAMEL SPRAYS**

PRODUCT APPLICATION (cont.)

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Previously coated surfaces must be sound and in good condition. Smooth, hard, or glossy finishes should be scarified by sanding to create a surface profile.

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead paint dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRIMING

Use of a Stops Rust Primer provides added corrosion protection, superior adhesion and hiding and is especially recommended for bare wood and metal. The following primers are recommended.

7769830	Rusty Metal Primer
7780830	Clean Metal Primer
2081830	Light Gray Auto Primer
2067830	Red Auto Primer
2089830	Dark Gray Auto Primer

PRODUCT APPLICATION (cont.)

APPLICATION

Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is between 50-90°F (10-32°C) and humidity is below 65% to ensure proper drying. Do not apply to surfaces that, when heated, exceed 200°F (93°C) or galvanized metal. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

Shake can vigorously for one minute after mixing ball begins to rattle. If mixing ball fails to rattle **DO NOT STRIKE CAN.** Contact Rust-Oleum. Shake often during use. Hold can upright 10-16" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply 2 or more light coats a few minutes apart to avoid runs and sags. Do not use near open flame.

DRY AND RECOAT TIMES

Based on 70°F (21°C) 50% relative humidity. Allow more time at cooler temperatures. Dries tack free in 2-4 hours, to handle in 5-9 hours and fully dry in 24 hours. Primers may be top coated immediately. Apply a second coat or clear coat within 1 hour or after 48 hours.

CLEAN UP

Wipe off tip before storing. Clean up wet paint with Xylene or mineral spirits. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

CLOGGING

If valve clogs, twist and pull off spray tip and rinse it in a solvent such as mineral spirits. Do not stick a pin or other objects into the stem.

	TECHNICAL DATA	SRT-01
	STOPS RUST® ENAMEL SPRAYS	

PHYSICAL PROPERTIES

		ENAMEL SPRAY FINISHES
Resin Type		Oil modified Alkyd
Pigment Type		Varies with color
Solvents		Acetone, N-Butyl Acetate, Aromatic Hydrocarbons
MIR		0.95 Max
Fill Weight		12 ounces
Recommended Dry Film Thickness (DFT) Per Coat		1.0-2.0 mils (25-50μ)
Practical Coverage at Recommended DFT (assumes 15% material loss)		6-10 sq. ft./can (0.6-0.9 m ² /can)
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	2-4 hours
	Handle	5-9 hours
	Recoat	Before 1 hour or after 48 hours
Dry Heat Resistance		200°F (93°C)
Shelf Life		5 years
Flash Point		-156°F (-104°C)
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.