

DESCRIPTION AND USES

Furniture Transformations™ is a process designed to re-finish furniture with a four step coating system. Furniture Transformations is suitable for use on dressers, armoires, bath vanities, end tables, entertainment centers, desks, tables & chairs, bannisters & moldings, children’s furniture and mantles.

Furniture Transformations uses an adhesive bond coat, decorative glaze (optional), and a protective clear top coat to create a highly durable finish. No stripping or sanding is required.

Available in 23 finish colors. The color appropriate kit must be tinted at the paint counter at time of purchase.

An instructional pamphlet is included in the Furniture Transformations kit. Read the pamphlet in its entirety before beginning the project.

Visit [Rustoleum Transformations.com](http://RustoleumTransformations.com) to view the instructional video to aid with the process and coating application. The kit also includes:

- Deglosser (266210)
- Bond Coat (266045)
- Decorative Glaze (266138)
- Protective Top Coat (266226)
- Decorative Glazing Cloths
- Scrub Pad
- Glazing Cloth
- Scrub Pad
- Instructional Pamphlet

Items not supplied with the kit which need to be purchased separately:

- (3) 2" Synthetic Paint Brushes – Premium Quality Angled or Straight
- (3) Disposable Paint Containers
- Smooth Painter’s Tape (2" size)
- Drop Cloths
- Disposable Gloves
- Lint-Free Rags

Suggested Items Needed:

- Screwdriver or Cordless Screwdriver
- Plastic Wood Filler and Putty Knife (if filling hardware holes)
- Plastic Cups or Baggies (for hardware)
- Sketch Paper and Marker

PRODUCTS

| SKU | Description |
|--------|--------------------------|
| 266043 | Furniture Coating System |

PRODUCT APPLICATION

Refer to the printed instructions for the complete, step by step, procedure on application of the materials.

IMPORTANT: Apply when air (ambient) temperature is 50-90°F (10-35°C) and relative humidity is below 60%.

SURFACE PREPARATION

Remove all dirt, grease, oil, and chemical contamination by washing the surfaces with a commercial detergent or other suitable cleaner. Rinse thoroughly with fresh water and allow to fully dry. All surfaces must be dry at the time of application.

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead paint dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

DEGLOSS

Wearing gloves fold the scrub pad in half and apply the Deglosser liberally onto the pad. Scrub the entire surface to remove all dirt and contaminants.

IMPORTANT: When deglossing wooden cabinetry, follow the grain pattern of the wood. Avoid scrubbing in a circular motion.

After deglossing, wipe down the surface with a damp cloth to remove any traces of the cleaner. Finish by wiping the surface with a clean, lint-free cloth. Wipe up any spilled Deglosser with a clean cloth. After removing the Deglosser, let the surface dry for 1 hour before applying the bond coat.

TECHNICAL DATA

FURNITURE TRANSFORMATIONS™

PRODUCT APPLICATION (cont.)

APPLICATION OF BOND COAT

For best results, apply in a clean, dust free area. Avoid application in direct sunlight. The Bond Coat is formulated to provide maximum adhesion to wood, laminate, and melamine surfaces. Two coats of Bond Coat are recommended.

Before applying the Bond Coat, wipe down the furniture one more time with a clean, lint-free cloth to remove any residue still left on the surface. If the furniture piece is an immovable object such as a bathroom vanity, mask off the outside edges of the cabinet and inside edges of the cabinet frame. Thoroughly mix the Bond Coat using a stir stick and pour a portion into a clean disposable container. For best results, always brush in the direction of the grain. Use up-and-down strokes on vertical surfaces and side-to-side strokes on horizontal surfaces. Apply the Bond Coat with a light, even coat. Avoid applying a heavy coat as a heavy coat will run. Remove an excess build up with the paint brush. Allow the first coat to dry for 2-3 hours. Apply a second coat using the same technique. If refinishing a furniture piece that has two sides such as a cabinet door, apply the Bond Coat to the back side of the doors first. Allow the Bond Coat to dry 2-3 hours between coats and before application of the Decorative Glaze (optional). Dry times may vary depending on temperature and humidity.

APPLICATION OF DECORATIVE GLAZE (optional)

The Decorative Glaze enhances the look by accenting the Bond Coat color. Thoroughly mix the Decorative Glaze using a stir stick. Pour a portion into a clean, disposable container. Apply the Decorative Glaze with the Glaze Cloth to the surface. Be sure to work in manageable sections. Gather two pieces of Decorative Glaze into a ball and wipe the surface in the direction of the grain to remove the glaze to your desired look. Light pressure will leave more Decorative Glaze whereas more pressure will remove more Decorative Glaze. For best results, rotate and re-fold the cloth often. If dissatisfied, while wet, wipe completely clean with a damp cloth and repeat the glazing process. Allow the Decorative Glaze to dry for a minimum of 8 hours before applying the Protective Top Coat.

PRODUCT APPLICATION (cont.)

APPLICATION OF THE TOPCOAT

The topcoat is formulated to provide excellent stain and scratch resistance.

Thoroughly mix the Protective Topcoat with the stir stick. Using a 2" synthetic brush, apply an even layer of the Protective Topcoat to the entire surface. Following the same procedure when applying the Bond Coat, use up-and-down strokes for vertical surfaces and side-to-side strokes for horizontal surfaces. Be sure to work in the direction of the grain.

IMPORTANT: It is important to avoid over-brushing in previously coated areas. If build-up occurs in recessed areas, simply wipe out with a clean, dry brush.

Allow the Protective Topcoat to dry undisturbed for 12 hours. Keep windows closed, pets away and ceiling fans off. Avoid using cleaners on new surface for 7 days. After 7 days, the surface will be completely cured and ready for cleaning.

CLEAN-UP

Clean up equipment and tools with soap and water.

TECHNICAL DATA

FURNITURE TRANSFORMATIONS™

PHYSICAL PROPERTIES

| | | DEGLOSSER (#266210) | BOND COAT (#266045) | TOP COAT (#266226) |
|--|----------------------|---|--|---|
| Resin Type | | None | Acrylic / Urethane | Acrylic / Urethane |
| Pigment Type | | None | Titanium Dioxide, Mica | Titanium Dioxide, Mica |
| Solvents | | Water | Water | Water |
| Weight | Per Gallon | 8.40 lbs. | 9.80-11.90 lbs. | 8.47 lbs. |
| | Per Liter | 1.01 kg | 1.17-1.43 kg | 1.05 kg |
| Solids | By Weight | 4.8% | 40-58% | 29% |
| | By Volume | 4.5% | 30-42% | 27% |
| Volatile Organic Compounds | | <465 g/l (3.85 lbs./gal.) | <85 g/l (0.70 lbs./gal.) | <272 g/l (2.3 lbs./gal.) |
| Recommended Dry Film Thickness (DFT) Per Coat | | NA | 3.5-4.0 mils (87.5-100µ) | 3.0 mils (75µ) |
| Wet Film to Achieve DFT (unthinned material) | | NA | 9.0-10.0 mils (225-250µ) | 11.0 mils (275µ) |
| Practical Coverage at Recommended DFT (assumes 15% material loss) | | NA | 35 sq.ft./quart (0.86 m ² /l) | 35 sq.ft./pint (0.86 m ² /l) |
| Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity | Dry to Recoat | 1 hour | 2-3 hours | NA |
| | Dry Hard | NA | NA | 12 hours |
| | Full Cure | NA | NA | 7 days |
| Shelf Life | | NA | 3 years | 3 years |
| Storage | | Store in a dry area between 40-100°F (4-38°C) | | |
| Flash Point | | 220°F (105°C) | 215°F (102°C) | 215°F (102°C) |
| Safety Information | | For additional information, see SDS | | |

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.