



**ROLL-A-TEX
TEXTURE ADDITIVE FOR PAINT**

DESCRIPTION AND USES

Roll-A-Tex Texture Additive for Paint is a blend of additives and texturing materials that, when added to paint, produces a durable and even-flowing texture with excellent covering and “fill-in” qualities. It is suitable for brick, cinder block, concrete, drywall, plaster, roofs, stucco and wood. Texture Additive for Paint is available in three different blends.

Fine Texture is designed for use on interior or exterior surfaces providing a “one-step” texture for any new construction surface. This easy-to-apply texture covers hairline cracks on repaired surfaces.

Medium Texture is designed for interior or exterior surfaces providing excellent repair qualities to fill and cover moderately flawed and cracked surfaces. It may be used on smooth surfaces where a pronounced textured look is desired or with extensively cracked walls that require extra cover-up.

Coarse Texture is excellent for interior or exterior surfaces where a higher degree of “fill-in” and covering qualities are required. It is suitable for use on large cracks and extensively repaired surfaces or wherever a more defined texture is desired. It provides excellent texturing to cinder blocks and brick in only one coat.

PERFORMANCE CHARACTERISTICS

- Permanently fills and covers cracks and flaws
- Eliminates the need for tedious and time consuming crack repairs
- Hides building defects
- Covers repaired surfaces in one coat without priming
- Prevents soaking, blotching and uneven paint coloring
- Restores and beautifies in one coat with a roller or brush

PRODUCTS

SKU	Description
22232	Fine Texture (1-Pound)
22233	Medium Texture (1-Pound)
22234	Coarse Texture (1-Pound)

PRODUCT APPLICATION (cont.)

INSTRUCTIONS FOR USE

Apply only when air, material, and surface temperatures are between 50-90°F (10-32°C) and the relative humidity is below 85%. While mixing, wear a NIOSH approved dust mask. In a separate container, add the contents of the package to one gallon of any paint. Add less for surfaces in good condition and more for surfaces that require more hiding and texturing. Thoroughly mix to ensure that the contents are incorporated. For best results, keep the mixture as thick as possible for best coverage. Use a 3/8” to 3/4” nap roller cover. Apply with light pressure and roll out on the surface. Less rolling will produce a better texture. A second coat of paint may be applied after partial or complete drying for greater hiding and a better texture.

CLEAN-UP

Clean hand and application tools with warm soapy water.

**TECHNICAL DATA****ROLL-A-TEX TEXTURE ADDITIVE FOR PAINT****PHYSICAL PROPERTIES**

Physical Properties		ROLL-A-TEX TEXTURE ADDITIVE FOR PAINT
Composition		Zinc Oxide, Limestone
Weight	Per Gallon	20.6 lbs.
	Per Liter	2.50 kg
Solids	By Weight	100.0%
	By Volume	100.0%
Volatile Organic Compounds		0 g/l
Shelf Life		5 years
Practical Coverage	Coarse – 80 to120 square feet – depending on product application	
	Medium – 100to120 square feet – depending on product application	
	Fine – 150 to200 square feet – depending on product application	
Flash Point		200°F (93°C)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.