



**SUREGRIP®
SPRAY-ON PASTE ACTIVATOR**

DESCRIPTION AND USES

Zinsser® SureGrip® Spray-On Paste Activator is designed to use on Pre-pasted borders and wallpaper. It is a convenient, ready-to-use, effective way to activate paste on all pre-pasted borders and wallpaper, and is suitable for use over painted or primed surfaces.

PRODUCT FEATURES

- Activates paste on pre-pasted paper
- Convenient, easy and fast
- Use over painted or primed surface
- Clear, no-staining, no odor
- Conditions paper without over-wetting
- Easy water clean-up

PRODUCTS

SKU	Container Size
2986	32 Ounces

PRODUCT APPLICATION

SURFACE PREPARATION

Surfaces should be clean, dry, sound and free of dust, grease, wax, oil, old wallcovering adhesive, mold and mildew and other residue. Inspect the surface for paint bonding, loose wallcoverings, damaged wallboard or plaster. Remove old or loose wallcovering and residual wallcovering adhesive with DIF® Wallpaper Stripper. Repair unsound surfaces. Seal loose paint or damaged drywall and fully cured skim coats with Gardz® High Performance Sealer as needed.

PRODUCT APPLICATION (cont.)

ENVIRONMENTAL CONDITIONS

The recommended temperature range for application is between 65-85°F (18-29°C) with less than 50% relative humidity.

APPLICATION

SureGrip Spray-On Paste Activator is ready to use. **Do Not Dilute.** Place wallpaper or border on a flat surface with the pasted side facing up. Hold spray nozzle 10-12 inches from the paper and spray generously over the entire surface, making sure the edges are covered. Book and hang according to the wallpaper or border manufacturer's instructions.

COVERAGE

SureGrip Spray-On Paste Activator will hang up to 8-10 spools of 6" border or 1 double roll (55 sq.ft.) of wallpaper. Spread rate may differ with various backings.

CLEAN-UP

After each sheet is hung, remove excess adhesive with a clean, damp sponge. Blot dry with a soft towel.

**TECHNICAL DATA****SUREGRIP® SPRAY-ON PASTE ACTIVATOR****PHYSICAL PROPERTIES**

		SUREGRIP SPRAY-ON PASTE ACTIVATOR
Resin Type		Methyl Hydroxy Ethyl Cellulose
Solvents		Water
Appearance		Clear
Odor		Mild
Volatile Organic Compounds		<75 g/l (0.62 lbs./gal.)
Practical Coverage at Recommended DFT (assumes 15% material loss)		8-10 spools of 6" border or 1 double roll (55 sq.ft.) of wallpaper
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Full Cure	24 hours
Shelf Life		3 years
Flash Point		>200°F (93°C)
Safety Information		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.