



PROJECT DETAILS

BEST FOR	Garages, Basements, Workshops, Laundry Rooms, Mud Rooms and More	WALK-ON READY	8-10 Hours
SUBSTRATES	Concrete, Wood, Drywall, Tile *See instructions for proper surface preparation	DRIVE READY	24 Hours
KIT COVERAGE	Up to 200-250 Sq. Ft.	# COATS NEEDED	1 Coat
# GARAGE	1 Car	APPLY WHEN TEMPERATURE IS	BETWEEN 40°-90° F

GARAGE

FLOOR COATING KIT



11 Hawthorn Place, Vernon Hills, IL 60061
1-800-451-4785
MADE IN THE USA
SATISFACTION GUARANTEED
If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-866-765-4474 for a full refund of the purchase price. Refer to product number and batch code on bottom of box.

rustoleum.com
1-866-765-4474

Category: Floor Coating
VOC < 1 g/L (0.01 lb/gal)
*Formulated without addition of VOC containing solvent.
*Formulado sin aditivo solvente que contenga COV.
U.S. PATENT NUMBER 8,381,983 B2

©2015 Rust-Oleum Corporation
60758-0215

GARAGE FLOOR GRAY 280891



SAFETY INFORMATION

BEFORE OPENING THE PACKAGE, READ ALL WARNING LABELS AND DATA SHEETS. FOLLOW ALL PRECAUTIONS. KEEP OUT OF REACH OF CHILDREN AND ANIMALS. DO NOT TAKE INTERNALLY.

WARNING: CONTAINS POLYURETHANE* RESIN, PROPRIETARY DEEN BLEND, TITANIUM DIOXIDE PIGMENT, 3-AMINOMETHYL-3,5-DIMETHYLBENZYLAMINE, POLYETHERAMINE, BENZYL ALCOHOL.
HARMFUL IF INHALED OR INGESTED. CAUSES SKIN AND EYE IRRITATION. MAY CAUSE ALLERGIC REACTIONS. MAY CAUSE RESPIRATORY IRRITATION, ASTHMA, OR BREATHING DIFFICULTIES IF INHALED.

USE ONLY WITH ADEQUATE VENTILATION. KEEP CHILDREN AND PETS AWAY FROM THE COATING. VAPOR MAY CAUSE FLASH FIRE. DO NOT SMOKE.

FIRST AID:
EYE CONTACT: IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH EXCESS OF WATER FOR AT LEAST 20 MINUTES AND GET MEDICAL ATTENTION.

SKIN CONTACT: IN CASE OF SKIN CONTACT, WASH THOROUGHLY WITH SOAP AND WATER. WASH CLOTHING BEFORE REUSE. THOROUGHLY CLEAN OR DESTROY CONTAMINATED SHIRTS.

INHALATION: IF AFFECTED BY INHALATION OF VAPOR, STOP WORK IMMEDIATELY, MOVE TO FRESH AIR, AND BREATHING DIFFICULTY PERSISTS OR OCCURS LATER, CONSULT A PHYSICIAN AND HAVE LABEL INFORMATION AVAILABLE.

INGESTION: IF SWALLOWED, GET MEDICAL ATTENTION IMMEDIATELY. DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.

PRECAUTIONS: **WARNING:** THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

EMERGENCY TELEPHONE: 1-800-424-2380

INFORMACIÓN DE SEGURIDAD

ANTES DE ABRIR EL ENVASE, LEA TODAS LAS ETIQUETAS DE ADVERTENCIA Y LAS HOJAS DE DATOS. SIGA TODAS LAS PRECAUCIONES. MANTÉNGALO FUERA DEL ALCANCE DE LOS NIÑOS Y DE LOS ANIMALES.

ADVERTENCIA: CONTIENE RESINA POLIURETANICA*, COMBINACION PATENTADA DE RESINA, PIGMENTO DE DIOXIDO DE TITANIO, 3-AMINOMETIL-3,5-DIMETILBENZILAMINA, POLIETERAMINA, ALCOHOL DE BENILOLO.
SU INHALACION O INGESTION EN PERSONAS PUEDE CAUSAR REACCIONES ALERGICAS, ENFOQUE DE VISION, EN LA PERSONA, PUEDE CAUSAR IRRITACION DEL SISTEMA RESPIRATORIO, ASMA O DIFICULTADES PARA RESPIRAR.

UTILICE EL PRODUCTO SOLO CON LA VENTILACION ADECUADA. MANTENGA EL PRODUCTO FUERA DEL ALCANCE DE LOS NIÑOS Y LAS ANIMALES. LOS VAPORES PUEDEN CAUSAR COMBUSTION INSTANTANEA. NO FUMAR.

PRIMEROS AUXILIOS:
CONTACTO CON LOS OJOS: EN CASO DE CONTACTO CON LOS OJOS, ENJUAGUE CON ABUNDANTE AGUA CORRIENTE AL MENOS 20 MINUTOS Y BUSQUE ATENCION MEDICA.

CONTACTO CON LA PIEL: EN CASO DE CONTACTO CON LA PIEL, LAVE CUIDADOSAMENTE CON AGUA Y JABON. LAVE LA ROPA ANTES DE VOLVER A USARLA. LAVE SU ROPAJERO Y DESTIENDA LOS ZAPATOS CONTAMINADOS.

INHALACION: EN CASO DE QUE SE INHALEN VAPORES O GASEO, BUSQUE ARE FRESCO. SI LA DIFICULTAD PARA RESPIRAR PERSISTE O SI SE PRESENTAN SINTOMAS DE ENFERMEDAD, BUSQUE ATENCION MEDICA INMEDIATAMENTE. NO INDUCE EL VOMITO. BUSQUE ATENCION MEDICA INMEDIATAMENTE.


INGESTION: EN CASO DE INGESTION, BUSQUE ATENCION MEDICA INMEDIATAMENTE. ESTE PRODUCTO ES CONOCIDO EN EL ESTADO DE CALIFORNIA COMO CAUSANTE DE CANCER Y DEFECTOS DE NACIMIENTO U OTROS DAÑOS REPRODUCTIVOS.

TELEFONO DE EMERGENCIA: 1-800-424-2380

EASY MIX BURST POUCH!



BURST




TIGHTLY ROLL POUCH UNTIL SEAL BURSTS ALLOWING CONTENTS TO MIX.

SHAKE



MIX CONTENTS BY SHAKING POUCH BACK AND FORTH AND ROCKETING THE SIDES AND CORNERS FOR 2-3 MINUTES.

POUR



CUT CORNER & POUR FOLLOW APPLICATION INSTRUCTIONS INCLUDED IN KIT.

GARAGE


FLOOR COATING KIT

POLYURETHANE* INNOVATION

The revolutionary RockSolid Polycuramine® combines key attributes from multiple chemistries into one. This creates an indestructible, self-leveling, fast curing, extreme high gloss coating system, that can be completed in one day.

20X STRONGER THAN EPOXY

POLYURETHANE* TECHNOLOGY



PENETRATES AND ATTACHES TO CONCRETE ON A MOLECULAR LEVEL FORMING MULTIPLE BONDING POINTS

SELF-LEVELING

FLEXES & MOVES WITH THE CONCRETE TO PREVENT CRACKING OR PEELING

TRUSTED QUALITY SINCE 1921

RUST-OLEUM®

ROCKSOLID®

THE WORLD'S TOUGHEST COATINGS™

GARAGE

FLOOR COATING KIT

INDUSTRIAL-GRADE POLYURETHANE*

KIT INCLUDES:



INSTRUCTIONS



CONCRETE ETCH



FOAM ROLLER



DENIM DECORATIVE CHIPS



POLYURETHANE BURST POUCH

OTHER SUPPLIES NEEDED:

OPTIONAL:

ROLLER FRAME

EXTENSION POLE

STIFF BRISTLED BROOM OR SCRUB BRUSH

3" PAINT BRUSH

ANTI-SKID ADDITIVE

HEAVY-DUTY DEGREASER

CONCRETE PATCH AND REPAIR

NO PEEL GUARANTEE

TRUSTED QUALITY SINCE 1921

RUST-OLEUM®

ROCKSOLID®

THE WORLD'S TOUGHEST COATINGS™

1 CAR GARAGE KIT

GARAGE

FLOOR COATING KIT

INDUSTRIAL-GRADE POLYURETHANE*

20X STRONGER THAN EPOXY

DRIVE ON 24 HOURS



EXTREME HIGH GLOSS

NO HOT TIRE PICKUP

CHEMICAL RESISTANT

LOW ODOR & VOC FREE*

GRAY SHOWN WITH DENIM DECORATIVE CHIPS

NET WT 76 FL OZ (2.25L)
1.6 LBS (726g)

KIT COVERS: UP TO 200-250 SQ. FT. ONE CAR GARAGE

WARNING: VAPOR HARMFUL. READ CAREFULLY OTHER CAUTIONS ON BACK PANEL.
ADVERTENCIA: VAPORES NOCIVOS. LEA ATENTAMENTE LAS ADVERTENCIAS ADICIONALES EN LA PARTE POSTERIOR.

FEATURES & BENEFITS

DRIVE ON 24 HOURS	20X STRONGER THAN EPOXY
NO HOT TIRE PICK UP	EXTREME HIGH GLOSS
IMPERVIOUS TO CHEMICALS	SELF-LEVELING AND BUILDABLE
ECO SAFE	LOW ODOR AND ZERO VOC*

EASY MIX BURST POUCH

GARAGE

FLOOR COATING KIT


EASY 3-STEP APPLICATION

1 PREPARE SURFACE




- Scrub heavily-soiled areas
- Etch entire floor with concrete etch (included)
- Rinse thoroughly & allow to dry completely

2 BURST-SHAKE-POUR



- Roll side A of pouch toward side B to burst and mix the two components
- Mix contents by shaking pouch back and forth and squeezing the edges and corners for 2-3 minutes
- Cut off one corner and pour out a ribbon of RockSolid Polycuramine® Garage Floor Coat

3 APPLY COATING



- Trim outer edges
- Apply coating in 4' x 4' sections with roller (included)
- If desired, sprinkle decorative chips (included) on freshly coated section

VISIT [RUSTOLEUM.COM/ROCKSOLID](http://rustoleum.com/rocksolid) FOR INSTRUCTIONAL VIDEOS, FAQs AND TIPS & TECHNIQUES