



**DIF® LIQUID CONCENTRATE
WALLPAPER STRIPPER**

DESCRIPTION AND USES

Zinsser® DIF® Liquid Concentrate Wallpaper Stripper is a biodegradable, non-toxic and non-staining wallpaper stripper which dissolves old paste fast. The 22 oz. bottle will make 2 gallons of stripper, enough to remove the wallpaper from a 12'x24' room.

The 1-gallon container will make 12 gallons of stripper. Simply add 10 oz. (1¼ cups) of concentrate to each gallon of warm water.

PRODUCTS

SKU	DESCRIPTION
2422	32 Fluid Ounces
2401	1-Gallon

PRODUCT APPLICATION

READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT

SURFACE PREPARATION

Spread a solvent resistant drop cloth covered with newspapers around the work area in case of drips and spills. Protect carpeting, furniture and porous ceilings before application. Protect eyes and skin. Wear safety goggles and chemical resistant gloves.

PRODUCT APPLICATION (cont.)

APPLICATION

Note: Ensure good cross ventilation during application. Wear a NIOSH approved respirator when spraying. If top layer does not peel off easily, score with Paper Tiger® to allow DIF to penetrate. The more holes, the better the penetration. Spray on DIF with a garden-type sprayer, or apply with a sponge or roller. (Do not use a fine mist sprayer). Wait 15 minutes. Repeat the application. Rewet a small section and scrape off loose wallpaper. Use the Paper Scraper™ to easily remove wallpaper without gouging the wall. To remove residual adhesive, reapply DIF, wait 15 minutes, scrape or sponge off. Rinse with clean water.

Note: Borders that are difficult to remove may have been hung with a non-water soluble adhesive and may require prolonged soaking and scraping.

KEEP OUT OF REACH OF CHILDREN.

SPILLAGE

Open container carefully and close after each use. If spilled, contain spilled material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Clean up rags, papers and waste promptly.

CLEAN-UP

Clean up tools and equipment with soap and water.



**DIF® LIQUID CONCENTRATE
WALLPAPER STRIPPER**

PHYSICAL PROPERTIES

		LIQUID CONCENTRATE WALLPAPER STRIPPER
Composition		Ethoxylated Alcohols, Propylene Glycol, Water
Weight	Per Gallon	8.4 lbs.
	Per Liter	1.01 kg
Volatile Organic Compounds		<25 g/l
Practical Coverage		Varies with porosity of wallpaper
Shelf Life		5 years
Flash Point		200°F (93°C)
Caution!		Harmful if swallowed. Do not take internally. If swallowed, drink two glasses of water and get medical attention. May cause respiratory irritation. Avoid contact with eyes and skin. If eye contact occurs, flush with water for at least 15 minutes. If irritation persists, seek medical attention. Do not take internally. KEEP OUT OF REACH OF CHILDREN.
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.