

- 3 plastic or unwaxed paper containers with clear volume measurements, smooth walls and flat bottom
- 3 Stir Sticks
- Plastic spreader or squeegee
- Disposable brush
- Waxed paper, newspaper or plastic drop cloth
- Latex. vinvl. or chemical-resistant safety aloves

Complete instructions included in box.

Watco Super Glaze is an ultra-thick, high gloss, Aged Wood tinted epoxy that provides maximum durability. Ideal as a waterproof finish for table and bar tops, it is also great for decorative projects and refinishing furniture. It can be used over almost any interior surface; from rough and unfinished to stained, painted or smooth surfaces. Read, understand, and follow all instructions included in this kit before using.



Measure:

Measure equal

volume of part A

and part B'into clean

separate containers.



24.8

Thoroughly mix part A with part B using a clean stir stick.



Pour:

Pour mixture over the entire surface and spread.

Unit Size	Sq. Feet*
Pint (16 oz.)	3.1
Quart (32 oz.)	6.2

*Based on almost 1/16" thickness

Gallon (128 oz.)

One pour of Super Glaze is One coat of regular poly. equal to 75 coats of poly. Dries to .82 mils thick Dries to 61.5 mils thick

THICKNESS COMPARISON





Maximum VOC content of this product is less than 100 g/L when mixed.

CONTAINS EPOXY RESIN, BRANCHED NONYLPHENOL, AMINES AND PROPYLENE CARBONATE. Causes nose and throat irritation. May cause allergic respiratory reaction. May cause allergic skin reaction. Harmful if swallowed. [Use only with adequate ventilation.] Avoid breathing dust, vapors, or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache, or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear and appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin, and clothing. Was thoroughly after handling. KEEP OUT OF REACH OF CHILDREN

First Aid In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean contaminated shoes. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. For emergency, call your physician, local poison control center or local emergency room. For product health information, call: (800)487-4785. **DISPOSAL**: Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

WARNING: Cancer – www.P65Warnings.ca.gov.

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-800-901-0411 for product replacement or a full refund of the purchase price. Refer to product number and batch code.



CORPORATION
11 Hawthorn Pkwy., Vernon Hills, IL 60061 800-901-0411 rustoleum.com/watco Made in USA | Hecho en E.U.A. ©2020 Rust-Oleum Corporation 368947 1020







POUR ON HIGH GLOSS EPOXY

EASY 1:1 RATIO / PRE-DYED RESIN

Maximum Durability **Resists Heat & Chemicals** Waterproof

Ideal for: Bars, Tabletops, Decorative Projects, Frames & more

1 QT (32 FL OZ) 946mL



SUPER GLAZE

ULTRA THICK TINTED FINISH



POUR ON HIGH GLOSS EPOXY

EASY 1:1 RATIO / PRE-DYED RESIN

Maximum **Durability** **Resists Heat** & Chemicals

Waterproof



BREATHTAKING CREATIONS



BEAUTIFUL TABLE TOPS



ENHANCES DECORATIVE PROJECTS



MAXIMUM DURABILITY







- 3 plastic or unwaxed paper containers with clear volume measurements, smooth walls and flat bottom
- 3 Stir Sticks
- Plastic spreader or squeegee
- Disposable brush
- Waxed paper, newspaper or plastic drop cloth
- Latex. vinvl. or chemical-resistant safety aloves

Complete instructions included in box.

Watco Super Glaze is an ultra-thick, high gloss, Classic Gray tinted epoxy that provides maximum durability. Ideal as a waterproof finish for table and bar tops, it is also great for decorative projects and refinishing furniture. It can be used over almost any interior surface; from rough and unfinished to stained, painted or smooth surfaces. Read, understand, and follow all instructions included in this kit before using.



Measure:

Unit Size

Pint (16 oz.)

Quart (32 oz.)

Gallon (128 oz.)


Measure equal

volume of part A

and part B'into clean

separate containers.





Mix:

Thoroughly mix part A with part B using a clean stir stick.

Pour mixture

Pour:

over the entire surface and spread.

Sq. Feet* 3.1 6.2

24.8

*Based on almost 1/16" thickness

THICKNESS COMPARISON

One pour of Super Glaze is One coat of regular poly. equal to 75 coats of poly. Dries to .82 mils thick Dries to 61.5 mils thick





Maximum VOC content of this product is less than 100 g/L when mixed.

CONTAINS EPOXY RESIN, BRANCHED NONYLPHENOL, AMINES AND PROPYLENE CARBONATE. Causes nose and throat irritation. May cause allergic respiratory reaction. May cause allergic skin reaction. Harmful if swallowed. [Use only with adequate ventilation.] Avoid breathing dust, vapors, or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache, or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear and appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin, and clothing. Was thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN**

First Aid In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean contaminated shoes. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. For emergency, call your physician, local poison control center or local emergency room. For product health information, call: (800)487-4785. **DISPOSAL**: Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

WARNING: Cancer – www.P65Warnings.ca.gov.
SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-800-901-0411 for product replacement or a full refund of the purchase price. Refer to product number and batch code.



CORPORATION
11 Hawthorn Pkwy., Vernon Hills, IL 60061 800-901-0411 rustoleum.com/watco Made in USA | Hecho en E.U.A. ©2020 Rust-Oleum Corporation 368948 1020



GLOSS EPOXY

EASY 1:1 RATIO / PRE-DYED RESIN

Maximum Durability **Resists Heat & Chemicals** Waterproof

Ideal for: Bars, Tabletops, Decorative Projects, Frames & more

1 QT (32 FL OZ) 946mL



SUPER GLAZE

ULTRA THICK TINTED FINISH



POUR ON HIGH GLOSS EPOXY

EASY 1:1 RATIO / PRE-DYED RESIN

Maximum **Durability** **Resists Heat** & Chemicals

Waterproof



BREATHTAKING CREATIONS



BEAUTIFUL TABLE TOPS



ENHANCES DECORATIVE PROJECTS



MAXIMUM DURABILITY





Required Tools:

- 3 plastic or unwaxed paper containers with clear volume measurements, smooth walls and flat bottom
- 3 Stir Sticks
- Plastic spreader or squeegee
- Disposable brush
- Waxed paper, newspaper or plastic drop cloth
- Latex. vinvl. or chemical-resistant safety

Complete instructions included in box.

Watco Super Glaze is an ultra-thick, high gloss, Crystal Clear epoxy that provides maximum durability. Ideal as a waterproof finish for table and bar tops, it is also great for decorative projects and refinishing furniture. It can be used over almost any interior surface; from rough and unfinished to stained, painted or smooth surfaces. Read, understand, and follow all instructions included in this kit before using.



Measure:

Unit Size

Pint (16 oz.)

Gallon (128 oz.)

Measure equal

volume of part A

and part Binto clean

separate containers.







Mix: Thoroughly mix part A with part B using a clean stir stick.

Pour: Pour mixture over the entire surface and spread.

THICKNESS COMPARISON

Sq. Feet* 3.1 6.2 Quart (32 oz.) 24.8

One pour of Super Glaze is One coat of regular poly. equal to 75 coats of poly. Dries to .82 mils thick Dries to 61.5 mils thick





*Based on almost 1/16" thickness

Maximum VOC content of this product is less than 100 g/L when mixed.

CONTAINS EPOXY RESIN, BRANCHED NONYLPHENOL, AMINES AND PROPYLENE CARBONATE. Causes nose and throat irritation. May cause allergic respiratory reaction. May cause allergic skin reaction. Harmful if swallowed. [Use only with adequate ventilation.] Avoid breathing dust, vapors, or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache, or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear and appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin, and clothing. Was thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN**

First Aid In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean contaminated shoes. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. For emergency, call your physician, local poison control center or local emergency room. For product health information, call: (800)487-4785. **DISPOSAL**: Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

WARNING: Cancer – www.P65Warnings.ca.gov.
SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-800-901-0411 for product replacement



CORPORATION
11 Hawthorn Pkwy., Vernon Hills, IL 60061 800-901-0411 rustoleum.com/watco Made in USA | Hecho en E.U.A. ©2020 Rust-Oleum Corporation 368949 1020

365342 CRYSTAL CLEAR

SUPER GLAZE ULTRA THICK TINTED FINISH **CRYSTAL CLEAR** ONE POUR 75 COATS OF VARNISH* BEFORE | AFTER

POUR ON HIGH GLOSS EPOXY

EASY 1:1 RATIO / CRYSTAL CLEAR RESIN

Maximum Durability **Resists Heat & Chemicals** Waterproof

Ideal for: Bars, Tabletops, Decorative Projects, Frames & more

1 QT (32 FL OZ) 946mL



SUPER GLAZE

ULTRA THICK TINTED FINISH



POUR ON HIGH GLOSS EPOXY

EASY 1:1 RATIO / CRYSTAL CLEAR RESIN

Maximum **Durability** **Resists Heat** & Chemicals

Waterproof



BREATHTAKING CREATIONS



BEAUTIFUL TABLE TOPS



ENHANCES DECORATIVE PROJECTS



MAXIMUM DURABILITY







Required Tools:

- 3 plastic or unwaxed paper containers with clear volume measurements, smooth walls and flat bottom
- 3 Stir Sticks
- Plastic spreader or squeegee
- Disposable brush
- Waxed paper, newspaper or plastic drop cloth
- Latex. vinvl. or chemical-resistant safety

Complete instructions included in box.

Watco Super Glaze is an ultra-thick, high gloss, Turquoise tinted epoxy that provides maximum durability. Ideal as a waterproof finish for table and bar tops, it is also great for decorative projects and refinishing furniture. It can be used over almost any interior surface; from rough and unfinished to stained, painted or smooth surfaces. Read, understand, and follow all instructions included in this kit before using.



Measure:

Unit Ciza

Measure equal

volume of part A

and part Binto clean

separate containers.





Mix: Thoroughly mix part A with part B using a clean stir stick.

Pour:

Pour mixture over the entire surface and spread.

		T	H	(
_					

	Ullit Size	Jų. reet
	Pint (16 oz.)	3.1
	Quart (32 oz.)	6.2
	Gallon (128 oz.)	24.8

Sn Foot*

*Based on almost 1/16" thickness

KNESS COMPARISON

One pour of Super Glaze is One coat of regular poly. equal to 75 coats of poly. Dries to .82 mils thick Dries to 61.5 mils thick





Maximum VOC content of this product is less than 100 g/L when mixed.

CONTAINS EPOXY RESIN, BRANCHED NONYLPHENOL, AMINES AND PROPYLENE CARBONATE. Causes nose and throat irritation. May cause allergic respiratory reaction. May cause allergic skin reaction. Harmful if swallowed. [Use only with adequate ventilation.] Avoid breathing dust vapors, or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache, or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear and appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin, and clothing. Was thoroughly after handling. KEEP OUT OF REACH OF CHILDREN

First Aid In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean contaminated shoes. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. For emergency, call your physician, local poison control center or local emergency room. For product health information, call: (800)487-4785. **DISPOSAL**: Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

WARNING: Cancer – www.P65Warnings.ca.gov.
SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 1-800-901-0411 for product replacement

RUST-OLEUM

CORPORATION
11 Hawthorn Pkwy., Vernon Hills, IL 60061 800-901-0411 rustoleum.com/watco Made in USA | Hecho en E.U.A. ©2020 Rust-Oleum Corporation 368951 1020





SUPER GLAZE

ULTRA THICK TINTED FINISH

TURQUOISE





EASY 1:1 RATIO / PRE-DYED RESIN

Maximum Durability **Resists Heat & Chemicals**

Ideal for: Bars, Tabletops, Decorative Projects, Frames & more

Waterproof

1 QT (32 FL OZ) 946mL



SUPER GLAZE

ULTRA THICK TINTED FINISH



POUR ON HIGH GLOSS EPOXY

EASY 1:1 RATIO / PRE-DYED RESIN

Maximum **Durability** **Resists Heat** & Chemicals

Waterproof



BREATHTAKING CREATIONS



BEAUTIFUL TABLE TOPS



ENHANCES DECORATIVE PROJECTS



MAXIMUM DURABILITY

