

| | | |
|--|-----------------------|---------------|
|  <p>RUST-OLEUM® ROCKSOLID® THE WORLD'S TOUGHEST COATINGS™</p> | TECHNICAL DATA | RSD-63 |
| ROCKSOLID® COMPOSITE DECK CLEANER | | |

DESCRIPTION AND USES

RockSolid® Composite Deck Cleaner removes tough stains from mold, mildew, algae, fungus and moss to prepare the composite deck surface for RockSolid Composite Deck Refresh. Our bleach gel formula allows cleaning agents to remain on vertical surfaces, such as side rails, longer to achieve the highest effective contact time. No scrubbing required. Just spray on, wait 5-10 minutes and rinse off.

PRODUCT FEATURES

- Cleans & brightens composite deck with no scrubbing
- Also great for brick, stone, concrete, wood decks and fences
- Removes stains caused by mold, mildew, algae and dirt
- Phosphate free

PRODUCT

| DESCRIPTION | SKU |
|---------------|--------|
| 56 Oz. Bottle | 350552 |

PRODUCT APPLICATION

DIRECTIONS

(Read entire directions and warnings prior to use.)

Spray any surrounding plants with clean water before you begin. Shake well before using. Attach hose to nozzle with valve in "OFF" position. Turn water on.

With valve in "CLEAN" position, apply cleaner to surface liberally and evenly. Allow to work up to 5-10 minutes. Do not allow to dry on surface. Rub with bristled brush (if necessary). Rinse off treated surface with valve in "RINSE" position. Move to a new area and repeat. If staining persists, a second coat may be required.

To stop spraying, turn knob to "OFF" position. Spray surrounding plants with water after use.

NOTE: Contains bleach. Test surface in an inconspicuous area for color fastness or adverse reaction prior to use. Do not use on fabrics. Avoid prolonged contact with metal and old porcelain.

KEEP OUT OF REACH OF CHILDREN.

PHYSICAL PROPERTIES

| | | COMPOSITE DECK CLEANER |
|---------------------------|------------------|--|
| Composition | | Water based biodegradable alkaline solution containing Sodium Hypochlorite |
| Color | | Colorless |
| Solids | By Weight | 1.4% |
| | By Volume | 1.1% |
| pH | | 10-12 |
| VOC | | 0% by weight |
| Practical Coverage | | Up to 800 sq. ft. |
| Shelf Life | | 2 Years |
| Flash Point | | >200°F (>94°C) |
| Caution | | PROTECT FROM FREEZING |
| Safety Information | | For additional information, see SDS |

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.