

TRUSTED QUALITY SINCE 1921
RUST-OLEUM
EPOXYSHIELD
 *1 TRUSTED BRAND FOR PROTECTION

PREMIUM TOPCOAT

CLEAR
 GARAGE FLOOR COATING

RUST-OLEUM
 CORPORATION
 11 Hawthorne Place, Vernon Hills, IL 60061
 800-451-4785 rustoleum.com/garage
 Made in USA | Manufactured in USA
 ©2018 Rust-Oleum Corporation 302314 1200

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 800-451-4785 for product replacement or a full refund of the purchase price. Refer to product number for full code.

SATISFACI3N GARANTIZADA: Si no est4 satisfecho con este producto, comuniquese con el Servicio al Cliente de Rust-Oleum al 800-451-4785 para obtener el reembolso del costo del precio de compra. Consulte el n4mero de producto y el c3digo de lote.

Category: Floor Coating
 U.S. PATENT NUMBER: 8380330 B2
 PREVIOUSLY CLEAR: 200253 16


SAFETY INFORMATION
 Avoid contact with skin and eyes. For skin contact wash affected area with soap and water and rinse well.
FIRST AID: In case of contact with eyes, flush with cold water for 15 minutes. If swallowed do not induce vomiting. Drink one or two glasses of water or milk. Contact a physician immediately.
 KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.
 *WARNING: Cancer and Reproductive Harm - www.P010910rds.com

INFORMACI3N DE SEGURIDAD
 Evite el contacto con la piel y los ojos. En caso de contacto con la piel, lave el 4rea afectada con jab3n y agua y enjuague bien.
PRIMEROS AUXILIOS: En caso de contacto con los ojos, enjuague con agua fraa por 15 minutos. En caso de ingest3n, no induzca el v3mito. Beba 1-2 vasos de agua o leche. Llame a un m4dico inmediatamente.
 MANTENGA FUERA DEL ALCANCE DE LOS NI3OS. NO INGERIR INTERNAMENTE.
 *ADVERTENCIA: C4ncer y da3os reproductivos - www.P010910rds.com



RUST-OLEUM CROSS-LINKING TECHNOLOGY™
 FORMS A BOND THAT IS STRONGER THAN CONCRETE & HELPS PREVENT CONCRETE FROM CHIPPING, CRACKING & DUSTING.

UNIT OF MEASURE	Galons, Liters, Quarts, Metric Quarts, Pint, Pints & Cups, 5-Gallon, 10-Gallon, 20-Gallon	WEIGHT IN READY TO USE STATE	0.88 Gallon
SUBSTRATE	Concrete, Epoxy Resin, Concrete Sealers, Most, Not All	COAT WEIGHT	1.00 lbs
COVERAGE	16-18 SQ FT (per gallon @ 0.055 GPM) per coat	COAT WEIGHT (100% SOLIDS)	1.00 lbs (per gallon @ 0.055 GPM)
FORMER	2.5 Gallon (per gallon @ 0.055 GPM)	APPLY WITH TOOLS/SPRAYER	ROLLER OR BRUSH

PROJECT DETAILS QUICK GLANCE

TRUSTED QUALITY SINCE 1921
RUST-OLEUM
EPOXYSHIELD
 *1 TRUSTED BRAND FOR PROTECTION

PREMIUM TOPCOAT

CLEAR
 GARAGE FLOOR COATING



- OTHER SUPPLIES NEEDED**
- Stiff bristle broom or scrub brush
 - Roller frame, tray, 3/8" nap roller cover
 - Extension pole
 - Squeegee for the most effective cleaning and to speed drying
 - Heavy-Duty Degreaser
 - Concrete Etch (for use on bare surfaces only)
- OPTIONAL**
- Concrete Patch & Repair



NO PEEL PROMISE
 Rust-Oleum's leading quality guarantee to protect long lasting results with no peeling or cracking.

*Per ASTM D-2496 when compared to Rust-Oleum 1-Part Concrete & Garage Floor Paint + Primer

NO PEEL PROMISE

TRUSTED QUALITY SINCE 1921
RUST-OLEUM

EPOXYSHIELD
 *1 TRUSTED BRAND FOR PROTECTION

2.5 CAR
 OVER COATED SURFACES

PREMIUM TOPCOAT

CLEAR
 GARAGE FLOOR COATING

15X
 MORE DURABLE THAN 1-PART EPOXY
DRIVE ON IN 3 DAYS

2-PART EPOXY
 100% SOLIDS

For Bare or Coated Concrete
 Adds Extra Layer of Protection
 Showroom Quality Finish
 100% Satisfaction Guarantee

HIGH GLOSS FORMULA

2.8 QT (90 FL OZ 2.68L)
WARNING: COMBUSTIBLE LIQUID AND VAPOR. HARMFUL IF SWALLOWED. SEE OTHER CAUTIONS ON BACK PANEL.

CLEAR HIGH GLOSS

COVERS UP TO
 200-250 SQ. FT. ON BARE CONCRETE
 450-500 SQ. FT. ON COATED CONCRETE

FEATURES & BENEFITS

DRIVE ON IN 3 DAYS	ECO FRIENDLY
NO HOT TIRE PICK UP	EASY MIX BURST POUCH
SUPERIOR ABRASION RESISTANCE	HIGH GLOSS
SUPERIOR CHEMICAL & WATER RESISTANCE	LOW ODOR & LOW VOC

10X MORE DURABLE THAN 1-PART EPOXY

PREMIUM TOPCOAT

CLEAR
 GARAGE FLOOR COATING

EASY 3-STEP APPLICATION

- PREPARE SURFACE**
 Coated Surface: If coating within 7 days of repaving or EpoxyShield Floor Coating, wipe surface clean to remove dust and other contaminants. If applying after 7 days, scrub and coated surface and clean.
 *See instructions for application over bare concrete.
 Rinse thoroughly and allow to dry completely.
- BURST-SHAKE-POUR**
 Roll the A side of pouch to burst and on the low speed mixer. Mix contents by shaking pouch back and forth and opening the edges and corners for 2-3 minutes.
 Cut off corner and pour into tray.
 *Colors included Anti-Static. Additional, treat mix together in a separate bucket.
- APPLY COATING**
 - Roll over edges.
 - Apply coating to 4' x 4' sections with roller.

VISIT RUSTOLEUM.COM/GARAGE FOR INSTRUCTIONAL VIDEOS, FAQs AND TIPS & TECHNIQUES