

• TRUSTED QUALITY SINCE 1921 •

# RUST-OLEUM®

## ANTI-SKID ADDITIVE



**FOR USE WITH ALL  
CONCRETE COATINGS**

**CREATES A SLIP RESISTANT SURFACE**

**DURABLE POLYCARBONATE BLEND**

**EASY TO CLEAN, BAREFOOT-FRIENDLY  
TEXTURE**

**MIX WITH ANY EPOXY, FLOOR PAINT,  
STAIN OR SEALER**

**#1 TRUSTED  
BRAND FOR  
PROTECTION**

**WARNING!**  
IRRITANT. HARMFUL IF SWALLOWED.  
See other cautions on back panel.

3.4 OZ. (96 g)

**¡ADVERTENCIA!**  
IRRITANTE. DAÑOSO SI ESTÁ TRAGADO.  
Ver otras precauciones en el panel posterior.

**RUST-OLEUM® ANTI-SKID ADDITIVE**, when mixed with epoxy, latex or oil-based paints, stains or sealers, creates a slip resistant coating for concrete, wood, metal or fiberglass. Due to the fine, uniform texture, **RUST-OLEUM® ANTI-SKID ADDITIVE** can be used with coatings that include **RUST-OLEUM® DECORATIVE COLOR CHIPS**. **ANTI-SKID ADDITIVE** will not change the color, performance or properties of the coating it is mixed into.

**WHERE TO USE:**

Garages • Basements • Stairs • Walkways • Porches • Patios • Decks • Ramps • Driveways

**MIXING INSTRUCTIONS:**

Use one bag of **RUST-OLEUM® ANTI-SKID ADDITIVE** per gallon or pouch of coating, paint, stain, or sealer. For use with all concrete coatings including **RUST-OLEUM® EPOXYSHIELD®**, **ROCKSOLID®** and **SEAL-KRETE®**. For extra anti-skid properties, use two bags per gallon of coating, paint, stain, or sealer. Add slowly while stirring and mix thoroughly until the additive is evenly dispersed. Stir frequently during use to prevent settling.

**APPLICATION INSTRUCTIONS:**

Refer to paint or stain manufacturers' product labels for surface preparation and application instructions. If applying more than one coat, mix **RUST-OLEUM® ANTI-SKID ADDITIVE** into the final topcoat.

**WARNING!** IRRITANT! HARMFUL IF SWALLOWED. MY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF DUST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. Do not use in an unventilated area. A respirator (NIOSH approved for organic vapor with P series particulate prefilter) will offer additional protection; however, obtain professional advise before using respirator. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. **FIRST AID:** If swallowed, call a physician immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin wash thoroughly with soap and water. **CAUTION: KEEP OUT OF REACH OF CHILDREN-DO NOT TAKE INTERNALLY.**

**SATISFACTION GUARANTEED:** If you are dissatisfied with this product, contact Rust-Oleum Product Support at 888-683-5667 for product replacement or a full refund of the purchase price. Refer to product number and batch code.

279847 ANTI-SKID ADDITIVE

**RUST-OLEUM  
CORPORATION**

11 Hawthorn Pkwy., Vernon Hills, IL 60061

888-683-5667 rustoleum.com/garage

Made in USA

©2022 Rust-Oleum Corporation 372452 0522



0 20066 24570 2