



RUST-OLEUM® IMAGINE SHIMMER SPRAY PAINTS

DESCRIPTION AND USES

Rust-Oleum® Imagine Shimmer Spray Paint offers a full coverage paint that shines when in artificial or natural light. Works on many surfaces such as wood, metal, ceramic, plastic and more. For interior and exterior use.

PRODUCTS

SKU	DESCRIPTION (11 Oz. Aerosol)
357648	Shimmer Emerald
357649	Shimmer Sapphire
357651	Shimmer Citrine
357652	Shimmer Amethyst

PRODUCT APPLICATION

READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT.

SURFACE PREPARATION

Remove loose paint and rust with wire brush or sandpaper. Lightly sand glossy surfaces. Clean with soap and water, rinse and let dry.

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead paint dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRIMING

Use of a Rust-Oleum primer provides superior adhesion and hiding and is especially recommended for bare wood and metal.

PRODUCT APPLICATION (cont.)

APPLICATION

Use outdoors or in a well ventilated area such as an open garage. Use when temperature is between 50-90°F (10-32°C) and humidity is below 60% to ensure proper drying. Do not use on objects that may exceed 200°F (93°C) surface temperature. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

PAINTING

Shake can vigorously for one minute after mixing ball begins to rattle. Shake often during use. If mixing ball fails to rattle **DO NOT STRIKE CAN.** Contact Rust-Oleum. Hold can upright 12-14" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply 2 or more light coats a few minutes apart.

DRY AND RECOAT TIMES

Based on 77°F and 50% relative humidity. Allow more time at cooler temperatures. May recoat within 1 hour or after 24 hours. Dries to the touch in 3 hours and to handle in 6 hours. Fully dry in 24 hours.

CLEAN UP

When finished spraying, clear spray valve by turning can upside down and pushing spray button for 5 seconds. Clean up wet paint with Xylol or mineral spirits. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

CLOGGING

If valve clogs, twist and pull off spray tip and rinse it in a solvent such as mineral spirits. Do not stick pin or other object into the stem.



**RUST-OLEUM® IMAGINE
SHIMMER SPRAY PAINTS**

PHYSICAL PROPERTIES

		IMAGINE SHIMMER SPRAY PAINTS
Resin Type		Acrylic modified alkyd
Pigment Type		Varies with Color
Solvents		Xylene, mineral spirits, n-butyl acetate, acetone
MIR		0.95 Max
Fill Weight		11 oz.
Recommended Dry Film Thickness (DFT) per Coat		1.0 mil (25µ)
Practical Coverage at Recommended DFT (assume 15% material loss)		20 sq. ft./can
Dry Times at 77°F (25°C) and 50% Relative Humidity	Touch	3 hours
	Handle	6 hours
	Recoat	Within 1 hour or after 24 hours
	Full Cure	24 hours
Shelf Life		5 years
Flash Point		-141°F (-96°C)
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.