



Concrete and Garage Metallic Floor Paint Application Instruction

- **RUST-OLEUM® METALLIC GARAGE FLOOR PAINT + PRIMER** is ready to use.
- Do not thin.
- Use only when air (ambient) temperature is 50-90°F (10-32°C) and relative humidity is below 85%.
- Do not paint outdoors if rain is expected within 48 hours.
- If using more than one gallon, intermix all cans of the same product to ensure color uniformity.
- Stir thoroughly before applying.
- Note: Painted floors may be slippery when wet.
- If desired, **RUST-OLEUM® ANTI-SKID ADDITIVE** (sold separately) may be mixed in.

Use a brush or edger to trim the perimeter and hard-to-reach areas. Use a long handled roller and a high-quality, 3/8" nap roller cover to apply an even coat of **RUST-OLEUM® METALLIC GARAGE FLOOR PAINT + PRIMER** onto the surface. Apply in 4'x 4' sections, and maintain a wet edge to prevent lap marks and gloss differences. Continue applying in 4'x 4' sections until complete. Wait 4-6 hours before applying the second coat and apply in a direction perpendicular to the first. **Two coats required. For best appearance, finish rolling in one direction.** Occasional touch-up may be necessary for areas subject to heavy vehicle traffic. **RUST-OLEUM® DECORATIVE COLOR CHIPS** (sold separately) can be added for an upgraded appearance. Chips should be applied in 4x4 sections while the coating is wet.