



# RUST-OLEUM HOME<sup>®</sup> COUNTERTOP COATING KITS

## DESCRIPTION AND USES

Rust-Oleum HOME<sup>®</sup> Countertop Coating is an extremely durable, easy to use, revolutionary technology that allows you to coat over a wide variety of countertops without stripping, sanding or priming. Transform outdated countertops in 2 steps - simply clean, apply the required Base Coat + Topcoat system for a brand-new look to your space.

Great for any bare, stained, sealed, or previously coated countertop surfaces such as outdated laminate, ceramic tile, porcelain tile, melamine, wood and much more.

## PRODUCT FEATURES

- 2 Step System
- No stripping, sanding, or priming
- Superior adhesion to tough surfaces
- Maximum wear & stain resistance
- Full use after 24 hours

## PRODUCTS

SKU	DESCRIPTION
384962	HOME White Tint Base Kit
384963	HOME Deep Tint Base Kit
384964	HOME Ultra White Marble Kit

## KIT CONTENTS

- 1-Quart Countertop Base Coat
- 1-Quart Countertop Satin Topcoat
- 1-4 oz. Heavy-Duty Cleaner
- 1-4 oz. Gray Marble Veining Paint (with Ultra White Marble kit only)

**NOTE:** White Tint Base can be applied as is for Ultra White or tinted prior to application. Two base coats are required when applying the White Tint Base in Ultra White. Deep Tint Base must be tinted prior to application.

## OTHER SUPPLIES NEEDED (not included in kit)

- 3/8" Nap Roller Sleeve
- 1/4" Nap Roller Sleeve
- Roller Frame
- Painter's Tape
- Paint Tray
- Bristle Brush
- Artist Brush (for marble kit only)
- Mist Bottle (for marble kit only)
- Tack Cloth

## PRODUCT APPLICATION

### READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT

**IMPORTANT:** All countertops should be tested for adhesion before coating the entire surface. Clean a small 3" x 3", inconspicuous area, let dry. Apply Base Coat over area and allow to dry for 12 hours. Take a utility knife and make an "X" in the coating down to the surface. Apply a 4" piece of duct tape over the "X" and press firmly. Remove the tape with one quick pull. If more than 10% of the coating comes off, the countertop will need to be sanded with #60-#80 grit sandpaper before coating the entire surface. After a successful adhesion test, lightly sand test area before fully coating.

### SURFACE PREPARATION

Rinse or wipe away any dirt and dust. Clean the countertop with the 4 oz. cleaner included with the kit or a cleaner degreaser, such as Original Krud Kutter<sup>®</sup> Cleaner Degreaser. Rinse thoroughly and allow to dry completely. For any areas where caulk is present, caulk needs to be removed before applying coating.

**NOTE:** Failure to follow this preparation method may result in poor adhesion and possible coating failure.

**WARNING!** If you scrape, sand, or remove old paint from any surface, you may release lead paint dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### SYSTEM APPLICATION

Rust-Oleum HOME Countertop Base Coat is ready to use. Do not thin. Stir thoroughly prior to use. If using more than one can of Base Coat, intermix cans together for color uniformity. Apply when air, material, and surface temperatures are between 50-90°F (10-32°C) and relative humidity is below 85%. Use a high-quality bristle brush or edger to trim the perimeter and hard-to-reach areas. Use a high-quality, 3/8" nap roller cover to apply an even coat onto the surface.

• TRUSTED QUALITY SINCE 1921 •  
**RUST-OLEUM**  
**HOME®**

# RUST-OLEUM HOME® COUNTERTOP COATING KITS

## PRODUCT APPLICATION (cont.)

### SYSTEM APPLICATION (cont.)

**STEP 1:** Apply Countertop Base Coat in 2' x 2' sections and maintain a wet edge while rolling. Do not let product puddle. Only one coat is recommended.

**\*NOTE: For White, 2 coats are required.** After coating the countertop, wait 4 hours before applying second base coat or applying any necessary touch-ups. Let touched-up areas dry for 1-2 hours (dry to touch) and then topcoat can be applied.

**OPTIONAL/MARBLE VEINING STEP:** Once base coat is completely dry, additional Rust-Oleum HOME coatings, such as the Gray Marble Veining Paint and Creative Accents, can be applied to create a faux finish look. Be sure to follow the on-bottle coating instructions and ensure the surface has thoroughly dried and is dust-free before applying the topcoat (Step 2).

**STEP 2:** Apply Rust-Oleum Home Countertop Topcoat. The Countertop Topcoat can be applied 4 hours after initial base coat application. Do not thin. Stir thoroughly prior to use. Apply when air (ambient) temperature is 50-90°F (10-32°C) and relative humidity is below 85%. Use a high-quality bristle brush or edger to trim the perimeter and hard-to-reach areas. Use a high-quality, 1/4" nap roller cover to apply an even coat onto the surface. Apply in 2' x 2' sections and maintain a wet edge while rolling. Do not let product puddle. Only one coat is recommended. If a second coat is desired for additional durability or uniformity, wait until the first coat is dry to touch (1-2 hours) before applying, but must apply within 24 hours. For vertical application, apply Countertop Topcoat in two thin coats.

**IMPORTANT: Rust-Oleum HOME Countertop Base Coat and Topcoat are required for the project.**

## PRODUCT APPLICATION (cont.)

### DRY & TOPCOAT TIMES

For full system, allow 24 hours for light countertop use. Allow 72 hours before replacing large or heavier items (avoid dragging). Full cure is 7 days. Do not clean before 7 days.

### CLEANUP AND STORAGE

Wash tools and equipment with warm water and a mild detergent. Dried product remove with lacquer/thinner. Protect unused product from freezing.

### LIMITATIONS

Not for use on exterior spaces. Not for use on interior surfaces that are sealed with a superhydrophobic sealer. Not intended to be used as a food preparation surface.

### MAINTENANCE

Fully cured countertop may be cleaned with mild soap and water or a general-purpose cleaner such as Original Krud Kutter Cleaner Degreaser after 7 days. Do not use an abrasive cleaner.

### USAGE

**Surface Protection:** As with most manufactured laminate and countertop surfaces, this paint finish will remain durable with proper use and care. Use a trivet or other protective material underneath all hot cookware and heated objects. Use cutting boards or other protective surfaces when preparing food. Heavy pounding, knives or other sharp utensils may scratch the surface. Do not allow water to pool for extended periods, clean up hot grease and any spills with a cloth or non-scratch abrasive pad.

<small>• TRUSTED QUALITY SINCE 1921 •</small> <b>RUST-OLEUM HOME®</b>	<b>TECHNICAL DATA</b>	<b>ROC-264</b>
<b>RUST-OLEUM HOME® COUNTERTOP COATING KITS</b>		

**PHYSICAL PROPERTIES**

		STEP 1 BASE COAT	STEP 2 TOPCOAT	MARBLE GRAY*	CLEANER
<b>Resin Type/Composition</b>		Water-based Acrylic			Proprietary Blend of Biodegradable Surfactants, Detergents and Emulsifiers
<b>pH</b>		NA	NA	NA	<12.2
<b>Pigment</b>		Titanium Dioxide, Inerts	N/A	Titanium Dioxide, Inerts	NA
<b>Solvent</b>		Water, Glycol Ethers			NA
<b>Weight</b>	<b>Per Gallon</b>	10.1-10.6 lbs.	8.5 lbs.	9.7-10.9 lbs.	NA
	<b>Per Liter</b>	1.2-1.3 kg	1.0 kg	1.14-1.24 kg	NA
<b>Solids</b>	<b>By Weight</b>	47.6-50.3%	34.2%	30-34%	NA
	<b>By Volume</b>	36.8-37.1%	35.8%	19-21%	NA
<b>Volatile Organic Compounds</b>		<50 g/l	<50 g/l	60g/l	0%
<b>Recommended Dry Film Thickness (DFT) Per Coat</b>		1.5-2.0 mils			NA
<b>Wet Film Thickness (WFT) to Achieve DFT</b>		4.0-5.5 mils			NA
<b>Practical Coverage at Recommended DFT</b>		75-100 sq. ft./qt. Coverage will vary depending on surface porosity and texture		7-9 sq. ft./bottle	75-100 sq. ft./qt. Coverage will vary depending on surface porosity and texture
<b>Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity</b>	<b>Touch</b>	2 hours		30 minutes	NA
	<b>Recoat/Topcoat</b>	4 hours		3 hours	NA
	<b>Normal Use</b>	24 hours		NA	NA
	<b>Full Cure</b>	7 days		24 hours	NA
<b>Flash Point</b>		>200°F			Non-Flammable
<b>Shelf Life</b>		2 years			NA
<b>Safety Information</b>		For additional information, see SDS			

Calculated values are shown and may vary from the actual manufactured material.

\*Marble Gray only included with 384964 HOME Ultra White Marble Kit.

The technical data and suggestions for use contained herein are correct to the best of our knowledge and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation  
11 Hawthorn Parkway  
Vernon Hills, Illinois 60061

Phone: 866-765-4474  
www.rustoleum.com/rohome

Form: ARJ-2551  
Rev.: 041525