Safety Data Sheet

RUST-OLEUM CORPORATION * Trusted Quality Since 1921* www.rustoleum.com

| 1. Identification | | | |
|----------------------|--|------------------|--|
| Product Name: | WHINK RUST STAIN RMVR 160Z BTL 6PK | Revision Date: | 10/18/2023 |
| Product Identifier: | 1291 | Supercedes Date: | 9/3/2020 |
| Recommended Use: | Rust Remover/Acidic | | |
| Supplier: | Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA | Manufacturer: | Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA |
| Preparer: | Regulatory Department | | |
| Emergency Telephone: | 24 Hour Hotline: 847-367-7700 | | |

2. Hazards Identification

Classification

Symbol(s) of Product



Signal Word Danger

GHS HAZARD STATEMENTS

| Acute Toxicity, Inhalation, category 4 | H332 | Harmful if inhaled. |
|---|--------------------------|---|
| Acute Toxicity, Oral and Dermal, category 3 | H301+H311 | Toxic if swallowed or in contact with skin. |
| Skin Corrosion, category 1 | H314 | Causes severe skin burns and eye damage. |
| GHS LABEL PRECAUTIONARY STATE | | e dust/fumes/gas/mist/vapours/spray. |
| P264 | Wash thoroug | hly after handling. |
| P271 | Use only outd | oors or in a well-ventilated area. |
| P280 | Wear protective | ve gloves / protective clothing / eye protection / face protection. |
| P301+P316 | IF SWALLOW | /ED: Get emergency medical help immediately. |
| P301+P330+P331 | IF SWALLOW | /ED: rinse mouth. Do NOT induce vomiting. |
| P302+P352 | IF ON SKIN: \ | Nash with plenty of soap and water. |
| P303+P361+P353 | IF ON SKIN (shower]. | or hair): Take off immediately all contaminated clothing. Rinse skin with water [or |
| P304+P340 | IF INHALED: | Remove person to fresh air and keep comfortable for breathing. |
| P305+P351+P338 | | Rinse cautiously with water for several minutes. Remove contact lenses, if present o. Continue rinsing. |
| P316 | Get emergeno | cy medical help immediately. |
| | | |

| Date Printed: 10/18/2023 | | Page 2 / 5 |
|------------------------------------|---|------------|
| P317 | Get medical help. | |
| P321 | Specific treatment (see notice on this label). | |
| P361+P364 | Take off immediately all contaminated clothing and wash it before reuse. | |
| P405 | Store locked up. | |
| P501 | Dispose of contents and container in accordance with local, regional and national reg | gulations. |
| GHS SDS PRECAUTIONARY STAT P270 | TEMENTS Do not eat, drink or smoke when using this product. | |
| P363 | Wash contaminated clothing before reuse. | |
| 2 Composition / Informati | | |

3. Composition / Information on Ingredients

| HAZARDOUS SUBSTANCES | | | | |
|----------------------|-----------|----------------------|-------------|------------------|
| Chemical Name | CAS-No. | <u>Wt.%</u> Range | GHS Symbols | GHS Statements |
| Hydrofluoric Acid | 7664-39-3 | 1.0-2.5 | GHS05-GHS06 | H300-310-314-330 |

4. First-Aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed. Remove contact lenses, if present and easy to do. Continue rinsing.

FIRST AID - SKIN CONTACT: Immediately flush skin with plenty of water for at least 15 minutes while removing clothing. Get medical attention immediately. Wash clothing separately before reuse.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

FIRST AID - INGESTION: If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cupfuls of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively. Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

5. Fire-Fighting Measures

EXTINGUISHING MEDIA: None Known

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep containers tightly closed.

SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred. Containers can rupture and release highly toxic material if exposed to heat. Substance is non-combustible but reacts with many metals to form explosive hydrogen gas.

Special Fire and Explosion Hazard (Combustible Dust): Not a combustible dust.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Avoid runoff into sewers and waterways. Provide ventilation and approach spill from upwind using proper personal protective equipment as indicated in Section 8. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

7. Handling and Storage

HANDLING: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing. **STORAGE:** Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Advice on Safe Handling of Combustible Dust: No Information

8. Exposure Controls / Personal Protection

| Chemical Name | CAS-No. | Weight % Less Than | ACGIH TLV- TWA | ACGIH TLV- STEL | OSHA PEL-TWA | OSHA PEL- CEILING |
|-------------------|-----------|-----------------------|-------------------|--------------------|--------------|----------------------|
| Hydrofluoric Acid | 7664-39-3 | 5.0 | 0.5 ppm | N.E. | 3 ppm | N.E. |

PERSONAL PROTECTION

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. A NIOSH/MSHA approved air purifying respirator with organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

SKIN PROTECTION: Use impervious gloves to prevent skin contact and absorption of this material through the skin.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

9. Physical and Chemical Properties

| Appearance: | Liquid | Physical State: | Liquid |
|--------------------------|-----------------------------|-----------------------------------|----------|
| Odor: | Acrid | Odor Threshold: | N.E. |
| Specific Gravity: | 1.016 | pH: | N.D. |
| Freeze Point, °C: | N.D. | Viscosity: | N.D. |
| Solubility in Water: | Miscible | Partition Coefficient, n-octanol/ | ND |
| Decomposition Temp., °C: | N.D. | water: | N.D. |
| Boiling Range, °C: | 100 - 537 | Explosive Limits, vol%: | N.A N.A. |
| Flammability: | Does not Support Combustion | Flash Point, °C: | 94 |
| Evaporation Rate: | Slower than Ether | Auto-Ignition Temp., °C: | N.D. |
| Vapor Density: | Heavier than Air | Vapor Pressure: | N.D. |
| | | | |

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

Conditions to Avoid: Avoid contact with metals. Avoid excess heat. Keep from freezing.

Incompatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalies. Product slowly corrodes copper, aluminum, zinc, and galvanized surfaces.

Hazardous Decomposition: When heated to decomposition, it emits acrid smoke and irritating fumes.

Hazardous Polymerization: Will not occur under normal conditions.

Stability: This product is stable under normal storage conditions.

11. Toxicological Information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Causes eye burns. Irritating, and may injure eye tissue if not removed promptly. High vapor concentrations can irritate eyes, nose and respiratory passages.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Substance is corrosive. Causes severe skin burns. Severely irritating; may cause permanent skin damage.

EFFECTS OF OVEREXPOSURE - INHALATION: High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. High vapor concentrations are irritating to the eyes, nose, throat and lungs.

EFFECTS OF OVEREXPOSURE - INGESTION: Corrosive and may cause severe and permanent damage to mouth, throat and stomach. Harmful if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: No Information

PRIMARY ROUTE(S) OF ENTRY: No Information

ACUTE TOXICITY VALUES

| The acute ef | fects of this product have not been tested. | Data on individual component | s are tabulated below: | |
|--------------|---|------------------------------|------------------------|---------------|
| CAS-No. | Chemical Name | Oral LD50 | Dermal LD50 | Vapor LC50 |
| 7664-39-3 | Hydrofluoric Acid | N.E. | N.E. | 0.79 mg/L Rat |

N.E. - Not Established

12. Ecological Information

ECOLOGICAL INFORMATION: No ecotoxicity data was found for this product.

13. Disposal Information

DISPOSAL: Dispose of material in accordance to local, state, and federal regulations and ordinances. RCRA Hazardous Waste: This material, when discarded or disposed of, could be a hazardous waste according to federal regulations (40 CFR 261) due to the characteristic of corrosivity (D002). Check state and local regulations for disposal requirements. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate, or otherwise inappropriate.

14. Transport Information

| UN Number: | <u>Domestic (USDOT)</u> N.A. | <u>International (IMDG)</u> 1790 | <u>Air (IATA)</u> 1790 | <u>TDG (Canada)</u> N.A. |
|-----------------------|--|-------------------------------------|-------------------------------|--|
| Proper Shipping Name: | Corrosive liquids in limited quantities | Hydrofluoric Acid Solution | Hydrofluoric Acid Solution | Corrosive liquids in limited quantities |
| Hazard Class: | N.A. | 8(6.1) | 8(6.1) | N.A. |
| Packing Group: | N.A. | II | II | N.A. |
| Limited Quantity: | Yes | Yes | Cargo Aircraft Only | Yes |

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Toxicity (any route of exposure), Skin Corrosion or Irritation

SARA Section 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

| Chemical Name | <u>CAS-No.</u> |
|-------------------|----------------|
| Hydrofluoric Acid | 7664-39-3 |

Toxic Substances Control Act

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. State Regulations:

California Proposition 65

WARNING:

No Prop. 65 warning is required.

| 16. Other Information | | | | | | |
|--|---------------------|--|----------------------|----------|----------------------|---|
| HMIS RATING Health: 3* | iS Flammability: | 1 | Physical Hazard: | 0 | Personal Protection: | х |
| NFPA RATINO Health: 3 | S Flammability: | 1 | Instability: | 0 | | |
| Volatile Organic Compounds: | | 0.00% | | | | |
| SDS REVISION DATE: | | 10/18/2023 | | | | |
| SDS REVISION DATE: REASON FOR REVISION: | | Substance and/or Product Pro Section(s): 02 - Hazard Identification 03 - Composition / Information 11 - Toxicological Information 15 - Regulatory Information Substance Hazard Threshold Revision Statement(s) Change | n on Ingr % Chang | redients | | |

Legend: N.A. - Not Applicable, N.D. - Not Determined, N.E. - Not Established

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.