Date Printed: 1/7/2025 Page 1 / 5

Safety Data Sheet



www.rustoleum.com

1/7/2025

USA

Rust-Oleum Corporation

11 Hawthorn Parkway

Vernon Hills, IL 60061

Revision Date:

Manufacturer:

1. Identification

Krud Kutter Original Degreaser & Stain Name on Label:

Remover Aerosol

KK 200Z 6PK ORIGINAL CLNR DEGSR **Product Name:**

AEROSOL

Product Identifier: 339798 Supercedes Date: 10/18/2023

Recommended Use: Aerosol Cleaner/Degreaser

Rust-Oleum Corporation Supplier:

11 Hawthorn Parkway Vernon Hills, IL 60061

USA

Preparer: Regulatory Department

24 Hour Hotline: 847-367-7700 **Emergency Telephone:**

2. Hazards Identification

Classification

Symbol(s) of Product





Signal Word Warning

Possible Hazards

8% of the mixture consists of ingredient(s) of unknown acute toxicity.

GHS Hazard Statements

Gases under Pressure; Compressed Gas H280 Contains gas under pressure; may explode if heated.

Skin Irritation, category 2 H315 Causes skin irritation.

Eye Irritation, category 2A H319 Causes serious eye irritation.

GHS Label Precautionary Statements

P264 Wash thoroughly after handling.

P280 Wear protective gloves / protective clothing / eye protection / face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water. P321 Specific treatment (see notice on this label).

P332+P313 If skin irritation occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P410+P403 Protect from sunlight. Store in a well-ventilated place.

3. Composition / Information on Ingredients

Date Printed: 1/7/2025 Page 2 / 5

HAZARDOUS SUBSTANCES

<u>Chemical Name</u>	CAS-No.	Wt.% Range	GHS Symbols	GHS Statements
n-Butane	106-97-8	1.0-5.0	GHS04	H280
Fatty Alcohol Ethoxylate	160875-66- 1	1.0-5.0	GHS05	H318
Propane	74-98-6	0.5-1.5	GHS04	H280
Sodium Metasilicate	6834-92-0	0.5-1.5	GHS05-GHS07	H302-314-335
Potassium Hydroxide	1310-58-3	0.1-1.0	GHS05-GHS06	H301-314

4. First-Aid Measures

First Aid - Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed. Remove contact lenses, if present and easy to do. Continue rinsing.

First Aid - Skin Contact: Immediately flush skin with plenty of water for at least 15 minutes while removing clothing. Get medical attention immediately. Wash clothing separately before reuse.

First Aid - Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

First Aid - Ingestion: If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cupfuls of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively. Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

Fire-Fighting Measures

EXTINGUISHING MEDIA: Dry Chemical, Dry Sand

Unusual Fire and Explosion Hazards: Closed containers may explode when exposed to extreme heat. Keep containers tightly closed. Perforation of the pressurized container may cause bursting of the can.

Special Fire Fighting Procedures: Water may be used to cool closed containers to prevent buildup of steam. Full protective equipment including self-contained breathing apparatus should be used. If water is used, fog nozzles are preferred. Evacuate area and fight fire from a safe distance. Containers can rupture and release highly toxic material if exposed to heat. Substance is non-combustible but reacts with many metals to form explosive hydrogen gas. Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

Special Fire and Explosion Hazard (Combustible Dust): Not a combustible dust.

Accidental Release Measures

Steps to Be Taken If Material Is Released or Spilled: Avoid runoff into sewers and waterways. Provide ventilation and approach spill from upwind using proper personal protective equipment as indicated in Section 8. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers.

7. Handling and Storage

Handling: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Do not get in eyes, on skin or clothing. Do not puncture or incinerate (burn) container, even after use.

Storage: Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Advice on Safe Handling of Combustible Dust: No Information

Date Printed: 1/7/2025 Page 3 / 5

8. Exposure Controls / Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL-TWA	OSHA PEL- CEILING
n-Butane	106-97-8	5.0	N.E.	1000 ppm	N.E.	N.E.
Fatty Alcohol Ethoxylate	160875-66-1	5.0	N.E.	N.E.	N.E.	N.E.
Propane	74-98-6	5.0	N.E.	N.E.	1000 ppm	N.E.
Sodium Metasilicate	6834-92-0	5.0	N.E.	N.E.	N.E.	N.E.
Potassium Hydroxide	1310-58-3	1.0	N.E.	N.E.	N.E.	N.E.

PERSONAL PROTECTION

Engineering Controls: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

Respiratory Protection: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 (U.S.) and/or SOR/86-304 Part XII 12.13 and CSA Standard Z180.1 (Canada) requirements must be followed whenever workplace conditions warrant a respirator's use.

Skin Protection: Use impervious gloves to prevent skin contact and absorption of this material through the skin.

Eye Protection: Use safety eyewear designed to protect against splash of liquids.

Other Protective Equipment: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

Hygienic Practices: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

9. Physical and Chemical Properties

Physical State Liquid Decomposition Temperature, °C N.D.	
Color Not Yet Specified pH 12.5-13.0	
Odor Mild Kinematic Viscosity N.D.	
Odor Threshold N.E. Solubility in Water Miscible	
Freezing Point / Melting Point, °C 30 Partition Coefficient, n-octanol/water N.D.	
Boiling Range, °C -22 - 537 Vapor Pressure N.D.	
Flammability Does not Support Evaporation Rate Slower than Ether	
Lower Explosive Limit, vol% 1.8 Specific Gravity 0.980	
Upper Explosive Limit, vol% 9.5 Vapor Density Heavier than Air	
Flash Point, °C 94	
Auto-Ignition Temperature, °C N.D. Particle Characteristics N.A.	

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

Conditions to Avoid: Avoid temperatures above 120°F (49°C). Avoid contact with metals. Avoid excess heat.

Incompatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalies. Product slowly corrodes copper, aluminum, zinc, and galvanized surfaces.

Hazardous Decomposition: When heated to decomposition, it emits acrid smoke and irritating fumes.

Hazardous Polymerization: Will not occur under normal conditions.

Stability: This product is stable under normal storage conditions.

11. Toxicological Information

Date Printed: 1/7/2025 Page 4 / 5

may lead to dermatitis with repeated exposures. Irritating, and may injure eye tissue if not removed promptly. High vapor concentrations can irritate eyes, nose and respiratory passages.

Effects of Overexposure - Skin Contact: Substance is corrosive. Causes severe skin burns. Severely irritating; may cause permanent skin damage.

Effects of Overexposure - Inhalation: High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. High vapor concentrations are irritating to the eyes, nose, throat and lungs.

Effects of Overexposure - Ingestion: Corrosive and may cause severe and permanent damage to mouth, throat and stomach. Harmful if swallowed.

Effects of Overexposure - Chronic Hazards: No Information

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
106-97-8	n-Butane	N.E.	N.E.	658 mg/L Rat
6834-92-0	Sodium Metasilicate	1153 mg/kg Rat	N.E.	N.E.
1310-58-3	Potassium Hydroxide	284 mg/kg Rat	N.E.	N.E.

N.E. - Not Established

12. Ecological Information

Ecological Information: No ecotoxicity data was found for this product.

13. Disposal Information

Disposal: Do not incinerate closed containers. Dispose of material in accordance to local, state, and federal regulations and ordinances. RCRA Hazardous Waste: This material, when discarded or disposed of, could be a hazardous waste according to federal regulations (40 CFR 261) due to the characteristic of corrosivity (D002). Check state and local regulations for disposal requirements. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate, or otherwise inappropriate.

14. Transport Information

	Domestic (USDOT)	International (IMDG)	<u>Air (IATA)</u>	TDG (Canada)
UN Number:	N.A.	1950	1950	N.A
Proper Shipping Name:	Aerosols non-flammable in limited quantities	Aerosols	Aerosols non flammable	Aerosols non- flammable in limited quantities
Hazard Class:	N.A.	2.2	2.2	N.A.
Packing Group:	N.A.	N.A.	N.A.	N.A.
Limited Quantity:	Yes	Yes	Yes	Yes

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Gas under pressure, Skin Corrosion or Irritation, Serious eye damage or eye irritation

SARA Section 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Date Printed: 1/7/2025 Page 5 / 5

No Sara 313 components exist in this product.

Toxic Substances Control Act

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. State Regulations:

California Proposition 65

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

16. Other Information

HMIS RATINGS

Health: Flammability: **Physical Hazard: Personal Protection:** Χ

NFPA RATINGS

Health: 2 Flammability: 1 Instability: 0

5.00% **Volatile Organic Compounds: SDS REVISION DATE:** 1/7/2025

REASON FOR REVISION: Revision Description Changed

Product Composition Changed Substance Chemical Name Changed Substance Hazard Threshold % Changed

Substance and/or Product Properties Changed in

Section(s):

01 - Identification

02 - Hazard Identification 05 - Fire-Fighting Measures 09 - Physical & Chemical Properties

14 - Transport Information 15 - Regulatory Information 16 - Other Information

Revision Statement(s) Changed

Legend: N.A. - Not Applicable, N.D. - Not Determined, N.E. - Not Established

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.