

Revision Date: 5/12/2020

Rust-Oleum Multi Component Product Information Sheet

359912 CNCRT KIT GALPK 5800 WB URE SFTY BLUE is a multi component product composed of the following individual chemical components:

363405 W HI BLU6 5800 BR SAFETY BLUE

312335 Covestro Bayhydur XP 2547

SDSs for each component follow this cover sheet.

Transportation Information

| UN Number: | <u>Domestic (USDOT)</u> N.A. | International (IMDG) N.A. | <u>Air (IATA)</u> N.A. | <u>TDG (Canada)</u> N.A. |
|-----------------------|---------------------------------|------------------------------|---------------------------|-----------------------------|
| or rumber. | п.д. | м .д. | N.A. | N.A. |
| Proper Shipping Name: | Not Regulated | Not Regulated | Not Regulated | Not Regulated |
| Hazard Class: | N.A. | N.A. | N.A. | N.A. |
| Packing Group: | N.A. | N.A. | N.A. | N.A. |
| Limited Quantity: | No | No | No | No |

Finished Good Schedule B Harmonized Tariff Code

3209.90.0000

Safety Data Sheet

RUST-OLEUM CORPORATION * Trusted Quality Since 1921 *

www.rustoleum.com

| 1. Identification | | | |
|----------------------|--|------------------|--|
| Product Name: | W HI BLU6 5800 BR SAFETY BLUE | Revision Date: | 4/22/2020 |
| Product Identifier: | 363405 | Supercedes Date: | 4/22/2020 |
| Recommended Use: | High Performance/Urethane coating | | |
| Supplier: | Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA | Manufacturer: | Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA |
| Preparer: | Regulatory Department | | |
| Emergency Telephone: | 24 Hour Hotline: 847-367-7700 | | |

2. Hazards Identification

Classification

Symbol(s) of Product

No symbol is required per 2012 OSHA Hazard Communication Standard 29 CFR 1910.1200.

Signal Word

No Signal Word has been assigned.

Possible Hazards

8% of the mixture consists of ingredient(s) of unknown acute toxicity.

3. Composition / Information on Ingredients

HAZARDOUS SUBSTANCES

| Chemical Name | CAS-No. | <u>Wt.%</u> Range | GHS Symbols | GHS Statements |
|-------------------------------------|------------|----------------------|---------------|----------------|
| Titanium Dioxide | 13463-67-7 | 2.5-10 | Not Available | Not Available |
| Propylene Glycol Monobutyl Ether | 5131-66-8 | 2.5-10 | GHS07 | H302-315-319 |
| Triethanolamine | 102-71-6 | 1.0-2.5 | Not Available | Not Available |
| Dipropylene Glycol Monomethyl Ether | 34590-94-8 | 0.1-1.0 | Not Available | Not Available |

4. First-Aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed. Remove contact lenses, if present and easy to do. Continue rinsing.

FIRST AID - SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

FIRST AID - INGESTION: If swallowed, rinse mouth with water. If feeling unwell, get medical attention. Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention. If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cupfuls of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively.

5. Fire-Fighting Measures

EXTINGUISHING MEDIA: Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep containers tightly closed. FLASH POINT IS TESTED TO BE GREATER THAN 200 DEGREES F. No unusual fire or explosion hazards noted.

SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

Special Fire and Explosion Hazard (Combustible Dust): No Information

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

7. Handling and Storage

HANDLING: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

STORAGE: Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Advice on Safe Handling of Combustible Dust: No Information

8. Exposure Controls / Personal Protection

| Chemical Name | CAS-No. | Weight % Less Than | ACGIH TLV- TWA | ACGIH TLV- STEL | OSHA PEL-TWA | OSHA PEL- CEILING |
|--|------------|-----------------------|-------------------|--------------------|--------------|----------------------|
| Titanium Dioxide | 13463-67-7 | 5.0 | 10 mg/m3 | N.E. | 15 mg/m3 | N.E. |
| Propylene Glycol Monobutyl Ether | 5131-66-8 | 5.0 | N.E. | N.E. | N.E. | N.E. |
| Triethanolamine | 102-71-6 | 5.0 | 5 mg/m3 | N.E. | N.E. | N.E. |
| Dipropylene Glycol Monomethyl Ether | 34590-94-8 | 1.0 | 100 ppm | 150 ppm | 100 ppm | N.E. |

PERSONAL PROTECTION

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

9. Physical and Chemical Properties

| Appearance: | Liquid | Physical State: | Liquid |
|-------------------------|-----------------------------|-----------------------------------|-----------|
| Odor: | Solvent Like | Odor Threshold: | N.E. |
| Specific Gravity: | 1.086 | pH: | N.A. |
| Freeze Point, °C: | N.D. | Viscosity: | N.D. |
| Solubility in Water: | Slight | Partition Coefficient, n-octanol/ | |
| Decompostion Temp., °C: | N.D. | water: | N.D. |
| Boiling Range, °C: | 100 - 171 | Explosive Limits, vol%: | 1.3 - 9.0 |
| Flammability: | Does not Support Combustion | Flash Point, °C: | 94 |
| Evaporation Rate: | Slower than Ether | Auto-ignition Temp., °C: | N.D. |
| Vapor Density: | Heavier than Air | Vapor Pressure: | N.D. |

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

Conditions to Avoid: Avoid excess heat. Keep from freezing.

Incompatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

Hazardous Decomposition: When heated to decomposition, it emits acrid smoke and irritating fumes.

Hazardous Polymerization: Will not occur under normal conditions.

Stability: This product is stable under normal storage conditions.

11. Toxicological Information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Irritating, and may injure eye tissue if not removed promptly.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Low hazard for usual industrial handling or commercial handling by trained personnel.

EFFECTS OF OVEREXPOSURE - INHALATION: High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist.

EFFECTS OF OVEREXPOSURE - INGESTION: Substance may be harmful if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Contains Titanium Dioxide. Titanium Dioxide is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC. No significant exposure to Titanium Dioxide is thought to occur during the use of products in which Titanium Dioxide is bound to other materials, such as in paints during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of Titanium Dioxide in the formula. (Ref: IARC Monograph, Vol. 93, 2010)

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| CAS-No. | Chemical Name | Oral LD50 | Dermal LD50 | Vapor LC50 |
|------------|-------------------------------------|------------------|---------------------|------------|
| 13463-67-7 | Titanium Dioxide | >10000 mg/kg Rat | 2500 mg/kg | N.E. |
| 5131-66-8 | Propylene Glycol Monobutyl Ether | 1900 mg/kg Rat | N.E. | N.E. |
| 102-71-6 | Triethanolamine | 4190 mg/kg Rat | >20000 mg/kg Rabbit | N.E. |
| 34590-94-8 | Dipropylene Glycol Monomethyl Ether | 5350 mg/kg Rat | 9500 mg/kg Rabbit | >20 mg/L |

N.E. - Not Established

12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components. No ecotoxicity data was found for this product.

13. Disposal Information

DISPOSAL INFORMATION: Dispose of material in accordance to local, state, and federal regulations and ordinances.

14. Transport Information

| | Domestic (USDOT) | International (IMDG) | <u>Air (IATA)</u> | <u>TDG (Canada)</u> |
|-----------------------|------------------|----------------------|-------------------|---------------------|
| UN Number: | N.A. | N.A. | N.A. | N.A. |
| Proper Shipping Name: | Not Regulated | Not Regulated | Not Regulated | Not Regulated |
| Hazard Class: | N.A. | N.A. | N.A. | N.A. |
| Packing Group: | N.A. | N.A. | N.A. | N.A. |
| Limited Quantity: | No | No | No | No |

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

None Known

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. State Regulations:

California Proposition 65:

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

| 16. Other Information | | | | | | | |
|-----------------------|--------------------|------------------|---------------------------------------|------------------------------|---------|----------------------|---|
| HMIS RAT Health: | 'INGS 2* | Flammability: | 1 | Physical Hazard: | 0 | Personal Protection: | х |
| NFPA RA1 Health: | 2 2 | Flammability: | 1 | Instability | 0 | | |
| Volatile Org | janic Co | ompounds | 120 g/L | | | | |
| SDS REVIS | SION D | ATE: | 4/22/2020 | | | | |
| REASON F | OR RE | VISION: | Substance and/c 01 - Identificatio | or Product Properties (n | Changed | in Section(s): | |
| Legend: | N.A. | - Not Applicable | e, N.D Not Deter | mined, N.E Not Esta | blished | | |

Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.

Safety Data Sheet



1. Identification

| R | | | |
|----------------------|--|------------------|--|
| Product Name: | Covestro Bayhydur XP 2547 | Revision Date: | 11/20/2019 |
| Product Identifier: | 312335 | Supercedes Date: | 11/19/2019 |
| Recommended Use: | Floor Coating Activator | | |
| Supplier: | Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA | Manufacturer: | Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA |
| Preparer: | Regulatory Department | | |
| Emergency Telephone: | 24 Hour Hotline: 847-367-7700 | | |
| | | | |

2. Hazards Identification

Classification

Symbol(s) of Product



Signal Word Danger

Possible Hazards

99% of the mixture consists of ingredient(s) of unknown acute toxicity.

| H335 | May cause respiratory irritation. | | |
|--|--|--|--|
| H302 | Harmful if swallowed. | | |
| H332 | Harmful if inhaled. | | |
| H317 | May cause an allergic skin reaction. | | |
| H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled. | | |
| MENTS | | | |
| Avoid breathing dust/fume/gas/mist/vapors/spray. | | | |
| Use only outdoors or in a well-ventilated area. | | | |
| IF INHALED: Remove person to fresh air and keep comfortable for breathing. | | | |
| Store in a wel | I-ventilated place. Keep container tightly closed. | | |
| Store locked | up. | | |
| Dispose of co | ntents/container in accordance with local, regional and national regulations. | | |
| Wash hands | thoroughly after handling. | | |
| Rinse mouth. | | | |
| IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. | | | |
| Contaminated | work clothing should not be allowed out of the workplace. | | |
| | H302 H332 H317 H334 MENTS Avoid breathi Use only outo IF INHALED: Store in a wel Store locked Dispose of co Wash hands Rinse mouth. IF SWALLOW | | |

| Date Printed: 5/12/2020 | | Page 2 / 5 |
|------------------------------|---|------------|
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. | |
| P302+P352 | IF ON SKIN: Wash with plenty of soap and water. | |
| P333+P313 | If skin irritation or rash occurs: Get medical advice/attention. | |
| P321 | For specific treatment see label | |
| P285 | In case of inadequate ventilation wear respiratory protection. | |
| P342+P311 | If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. | |
| GHS SDS PRECAUTIONARY STATEM | IENTS | |

P270 P363

Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

3. Composition / Information on Ingredients

HAZARDOUS SUBSTANCES

| Chemical Name | CAS-No. | <u>Wt.%</u> Range | GHS Symbols | GHS Statements |
|---|-----------------|----------------------|---------------|--------------------------------------|
| Hexamethylene diisocyanate homopolymer | 28182-81-2 | 75-100 | GHS07-GHS08 | H317-332-334-335 |
| Hydrophilic Aliphatic Polyisocyanate based on Hexamethylene Diisocyanate | 666723-27- 9 | 10-25 | Not Available | Not Available |
| N,N-Dimethylcyclohexylamine | 98-94-2 | 1.0-2.5 | GHS06 | H301-330 |
| Hexamethylene Diisocyanate | 822-06-0 | 0.1-1.0 | GHS06-GHS08 | H302-311-315-317-319-330-334 -335 |

4. First-Aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

FIRST AID - SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

FIRST AID - INGESTION: Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention. If swallowed, rinse mouth with water. If feeling unwell, get medical attention.

5. Fire-Fighting Measures

EXTINGUISHING MEDIA: Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: No unusual fire or explosion hazards noted. Keep containers tightly closed. FLASH POINT IS TESTED TO BE GREATER THAN 200 DEGREES F.

SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

Special Fire and Explosion Hazard (Combustible Dust): No Information

Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

Handling and Storage

HANDLING: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

STORAGE: Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Advice on Safe Handling of Combustible Dust: No Information

8. Exposure Controls / Personal Protection ACGIH TLV-ACGIH TLV-Weight % **Chemical Name** CAS-No. **OSHA PEL-TWA** Less Than STEL TWA Hexamethylene diisocyanate 28182-81-2 80.0 N.E. N.E. N.E. homopolymer Hydrophilic Aliphatic Polyisocyanate based on 666723-27-9 20.0 N.E. N.E. N.E.

1.0

1.0

Hexamethylene Diisocyanate PERSONAL PROTECTION

Hexamethylene Diisocyanate N,N-Dimethylcyclohexylamine

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

N.E.

0.005 ppm

N.E

N.E

N.E

N.E

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

98-94-2

822-06-0

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

9. Physical and Chemical Properties

| Appearance: | Liquid | Physical State: | Liquid |
|-------------------------|-------------------|-----------------------------------|----------|
| Odor: | Solvent Like | Odor Threshold: | N.E. |
| Specific Gravity: | 1.150 | pH: | N.A. |
| Freeze Point, °C: | N.D. | Viscosity: | N.D. |
| Solubility in Water: | None | Partition Coefficient, n-octanol/ | |
| Decompostion Temp., °C: | N.D. | water: | N.D. |
| Boiling Range, °C: | -1818 | Explosive Limits, vol%: | N.A N.A. |
| Flammability: | No Information | Flash Point, °C: | 185 |
| Evaporation Rate: | Slower than Ether | Auto-ignition Temp., °C: | N.D. |
| Vapor Density: | Heavier than Air | Vapor Pressure: | N.D. |

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

Conditions to Avoid: No Information

Incompatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

Hazardous Decomposition: When heated to decomposition, it emits acrid smoke and irritating fumes.

Hazardous Polymerization: Will not occur under normal conditions.

Stability: This product is stable under normal storage conditions.

11. Toxicological Information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Irritating, and may injure eye tissue if not removed promptly. EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Causes skin irritation. Allergic reactions are possible. May cause skin

OSHA PEL-

CEILING

N.E.

N.E.

N.E

N.E

sensitization, an allergic reaction, which becomes evident upon re-exposure to this material. Low hazard for usual industrial handling or commercial handling by trained personnel.

EFFECTS OF OVEREXPOSURE - INHALATION: Avoid breathing fumes, spray, vapors, or mist. May cause allergic respiratory reaction. High vapor concentrations are irritating to the eyes, nose, throat and lungs. High gas, vapor, mist or dust concentrations may be harmful if inhaled.

EFFECTS OF OVEREXPOSURE - INGESTION: Substance may be harmful if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Overexposure may cause lung damage.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| CAS-No. | Chemical Name | Oral LD50 | Dermal LD50 | Vapor LC50 |
|------------|--|---------------|------------------|---------------|
| 28182-81-2 | Hexamethylene diisocyanate homopolymer | N.E. | N.E. | 18.5 mg/L Rat |
| 98-94-2 | N,N-Dimethylcyclohexylamine | 272 mg/kg Rat | N.E. | 1.9 mg/L Rat |
| 822-06-0 | Hexamethylene Diisocyanate | 738 mg/kg Rat | 593 mg/kg Rabbit | 0.06 mg/L Rat |

N.E. - Not Established

12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components.

13. Disposal Information

DISPOSAL INFORMATION: Dispose of material in accordance to local, state, and federal regulations and ordinances.

| | Domestic (USDOT) | International (IMDG) | <u>Air (IATA)</u> | <u>TDG (Canada)</u> |
|-----------------------|------------------|----------------------|-------------------|---------------------|
| UN Number: | N.A. | N.A. | N.A. | N.A. |
| Proper Shipping Name: | Not Regulated | Not Regulated | Not Regulated | Not Regulated |
| Hazard Class: | N.A. | N.A. | N.A. | N.A. |
| Packing Group: | N.A. | N.A. | N.A. | N.A. |
| Limited Quantity: | No | No | No | No |

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Toxicity (any route of exposure), Respiratory or Skin Sensitization, Specific target organ toxicity (single or repeated exposure)

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name

Hexamethylene Diisocyanate

CAS-No. 822-06-0

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. State Regulations:

California Proposition 65:

WARNING: No Prop. 65 warning is required.

| 16. Other Information | | | | | | | |
|--|--------------------|---------------|---|------------------|---|----------------------|---|
| HMIS RAT Health: | 'INGS 2* | Flammability: | 1 | Physical Hazard: | 0 | Personal Protection: | х |
| NFPA RA1 Health: | 2 2 | Flammability: | 1 | Instability | 0 | | |
| Volatile Organic Compounds | | 0 g/L | | | | | |
| SDS REVISION DATE: | | 11/20/2019 | | | | | |
| REASON FOR REVISION: Substance and/or Product Properties Changed in Section(s): 01 - Identification | | | | | | | |
| Legend: N.A Not Applicable, N.D Not Determined, N.E Not Established | | | | | | | |

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.