Date Printed: 6/6/2023 Page 1 / 6

Safety Data Sheet



Trusted Quality Since 1921 * www.rustoleum.com

1. Identification

Product Name: INDHP 1-GL 2PK ROCTHN 9800 GLS YEL

BASE

Product Identifier: 9806470

Recommended Use: Tint Base/Polyurethane

Supplier: Rust-Oleum Corporation 11 Hawthorn Parkway

Vernon Hills, IL 60061

USA

Rust-Oleum Canada (ROCA) 200 Confederation Parkway Concord, ON L4K 4T8

Canada

Emergency Phone: 800-387-3625

Preparer: Regulatory Department

Emergency Telephone: 24 Hour Hotline: 847-367-7700

Revision Date: 6/6/2023

Supercedes Date: 8/6/2018

Manufacturer: Rust-Oleum Corporation

11 Hawthorn Parkway Vernon Hills, IL 60061

USA

2. Hazards Identification

Classification

Symbol(s) of Product







Signal Word

Danger

Possible Hazards

3% of the mixture consists of ingredient(s) of unknown acute toxicity.

GHS HAZARD STATEMENTS

Carcinogenicity, category 1B H350 May cause cancer.
Flammable Liquid, category 3 H226 Flammable liquid and vapor.
Germ Cell Mutagenicity, category 1B H340 May cause genetic defects.

Reproductive Toxicity, category 2 H361 Suspected of damaging fertility or the unborn child.

Respiratory Sensitizer, category 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

STOT, Single Exposure, category 3, NE H336 May cause drowsiness or dizziness. Skin Sensitizer, category 1 H317 May cause an allergic skin reaction.

GHS LABEL PRECAUTIONARY STATEMENTS

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. NO

SMOKING.

Date Printed: 6/6/2023 Page 2 / 6

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P285 In case of inadequate ventilation wear respiratory protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P321 For specific treatment see label.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

P370+P378 In case of fire: Use alcohol film forming foam, carbon dioxide, dry chemical, dry sand to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local, regional and national regulations.

GHS SDS PRECAUTIONARY STATEMENTS

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P363 Wash contaminated clothing before reuse.

3. Composition / Information on Ingredients

HAZARDOUS SUBSTANCES

| <u>Chemical Name</u> | CAS-No. | Wt.% Range | GHS Symbols | GHS Statements |
|---|-----------------|---------------|-----------------------|----------------------|
| Methyl n-Amyl Ketone | 110-43-0 | 10-25 | GHS02-GHS07 | H226-302-332-336 |
| n-Butyl Acetate | 123-86-4 | 10-25 | GHS02-GHS07 | H226-336 |
| Ethyl 3-Ethoxypropionate | 763-69-9 | 1.0-2.5 | GHS06 | H331 |
| bis(1,2,2,6,6-Pentamethyl-4-Piperidinyl) Sebacate | 41556-26-7 | 0.1-1.0 | GHS07-GHS08 | H317-361 |
| Naphtha (Petroleum), Heavy Alkylate | 64741-65-7 | 0.1-1.0 | GHS06-GHS08 | H304-331-340-350 |
| p-Toluenesulfonyl Isocyanate | 4083-64-1 | 0.1-1.0 | GHS06-GHS07- GHS08 | H315-319-331-334-335 |
| Polymeric Benzotriazole | 104810-48- 2 | 0.1-1.0 | GHS07 | H317 |
| Polymeric Benzotriazole | 104810-47- 1 | 0.1-1.0 | GHS07 | H317 |
| Methyl(1,2,2,6,6-Pentamethyl-4-Piperidinyl) Sebacate | 82919-37-7 | 0.1-1.0 | GHS07-GHS08 | H317-361 |
| Xylenes (o-, m-, p- Isomers) | 1330-20-7 | 0.1-1.0 | GHS02-GHS07 | H226-315-319-332 |

4. First-Aid Measures

Date Printed: 6/6/2023 Page 3 / 6

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

FIRST AID - SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

FIRST AID - INGESTION: Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention. If swallowed, get medical attention.

5. Fire-Fighting Measures

EXTINGUISHING MEDIA: Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may explode when exposed to extreme heat due to buildup of steam. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. No unusual fire or explosion hazards noted.

SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion. Evacuate area and fight fire from a safe distance. Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

Special Fire and Explosion Hazard (Combustible Dust): No Information

Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

7. Handling and Storage

HANDLING: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

STORAGE: Store in a dry, well ventilated place. Keep container tightly closed when not in use. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Do not store above 120°F (49°C). Store large quantities in buildings designed and protected for storage of NFPA Class II combustible liquids. Keep away from heat, sparks, flame and sources of ignition. Avoid excess heat. Product should be stored in tightly sealed containers and protected from heat, moisture, and foreign materials.

Advice on Safe Handling of Combustible Dust: No Information

8. Exposure Controls / Personal Protection

| Chemical Name | CAS-No. | Weight % Less Than | ACGIH TLV- TWA | ACGIH TLV- STEL | OSHA PEL-TWA | OSHA PEL- CEILING |
|---|-------------|-----------------------|-------------------|--------------------|--------------|----------------------|
| Methyl n-Amyl Ketone | 110-43-0 | 20.0 | 50 ppm | N.E. | 100 ppm | N.E. |
| n-Butyl Acetate | 123-86-4 | 15.0 | 50 ppm | 150 ppm | 150 ppm | N.E. |
| Ethyl 3-Ethoxypropionate | 763-69-9 | 5.0 | N.E. | N.E. | N.E. | N.E. |
| bis(1,2,2,6,6-Pentamethyl-4- Piperidinyl) Sebacate | 41556-26-7 | 1.0 | N.E. | N.E. | N.E. | N.E. |
| Naphtha (Petroleum), Heavy Alkylate | 64741-65-7 | 1.0 | N.E. | N.E. | N.E. | N.E. |
| p-Toluenesulfonyl Isocyanate | 4083-64-1 | 1.0 | N.E. | N.E. | N.E. | N.E. |
| Polymeric Benzotriazole | 104810-48-2 | 1.0 | N.E. | N.E. | N.E. | N.E. |
| Polymeric Benzotriazole | 104810-47-1 | 1.0 | N.E. | N.E. | N.E. | N.E. |
| Methyl(1,2,2,6,6-Pentamethyl-4-Piperidinyl) Sebacate | 82919-37-7 | 1.0 | N.E. | N.E. | N.E. | N.E. |
| Xylenes (o-, m-, p- Isomers) | 1330-20-7 | 1.0 | 20 ppm | N.E. | 100 ppm | N.E. |

PERSONAL PROTECTION

Date Printed: 6/6/2023 Page 4 / 6

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or in any other circumstances where air purifying respirators may not provide adequate protection.

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

9. Physical and Chemical Properties

| Appearance: | Liquid | Physical State: | Liquid |
|--------------------------|---------------------|-----------------------------------|------------|
| Odor: | Solvent Like | Odor Threshold: | N.E. |
| Specific Gravity: | 1.091 | pH: | N.A. |
| Freeze Point, °C: | ND | Viscosity: | N.D. |
| Solubility in Water: | Soluble | Partition Coefficient, n-octanol/ | N.D. |
| Decomposition Temp., °C: | N.D. | water: | N.D. |
| Boiling Range, °C: | 121 - 537 | Explosive Limits, vol%: | 1.1 - 10.4 |
| Flammability: | Supports Combustion | Flash Point, °C: | 36 |
| Evaporation Rate: | Slower than Ether | Auto-Ignition Temp., °C: | N.D. |
| Vapor Density: | Heavier than Air | Vapor Pressure: | N.D. |

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

Conditions to Avoid: Avoid temperatures above 120°F (49°C). Avoid all possible sources of ignition.

Incompatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

Hazardous Decomposition: By open flame, carbon monoxide and carbon dioxide. When heated to decomposition, it emits acrid smoke and irritating fumes. Contains solvents which may form carbon monoxide, carbon dioxide, and formaldehyde.

Hazardous Polymerization: Will not occur under normal conditions.

Stability: This product is stable under normal storage conditions.

11. Toxicological Information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Causes Serious Eye Irritation

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Causes skin irritation. Allergic reactions are possible. May cause skin sensitization, an allergic reaction, which becomes evident upon re-exposure to this material.

EFFECTS OF OVEREXPOSURE - INHALATION: Harmful if inhaled. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. High vapor concentrations are irritating to the eyes, nose, throat and lungs. Prolonged or excessive inhalation may cause respiratory tract irritation.

EFFECTS OF OVEREXPOSURE - INGESTION: Harmful if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis, and blurred vision) and/or damage. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Overexposure to xylene in laboratory animals has been associated with liver abnormalities, kidney, lung, spleen, eye and blood damage as well as reproductive disorders. Effects in humans, due to chronic overexposure, have included liver, cardiac abnormalities and nervous system damage.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

Date Printed: 6/6/2023 Page 5 / 6

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| CAS-No. | Chemical Name | Oral LD50 | Dermal LD50 | Vapor LC50 |
|------------|---|-----------------|---------------------|---------------------|
| 110-43-0 | Methyl n-Amyl Ketone | 1600 mg/kg Rat | 10300 mg/kg Rabbit | N.E. |
| 123-86-4 | n-Butyl Acetate | 10768 mg/kg Rat | >17600 mg/kg Rabbit | > 21 mg/L Rat |
| 763-69-9 | Ethyl 3-Ethoxypropionate | 5000 mg/kg Rat | >9500 mg/kg Rabbit | >5.96 mg/L Rat |
| 41556-26-7 | bis(1,2,2,6,6-Pentamethyl-4-Piperidinyl) Sebacate | 2615 mg/kg Rat | N.E. | N.E. |
| 64741-65-7 | Naphtha (Petroleum), Heavy Alkylate | >7000 mg/kg Rat | >2000 mg/kg Rabbit | >5.04 mg/L Rat |
| 4083-64-1 | p-Toluenesulfonyl Isocyanate | 2234 mg/kg Rat | N.E. | >640 ppm (Rat, 1Hr) |
| 1330-20-7 | Xylenes (o-, m-, p- Isomers) | 3500 mg/kg Rat | >4350 mg/kg Rabbit | 29.08 mg/L Rat |

N.E. - Not Established

12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components.

13. Disposal Information

DISPOSAL: Do not incinerate closed containers. Dispose of material in accordance to local, state, and federal regulations and ordinances.

14. Transport Information

| | Domestic (USDOT) | International (IMDG) | <u>Air (IATA)</u> | TDG (Canada) |
|-----------------------|---|----------------------|-------------------|---|
| UN Number: | N.A. | 1263 | 1263 | N.A. |
| | | | | |
| Proper Shipping Name: | Paint Products in Limited Quantities | Paint | Paint | Paint Products in Limited Quantities |
| | | | | |
| Hazard Class: | N.A. | 3 | 3 | N.A. |
| Packing Group: | N.A. | III | III | N.A. |
| Limited Quantity: | Yes | Yes | Yes | Yes |

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Reproductive toxicity, Respiratory or Skin Sensitization, Specific target organ toxicity (single or repeated exposure), Germ cell mutagenicity

SARA Section 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical NameCAS-No.Xylenes (o-, m-, p- Isomers)1330-20-7

Toxic Substances Control Act

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

Date Printed: 6/6/2023 Page 6 / 6

U.S. State Regulations:

California Proposition 65

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

16. Other Information

HMIS RATINGS

Health: 2* Flammability: 3 Physical Hazard: 1 Personal Protection: B

NFPA RATINGS

Health: 2 Flammability: 3 Instability: 0

Volatile Organic Compounds: 383 g/L SDS REVISION DATE: 6/6/2023

REASON FOR REVISION: Product Composition Changed

Substance and/or Product Properties Changed in

Section(s):

01 - Identification

02 - Hazard Identification

03 - Composition / Information on Ingredients

05 - Fire-Fighting Measures

08 - Exposure Controls / Personal Protection

09 - Physical & Chemical Properties11 - Toxicological Information15 - Regulatory Information

Substance Chemical Name Changed Substance Hazard Threshold % Changed Substance Hazardous Flag Changed Revision Statement(s) Changed

Legend: N.A. - Not Applicable, N.D. - Not Determined, N.E. - Not Established

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.