

Material Safety Data Sheet

Section 1 General Information

Manufacturer:

Rust-Oleum Corporation

11 Hawthorn Parkway

Vernon Hills, IL 60061

24 Hour Assistance: 1-847-367-7700www.rustoleum.com**Date: September 11, 2009****Product Name: Parks Power Stripper Aerosol****Codes: 42101**

Section 2 Hazardous Ingredients

<u>Hazardous Component</u>	<u>CAS#</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Methylene Chloride	75-09-2	25 ppm 125 ppm (STEL)	50 ppm
Dipropylene Glycol-Methyl Ether	34590-94-8	100 ppm	100 ppm 150 ppm (STEL)
Methanol	67-56-1	200 ppm	200 ppm 250 ppm (STEL)
Toluene	108-88-3	200 ppm 300 ppm (C)	50 ppm
Propane	74-98-6	1,000 ppm	1,000 ppm
Isobutane	75-28-5	N/E	1,000 ppm

C = Ceiling Value

Section 3 Hazard Identification

Emergency Overview: This product is an aerosol paint stripper. Contents under pressure. Extremely flammable liquid and vapor. Vapors may ignite explosively. Vapors may cause flash fire. May cause eye burns.

Primary Routes of Exposure:

Skin Contact

Eye Contact

Inhalation

Potential Acute Health Effects:

N/A: Not Applicable N/D: Not Determined N/E: Not Established N/R: Not Required Est.: Estimated

Eye: Exposure may cause severe eye irritation and eye burns. Symptoms may include burning, stinging, tearing, and redness.

Skin: Exposure to skin may cause skin irritation or a burning sensation. Prolonged or repeated contact may cause skin to become reddened, rough and dry due to the removal of natural oils and may result in dermatitis. May be harmful if absorbed through skin. May cause allergic skin reaction.

Ingestion: Although ingestion is not a likely route of exposure, the ingredients of this material may be harmful or fatal if swallowed. Contains methanol which cannot be made non poisonous and may cause blindness if swallowed. Swallowing this material may cause gastrointestinal irritation (nausea, vomiting, and diarrhea) and central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness). This material may pose an aspiration hazard. Aspiration of this material into the lungs may cause chemical pneumonitis, which may be fatal.

Inhalation: Inhalation of vapor may be harmful. Inhalation may cause respiratory irritation. May affect the brain or nervous system causing dizziness, headache or nausea, mental confusion, depression, fatigue, loss of appetite, vomiting, cough, loss of sense of balance, visual disturbances and other central nervous system effects. Excessive inhalation may produce symptoms of central nervous system depression, ranging from light headedness, nausea and vomiting to pulmonary edema, unconsciousness and death. Persons with angina or other cardiovascular diseases should not be exposed to this product.

Potential Chronic Health Effects:

Signs and Symptoms: May cause liver effects, kidney effects, bronchitis, loss of appetite, nausea, lack of balance, and visual disturbances. Methylene chloride may cause cancer. Prolonged or repeated skin contact may cause dermatitis.

(See also Sections 4, 8, and 11 for related information)

Section 4 First Aid Measures

Eye contact: Immediately flush eyes with large amounts of water for at least 15 minutes holding eyelids apart to ensure flushing of the entire eye surface. Get medical attention immediately.

Skin contact: In case of skin contact, wash thoroughly with soap and water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention if symptoms persist.

Ingestion: If swallowed, contact a physician or poison control center immediately. DO NOT induce vomiting unless directed to do so by medical personnel. The ingredients of this material may pose an aspiration hazard. Aspiration of this material into the lungs may cause chemical pneumonitis, which may be fatal. If spontaneous vomiting occurs, monitor breathing for difficulty. Treat symptomatically and supportively.

Inhalation: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If breathing is difficult, have trained person administer oxygen. If breathing has stopped, give mouth-to-mouth resuscitation.

N/A: Not Applicable	N/D: Not Determined	N/E: Not Established	N/R: Not Required	Est.: Estimated
---------------------	---------------------	----------------------	-------------------	-----------------

Section 5 Fire Fighting Measures

Flash Point (method): < 32° F

Extinguishing Media: Foam, Dry Chemical, Water Fog, CO₂

Protection of Firefighters: As in any fire, wear self-contained breathing apparatus in pressure demand mode and full protective gear.

Unusual Fire or Explosion Hazards: Contact with flame or hot surface may produce toxic/corrosive gases.

Section 6 Accidental Release Measures

Clean Up Methods: Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120°F. Do not breathe vapors or spray mist. Call your local sanitation department for aid in disposing of unwanted product in your area or call the Environmental Protection Agency Solvent and Hazardous Waste Hotline at 1-800-424-9345. Do not dump on the ground or in local sewer or discharge system.

(See also Section 8 for information on Exposure Controls and Personal Protective Equipment)

Section 7 Handling and Storage

Handling: Do not breathe vapors or spray mist. Keep away from heat, sparks, and flame. Do not smoke. Extinguish all flames, pilot lights and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Do not get in eyes, on skin or on clothing. Do not breathe vapors or spray mist. Wash thoroughly after handling. Wash clothing before reuse. Thoroughly clean or discard contaminated shoes. Always read and obey hazard warnings. Use this product outdoors, if possible. If you must use it indoors, open all windows and doors or use other means to ensure fresh air movement during application and drying. Ensure fresh air entry during application and drying. Do not use in basement or other unventilated area. Prevent the build-up of vapors by opening windows and doors to achieve cross-ventilation. USE ONLY WITH ADEQUATE VENTILATION. Prevent build-up of vapors by opening windows and doors to achieve cross-ventilation. Vapors are heavier than air and may spread over long distances.

Storage: Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120°F. Store away from heat, sparks and flames. Do not store near oxidizers. Store in a cool, dry, well-ventilated place away from incompatible materials. Vapors of this product are heavier than air and will collect in low places, such as pits or other poorly ventilated areas. Do not enter places where vapors are suspected. KEEP OUT OF REACH OF CHILDREN.

Section 8 Exposure Controls / Personal Protection

N/A: Not Applicable	N/D: Not Determined	N/E: Not Established	N/R: Not Required	Est.: Estimated
---------------------	---------------------	----------------------	-------------------	-----------------

Engineering Controls: Use this product outdoors, if possible. If you must use it indoors, open all windows and doors or use other means to ensure fresh air movement during application and drying. Use only in well-ventilated areas. Do not use in basement or other unventilated area. If necessary, use mechanical local exhaust ventilation or general room dilution ventilation to reduce the flammability risk and to reduce vapor concentrations below applicable exposure limits. If workplace exposure monitoring indicates methylene chloride levels cannot be controlled to below the established OSHA exposure limits (29 CFR 1910.1050), then appropriate respiratory protection must be provided. Obtain professional advice before using respiratory protection. A dust mask does not provide protection against vapors.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Personal Protective Equipment (PPE):

Eye Protection: Do not get in eyes. Wear chemical splash goggles or similar eye protection to prevent eye contact.

Skin Protection: Prevent skin contact. Wear PVA, rubber or other impermeable gloves to prevent skin contact. Depending on conditions of use additional protective equipment may be necessary such as face-shield, apron or coveralls.

Respiratory Protection: Do not breathe vapors or spray mist. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels exceed applicable occupational exposure limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.

General Hygiene Practices: Wash after handling material. Do not get in eyes. Prevent skin and inhalation contact. Wash thoroughly before handling food, cosmetics, or before smoking.

Section 9 Physical Data

Appearance: Cloudy white aerosol

Odor: Solvent type

Physical State: Aerosol mist

pH: N/D

Boiling Point: N/D

Melting Point: N/D

Vapor Pressure: N /D

Vapor Density: Heavier than air.

Viscosity: N/D

Solubility in Water: Insoluble.

Specific Gravity (water = 1): > 1

N/A: Not Applicable N/D: Not Determined N/E: Not Established N/R: Not Required Est.: Estimated

Section 10 Stability and Reactivity

Stability: Stable.

Hazardous Polymerization: Will not occur.

Hazardous Decomposition Products: Combustion may yield carbon monoxide and carbon dioxide.

Conditions to Avoid: Open flames, welding arcs or other high temperature sources.

Incompatibility: Avoid contact with oxidizers and reactive metals (i.e., Aluminum, Potassium, Sodium, etc.).

Section 11 Toxicological Information

Carcinogenicity: The following ingredients are present at greater than 0.1% and are classified by IARC, NTP, or OSHA as carcinogenic:

<u>Ingredient</u>	<u>CAS #</u>	<u>IARC</u>	<u>NTP</u>	<u>OSHA</u>
Methylene Chloride	75-09-2	Yes	Yes	Yes

Methylene Chloride: A 1986 NTP, 2-year animal inhalation study report states that there is "clear evidence of carcinogenicity" in mice (lung and liver tumors) and female rats (mammary tumors). NTP list methylene chloride as reasonable anticipated to be a human carcinogen. IARC lists methylene chloride as a Group 2B Carcinogen (having inadequate evidence in humans and sufficient evidence in animals to evaluate carcinogenicity). Methylene chloride has been shown to cause cancer in certain laboratory animal tests. Risk to your health depends on level and duration of exposure. Methylene chloride reduces the blood's oxygen-carrying capacity.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

(See also Section 15 for related information)

Section 12 Ecological Information

Chemical Fate and Effects: None known

Section 13 Disposal Considerations

Recommended Waste Disposal Method: This material, when discarded or disposed of, could be a hazardous waste according to federal regulations (40 CFR 261) due to the characteristic of ignitability (D001). The transportation, storage, treatment, and disposal of this waste must be conducted in compliance with 40 CFR 262, 263, 264, 268, and 270. Disposal can only occur in properly permitted

N/A: Not Applicable N/D: Not Determined N/E: Not Established N/R: Not Required Est.: Estimated

facilities. Check state and local regulations for any additional requirements as these may be more restrictive than federal laws and regulations. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this MSDS incomplete, inaccurate, or otherwise inappropriate.

Section 14 Transportation Information

Regulated by the DOT: Yes

DOT Proper Shipping Name: Consumer Commodity

Hazard Class: ORM-D

Section 15 Regulatory Information

CERCLA:

The Comprehensive Environmental Response Compensation and Liability Act of 1980 (CERCLA) requires notification to the National Response Center for releases of quantities of Hazardous Substances equal to or greater than the reportable quantities (RQs) in 40 CFR 302.4 (for CERCLA 102).

Components present in this product at a level which could require reporting under the statute are:

<u>Chemical Name</u>	<u>CAS#</u>	<u>Maximum Concentration (Wt. %)</u>
Methylene Chloride	75-09-2	75.0 %
Methanol	67-56-1	4.0 %

SARA Title III, section 311/312:

The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires emergency planning based on Threshold Planning Quantities (TPQs) and release reporting based on Reportable Quantities (RQs) in 40 CFR 355 (used for SARA 302, 304, 311 and 312).

Components present in this product at a level which could require reporting under the statute are:

<u>Chemical Name</u>	<u>CAS#</u>	<u>Maximum Concentration (Wt. %)</u>
None	N/A	N/A

SARA Title III, section 313:

The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires submission of annual reports of release of toxic chemicals that appear in 40 CFR 372 (for SARA 313).

Components present in this product at a level which could require reporting under the statute are:

<u>Chemical Name</u>	<u>CAS#</u>	<u>Maximum Concentration (Wt. %)</u>
Methylene Chloride	75-09-2	75.0 %

N/A: Not Applicable	N/D: Not Determined	N/E: Not Established	N/R: Not Required	Est.: Estimated
---------------------	---------------------	----------------------	-------------------	-----------------

TSCA:

The components of this mixture are listed in the Toxic Substance Control Act Inventory of Chemical Substances.

Section 16 Other Information

Legend: N/A: Not Applicable N/D: Not Determined
N/E: Not Established N/R: Not Required
cps: Centipoise KU: Krebs Units
STEL: Short Term Exposure Limit C: OSHA Ceiling Value
PPM: Parts Per Million PPB: Parts Per Billion
PEL: Permissible Exposure Limit TLV: Threshold Limit Value
TWA: Time Weighted Average mg/m³: Milligrams per cubic Meter
mppcf: Million particles per cubic foot of air.
ACGIH: American Conference of Governmental Industrial Hygienists
OSHA: Occupational Safety and Health Administration (US Dept. of Labor)
RCRA: Resource Conservation and recovery Act
SARA: Superfund Amendment and Reauthorization Act
TSCA: Toxic Substance Control Act
FHSA: Federal Hazardous Substance Act

Prepared By: Rust-Oleum Regulatory Compliance Dept.
173 Belmont Drive Somerset, NJ 08875 (732) 469-8100

Disclaimer: Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this material safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials and make no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and data and to comply with all applicable international, federal, state, and local laws and regulations.