



# RUST-OLEUM AUSTRALIA

**Attachment for: 279170 R-O SSPR 6PK AUS PEELCOAT CLEAR Australian SDS**

The following information is supplied in addition to the attached Australian SDS in order to meet the requirements of the Hazardous Substances Safety Data Sheet Notice (2017).

**Section 1: Identification**

**New Zealand Supplier:**

Rust-Oleum New Zealand  
Quad7, Level 1, 6 Leonard Isitt Drive  
Auckland Airport, Auckland 2022  
New Zealand  
Ph: 0800 (78 78 65)

Rust-Oleum New Zealand  
PO BOX 58340  
Botany, Auckland 2163  
New Zealand

Website: [www.rustoleum.co.nz](http://www.rustoleum.co.nz)

Email: [technical@rustoleum.co.nz](mailto:technical@rustoleum.co.nz)

**Poison Centre Contact Information: 0800 764 766**

**Section 2: Hazard Identification**

In addition to the information provided in Section 2 of the attached Safety Data Sheet, this product carries the following hazards per the HSNO guidance provided by the New Zealand EPA:

GHS Hazard Statements

9.1C Aquatic toxicity (Chronic), Category 3      H412      Harmful to aquatic life with long-lasting effects

NZ GHS Classification: 6.7B, 6.4A, 2.1.2a, 6.8B, 6.3A

GHS LABEL PRECAUTIONARY STATEMENTS

P273

Avoid release to the environment.

**Section 14: Transportation Information**

Land Transport Rule Dangerous Goods classification: UN1950, Aerosols, 2.1, Limited Quantity

**Section 15: Regulatory Information**

All substances used in this formula are listed on the NZIoC or are otherwise exempt.

This product is approved under Group Standard HSR002517

**This attachment must be read in conjunction with the attached SDS.**

# Safety Data Sheet

**RUST-OLEUM**  
AUSTRALIA

www.rustoleum.com.au

## 1. Identification

|                             |   |   |  |
|-----------------------------|---|---|--|
| <b>Product Name:</b>        | R-O SSPR 6PK AUS PEELCOAT CLEAR   | <b>Revision Date:</b>   | 10/31/2018   |
| <b>Name on Label:</b>       | Peel Coat Removable Rubber Coating  | <b>Supersedes Date:</b>   | 7/24/2018  |
| <b>Product Identifier:</b>  | 279170  |   |  |
| <b>Product Use/Class:</b>   | Temporary Topcoat/Aerosols  |   |  |
| <b>Supplier:</b>            | Rust-Oleum Australia<br>Unit 12, 4 Southridge St.<br>Eastern Creek, NSW 2766<br>Australia<br>Ph 2-8808-0600 | <b>Manufacturer:</b>  | Rust-Oleum Corporation<br>11 Hawthorn Parkway<br>Vernon Hills, IL 60061<br>USA |
| <b>Preparer:</b>            | Regulatory Department   | <b>*Please refer to the attached cover sheet for New Zealand-specific Safety Data Sheet information</b> |  |
| <b>Emergency Telephone:</b> | 24 Hour Hotline: 1-300-366-961  |   |  |

## 2. Hazard Identification

This product is classified as a Dangerous Good per the Australian Code for the Transport of Dangerous Goods by Road and Rail. This product was assessed per Safe Work Australia criteria.

### Classification

#### Symbol(s) of Product



#### Signal Word

Danger

#### Possible Hazards

51% of the mixture consists of ingredient(s) of unknown acute toxicity.

#### GHS HAZARD STATEMENTS

|                                       |      |   |
|---------------------------------------|------|---|
| Flammable Aerosol, category 1         | H222 | Extremely flammable aerosol.                        |
| Compressed Gas                        | H280 | Contains gas under pressure; may explode if heated. |
| Germ Cell Mutagenicity, category 1B   | H340 | May cause genetic defects.                          |
| Carcinogenicity, category 1A          | H350 | May cause cancer.                                   |
| STOT, single exposure, category 3, NE | H336 | May cause drowsiness or dizziness.                  |
| Skin Irritation, category 2           | H315 | Causes skin irritation.                             |
| Eye Irritation, category 2            | H319 | Causes serious eye irritation.                      |

#### GHS LABEL PRECAUTIONARY STATEMENTS

|           |  |
|-----------|--|
| P210      | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P211      | Do not spray on an open flame or other ignition source.  |
| P251      | Do not pierce or burn, even after use.   |
| P410+P412 | Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.                   |
| P410+P403 | Protect from sunlight. Store in a well-ventilated place.                                       |
| P201      | Obtain special instructions before use.  |

|                |  |
|----------------|--|
| P280           | Wear protective gloves/protective clothing/eye protection/face protection.   |
| P308+P313      | IF exposed or concerned: Get medical advice/attention.   |
| P405           | Store locked up.   |
| P501           | Dispose of contents/container in accordance with local, regional and national regulations.                                       |
| P261           | Avoid breathing dust/fume/gas/mist/vapors/spray.   |
| P271           | Use only outdoors or in a well-ventilated area.  |
| P304+P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.   |
| P312           | Call a POISON CENTER or doctor/physician if you feel unwell.   |
| P403+P233      | Store in a well-ventilated place. Keep container tightly closed.   |
| P264           | Wash hands thoroughly after handling.  |
| P302+P352      | IF ON SKIN: Wash with plenty of soap and water.  |
| P321           | For specific treatment see label   |
| P332+P313      | If skin irritation occurs: Get medical advice/attention.   |
| P362+P364      | Take off contaminated clothing and wash it before reuse.   |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P337+P313      | If eye irritation persists: Get medical advice/attention.  |

### 3. Composition/Information On Ingredients

#### HAZARDOUS SUBSTANCES

| <u>Chemical Name</u>                   | <u>CAS-No.</u> | <u>Wt.% Range</u> | <u>GHS Symbols</u> | <u>GHS Statements</u> |
|--|----------------|-------------------|--------------------|-----------------------|
| Acetone                                | 67-64-1        | 25-50             | GHS02-GHS07        | H225-319-332-336      |
| Naphtha, Petroleum, Hydrotreated Light | 64742-49-0     | 25-50             | Not Available      | Not Available         |
| Propane                                | 74-98-6        | 10-25             | GHS04              | H280                  |
| n-Butane                               | 106-97-8       | 2.5-10            | GHS04-GHS08        | H280-340-350          |
| Methyl Acetate                         | 79-20-9        | 2.5-10            | GHS02-GHS07        | H225-319-336          |
| Xylenes (o-, m-, p- isomers)           | 1330-20-7      | 2.5-10            | GHS02-GHS07        | H226-315-319-332-335  |
| Ethylbenzene                           | 100-41-4       | 1.0-2.5           | GHS02-GHS07        | H225-315-319-332      |
| Octane                                 | 111-65-9       | 1.0-2.5           | GHS02-GHS07-GHS08  | H225-304-315-336      |
| n-Heptane                              | 142-82-5       | 1.0-2.5           | GHS02-GHS07-GHS08  | H225-304-315-336      |
| Methanol                               | 67-56-1        | 0.1-1.0           | GHS02-GHS06-GHS08  | H225-331-370          |

The balance of the product is Nonhazardous.

### 4. First-Aid Measures

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**FIRST AID - INGESTION:** Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention. If swallowed, get medical attention.

## 5. Fire-fighting Measures

**ADG HAZCHEM CODE:** None

**EXTINGUISHING MEDIA:** Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** FLASH POINT IS LESS THAN 20°F. EXTREMELY FLAMMABLE LIQUID AND VAPOR! Water spray may be ineffective. Closed containers may explode when exposed to extreme heat due to buildup of steam. Closed containers may explode when exposed to extreme heat. Vapors may form explosive mixtures with air. Vapors can travel to a source of ignition and flash back. Isolate from heat, electrical equipment, sparks and open flame. Perforation of the pressurized container may cause bursting of the can. No unusual fire or explosion hazards noted. Keep containers tightly closed.

**SPECIAL FIREFIGHTING PROCEDURES:** Full protective equipment including self-contained breathing apparatus should be used. Evacuate area and fight fire from a safe distance. Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion. Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

## 6. Accidental Release Measures

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

## 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

**STORAGE:** Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Contents under pressure. Do not store above 120 ° F. Store large quantities in buildings designed and protected for storage of flammable aerosols. Product should be stored in tightly sealed containers and protected from heat, moisture, and foreign materials. Store in a dry, well ventilated place. Keep container tightly closed when not in use. Keep away from heat, sparks, flame and sources of ignition. Avoid excess heat.

**Advice on Safe Handling of Combustible Dust:** No Information

## 8. Exposure Controls / Personal Protection

| Chemical Name                          | CAS-No.    | Weight % Less Than | WHS WES TLV-TWA | WHS WES TLV-STEL |
|--|------------|--------------------|-----------------|------------------|
| Acetone                                | 67-64-1    | 30.0               | 250 ppm         | 500 ppm          |
| Naphtha, Petroleum, Hydrotreated Light | 64742-49-0 | 30.0               | N.E.            | N.E.             |
| Propane                                | 74-98-6    | 20.0               | N.E.            | N.E.             |
| n-Butane                               | 106-97-8   | 10.0               | N.E.            | 1000 ppm         |
| Methyl Acetate                         | 79-20-9    | 10.0               | 200 ppm         | 250 ppm          |
| Xylenes (o-, m-, p- isomers)           | 1330-20-7  | 10.0               | 100 ppm         | 150 ppm          |
| Ethylbenzene                           | 100-41-4   | 5.0                | 20 ppm          | N.E.             |
| Octane                                 | 111-65-9   | 5.0                | 300 ppm         | N.E.             |
| n-Heptane                              | 142-82-5   | 5.0                | 400 ppm         | 500 ppm          |
| Methanol                               | 67-56-1    | 1.0                | 200 ppm         | 250 ppm          |

### PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Use explosion-proof ventilation equipment. Provide general dilution of local exhaust ventilation in volume and pattern to keep TLV of hazardous ingredients below acceptable limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. A NIOSH/MSHA approved air purifying respirator with organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

**SKIN PROTECTION:** Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

**EYE PROTECTION:** Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

**Engineering Measures for Combustible Dust:** No Information

## 9. Physical and Chemical Properties

|                                 |                     |  |            |
|---------------------------------|---------------------|--|------------|
| <b>Appearance:</b>              | Aerosolized Mist    | <b>Physical State:</b>                         | Liquid     |
| <b>Odor:</b>                    | Solvent Like        | <b>Odor Threshold:</b>                         | N.E.       |
| <b>Relative Density:</b>        | 0.710               | <b>pH:</b>                                     | N.A.       |
| <b>Freeze Point, °C:</b>        | N.D.                | <b>Viscosity:</b>                              | N.D.       |
| <b>Solubility in Water:</b>     | Slight              | <b>Partition Coefficient, n-octanol/water:</b> | N.D.       |
| <b>Decomposition Temp., °C:</b> | N.D.                | <b>Explosive Limits, vol%:</b>                 | 0.9 - 16.0 |
| <b>Boiling Range, °C:</b>       | -37 - 537           | <b>Flash Point, °C:</b>                        | -96        |
| <b>Flammability:</b>            | Supports Combustion | <b>Auto-ignition Temp., °C:</b>                | N.D.       |
| <b>Evaporation Rate:</b>        | Faster than Ether   | <b>Vapor Pressure:</b>                         | N.D.       |
| <b>Vapor Density:</b>           | Heavier than Air    |  |            |

(See "Other information" Section for abbreviation legend)

## 10. Stability and Reactivity

**CONDITIONS TO AVOID:** Avoid temperatures above 120°F (49°C). Avoid all possible sources of ignition.

**INCOMPATIBILITY:** Incompatible with strong oxidizing agents, strong acids and strong alkalies.

**HAZARDOUS DECOMPOSITION:** By open flame, carbon monoxide and carbon dioxide. When heated to decomposition, it emits acrid smoke and irritating fumes. Contains solvents which may form carbon monoxide, carbon dioxide, and formaldehyde.

**HAZARDOUS POLYMERIZATION:** Will not occur under normal conditions.

**STABILITY:** This product is stable under normal storage conditions.

## 11. Toxicological Information

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** Causes Serious Eye Irritation

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** May cause skin irritation. Allergic reactions are possible.

**EFFECTS OF OVEREXPOSURE - INHALATION:** High gas, vapor, mist or dust concentrations may be harmful if inhaled. High vapor concentrations are irritating to the eyes, nose, throat and lungs. Harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. Prolonged or excessive inhalation may cause respiratory tract irritation.

**EFFECTS OF OVEREXPOSURE - INGESTION:** Poison, may be fatal or cause blindness if swallowed. Harmful if swallowed.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** Overexposure to xylene in laboratory animals has been associated with liver abnormalities, kidney, lung, spleen, eye and blood damage as well as reproductive disorders. Effects in humans, due to chronic overexposure, have included liver, cardiac abnormalities and nervous system damage. IARC lists Ethylbenzene as a possible human carcinogen (group 2B). May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis, and blurred vision) and/or damage.

**PRIMARY ROUTE(S) OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

### ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| <u>CAS-No.</u> | <u>Chemical Name</u>                   | <u>Oral LD50</u> | <u>Dermal LD50</u>  | <u>Vapor LC50</u> |
|----------------|--|------------------|---------------------|-------------------|
| 67-64-1        | Acetone                                | 5800 mg/kg Rat   | >15700 mg/kg Rabbit | 50.1 mg/L Rat     |
| 64742-49-0     | Naphtha, Petroleum, Hydrotreated Light | >5000 mg/kg Rat  | >3160 mg/kg Rabbit  | >4951 mg/L Rat    |
| 106-97-8       | n-Butane                               | N.E.             | N.E.                | 658 mg/L Rat      |
| 79-20-9        | Methyl Acetate                         | >5000 mg/kg Rat  | >5000 mg/kg Rabbit  | >49 mg/L Rat      |
| 1330-20-7      | Xylenes (o-, m-, p- isomers)           | 3500 mg/kg Rat   | >4350 mg/kg Rabbit  | 29.08 mg/L Rat    |
| 100-41-4       | Ethylbenzene                           | 3500 mg/kg Rat   | 15400 mg/kg Rabbit  | 17.4 mg/L Rat     |
| 111-65-9       | Octane                                 | N.E.             | N.E.                | >23.36 mg/L Rat   |
| 142-82-5       | n-Heptane                              | N.E.             | 3000 mg/kg Rabbit   | 103 mg/L Rat      |

67-56-1 Methanol

6200 mg/kg Rat

15840 mg/kg Rabbit

N.E.

N.E. - Not Established

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** Product is a mixture of listed components.

## 13. Disposal Information

**DISPOSAL INFORMATION:** Do not incinerate closed containers. This product as supplied is a USEPA defined ignitable hazardous waste. Dispose of unusable product as a hazardous waste (D001) in accordance with local, state, and federal regulation.

## 14. Transport Information

|                              | <u>Domestic (USDOT)</u>                     | <u>International (IMDG)</u> | <u>Air (IATA)</u>   | <u>ADG</u> |
|------------------------------|---|-----------------------------|---------------------|------------|
| <b>UN Number:</b>            | N.A.  | 1950                        | 1950                | 1950       |
| <b>Proper Shipping Name:</b> | Paint and Related Spray Products in Ltd Qty | Aerosols                    | Aerosols, flammable | Aerosols   |
| <b>Hazard Class:</b>         | N.A.  | 2                           | 2.1                 | 2.1        |
| <b>Packing Group:</b>        | N.A.  | N.A.                        | N.A.                | N.A.       |
| <b>Limited Quantity:</b>     | Yes   | Yes                         | Yes                 | Yes        |
| <b>ADG Hazchem: Code</b>     | None  |                             |                     |            |

## 15. Regulatory Information

### Montreal Protocol

No Montreal Protocol components exist in this product.

### Stockholm Convention

No Stockholm Convention components exist in this product.

### Rotterdam Convention

No Rotterdam Convention components exist in this product.

### MARPOL

This product contains the following substances listed under the MARPOL regulations:

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|----------------------|----------------|
| Octane               | 111-65-9       |
| n-Heptane            | 142-82-5       |
| Naphthalene          | 91-20-3        |

### SUSMP

This product contains the following substances classified as poisons as regulated by the Poisons Standard (SUSMP):

| <u>Chemical Name</u> | <u>Schedule Number(s)</u> |
|----------------------|---------------------------|
|----------------------|---------------------------|

Acetone  
Liquid Hydrocarbons

Schedule 5  
Schedule 5

### Capital Territories Environmental Regulations

This product contains the following substances listed under the Australian Capital Territories Environmental Protection Regulation:

| <u>Chemical Name</u>         | <u>Schedule</u> | <u>Schedule Name</u>                 |
|------------------------------|-----------------|--------------------------------------|
| Xylenes (o-, m-, p- isomers) | 3               | DOM - Organic Chemicals              |
| Ethylbenzene                 | 3               | Non-pesticide Anthropogenic Organics |
| Toluene                      | 3               | Non-pesticide Anthropogenic Organics |
| Benzene                      | 3               | Non-pesticide Anthropogenic Organics |

## 16. Other Information

SDS REVISION DATE: 10/31/2018

REASON FOR REVISION: Substance and/or Product Properties Changed in Section(s):  
02 - Hazard Identification  
03 - Composition/Information on Ingredients  
14 - Transport Information  
15 - Regulatory Information  
Revision Statement(s) Changed

Legend:

N.A. - Not Applicable    N.D. - Not Determined    N.E. - Not Established  
S.T.E.L. - Short Term Exposure Limit  
T.W.A. - Time Weighted Average  
W.E.S. - Workplace Exposure Standard  
W.H.S. - Work Health and Safety regulation

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.