

Safety Data Sheet



www.rustoleum.com.au

1. Identification

Product Name: UNVRSL SSPR 6PK GLOSS BLACK **Revision Date:** 05/01/2021

Name on Label: Universal Paint & Primer In One Gloss Black **Supersedes Date:** 02/11/2018

Product Identifier: 245196

Product Use/Class: Topcoat/Aerosols

Supplier: Rust-Oleum Australia & New Zealand Pty. Ltd.
8 Lakeview Drive
Scoresby, Melbourne, Victoria 3179
Australia
Ph 1 300 784 476

Manufacturer: Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, IL 60061
USA

Preparer: Regulatory Department

Emergency Telephone: 24 Hour Hotline: 1-300-366-961

2. Hazard Identification

This product is classified as a Dangerous Good per the Australian Code for the Transport of Dangerous Goods by Road and Rail. This product was assessed per Safe Work Australia criteria.

Classification

Symbol(s) of Product



Signal Word

Danger

Possible Hazards

32% of the mixture consists of ingredient(s) of unknown acute toxicity.

GHS HAZARD STATEMENTS

| | | |
|---------------------------------------|------|--|
| Carcinogenicity, category 1A | H350 | May cause cancer. |
| Compressed Gas | H280 | Contains gas under pressure; may explode if heated. |
| Eye Irritation, category 2A | H319 | Causes serious eye irritation. |
| Flammable Aerosol, category 1 | H222 | Extremely flammable aerosol. |
| Germ Cell Mutagenicity, category 1B | H340 | May cause genetic defects. |
| STOT, repeated exposure, category 2 | H373 | May cause damage to organs through prolonged or repeated exposure. |
| STOT, single exposure, category 3, NE | H336 | May cause drowsiness or dizziness. |

GHS LABEL PRECAUTIONARY STATEMENTS

| | |
|------|--|
| P201 | Obtain special instructions before use. |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. NO SMOKING. |
| P211 | Do not spray on an open flame or other ignition source. |
| P251 | Do not pierce or burn, even after use. |
| P260 | Do not breathe dust/fume/gas/mist/vapors/spray. |
| P264 | Wash hands thoroughly after handling. |

| | |
|----------------|--|
| P271 | Use only outdoors or in a well-ventilated area. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308+P313 | IF exposed or concerned: Get medical advice/attention. |
| P312 | Call a POISON CENTER or doctor/physician if you feel unwell. |
| P337+P313 | If eye irritation persists: Get medical advice/attention. |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |
| P405 | Store locked up. |
| P410+P403 | Protect from sunlight. Store in a well-ventilated place. |
| P410+P412 | Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F. |
| P501 | Dispose of contents/container in accordance with local, regional and national regulations. |

3. Composition/Information On Ingredients

HAZARDOUS SUBSTANCES

| <u>Chemical Name</u> | <u>CAS-No.</u> | <u>Wt.% Range</u> | <u>GHS Symbols</u> | <u>GHS Statements</u> |
|----------------------------------|----------------|-----------------------|--------------------|------------------------------|
| Acetone | 67-64-1 | 25-50 | GHS02-GHS07 | H225-319-332-336 |
| Propane | 74-98-6 | 10-25 | GHS04 | H280 |
| n-Butyl Acetate | 123-86-4 | 10-25 | GHS02-GHS07 | H226-336 |
| n-Butane | 106-97-8 | 2.5-10 | GHS04 | H280 |
| Solvent Naphtha, Light Aromatic | 64742-95-6 | 2.5-10 | GHS07-GHS08 | H304-315-319-332-372 |
| Barium Sulfate | 7727-43-7 | 2.5-10 | GHS07 | H332 |
| Propylene Glycol Monobutyl Ether | 5131-66-8 | 1.0-2.5 | GHS07 | H302-315-319 |
| 1,2,4-Trimethylbenzene | 95-63-6 | 1.0-2.5 | GHS02-GHS07-GHS08 | H226-304-315-319-332-335 |
| Carbon Black | 1333-86-4 | 1.0-2.5 | GHS08 | H373 |
| Ethylbenzene | 100-41-4 | 0.1-1.0 | GHS02-GHS07 | H225-315-319-332 |
| Methyl Ethyl Ketoxime | 96-29-7 | 0.1-1.0 | GHS05-GHS06-GHS08 | H302-312-317-318-331-351 |
| Cobalt 2-Ethylhexanoate | 136-52-7 | 0.1-1.0 | GHS08 | H317-319-334-350-372 |
| Naphtha, Hydrotreated Heavy | 64742-48-9 | 0.1-1.0 | GHS08 | H304-340-350 |
| Solvent Naphtha, Light Aromatic | 64742-95-6 | 0.1-1.0 | GHS07-GHS08 | H304-315-319-332-340-350-372 |

The balance of the product is Nonhazardous.

4. First-Aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

FIRST AID - SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

FIRST AID - INGESTION: Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention. If swallowed, get medical attention.

5. Fire-fighting Measures

ADG HAZCHEM CODE: None

EXTINGUISHING MEDIA: Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: FLASH POINT IS LESS THAN 20°F. EXTREMELY FLAMMABLE LIQUID AND VAPOR! Water spray may be ineffective. Closed containers may explode when exposed to extreme heat due to buildup of steam. Closed containers may explode when exposed to extreme heat. Vapors may form explosive mixtures with air. Vapors can travel to a source of ignition and flash back. Isolate from heat, electrical equipment, sparks and open flame. Perforation of the pressurized container may cause bursting of the can.

SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion. Full protective equipment including self-contained breathing apparatus should be used. Evacuate area and fight fire from a safe distance. Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

7. Handling and Storage

HANDLING: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only in a well-ventilated area. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

STORAGE: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Contents under pressure. Do not store above 120 ° F. Store large quantities in buildings designed and protected for storage of flammable aerosols. Keep away from heat, sparks, flame and sources of ignition. Contents under pressure. Do not expose to heat or store above 120 ° F. Avoid excess heat. Product should be stored in tightly sealed containers and protected from heat, moisture, and foreign materials.

Advice on Safe Handling of Combustible Dust: No Information

8. Exposure Controls / Personal Protection

| Chemical Name | CAS-No. | Weight % Less Than | WHS WES TLV-TWA | WHS WES TLV-STEL |
|----------------------------------|------------|--------------------|-----------------|------------------|
| Acetone | 67-64-1 | 30.0 | 250 ppm | 500 ppm |
| Propane | 74-98-6 | 20.0 | N.E. | N.E. |
| n-Butyl Acetate | 123-86-4 | 15.0 | 50 ppm | 150 ppm |
| n-Butane | 106-97-8 | 10.0 | N.E. | 1000 ppm |
| Solvent Naphtha, Light Aromatic | 64742-95-6 | 5.0 | N.E. | N.E. |
| Barium Sulfate | 7727-43-7 | 5.0 | 5 mg/m3 | N.E. |
| Propylene Glycol Monobutyl Ether | 5131-66-8 | 5.0 | N.E. | N.E. |
| 1,2,4-Trimethylbenzene | 95-63-6 | 5.0 | N.E. | N.E. |
| Carbon Black | 1333-86-4 | 5.0 | 3 mg/m3 | N.E. |
| Ethylbenzene | 100-41-4 | 1.0 | 20 ppm | N.E. |
| Methyl Ethyl Ketoxime | 96-29-7 | 1.0 | 10 ppm | N.E. |
| Cobalt 2-Ethylhexanoate | 136-52-7 | 1.0 | N.E. | N.E. |
| Naphtha, Hydrotreated Heavy | 64742-48-9 | 1.0 | N.E. | N.E. |
| Solvent Naphtha, Light Aromatic | 64742-95-6 | 1.0 | N.E. | N.E. |

PERSONAL PROTECTION

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment. Provide general dilution of local exhaust ventilation in volume and pattern to keep TLV of hazardous ingredients below acceptable limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. A NIOSH/MSHA approved air purifying respirator with organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

SKIN PROTECTION: Use impervious gloves to prevent skin contact and absorption of this material through the skin.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications. Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

9. Physical and Chemical Properties

| | | | |
|---------------------------------|---------------------|--|------------|
| Appearance: | Aerosolized Mist | Physical State: | Liquid |
| Odor: | Solvent Like | Odor Threshold: | N.E. |
| Specific Gravity: | 0.775 | pH: | N.A. |
| Freeze Point, °C: | N.D. | Viscosity: | N.D. |
| Solubility in Water: | Slight | Partition Coefficient, n-octanol/water: | N.D. |
| Decomposition Temp., °C: | N.D. | Explosive Limits, vol%: | 1.0 - 13.0 |
| Boiling Range, °C: | -37 - 3,000 | Flash Point, °C: | -96 |
| Flammability: | Supports Combustion | Auto-Ignition Temp., °C: | N.D. |
| Evaporation Rate: | Faster than Ether | Vapor Pressure: | N.D. |
| Vapor Density: | Heavier than Air | | |

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

Conditions to Avoid: Avoid temperatures above 120°F (49°C). Avoid all possible sources of ignition.

Incompatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

Hazardous Decomposition: By open flame, carbon monoxide and carbon dioxide. When heated to decomposition, it emits acrid smoke and irritating fumes. Contains solvents which may form carbon monoxide, carbon dioxide, and formaldehyde.

Hazardous Polymerization: Will not occur under normal conditions.

Stability: This product is stable under normal storage conditions.

11. Toxicological Information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Causes Serious Eye Irritation

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Substance may cause slight skin irritation. Prolonged or repeated contact may cause skin irritation.

EFFECTS OF OVEREXPOSURE - INHALATION: Harmful if inhaled. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. High vapor concentrations are irritating to the eyes, nose, throat and lungs. Prolonged or excessive inhalation may cause respiratory tract irritation.

EFFECTS OF OVEREXPOSURE - INGESTION: Harmful if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis, and blurred vision) and/or damage. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Contains carbon black. Chronic inflammation, lung fibrosis, and lung tumors have been observed in some rats experimentally exposed for long periods of time to excessive concentrations of carbon black and several insoluble fine dust particles. Tumors have not been observed in other animal species (i.e., mouse and hamster) under similar circumstances and study conditions. Epidemiological studies of North American workers show no evidence of clinically significant adverse health effects due to occupational exposure to carbon black.

Carbon black is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC and is proposed to be listed as A4- "not classified as a human carcinogen" by the American Conference of Governmental Industrial Hygienists. Significant exposure is not anticipated during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of carbon black in the formula. IARC lists Ethylbenzene as a possible human carcinogen (group 2B). May cause genetic defects.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| <u>CAS-No.</u> | <u>Chemical Name</u> | <u>Oral LD50</u> | <u>Dermal LD50</u> | <u>Vapor LC50</u> |
|----------------|----------------------------------|------------------|---------------------|-------------------|
| 67-64-1 | Acetone | 5800 mg/kg Rat | >15700 mg/kg Rabbit | 50.1 mg/L Rat |
| 123-86-4 | n-Butyl Acetate | 10768 mg/kg Rat | >17600 mg/kg Rabbit | > 21 mg/L Rat |
| 106-97-8 | n-Butane | N.E. | N.E. | 658 mg/L Rat |
| 64742-95-6 | Solvent Naphtha, Light Aromatic | 8400 mg/kg Rat | >2000 mg/kg Rabbit | N.E. |
| 7727-43-7 | Barium Sulfate | 307000 mg/kg Rat | N.E. | N.E. |
| 5131-66-8 | Propylene Glycol Monobutyl Ether | 1900 mg/kg Rat | N.E. | N.E. |
| 95-63-6 | 1,2,4-Trimethylbenzene | 3280 mg/kg Rat | >3160 mg/kg Rabbit | 18 mg/L Rat |
| 1333-86-4 | Carbon Black | >15400 mg/kg Rat | N.E. | N.E. |
| 100-41-4 | Ethylbenzene | 3500 mg/kg Rat | 15400 mg/kg Rabbit | 17.4 mg/L Rat |
| 96-29-7 | Methyl Ethyl Ketoxime | 930 mg/kg Rat | 1100 mg/kg Rabbit | >4.83 mg/L Rat |
| 136-52-7 | Cobalt 2-Ethylhexanoate | N.E. | >5000 mg/kg Rabbit | N.E. |
| 64742-48-9 | Naphtha, Hydrotreated Heavy | >6000 mg/kg Rat | >3160 mg/kg Rabbit | N.E. |
| 64742-95-6 | Solvent Naphtha, Light Aromatic | 8400 mg/kg Rat | >2000 mg/kg Rabbit | N.E. |

N.E. - Not Established

12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components. Product is a mixture of listed components.

13. Disposal Information

DISPOSAL INFORMATION: Do not incinerate closed containers. Dispose of material in accordance to local, state, and federal regulations and ordinances. This product as supplied is a USEPA defined ignitable hazardous waste. Dispose of unusable product as a hazardous waste (D001) in accordance with local, state, and federal regulation.

14. Transport Information

| | <u>Domestic (USDOT)</u> | <u>International (IMDG)</u> | <u>Air (IATA)</u> | <u>ADG</u> |
|------------------------------|---|-----------------------------|---------------------|------------|
| UN Number: | N.A. | 1950 | 1950 | 1950 |
| Proper Shipping Name: | Paint and Related Spray Products in Ltd Qty | Aerosols | Aerosols, flammable | Aerosols |
| Hazard Class: | N.A. | 2 | 2.1 | 2.1 |
| Packing Group: | N.A. | N.A. | N.A. | N.A. |
| Limited Quantity: | Yes | Yes | Yes | Yes |
| ADG Hazchem Code: | None | | | |

15. Regulatory Information

Montreal Protocol

No Montreal Protocol components exist in this product.

Stockholm Convention

No Stockholm Convention components exist in this product.

Rotterdam Convention

No Rotterdam Convention components exist in this product.

MARPOL

This product contains the following substances listed under the MARPOL regulations:

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|----------------------|----------------|
| n-Nonane | 111-84-2 |
| Naphthalene | 91-20-3 |

SUSMP

This product contains the following substances classified as poisons as regulated by the Poisons Standard (SUSMP):

| <u>Chemical Name</u> | <u>Schedule Number(s)</u> |
|----------------------|---------------------------|
| Acetone | Schedule 5 |
| Liquid Hydrocarbons | Schedule 5 |

Capital Territories Environmental Regulations

This product contains the following substances listed under the Australian Capital Territories Environmental Protection Regulation:

| <u>Chemical Name</u> | <u>Schedule</u> | <u>Schedule Name</u> |
|------------------------------|-----------------|--------------------------------------|
| Xylenes (o-, m-, p- Isomers) | 3 | DOM - Organic Chemicals |
| Ethylbenzene | 3 | Non-pesticide Anthropogenic Organics |
| Toluene | 3 | Non-pesticide Anthropogenic Organics |
| Cadmium Compounds | 3 | AQUA - Inorganic Chemicals |
| Lead Compounds | 3 | AQUA - Inorganic Chemicals |
| Benzene | 3 | Non-pesticide Anthropogenic Organics |

16. Other Information

SDS REVISION DATE: 05/01/2021

REASON FOR REVISION: Product Composition Changed
 Substance and/or Product Properties Changed in Section(s):
 01 - Identification
 02 - Hazard Identification
 09 - Physical & Chemical Properties
 14 - Transport Information
 16 - Other Information
 Revision Statement(s) Changed

Legend:

N.A. - Not Applicable N.D. - Not Determined N.E. - Not Established
 S.T.E.L. - Short Term Exposure Limit
 T.W.A. - Time Weighted Average
 W.E.S. - Workplace Exposure Standard
 W.H.S. - Work Health and Safety regulation

Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.