

Revision Date: 05/06/2024

Rust-Oleum Australia Multi Component Product Information Sheet

274268 TRANSF KIT 2PK IBU BENCHTOP DIAMOND WHT is a multi component product composed of the following individual chemical components:

295388 TRANSF PT 12PK AUS TOP COAT PART B WHITE

293538 TRANSF HP 6PK AUS TOP COAT PART A

293532 TRANSF QT 4PK AUS ADHESIVE BASE COAT WH

SDSs for each component follow this cover sheet.

Transportation Information

	Domestic (USDOT)	International (IMDG)	<u>Air (IATA)</u>	ADG (Australia)
UN Number:	N.A.	1263	1263	1263
Proper Shipping Name:	Paint Products in Limited Quantities	Paint	Paint	Paint
Hazard Class:	N.A.	3	3	3
Packing Group:	N.A.	III	III	III
Limited Quantity:	Yes	Yes	Yes	Yes

Finished Good Schedule B Harmonized Tariff Code 3907.30.0000

Revision Date: 05/06/2024

Date Printed: 05/06/2024 Page 1 / 5

Safety Data Sheet



www.rustoleum.com.au

1. Identification

Product Name: TRANSF PT 12PK AUS TOP COAT PART B

Revision Date:

05/06/2024

Name on Label: Top Coat Part B

Supercedes Date:

01/12/2023

Product Identifier: 295388

Product Use/Class:

Top Coat Part B/ Transformations

Supplier: Rust-Oleum Australia & New Zealand Pty.

Ltd.

Level 2, 307 Ferntree Gully Road Mount Waverley, Victoria 3149

Australia

WHITE

Ph 1 300 784 476

Preparer: Regulatory Department

Emergency Telephone: 24 Hour Hotline: 1-300-366-961

Manufacturer:

Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061

USA

2. Hazard Identification

This product is not classified as a Dangerous Good per the Australian Code for the Transport of Dangerous Goods by Road and Rail. This product was assessed per Safe Work Australia criteria.

Classification

Symbol(s) of Product

Not a hazardous substance or mixture per Safe Work Australia criteria.

Signal Word

No Signal Word has been assigned.

Possible Hazards

1% of the mixture consists of ingredient(s) of unknown acute toxicity.

3. Composition/Information On Ingredients

HAZARDOUS SUBSTANCES

<u>Chemical Name</u> <u>CAS-No.</u> <u>Range</u> <u>GHS Symbols</u> <u>GHS Statements</u>

Wt.%

Proprietary Hydrocarbon Solvent PROPRIET ARY 1.0-2.5 Not Available Not Available

The balance of the product is Nonhazardous.

4. First-Aid Measures

Date Printed: 05/06/2024 Page 2 / 5

First Aid - Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed. Remove contact lenses, if present and easy to do. Continue rinsing.

First Aid - Skin Contact: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

First Aid - Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

First Aid - Ingestion: If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cupfuls of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively.

5. Fire-fighting Measures

ADG HAZCHEM CODE: Not Hazardous

EXTINGUISHING MEDIA: Agueous Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

Unusual Fire and Explosion Hazards: Keep containers tightly closed. No unusual fire or explosion hazards noted.

Special Fire Fighting Procedures: Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

6. Accidental Release Measures

Steps to Be Taken If Material Is Released or Spilled: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

Handling and Storage

Handling: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

Storage: Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Advice on Safe Handling of Combustible Dust: No Information

8. Exposure Controls / Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	WHS WES TLV-TWA	WHS WES TLV-STEL
Proprietary Hydrocarbon Solvent	PROPRIETARY	5.0	N.E.	N.E.

PERSONAL PROTECTION

Engineering Controls: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

Respiratory Protection: Wear an approved (or equivalent) full-facepiece airline respirator according to AS/NZS 1715-2009 and AS/NZS 1716-2012 in the positive pressure mode with emergency escape provisions. An approved air purifying respirator with organic vapor cartridge or canister according to AS/NZS 1715-2009 and AS/NZS 1716-2012 may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. A respiratory protection program that meets AS/NZS 1715-2009 and AS/NZS 1716-2012 requirements must be followed whenever workplace conditions warrant a respirator's use. Users of this product in industrial/OEM applications must use one of the following forms of respiratory protection:

- a. AS/NZS 1715-2009 and AS/NZS 1716-2012 compliant supplied-air respirator operated in pressure demand or continuous flow mode and equipped with a tight fitting facepiece
- b. AS/NZS 1715-2009 and AS/NZS 1716-2012 compliant air-purifying respirator equipped with a full facepiece and organic gas/vapor cartridges
- c. AS/NZS 1715-2009 and AS/NZS 1716-2012 compliant powered air-purifying respirator equipped with a full facepeice and organic gas/vapor cartridges.

Skin Protection: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

Eye Protection: Use safety eyewear designed to protect against splash of liquids.

Date Printed: 05/06/2024 Page 3 / 5

Other Protective Equipment: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

Hygienic Practices: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

9. Physical and Chemical Properties

Appearance: Liquid Physical State: Liquid Odor: Odor Threshold: Solvent Like N.E. Specific Gravity: pH: 1.009 N.A. Freeze Point, °C: N.D. Viscosity: N.D. Solubility in Water: Partition Coefficient, n-octanol/ None N.D. water: Decomposition Temp., °C: N.D. Boiling Range, °C: **Explosive Limits, vol%:** 204 - 537 N.A. - N.A. Flammability: Flash Point, °C: Does not Support Combustion 94 Auto-Ignition Temp., °C: **Evaporation Rate:** Slower than Ether N.D. Vapor Density: Vapor Pressure: N.D. Heavier than Air

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

Conditions to Avoid: Avoid excess heat.

Incompatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

Hazardous Decomposition: When heated to decomposition, it emits acrid smoke and irritating fumes.

Hazardous Polymerization: Will not occur under normal conditions. **Stability:** This product is stable under normal storage conditions.

11. Toxicological Information

Effects of Overexposure - Eye Contact: Irritating, and may injure eye tissue if not removed promptly.

Effects of Overexposure - Skin Contact: Low hazard for usual industrial handling or commercial handling by trained personnel.

Effects of Overexposure - Inhalation: High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. Routine handling and application does not require use of respiratory protection; however, if air monitoring demonstrates vapor, mist, or dust levels above applicable limits, wear an appropriate, properly fitted respirator (meets AS/NZS 1715-2009 and AS/NZS 1716-2012 requirements) during handling and application. Follow respirator manufacturer's directions for respirator use.

Effects of Overexposure - Ingestion: Substance may be harmful if swallowed.

Effects of Overexposure - Chronic Hazards: No Information

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u> <u>Chemical Name</u> <u>Oral LD50</u> <u>Dermal LD50</u> <u>Vapor LC50</u>

No hazardous items exist.

N.E. - Not Established

12. Ecological Information

Ecological Information: No ecotoxicity data was found for this product.

Toxicity: The acute toxicity effects of this product have not been tested. Data on individual components are tabulated below:

Date Printed: 05/06/2024 Page 4 / 5

AQUATIC ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No. Chemical Name Algae Daphnia/Aquatic Fish

No

hazardous items exist

N.E. - Not Established

Persistence and degradability: The persistence and degradability of this product have not been tested.

BIOACCUMULATIVE POTENTIAL:

Product/ingredient name Octanol-water par. Coeff (log KOW) Bio. Conc. Factor (BCF)

No information available

Mobility in Soil: The mobility in soil of this product has not been tested.

Other adverse effects: This product has not been tested for other adverse ecological effects.

13. Disposal Information

Disposal: Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not incinerate closed containers.

14. Transport Information

	Domestic (USDOT)	<u>International (IMDG)</u>	<u>Air (IATA)</u>	<u>ADG</u>
UN Number:	N.A.	N.A.	N.A.	N.A.

Proper Shipping Name: Not Regulated Not Regulated Not Regulated Not Regulated

 Hazard Class:
 N.A.
 N.A.
 N.A.
 N.A.

 Packing Group:
 N.A.
 N.A.
 N.A.
 N.A.
 N.A.

 Limited Quantity:
 No
 No
 No
 No
 No

ADG Hazchem Code: Not Hazardous

15. Regulatory Information

Montreal Protocol

No Montreal Protocol components exist in this product.

Stockholm Convention

No Stockholm Convention components exist in this product.

Rotterdam Convention

No Rotterdam Convention components exist in this product.

MARPOL

No substances listed under the MARPOL regulations exist in this product.

Date Printed: 05/06/2024 Page 5 / 5

SUSMP

This product contains the following substances classified as poisons as regulated by the Poisons Standard (SUSMP):

<u>Chemical Name</u> <u>Schedule Number(s)</u>

None N.A.

Capital Territories Environmental Regulations

No Capital Territory components exist in this product.

16. Other Information

SDS REVISION DATE: 05/06/2024

REASON FOR REVISION: Substance and/or Product Properties Changed in Section(s):

14 - Transport Information Revision Statement(s) Changed

Legend:

N.A. - Not Applicable N.D. - Not Determined N.E. - Not Established

S.T.E.L. - Short Term Exposure Limit T.W.A. - Time Weighted Average W.E.S. - Workplace Exposure Standard

W.H.S. - Work Health and Safety regulation

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.

Page 1 / 6 Date Printed: 05/06/2024

Safety Data Sheet



www.rustoleum.com.au

1. Identification

TRANSF HP 6PK AUS TOP COAT PART A **Product Name: Revision Date:** 05/06/2024

Name on Label: Top Coat Part A Supercedes Date: 01/12/2023

Product Identifier: 293538

Product Use/Class: Top Coat Part A/ Transformation

Rust-Oleum Australia & New Zealand Pty. **Rust-Oleum Corporation** Manufacturer: Supplier:

11 Hawthorn Parkway Vernon Hills, IL 60061

USA

Level 2, 307 Ferntree Gully Road

Mount Waverley, Victoria 3149

Australia

Ph 1 300 784 476

Preparer: Regulatory Department

Emergency Telephone: 24 Hour Hotline: 1-300-366-961

2. Hazard Identification

This product is classified as a Dangerous Good per the Australian Code for the Transport of Dangerous Goods by Road and Rail. This product was assessed per Safe Work Australia criteria.

Classification

Symbol(s) of Product





Possible Hazards

70% of the mixture consists of ingredient(s) of unknown acute toxicity.

GHS Hazard Statements

H226 Flammable liquid and vapour. Flammable Liquid, category 3 STOT, Single Exposure, category 3, NE H336 May cause drowsiness or dizziness. Acute Toxicity, Oral and Inhalation, category H302+H332 Harmful if swallowed or if inhaled.

GHS Label Precautionary Statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / protective clothing / eye protection / face protection.

P330 Rinse mouth. P405 Store locked up.

P501 Dispose of contents and container in accordance with local, regional and national regulations. P303+P361+P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or

shower].

Date Printed: 05/06/2024 Page 2 / 6

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P370+P378 In case of fire: Extinguish using suitable extinguishing media. P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P317 Get medical help.

P301+P316 IF SWALLOWED: Get emergency medical help immediately.

GHS SDS Precautionary Statements

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical, ventilating, lighting, or pouring equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P270 Do not eat, drink or smoke when using this product.

3. Composition/Information On Ingredients

HAZARDOUS SUBSTANCES

Chemical Name	CAS-No.	Wt.% Range	GHS Symbols	GHS Statements
Carboxyl Functional Polyester	PROPRIET ARY	50-75	Not Available	Not Available
Methyl n-Amyl Ketone	110-43-0	10-25	GHS02-GHS07	H226-302+H332-336
2-Propanol	67-63-0	2.5-10	GHS02-GHS07	H225-302-319-336
Propylene Glycol Monomethyl Ether	107-98-2	2.5-10	GHS02-GHS07	H226-332-336
1,4,5,6,7,7-Hexachloro-5-norbornene-2,3-dicarboxylic acid	115-28-6	0.1-1.0	GHS07	H302

The balance of the product is Nonhazardous.

4. First-Aid Measures

First Aid - Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed. Remove contact lenses, if present and easy to do. Continue rinsing.

First Aid - Skin Contact: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

First Aid - Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

First Aid - Ingestion: If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cupfuls of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively. If swallowed, get medical attention.

5. Fire-fighting Measures

ADG HAZCHEM CODE: .3Y

EXTINGUISHING MEDIA: Agueous Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

Unusual Fire and Explosion Hazards: Closed containers may explode when exposed to extreme heat due to buildup of steam. Vapors can travel to a source of ignition and flash back. Keep containers tightly closed. Combustible liquid and vapor.

Special Fire Fighting Procedures: Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion. Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred. Evacuate area and fight fire from a safe distance. Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

Date Printed: 05/06/2024 Page 3 / 6

Accidental Release Measures

Steps to Be Taken If Material Is Released or Spilled: Eliminate all ignition sources; use explosion-proof equipment. Place material in a container and dispose of according to local, provincial, state and federal regulations. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

7. Handling and Storage

Handling: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Ground and bond containers when transferring material from one vessel to another. Vapor can be ignited by static discharge. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

Storage: Keep away from heat, sparks, flame and sources of ignition. Avoid excess heat. Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Advice on Safe Handling of Combustible Dust: No Information

8. Exposure Controls / Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	WHS WES TLV-TWA	WHS WES TLV-STEL
Carboxyl Functional Polyester	PROPRIETARY	70.0	N.E.	N.E.
Methyl n-Amyl Ketone	110-43-0	25.0	50 ppm	N.E.
2-Propanol	67-63-0	5.0	200 ppm	400 ppm
Propylene Glycol Monomethyl Ether	107-98-2	5.0	50 ppm	100 ppm
1,4,5,6,7,7-Hexachloro-5-norbornene-2,3-dicarboxylic acid	115-28-6	1.0	N.E.	N.E.

PERSONAL PROTECTION

Engineering Controls: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

Respiratory Protection: Wear an approved (or equivalent) full-facepiece airline respirator according to AS/NZS 1715-2009 and AS/NZS 1716-2012 in the positive pressure mode with emergency escape provisions. An approved air purifying respirator with organic vapor cartridge or canister according to AS/NZS 1715-2009 and AS/NZS 1716-2012 may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. A respiratory protection program that meets AS/NZS 1715-2009 and AS/NZS 1716-2012 requirements must be followed whenever workplace conditions warrant a respirator's use. Users of this product in industrial/OEM applications must use one of the following forms of respiratory protection:

- a. AS/NZS 1715-2009 and AS/NZS 1716-2012 compliant supplied-air respirator operated in pressure demand or continuous flow mode and equipped with a tight fitting facepiece
- b. AS/NZS 1715-2009 and AS/NZS 1716-2012 compliant air-purifying respirator equipped with a full facepiece and organic gas/vapor cartridges
- AS/NZS 1715-2009 and AS/NZS 1716-2012 compliant powered air-purifying respirator equipped with a full facepeice and organic gas/vapor cartridges.

Skin Protection: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

Eye Protection: Use safety eyewear designed to protect against splash of liquids.

Other Protective Equipment: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

Hygienic Practices: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

Date Printed: 05/06/2024 Page 4 / 6

9. Physical and Chemical Properties

Physical State: Appearance: Liquid Liquid Odor: Solvent Like **Odor Threshold:** N.E. Specific Gravity: :Ha 1.231 N.A. Freeze Point, °C: Viscosity: N.D. N.D. Partition Coefficient, n-octanol/ Solubility in Water: Slight N.D. water: Decomposition Temp., °C: N.D. Explosive Limits, vol%: Boiling Range, °C: 82 - 149 N.A. - N.A. Flammability: Supports Combustion Flash Point, °C: 24 **Evaporation Rate:** Auto-Ignition Temp., °C: Slower than Ether N.D. Vapor Density: Heavier than Air Vapor Pressure: NΩ

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

Conditions to Avoid: Avoid temperatures above 120°F (49°C). Avoid all possible sources of ignition. Avoid excess heat.

Incompatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

Hazardous Decomposition: When heated to decomposition, it emits acrid smoke and irritating fumes.

Hazardous Polymerization: Will not occur under normal conditions. **Stability:** This product is stable under normal storage conditions.

11. Toxicological Information

Effects of Overexposure - Eye Contact: Irritating, and may injure eye tissue if not removed promptly.

Effects of Overexposure - Skin Contact: Low hazard for usual industrial handling or commercial handling by trained personnel.

Effects of Overexposure - Inhalation: High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. Routine handling and application does not require use of respiratory protection; however, if air monitoring demonstrates vapor, mist, or dust levels above applicable limits, wear an appropriate, properly fitted respirator (meets AS/NZS 1715-2009 and AS/NZS 1716-2012 requirements) during handling and application. Follow respirator manufacturer's directions for respirator use.

Effects of Overexposure - Ingestion: Substance may be harmful if swallowed.

Effects of Overexposure - Chronic Hazards: High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis, and blurred vision) and/or damage. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
110-43-0	Methyl n-Amyl Ketone	1600 mg/kg Rat	10300 mg/kg Rabbit	N.E.
67-63-0	2-Propanol	1870 mg/kg Rat	4059 mg/kg Rabbit	72.6 mg/L Rat
107-98-2	Propylene Glycol Monomethyl Ether	5000 mg/kg Rat	13000 mg/kg Rabbit	25
115-28-6	1,4,5,6,7,7-Hexachloro-5-norbornene-2,3-dicarboxylic acid	1770 mg/kg Rat	N.E.	N.E.

N.E. - Not Established

12. Ecological Information

Ecological Information: Product is a mixture of listed components. No ecotoxicity data was found for this product.

Toxicity: The acute toxicity effects of this product have not been tested. Data on individual components are tabulated below:

AQUATIC ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	<u>Algae</u>	Daphnia/Aquatic	<u>Fish</u>
110-43-0	Methyl n-Amyl Ketone	N.E.	N.E.	126 - 137 mg/L
67-63-0	2-Propanol	>1000 mg/L	13299 mg/L	9640 mg/L
107-98-2	Propylene Glycol Monomethyl Ether	N.E.	23300 mg/L	20.8 g/L

Date Printed: 05/06/2024 Page 5 / 6

N.E. - Not Established

Persistence and degradability: The persistence and degradability of this product have not been tested.

BIOACCUMULATIVE POTENTIAL:

Product/ingredient name	Octanol-water par. Coeff (log KOW)	Bio. Conc. Factor (BCF)
Methyl n-Amyl Ketone	2.26	N.I.
2-Propanol	0.05	N.I.
Propylene Glycol Monomethyl Ether	<1	<2 dimensionless

Mobility in Soil: The mobility in soil of this product has not been tested.

Other adverse effects: This product has not been tested for other adverse ecological effects.

13. Disposal Information

Disposal: Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not incinerate closed containers.

14. Transport Information

	Domestic (USDOT)	International (IMDG)	<u>Air (IATA)</u>	<u>ADG</u>
UN Number:	N.A.	1263	1263	1263
Proper Shipping Name:	Paint Products in Limited Quantities	Paint	Paint	Paint
Hazard Class:	N.A.	3	3	3
Packing Group:	N.A.	III	III	III
Limited Quantity:	Yes	Yes	Yes	Yes
ADG Hazchem Code:	.3Y			

15. Regulatory Information

Montreal Protocol

No Montreal Protocol components exist in this product.

Stockholm Convention

No Stockholm Convention components exist in this product.

Rotterdam Convention

No Rotterdam Convention components exist in this product.

MARPOL

No substances listed under the MARPOL regulations exist in this product.

SUSMP

This product contains the following substances classified as poisons as regulated by the Poisons Standard (SUSMP):

Chemical Name

Schedule Number(s)

None Top Coat Part A N.A.

Date Printed: 05/06/2024 Page 6 / 6

Capital Territories Environmental Regulations

No Capital Territory components exist in this product.

16. Other Information

SDS REVISION DATE: 05/06/2024

REASON FOR REVISION: Substance and/or Product Properties Changed in Section(s):

14 - Transport Information Revision Statement(s) Changed

Legend:

N.A. - Not Applicable N.D. - Not Determined N.E. - Not Established

S.T.E.L. - Short Term Exposure Limit T.W.A. - Time Weighted Average W.E.S. - Workplace Exposure Standard W.H.S. - Work Health and Safety regulation

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.

Date Printed: 05/06/2024 Page 1 / 6

Safety Data Sheet



05/06/2024

04/12/2023

1. Identification

Product Name: TRANSF QT 4PK AUS ADHESIVE BASE

COAT WH

Name on Label: Base Coat

Product Identifier: 293532

Product Use/Class: Base Coat/ Transformations

Supplier: Rust-Oleum Australia & New Zealand Pty.

Ltd.

Level 2, 307 Ferntree Gully Road Mount Waverley, Victoria 3149

Australia

Ph 1 300 784 476

Preparer: Regulatory Department

Emergency Telephone: 24 Hour Hotline: 1-300-366-961

www.rustoleum.com.au

Revision Date:

Supercedes Date:

Manufacturer: Rust-Oleum Corporation

11 Hawthorn Parkway Vernon Hills, IL 60061

USA

2. Hazard Identification

This product is not classified as a Dangerous Good per the Australian Code for the Transport of Dangerous Goods by Road and Rail. This product was assessed per Safe Work Australia criteria.

Classification

Symbol(s) of Product



Signal Word

Danger

Possible Hazards

21% of the mixture consists of ingredient(s) of unknown acute toxicity.

GHS Hazard Statements

Respiratory Sensitizer, category 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carcinogenicity, category 1B H350 May cause cancer.

GHS Label Precautionary Statements

P201 Obtain special instructions before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves / protective clothing / eye protection / face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P405 Store locked up.

P501 Dispose of contents and container in accordance with local, regional and national regulations.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P342+P316 If experiencing respiratory symptoms: Get emergency medical help immediately.

Date Printed: 05/06/2024 Page 2 / 6

3. Composition/Information On Ingredients

HAZARDOUS SUBSTANCES

<u>Chemical Name</u>	CAS-No.	Wt.% Range	GHS Symbols	GHS Statements
Titanium Dioxide	13463-67-7	10-25	Not Available	Not Available
Hydrous Magnesium Silicate	14807-96-6	1.0-2.5	Not Available	Not Available
Ethylene Glycol	107-21-1	1.0-2.5	GHS07-GHS08	H334-335
Zinc Oxide	1314-13-2	0.1-1.0	Not Available	Not Available
Distillates (Petroleum) Solvent-Dewaxed Heavy Paraffinic	64742-65-0	0.1-1.0	GHS07	H315-332
Hydrotreated Heavy Paraffinic Petroleum Distillates	64742-54-7	0.1-1.0	GHS07-GHS08	H315-332-350-361D
Amorphous Silica	7631-86-9	0.1-1.0	GHS08	H372
Sodium Nitrite	7632-00-0	0.1-1.0	GHS03-GHS06	H272-301+H331-319
Carbamic Acid, 1H-Benzimidazol-2-yl-, Methyl Ester	10605-21-7	<0.1	GHS08	H340-360FD

The balance of the product is Nonhazardous.

4. First-Aid Measures

First Aid - Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed. Remove contact lenses, if present and easy to do. Continue rinsing.

First Aid - Skin Contact: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

First Aid - Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

First Aid - Ingestion: If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cupfuls of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively.

5. Fire-fighting Measures

ADG HAZCHEM CODE: Not Hazardous

EXTINGUISHING MEDIA: Aqueous Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

Unusual Fire and Explosion Hazards: Keep containers tightly closed. No unusual fire or explosion hazards noted.

Special Fire Fighting Procedures: Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

Accidental Release Measures

Steps to Be Taken If Material Is Released or Spilled: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

7. Handling and Storage

Date Printed: 05/06/2024 Page 3 / 6

Handling: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

Storage: Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Advice on Safe Handling of Combustible Dust: No Information

8. Exposure Controls / Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	WHS WES TLV-TWA	WHS WES TLV-STEL
Titanium Dioxide	13463-67-7	20.0	0.2 mg/m3	N.E.
Hydrous Magnesium Silicate	14807-96-6	5.0	2 mg/m3	N.E.
Ethylene Glycol	107-21-1	5.0	25 ppm	50 ppm
Zinc Oxide	1314-13-2	1.0	2 mg/m3	10 mg/m3
Distillates (Petroleum) Solvent-Dewaxed Heavy Paraffinic	64742-65-0	1.0	N.E.	N.E.
Hydrotreated Heavy Paraffinic Petroleum Distillates	64742-54-7	1.0	N.E.	N.E.
Amorphous Silica	7631-86-9	1.0	N.E.	N.E.
Sodium Nitrite	7632-00-0	1.0	N.E.	N.E.
Carbamic Acid, 1H-Benzimidazol-2-yl-, Methyl Ester	10605-21-7	0.1	N.E.	N.E.

PERSONAL PROTECTION

Engineering Controls: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

Respiratory Protection: Wear an approved (or equivalent) full-facepiece airline respirator according to AS/NZS 1715-2009 and AS/NZS 1716-2012 in the positive pressure mode with emergency escape provisions. An approved air purifying respirator with organic vapor cartridge or canister according to AS/NZS 1715-2009 and AS/NZS 1716-2012 may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. A respiratory protection program that meets AS/NZS 1715-2009 and AS/NZS 1716-2012 requirements must be followed whenever workplace conditions warrant a respirator's use. Users of this product in industrial/OEM applications must use one of the following forms of respiratory protection:

- a. AS/NZS 1715-2009 and AS/NZS 1716-2012 compliant supplied-air respirator operated in pressure demand or continuous flow mode and equipped with a tight fitting facepiece
- b. AS/NZS 1715-2009 and AS/NZS 1716-2012 compliant air-purifying respirator equipped with a full facepiece and organic gas/vapor cartridges
- c. AS/NZS 1715-2009 and AS/NZS 1716-2012 compliant powered air-purifying respirator equipped with a full facepeice and organic gas/vapor cartridges.

Skin Protection: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

Eye Protection: Use safety eyewear designed to protect against splash of liquids.

Other Protective Equipment: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

Hygienic Practices: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

9. Physical and Chemical Properties

Appearance:	Liquid	Physical State:	Liquid
Odor:	Mild	Odor Threshold:	N.E.
Specific Gravity:	1.409	pH:	N.A.
Freeze Point, °C:	N.D.	Viscosity:	N.D.
Solubility in Water:	Miscible	Partition Coefficient, n-octanol/	ND
Decomposition Temp., °C:	N.D.	water:	N.D.
Boiling Range, °C:	100 - 537	Explosive Limits, vol%:	3.2 - 15.3
Flammability:	Does not Support Combustion	Flash Point, °C:	100
Evaporation Rate:	Slower than Ether	Auto-Ignition Temp., °C:	N.D.
Vapor Density:	Heavier than Air	Vapor Pressure:	N.D.

(See "Other information" Section for abbreviation legend)

Date Printed: 05/06/2024 Page 4 / 6

10. Stability and Reactivity

Conditions to Avoid: Avoid excess heat.

Incompatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

Hazardous Decomposition: When heated to decomposition, it emits acrid smoke and irritating fumes.

Hazardous Polymerization: Will not occur under normal conditions. **Stability:** This product is stable under normal storage conditions.

11. Toxicological Information

Effects of Overexposure - Eye Contact: Irritating, and may injure eye tissue if not removed promptly.

Effects of Overexposure - Skin Contact: Low hazard for usual industrial handling or commercial handling by trained personnel.

Effects of Overexposure - Inhalation: High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. Constituents of this product include crystalline silica dust which, if inhalable, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems. Routine handling and application does not require use of respiratory protection; however, if air monitoring demonstrates vapor, mist, or dust levels above applicable limits, wear an appropriate, properly fitted respirator (meets AS/NZS 1715-2009 and AS/NZS 1716-2012 requirements) during handling and application. Follow respirator manufacturer's directions for respirator use.

Effects of Overexposure - Ingestion: Substance may be harmful if swallowed.

Effects of Overexposure - Chronic Hazards: Contains Titanium Dioxide. Titanium Dioxide is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC. No significant exposure to Titanium Dioxide is thought to occur during the use of products in which Titanium Dioxide is bound to other materials, such as in paints during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of Titanium Dioxide in the formula. (Ref: IARC Monograph, Vol. 93, 2010)

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Contact

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	<u>Chemical Name</u>	Oral LD50	Dermal LD50	Vapor LC50
13463-67-7	Titanium Dioxide	>10000 mg/kg Rat	6000	N.E.
14807-96-6	Hydrous Magnesium Silicate	6000	N.E.	30
107-21-1	Ethylene Glycol	4700 mg/kg Rat	10600 mg/kg Rat	N.E.
1314-13-2	Zinc Oxide	>5000 mg/kg Rat	>2000 mg/kg Rat	N.E.
64742-65-0	Distillates (Petroleum) Solvent-Dewaxed Heavy Paraffinic	>15000 mg/kg Rat	>5000 mg/kg Rabbit	21 mg/L
64742-54-7	Hydrotreated Heavy Paraffinic Petroleum Distillates	15000 mg/kg Rat	>5000 mg/kg Rabbit	N.E.
7631-86-9	Amorphous Silica	7900 mg/kg Rat	>5000 mg/kg Rabbit	25 mg/L
7632-00-0	Sodium Nitrite	85 mg/kg Rat	N.E.	5.5 mg/L Rat
10605-21-7	Carbamic Acid, 1H-Benzimidazol-2-yl-, Methyl Ester	>5050 mg/kg Rat	>10000 mg/kg Rabbit	N.E.

N.E. - Not Established

12. Ecological Information

Ecological Information: No ecotoxicity data was found for this product.

Toxicity: The acute toxicity effects of this product have not been tested. Data on individual components are tabulated below:

AQUATIC ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	<u>Algae</u>	Daphnia/Aquatic	<u>Fish</u>
14807-96-6	Hydrous Magnesium Silicate	N.E.	N.E.	>100 g/L
107-21-1	Ethylene Glycol	6500 - 13000 mg/L	46300 mg/L	41000 mg/L
1314-13-2	Zinc Oxide	N.E.	N.E.	1.55 mg/L
64742-65-0	Distillates (Petroleum) Solvent-Dewaxed	N.E.	>1000 mg/L	>5000 mg/L
	Heavy Paraffinic	14.2.	- 1000 mg/L	7 0000 mg/L
64742-54-7	Hydrotreated Heavy Paraffinic Petroleum	N.E.	>1000 mg/L	>5000 mg/L
	Distillates			5555g. =
7631-86-9	Amorphous Silica	440 mg/L	7600 mg/L	5000 mg/L

Date Printed: 05/06/2024 Page 5 / 6

7632-00-0 Sodium Nitrite N.E. N.E. 0.19 mg/L

N.E. - Not Established

Persistence and degradability: The persistence and degradability of this product have not been tested.

BIOACCUMULATIVE POTENTIAL:

Product/ingredient name	Octanol-water par. Coeff (log KOW)	Bio. Conc. Factor (BCF)
Ethylene Glycol	-1.36	N.I.
Sodium Nitrite	-3.7	N.I.
Carbamic Acid, 1H-Benzimidazol-2-yl-, Methyl Ester	>1.4 - <1.5	N.I.

Mobility in Soil: The mobility in soil of this product has not been tested.

Other adverse effects: This product has not been tested for other adverse ecological effects.

13. Disposal Information

Disposal: Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not incinerate closed containers.

14. Transport Information

	Domestic (USDOT)	<u>International (IMDG)</u>	<u>Air (IA I A)</u>	<u>ADG</u>
UN Number:	N.A.	N.A.	N.A.	N.A.

Proper Shipping Name:	Not Regulated	Not Regulated	Not Regulated	Not Regulated

Hazard Class:	N.A.	N.A.	N.A.	N.A.
Packing Group:	N.A.	N.A.	N.A.	N.A.
Limited Quantity:	No	No	No	No

ADG Hazchem Code: Not Hazardous

15. Regulatory Information

Montreal Protocol

No Montreal Protocol components exist in this product.

Stockholm Convention

No Stockholm Convention components exist in this product.

Rotterdam Convention

This product contains the following substances listed under the Rotterdam Convention:

Chemical NameCAS-No.Ethylene Oxide75-21-8

MARPOL

This product contains the following substances listed under the MARPOL regulations:

<u>Chemical Name</u> <u>CAS-No.</u>

Carbamic Acid, 1H-Benzimidazol-2-yl-, Methyl Ester 10605-21-7

Date Printed: 05/06/2024 Page 6 / 6

Aqueous Ammonia 1336-21-6

SUSMP

This product contains the following substances classified as poisons as regulated by the Poisons Standard (SUSMP):

Chemical NameSchedule Number(s)Liquid HydrocarbonsSchedule 5

Capital Territories Environmental Regulations

This product contains the following substances listed under the Australian Capital Territories Environmental Protection Regulation:

<u>Chemical Name</u>	<u>Schedule</u>	Schedule Name
Chlorite Mineral	4	DOM - Disinfection By-products
Carbamic Acid, 1H-Benzimidazol-2-yl-, Methyl Ester	3	DOM - Pesticides
Lead Compounds	3	AQUA - Inorganic Chemicals
Cadmium Compounds	3	AQUA - Inorganic Chemicals
Formaldehyde	3	DOM - Disinfection By-products

16. Other Information

SDS REVISION DATE: 05/06/2024

REASON FOR REVISION: Substance and/or Product Properties Changed in Section(s):

03 - Composition / Information on Ingredients 08 - Exposure Controls / Personal Protection

11 - Toxicological Information14 - Transport Information

Substance Hazard Threshold % Changed

Revision Statement(s) Changed

Legend:

N.A. - Not Applicable N.D. - Not Determined N.E. - Not Established

S.T.E.L. - Short Term Exposure Limit T.W.A. - Time Weighted Average W.E.S. - Workplace Exposure Standard W.H.S. - Work Health and Safety regulation

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.