

Safety Data Sheet



www.rustoleum.com.au

1. Identification

Product Name: ULTCOV 2X +SSPR 6PK IBU GLOSS OCEAN MIST
Revision Date: 04/12/2023

Name on Label: ULTRACOVER 2X GLOSS OCEAN MIST
Supercedes Date: 30/03/2021

Product Identifier: 286841

Product Use/Class: Topcoat/Aerosol

Supplier: Rust-Oleum Australia & New Zealand Pty. Ltd.
 Level 2, 307 Ferntree Gully Road
 Mount Waverley, Victoria 3149
 Australia
 Ph 1 300 784 476

Manufacturer: Rust-Oleum Corporation
 11 Hawthorn Parkway
 Vernon Hills, IL 60061
 USA

Preparer: Regulatory Department

Emergency Telephone: 24 Hour Hotline: 1-300-366-961

2. Hazard Identification

This product is classified as a Dangerous Good per the Australian Code for the Transport of Dangerous Goods by Road and Rail. This product was assessed per Safe Work Australia criteria.

Classification

Symbol(s) of Product



Signal Word

Danger

Possible Hazards

37% of the mixture consists of ingredient(s) of unknown acute toxicity.

GHS HAZARD STATEMENTS

Pressurized Container; may burst if heated.	H229	Pressurized container: may burst if heated.
Eye Irritation, category 2A	H319	Causes serious eye irritation.
Flammable Aerosol, category 1	H222	Extremely flammable aerosol.
Skin Irritation, category 2	H315	Causes skin irritation.
STOT, Repeated Exposure, category 2	H373	May cause damage to organs.
STOT, Single Exposure, category 3, NE	H336	May cause drowsiness or dizziness.

GHS LABEL PRECAUTIONARY STATEMENTS

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust/fumes/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P280	Wear protective gloves / protective clothing / eye protection / face protection.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.

P304+P340
P305+P351+P338

IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Get medical help.
Get medical help if you feel unwell.
Specific treatment (see notice on this label).
If skin irritation occurs: Get medical help.
If eye irritation persists: Get medical help.
Take off contaminated clothing and wash it before reuse.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
Dispose of contents and container in accordance with local, regional and national regulations.

P317
P319
P321
P332+P317
P337+P317
P362+P364
P403+P233
P405
P410+P412
P501

3. Composition/Information On Ingredients

HAZARDOUS SUBSTANCES

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt.% Range</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Propane	74-98-6	10-25	GHS04	H280
Acetone	67-64-1	10-25	GHS02-GHS07	H225-319-332-336
Titanium Dioxide	13463-67-7	10-25	Not Available	Not Available
n-Butane	106-97-8	2.5-10	GHS04	H280
n-Butyl Acetate	123-86-4	2.5-10	GHS02-GHS07	H226-336
Naphtha, Petroleum, Hydrotreated Light	64742-49-0	2.5-10	GHS07-GHS08	H304-315-319-372
Dimethyl Carbonate	616-38-6	2.5-10	GHS02-GHS06	H225-331
1-Methoxy-2-Propyl Acetate	108-65-6	2.5-10	GHS02-GHS07	H226-332
Solvent Naphtha, Light Aromatic	64742-95-6	2.5-10	GHS07-GHS08	H304-315-319-332-372
Xylenes (o-, m-, p- Isomers)	1330-20-7	1.0-2.5	GHS02-GHS07-GHS08	H226-304-315-319-332-335
Propylene Glycol Monobutyl Ether	5131-66-8	1.0-2.5	GHS07	H302-315-319
1,2,4-Trimethylbenzene	95-63-6	1.0-2.5	GHS02-GHS07-GHS08	H226-304-315-319-332-335
Ethylbenzene	100-41-4	0.1-1.0	GHS02-GHS07-GHS08	H225-304-315-319-332-373
Zirconium 2-Ethylhexanoate	22464-99-9	0.1-1.0	GHS07	H315+H320
Zirconium Acetate	5153-24-2	<0.1	Not Available	Not Available

The balance of the product is Nonhazardous.

4. First-Aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed. Remove contact lenses, if present and easy to do. Continue rinsing.

FIRST AID - SKIN CONTACT: Immediately flush skin with plenty of water for at least 15 minutes while removing clothing. Get medical attention immediately. Wash clothing separately before reuse.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

FIRST AID - INGESTION: If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cupfuls of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively. Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

5. Fire-fighting Measures

ADG HAZCHEM CODE: None

EXTINGUISHING MEDIA: Aqueous Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: FLASH POINT IS LESS THAN -7°C (20°F). EXTREMELY FLAMMABLE LIQUID AND VAPOR! Water spray may be ineffective. Closed containers may explode when exposed to extreme heat. Vapors may form explosive mixtures with air. Vapors can travel to a source of ignition and flash back. Isolate from heat, electrical equipment, sparks and open flame. Perforation of the pressurized container may cause bursting of the can.

SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred. Evacuate area and fight fire from a safe distance. Containers can rupture and release highly toxic material if exposed to heat. Substance is non-combustible but reacts with many metals to form explosive hydrogen gas. Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Avoid runoff into sewers and waterways. Provide ventilation and approach spill from upwind using proper personal protective equipment as indicated in Section 8. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers.

7. Handling and Storage

HANDLING: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Do not get in eyes, on skin or clothing. Do not puncture or incinerate (burn) container, even after use.

STORAGE: Contents under pressure. Do not store above 120°F (49°C). Store large quantities in buildings designed and protected for storage of flammable aerosols. Keep away from heat, sparks, flame and sources of ignition.

Advice on Safe Handling of Combustible Dust: No Information

8. Exposure Controls / Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	WHS WES TLV-TWA	WHS WES TLV-STEL
Propane	74-98-6	20.0	N.E.	N.E.
Acetone	67-64-1	20.0	250 ppm	500 ppm
Titanium Dioxide	13463-67-7	15.0	0.2 mg/m3	N.E.
n-Butane	106-97-8	10.0	N.E.	1000 ppm
n-Butyl Acetate	123-86-4	10.0	50 ppm	150 ppm
Naphtha, Petroleum, Hydrotreated Light	64742-49-0	10.0	N.E.	N.E.
Dimethyl Carbonate	616-38-6	10.0	N.E.	N.E.
1-Methoxy-2-Propyl Acetate	108-65-6	5.0	N.E.	N.E.
Solvent Naphtha, Light Aromatic	64742-95-6	5.0	N.E.	N.E.
Xylenes (o-, m-, p- Isomers)	1330-20-7	5.0	20 ppm	N.E.
Propylene Glycol Monobutyl Ether	5131-66-8	5.0	N.E.	N.E.
1,2,4-Trimethylbenzene	95-63-6	5.0	10 ppm	N.E.
Ethylbenzene	100-41-4	1.0	20 ppm	N.E.
Zirconium 2-Ethylhexanoate	22464-99-9	1.0	5 mg/m3	10 mg/m3
Zirconium Acetate	5153-24-2	0.1	5 mg/m3	10 mg/m3

PERSONAL PROTECTION

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

RESPIRATORY PROTECTION: Wear an approved (or equivalent) full-facepiece airline respirator according to AS/NZS 1715-2009 and AS/NZS 1716-2012 in the positive pressure mode with emergency escape provisions. A respiratory protection program that meets AS/NZS 1715-2009 and AS/NZS 1716-2012 requirements must be followed whenever workplace conditions warrant a respirator's use. An approved air purifying respirator with organic vapor cartridge or canister according to AS/NZS 1715-2009 and AS/NZS 1716-2012 may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Users of this product in industrial/OEM applications must use one of the following forms of respiratory protection:

- AS/NZS 1715-2009 and AS/NZS 1716-2012 compliant supplied-air respirator operated in pressure demand or continuous flow mode and equipped with a tight fitting facepiece
- AS/NZS 1715-2009 and AS/NZS 1716-2012 compliant air-purifying respirator equipped with a full facepiece and organic gas/vapor cartridges
- AS/NZS 1715-2009 and AS/NZS 1716-2012 compliant powered air-purifying respirator equipped with a full facepiece and organic gas/vapor cartridges.

SKIN PROTECTION: Use impervious gloves to prevent skin contact and absorption of this material through the skin.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

9. Physical and Chemical Properties

Appearance:	Aerosolized Mist	Physical State:	Liquid
Odor:	Solvent Like	Odor Threshold:	N.E.
Specific Gravity:	0.830	pH:	N.A.
Freeze Point, °C:	N.D.	Viscosity:	N.D.
Solubility in Water:	Slight	Partition Coefficient, n-octanol/water:	N.D.
Decomposition Temp., °C:	N.D.	Explosive Limits, vol%:	0.9 - 13.0
Boiling Range, °C:	-37 - 537	Flash Point, °C:	-96
Flammability:	Supports Combustion	Auto-Ignition Temp., °C:	N.D.
Evaporation Rate:	Faster than Ether	Vapor Pressure:	N.D.
Vapor Density:	Heavier than Air		

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

Conditions to Avoid: Avoid temperatures above 120°F (49°C). Avoid all possible sources of ignition. Avoid contact with metals. Avoid excess heat. Keep from freezing.

Incompatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalies. Product slowly corrodes copper, aluminum, zinc, and galvanized surfaces.

Hazardous Decomposition: When heated to decomposition, it emits acrid smoke and irritating fumes. Contains solvents which may form carbon monoxide, carbon dioxide, and formaldehyde.

Hazardous Polymerization: Will not occur under normal conditions.

Stability: This product is stable under normal storage conditions.

11. Toxicological Information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Can cause severe eye irritation. Causes eye burns. Causes eye and skin irritation which may lead to dermatitis with repeated exposures. Irritating, and may injure eye tissue if not removed promptly. High vapor concentrations can irritate eyes, nose and respiratory passages.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Substance is corrosive. Causes severe skin burns. Severely irritating; may cause permanent skin damage.

EFFECTS OF OVEREXPOSURE - INHALATION: High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. High vapor concentrations are irritating to the eyes, nose, throat and lungs. Routine handling and application does not require use of respiratory protection; however, if air monitoring demonstrates vapor, mist, or dust levels above applicable limits, wear an appropriate, properly fitted respirator (meets AS/NZS 1715-2009 and AS/NZS 1716-2012 requirements) during handling and application. Follow respirator manufacturer's directions for respirator use.

EFFECTS OF OVEREXPOSURE - INGESTION: Corrosive and may cause severe and permanent damage to mouth, throat and stomach. Harmful if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis, and blurred vision) and/or damage. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Overexposure to xylene in laboratory animals has been associated with liver abnormalities, kidney, lung, spleen, eye and blood damage as well as reproductive disorders. Effects in humans, due to chronic overexposure, have included liver, cardiac abnormalities and nervous system damage. IARC lists Ethylbenzene as a possible human carcinogen (group 2B). Contains Titanium Dioxide. Titanium Dioxide is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC. No significant exposure to Titanium Dioxide is thought to occur during the use of products in which Titanium Dioxide is bound to other materials, such as in paints during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of Titanium Dioxide in the formula. (Ref: IARC Monograph, Vol. 93, 2010)

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
67-64-1	Acetone	5800 mg/kg Rat	>15700 mg/kg Rabbit	50.1 mg/L Rat
13463-67-7	Titanium Dioxide	>10000 mg/kg Rat	6000	N.E.
106-97-8	n-Butane	N.E.	N.E.	658 mg/L Rat
123-86-4	n-Butyl Acetate	10768 mg/kg Rat	>17600 mg/kg Rabbit	> 21 mg/L Rat
64742-49-0	Naphtha, Petroleum, Hydrotreated Light	>5000 mg/kg Rat	>3160 mg/kg Rabbit	>4951 mg/L Rat
616-38-6	Dimethyl Carbonate	13000 mg/kg Rat	>5000 mg/kg Rabbit	>5.36 mg/L Rat
108-65-6	1-Methoxy-2-Propyl Acetate	8532 mg/kg Rat	>5000 mg/kg Rabbit	16 mg/L Rat
64742-95-6	Solvent Naphtha, Light Aromatic	8400 mg/kg Rat	>2000 mg/kg Rabbit	N.E.
1330-20-7	Xylenes (o-, m-, p- Isomers)	3500 mg/kg Rat	>4350 mg/kg Rabbit	29.08 mg/L Rat
5131-66-8	Propylene Glycol Monobutyl Ether	1900 mg/kg Rat	>2000 mg/kg Rat	N.E.
95-63-6	1,2,4-Trimethylbenzene	3280 mg/kg Rat	>3160 mg/kg Rabbit	18 mg/L Rat
100-41-4	Ethylbenzene	3500 mg/kg Rat	15400 mg/kg Rabbit	17.4 mg/L Rat

N.E. - Not Established

12. Ecological Information

ECOLOGICAL INFORMATION: No ecotoxicity data was found for this product.

TOXICITY: The acute toxicity effects of this product have not been tested. Data on individual components are tabulated below:

AQUATIC ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Algae	Daphnia/Aquatic	Fish
67-64-1	Acetone	N.E.	10294 - 17704 mg/L	4.74 - 6.33 mL/L
123-86-4	n-Butyl Acetate	674.7 mg/L	N.E.	100 mg/L
64742-49-0	Naphtha, Petroleum, Hydrotreated Light	N.E.	N.E.	8.41 mg/L
616-38-6	Dimethyl Carbonate	N.E.	N.E.	>=100 mg/L
108-65-6	1-Methoxy-2-Propyl Acetate	N.E.	>500 mg/L	161 mg/L
64742-95-6	Solvent Naphtha, Light Aromatic	N.E.	6.14 mg/L	9.22 mg/L
1330-20-7	Xylenes (o-, m-, p- Isomers)	N.E.	3.82 mg/L	13.4 mg/L
95-63-6	1,2,4-Trimethylbenzene	N.E.	6.14 mg/L	7.19 - 8.28 mg/L
100-41-4	Ethylbenzene	4.6 mg/L	1.8 - 2.4 mg/L	11.0 - 18.0 mg/L

N.E. - Not Established

PERSISTENCE AND DEGRADABILITY: The persistence and degradability of this product have not been tested.

BIOACCUMULATIVE POTENTIAL:

Product/ingredient name	Octanol-water par. Coeff (log KOW)	Bio. Conc. Factor (BCF)
Propane	1.09	N.I.
Acetone	-0.24	0.69 dimensionless
n-Butane	2.31	N.I.
n-Butyl Acetate	1.81	N.I.
Dimethyl Carbonate	0.354	N.I.
1-Methoxy-2-Propyl Acetate	1.2	N.I.
Xylenes (o-, m-, p- Isomers)	2.77 - 3.15	0.6 - 15 dimensionless
Propylene Glycol Monobutyl Ether	1.2	N.I.
1,2,4-Trimethylbenzene	3.63	N.I.

Ethylbenzene

3.6

15 dimensionless

MOBILITY IN SOIL: The mobility in soil of this product has not been tested.**OTHER ADVERSE EFFECTS:** This product has not been tested for other adverse ecological effects.**13. Disposal Information****DISPOSAL:** Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not incinerate closed containers.**14. Transport Information**

	<u>Domestic (USDOT)</u>	<u>International (IMDG)</u>	<u>Air (IATA)</u>	<u>ADG</u>
UN Number:	N.A.	1950	1950	1950
Proper Shipping Name:	Paint and Related Spray Products in Ltd Qty	Aerosols	Aerosols, flammable	Aerosols
Hazard Class:	N.A.	2	2.1	2.1
Packing Group:	N.A.	N.A.	N.A.	N.A.
Limited Quantity:	Yes	Yes	Yes	Yes
ADG Hazchem Code:	None			

15. Regulatory Information**Montreal Protocol**

No Montreal Protocol components exist in this product.

Stockholm Convention

No Stockholm Convention components exist in this product.

Rotterdam Convention

No Rotterdam Convention components exist in this product.

MARPOL

This product contains the following substances listed under the MARPOL regulations:

<u>Chemical Name</u>	<u>CAS-No.</u>
n-Nonane	111-84-2

SUSMP

This product contains the following substances classified as poisons as regulated by the Poisons Standard (SUSMP):

<u>Chemical Name</u>	<u>Schedule Number(s)</u>
Liquid Hydrocarbons	Schedule 5

Capital Territories Environmental Regulations

This product contains the following substances listed under the Australian Capital Territories Environmental Protection Regulation:

<u>Chemical Name</u>	<u>Schedule</u>	<u>Schedule Name</u>
----------------------	-----------------	----------------------

Xylenes (o-, m-, p- Isomers)	3	DOM - Organic Chemicals
Ethylbenzene	3	Non-pesticide Anthropogenic Organics
Toluene	3	Non-pesticide Anthropogenic Organics
Benzene	3	Non-pesticide Anthropogenic Organics

16. Other Information

SDS REVISION DATE: 04/12/2023

REASON FOR REVISION: Product Composition Changed
Substance and/or Product Properties Changed in Section(s):
01 - Identification
02 - Hazard Identification
03 - Composition / Information on Ingredients
05 - Fire-Fighting Measures
08 - Exposure Controls / Personal Protection
09 - Physical & Chemical Properties
11 - Toxicological Information
12 - Ecological Information
16 - Other Information
Substance Hazard Threshold % Changed
Substance Hazardous Flag Changed
Revision Statement(s) Changed

Legend:

N.A. - Not Applicable N.D. - Not Determined N.E. - Not Established

S.T.E.L. - Short Term Exposure Limit

T.W.A. - Time Weighted Average

W.E.S. - Workplace Exposure Standard

W.H.S. - Work Health and Safety regulation

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.