



Fecha última revisión:
Rust-Oleum Australia Multi Component Product
Information Sheet

291851 TRANSF KIT 2PK IBU CABINET LIGHT TB es un producto multicomponente compuesto por los siguientes componentes químicos individuales:

327264 4PK QT AUS CABINET LIGHT TB COAT
327606 TRANSF QT 12PK AUS CABINET DEGLOSSER

SDSs for each component follow this cover sheet.

Transportation Information

	<u>Nacional (USDOT)</u>	<u>Internacional (IMDG)</u>	<u>Aire (IATA)</u>	<u>ADG (Australia)</u>
UN Numero:	N.A.	N.A.	N.A.	N.A.
Denominación adecuada de envío:	No regulado	No regulado	No regulado	No regulado
Clase De Riesgos:	N.A.	N.A.	N.A.	N.A.
Grupo embalaje:	N.A.	N.A.	N.A.	N.A.
Cantidad Limitada:	No	No	No	No
Terminado Buena Anexo B homologación arancelaria		3209.10.0000		

Safety Data Sheet

www.rustoleum.com.au

1. Identification

Product Name: 4PK QT AUS CABINET LIGHT TB COAT
Name on Label: Light Tint Base Coat
Product Identifier: 327264
Product Use/Class: Transformations/Waterborne
Supplier: Rust-Oleum Australia & New Zealand Pty. Ltd.
Level 2, 307 Ferntree Gully Road
Mount Waverley, Victoria 3149
Australia
Ph 1 300 784 476
Manufacturer: Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, IL 60061
USA
Preparer: Regulatory Department
Emergency Telephone: 24 Hour Hotline: 1-300-366-961

2. Hazard Identification

This product is not classified as a Dangerous Good per the Australian Code for the Transport of Dangerous Goods by Road and Rail. This product was assessed per Safe Work Australia criteria.

Classification

Symbol(s) of Product

Not a hazardous substance or mixture per Safe Work Australia criteria.

Signal Word

No Signal Word has been assigned.

Possible Hazards

23% of the mixture consists of ingredient(s) of unknown acute toxicity.

3. Composition/Information On Ingredients

HAZARDOUS SUBSTANCES

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt.% Range</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Titanium Dioxide	13463-67-7	10-25	Not Available	Not Available
Triethylamine	121-44-8	0.1-1.0	GHS02-GHS05-GHS06	H225-302-311+H331-314-335
Amorphous Silica	7631-86-9	0.1-1.0	GHS08	H372
Dodecamethylcyclohexasiloxane	540-97-6	<0.1	Not Available	Not Available

The balance of the product is Nonhazardous.

4. First-Aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed. Remove contact lenses, if present and easy to do. Continue rinsing.

FIRST AID - SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

FIRST AID - INGESTION: If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cupfuls of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively.

5. Fire-fighting Measures

ADG HAZCHEM CODE: Not Hazardous

EXTINGUISHING MEDIA: Aqueous Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep containers tightly closed. No unusual fire or explosion hazards noted.

SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

7. Handling and Storage

HANDLING: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

STORAGE: Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Advice on Safe Handling of Combustible Dust: No Information

8. Exposure Controls / Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	WHS WES TLV-TWA	WHS WES TLV-STEL
Titanium Dioxide	13463-67-7	25.0	0.2 mg/m3	N.E.
Triethylamine	121-44-8	1.0	0.5 ppm	1 ppm
Amorphous Silica	7631-86-9	1.0	N.E.	N.E.
Dodecamethylcyclhexasiloxane	540-97-6	0.1	N.E.	N.E.

PERSONAL PROTECTION

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

RESPIRATORY PROTECTION: Wear an approved (or equivalent) full-facepiece airline respirator according to AS/NZS 1715-2009 and AS/NZS 1716-2012 in the positive pressure mode with emergency escape provisions. An approved air purifying respirator with organic vapor cartridge or canister according to AS/NZS 1715-2009 and AS/NZS 1716-2012 may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. A respiratory protection program that meets AS/NZS 1715-2009 and AS/NZS 1716-2012 requirements must be followed whenever workplace conditions warrant a respirator's use. Users of this product in industrial/OEM applications must use one of the following forms of respiratory protection:

- AS/NZS 1715-2009 and AS/NZS 1716-2012 compliant supplied-air respirator operated in pressure demand or continuous flow mode and equipped with a tight fitting facepiece
- AS/NZS 1715-2009 and AS/NZS 1716-2012 compliant air-purifying respirator equipped with a full facepiece and organic gas/vapor cartridges
- AS/NZS 1715-2009 and AS/NZS 1716-2012 compliant powered air-purifying respirator equipped with a full facepiece and organic gas/vapor cartridges.

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

9. Physical and Chemical Properties

Appearance:	Liquid	Physical State:	Liquid
Odor:	Mild	Odor Threshold:	N.E.
Specific Gravity:	1.259	pH:	N.A.
Freeze Point, °C:	N.D.	Viscosity:	N.D.
Solubility in Water:	Miscible	Partition Coefficient, n-octanol/water:	N.D.
Decomposition Temp., °C:	N.D.	Explosive Limits, vol%:	2.6 - 12.6
Boiling Range, °C:	100 - 537	Flash Point, °C:	99
Flammability:	Does not Support Combustion	Auto-Ignition Temp., °C:	N.D.
Evaporation Rate:	Slower than Ether	Vapor Pressure:	N.D.
Vapor Density:	Heavier than Air		

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

Conditions to Avoid: Avoid excess heat. Keep from freezing.

Incompatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

Hazardous Decomposition: When heated to decomposition, it emits acrid smoke and irritating fumes.

Hazardous Polymerization: Will not occur under normal conditions.

Stability: This product is stable under normal storage conditions.

11. Toxicological Information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Irritating, and may injure eye tissue if not removed promptly.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Low hazard for usual industrial handling or commercial handling by trained personnel.

EFFECTS OF OVEREXPOSURE - INHALATION: High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. Routine handling and application does not require use of respiratory protection; however, if air monitoring demonstrates vapor, mist, or dust levels above applicable limits, wear an appropriate, properly fitted respirator (meets AS/NZS 1715-2009 and AS/NZS 1716-2012 requirements) during handling and application. Follow respirator manufacturer's directions for respirator use.

EFFECTS OF OVEREXPOSURE - INGESTION: Substance may be harmful if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Contains Titanium Dioxide. Titanium Dioxide is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC. No significant exposure to Titanium Dioxide is thought to occur during the use of products in which Titanium Dioxide is bound to other materials, such as in paints during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of Titanium Dioxide in the formula. (Ref: IARC Monograph, Vol. 93, 2010)

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
13463-67-7	Titanium Dioxide	>10000 mg/kg Rat	6000	N.E.
121-44-8	Triethylamine	460 mg/kg Rat	415 mg/kg Rabbit	14.5 mg/L Rat
7631-86-9	Amorphous Silica	7900 mg/kg Rat	>5000 mg/kg Rabbit	25 mg/L
540-97-6	Dodecamethylcyclohexasiloxane	50000 mg/kg Rat	>2000 mg/kg Rat	N.E.

N.E. - Not Established

12. Ecological Information

ECOLOGICAL INFORMATION: No ecotoxicity data was found for this product.

TOXICITY: The acute toxicity effects of this product have not been tested. Data on individual components are tabulated below:

AQUATIC ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Algae</u>	<u>Daphnia/Aquatic</u>	<u>Fish</u>
121-44-8	Triethylamine	N.E.	200 mg/L	43.7 mg/L
7631-86-9	Amorphous Silica	440 mg/L	7600 mg/L	5000 mg/L

N.E. - Not Established

PERSISTENCE AND DEGRADABILITY: The persistence and degradability of this product have not been tested.

BIOACCUMULATIVE POTENTIAL:

<u>Product/ingredient name</u>	<u>Octanol-water par. Coeff (log KOW)</u>	<u>Bio. Conc. Factor (BCF)</u>
Triethylamine	1.45	<0.5 dimensionless
Dodecamethylcyclohexasiloxane	8.87	N.I.

MOBILITY IN SOIL: The mobility in soil of this product has not been tested.

OTHER ADVERSE EFFECTS: This product has not been tested for other adverse ecological effects.

13. Disposal Information

DISPOSAL: Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not incinerate closed containers.

14. Transport Information

	<u>Domestic (USDOT)</u>	<u>International (IMDG)</u>	<u>Air (IATA)</u>	<u>ADG</u>
UN Number:	N.A.	N.A.	N.A.	N.A.
Proper Shipping Name:	Not Regulated	Not Regulated	Not Regulated	Not Regulated
Hazard Class:	N.A.	N.A.	N.A.	N.A.
Packing Group:	N.A.	N.A.	N.A.	N.A.
Limited Quantity:	No	No	No	No
ADG Hazchem Code:	Not Hazardous			

15. Regulatory Information

Montreal Protocol

No Montreal Protocol components exist in this product.

Stockholm Convention

No Stockholm Convention components exist in this product.

Rotterdam Convention

This product contains the following substances listed under the Rotterdam Convention:

<u>Chemical Name</u>	<u>CAS-No.</u>
Ethylene Oxide	75-21-8

MARPOL

No substances listed under the MARPOL regulations exist in this product.

SUSMP

This product contains the following substances classified as poisons as regulated by the Poisons Standard (SUSMP):

<u>Chemical Name</u>	<u>Schedule Number(s)</u>
Liquid Hydrocarbons	Schedule 5

Capital Territories Environmental Regulations

This product contains the following substances listed under the Australian Capital Territories Environmental Protection Regulation:

<u>Chemical Name</u>	<u>Schedule</u>	<u>Schedule Name</u>
Formaldehyde	3	DOM - Disinfection By-products
Lead Compounds	3	AQUA - Inorganic Chemicals
Chromium Compounds	3	AQUA - Inorganic Chemicals

16. Other Information

SDS REVISION DATE: 05/12/2023

REASON FOR REVISION: Product Composition Changed
 Substance and/or Product Properties Changed in Section(s):
 01 - Identification
 02 - Hazard Identification
 03 - Composition / Information on Ingredients
 05 - Fire-Fighting Measures
 08 - Exposure Controls / Personal Protection
 09 - Physical & Chemical Properties
 11 - Toxicological Information
 12 - Ecological Information
 Substance Hazard Threshold % Changed
 Substance Hazardous Flag Changed
 Revision Statement(s) Changed

Legend:

N.A. - Not Applicable N.D. - Not Determined N.E. - Not Established
 S.T.E.L. - Short Term Exposure Limit
 T.W.A. - Time Weighted Average
 W.E.S. - Workplace Exposure Standard
 W.H.S. - Work Health and Safety regulation

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.

Safety Data Sheet



www.rustoleum.com.au

1. Identification

Product Name:	TRANSF QT 12PK AUS CABINET DEGLOSSER	Revision Date:	05/12/2023
Name on Label:	Cabinet Deglosser	Supersedes Date:	31/03/2021
Product Identifier:	327606		
Product Use/Class:	Cabinet Non-Sanding Cleaner/ Transformations		
Supplier:	Rust-Oleum Australia & New Zealand Pty. Ltd. Level 2, 307 Ferntree Gully Road Mount Waverley, Victoria 3149 Australia Ph 1 300 784 476	Manufacturer:	Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA
Preparer:	Regulatory Department		
Emergency Telephone:	24 Hour Hotline: 1-300-366-961		

2. Hazard Identification

This product is not classified as a Dangerous Good per the Australian Code for the Transport of Dangerous Goods by Road and Rail. This product was assessed per Safe Work Australia criteria.

Classification

Symbol(s) of Product



Signal Word

Warning

Possible Hazards

4% of the mixture consists of ingredient(s) of unknown acute toxicity.

GHS HAZARD STATEMENTS

Eye Irritation, category 2A	H319	Causes serious eye irritation.
-----------------------------	------	--------------------------------

GHS LABEL PRECAUTIONARY STATEMENTS

P264	Wash thoroughly after handling.
P280	Wear protective gloves / protective clothing / eye protection / face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P317	If eye irritation persists: Get medical help.

3. Composition/Information On Ingredients

HAZARDOUS SUBSTANCES

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. % Range</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Ethylene Glycol Monobutyl Ether	111-76-2	2.5-10	GHS07	H302+H312+H332-315-319
Ethoxylated Alcohols, C12-16	68551-12-2	1.0-2.5	GHS05-GHS07	H302-315-318
Polyoxyethylene alkyl (C8-10) ether phosphate	68412-53-3	1.0-2.5	Not Available	Not Available
Alcohols, C6-12, ethoxylated	68439-45-2	0.1-1.0	GHS05-GHS07	H302-318

The balance of the product is Nonhazardous.

4. First-Aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed. Remove contact lenses, if present and easy to do. Continue rinsing.

FIRST AID - SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

FIRST AID - INGESTION: If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cupfuls of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively.

5. Fire-fighting Measures

ADG HAZCHEM CODE: Not Hazardous

EXTINGUISHING MEDIA: Aqueous Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep containers tightly closed. No unusual fire or explosion hazards noted.

SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

7. Handling and Storage

HANDLING: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Do not get in eyes, on skin or clothing.

STORAGE: Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Advice on Safe Handling of Combustible Dust: No Information

8. Exposure Controls / Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	WHS WES TLV-TWA	WHS WES TLV-STEL
Ethylene Glycol Monobutyl Ether	111-76-2	5.0	20 ppm	N.E.
Ethoxylated Alcohols, C12-16	68551-12-2	5.0	N.E.	N.E.

Cabinet Deglosser

Polyoxyethylene alkyl (C8-10) ether phosphate	68412-53-3	5.0	N.E.	N.E.
Alcohols, C6-12, ethoxylated	68439-45-2	1.0	N.E.	N.E.

PERSONAL PROTECTION

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

RESPIRATORY PROTECTION: Wear an approved (or equivalent) full-facepiece airline respirator according to AS/NZS 1715-2009 and AS/NZS 1716-2012 in the positive pressure mode with emergency escape provisions. An approved air purifying respirator with organic vapor cartridge or canister according to AS/NZS 1715-2009 and AS/NZS 1716-2012 may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. A respiratory protection program that meets AS/NZS 1715-2009 and AS/NZS 1716-2012 requirements must be followed whenever workplace conditions warrant a respirator's use. Users of this product in industrial/OEM applications must use one of the following forms of respiratory protection:

- AS/NZS 1715-2009 and AS/NZS 1716-2012 compliant supplied-air respirator operated in pressure demand or continuous flow mode and equipped with a tight fitting facepiece
- AS/NZS 1715-2009 and AS/NZS 1716-2012 compliant air-purifying respirator equipped with a full facepiece and organic gas/vapor cartridges
- AS/NZS 1715-2009 and AS/NZS 1716-2012 compliant powered air-purifying respirator equipped with a full facepiece and organic gas/vapor cartridges.

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

9. Physical and Chemical Properties

Appearance:	Liquid	Physical State:	Liquid
Odor:	Mild	Odor Threshold:	N.E.
Specific Gravity:	1.004	pH:	7.0
Freeze Point, °C:	N.D.	Viscosity:	N.D.
Solubility in Water:	Miscible	Partition Coefficient, n-octanol/water:	N.D.
Decomposition Temp., °C:	N.D.	Explosive Limits, vol%:	1.1 - 10.6
Boiling Range, °C:	94 - 173	Flash Point, °C:	94
Flammability:	Does not Support Combustion	Auto-Ignition Temp., °C:	N.D.
Evaporation Rate:	Slower than Ether	Vapor Pressure:	N.D.
Vapor Density:	Heavier than Air		

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

Conditions to Avoid: Avoid excess heat. Keep from freezing.

Incompatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalis.

Hazardous Decomposition: When heated to decomposition, it emits acrid smoke and irritating fumes.

Hazardous Polymerization: Will not occur under normal conditions.

Stability: This product is stable under normal storage conditions.

11. Toxicological Information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Can cause severe eye irritation. Causes eye and skin irritation which may lead to dermatitis with repeated exposures. Irritating, and may injure eye tissue if not removed promptly.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Low hazard for usual industrial handling or commercial handling by trained personnel.

EFFECTS OF OVEREXPOSURE - INHALATION: High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. Routine handling and application does not require use of respiratory protection; however, if air monitoring demonstrates vapor, mist, or dust levels above applicable limits, wear an appropriate, properly fitted respirator (meets AS/NZS 1715-2009 and AS/NZS 1716-2012 requirements) during handling and application. Follow respirator manufacturer's

directions for respirator use.

EFFECTS OF OVEREXPOSURE - INGESTION: Substance may be harmful if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: No Information

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
111-76-2	Ethylene Glycol Monobutyl Ether	470 mg/kg Rat	1,060 mg/kg Rabbit	11 mg/L

N.E. - Not Established

12. Ecological Information

ECOLOGICAL INFORMATION: No ecotoxicity data was found for this product.

TOXICITY: The acute toxicity effects of this product have not been tested. Data on individual components are tabulated below:

AQUATIC ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Algae</u>	<u>Daphnia/Aquatic</u>	<u>Fish</u>
111-76-2	Ethylene Glycol Monobutyl Ether	N.E.	>1000 mg/L	1490 mg/L

N.E. - Not Established

PERSISTENCE AND DEGRADABILITY: The persistence and degradability of this product have not been tested.

BIOACCUMULATIVE POTENTIAL:

<u>Product/ingredient name</u>	<u>Octanol-water par. Coeff (log KOW)</u>	<u>Bio. Conc. Factor (BCF)</u>
Ethylene Glycol Monobutyl Ether	0.81	N.I.

MOBILITY IN SOIL: The mobility in soil of this product has not been tested.

OTHER ADVERSE EFFECTS: This product has not been tested for other adverse ecological effects.

13. Disposal Information

DISPOSAL: Dispose of material in accordance with local, state, and federal regulations and ordinances. Do not incinerate closed containers.

14. Transport Information

	<u>Domestic (USDOT)</u>	<u>International (IMDG)</u>	<u>Air (IATA)</u>	<u>ADG</u>
UN Number:	N.A.	N.A.	N.A.	N.A.
Proper Shipping Name:	Not Regulated	Not Regulated	Not Regulated	Not Regulated
Hazard Class:	N.A.	N.A.	N.A.	N.A.
Packing Group:	N.A.	N.A.	N.A.	N.A.
Limited Quantity:	No	No	No	No
ADG Hazchem Code:	Not Hazardous			

15. Regulatory Information

Montreal Protocol

No Montreal Protocol components exist in this product.

Stockholm Convention

No Stockholm Convention components exist in this product.

Rotterdam Convention

No Rotterdam Convention components exist in this product.

MARPOL

This product contains the following substances listed under the MARPOL regulations:

<u>Chemical Name</u>	<u>CAS-No.</u>
Ethoxylated Alcohols, C12-16	68551-12-2

SUSMP

This product contains the following substances classified as poisons as regulated by the Poisons Standard (SUSMP):

<u>Chemical Name</u>	<u>Schedule Number(s)</u>
None	N.A.

Capital Territories Environmental Regulations

No Capital Territory components exist in this product.

16. Other Information

SDS REVISION DATE: 05/12/2023

REASON FOR REVISION: Product Composition Changed
Substance and/or Product Properties Changed in Section(s):
03 - Composition / Information on Ingredients
05 - Fire-Fighting Measures
09 - Physical & Chemical Properties
12 - Ecological Information
Substance Hazardous Flag Changed
Substance Hazard Threshold % Changed
Revision Statement(s) Changed

Legend:

N.A. - Not Applicable N.D. - Not Determined N.E. - Not Established
S.T.E.L. - Short Term Exposure Limit
T.W.A. - Time Weighted Average
W.E.S. - Workplace Exposure Standard
W.H.S. - Work Health and Safety regulation

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.