

# Safety Data Sheet



www.rustoleum.com.au

## 1. Identification

**Product Name:** INDHP 1-GL 2PK ROCTHN 9800 GLS ALUMIN

**Revision Date:** 27/11/2023

**Name on Label:** 9800 System DTM Urethane Mastic Gloss Aluminum

**Supercedes Date:** 05/04/2021

**Product Identifier:** 9815419

**Product Use/Class:** Topcoat/Polyurethane

**Supplier:** Rust-Oleum Australia & New Zealand Pty. Ltd.  
Level 2, 307 Ferntree Gully Road  
Mount Waverley, Victoria 3149  
Australia  
Ph 1 300 784 476

**Manufacturer:** Rust-Oleum Corporation  
11 Hawthorn Parkway  
Vernon Hills, IL 60061  
USA

**Preparer:** Regulatory Department

**Emergency Telephone:** 24 Hour Hotline: 1-300-366-961

## 2. Hazard Identification

This product is classified as a Dangerous Good per the Australian Code for the Transport of Dangerous Goods by Road and Rail. This product was assessed per Safe Work Australia criteria.

### Classification

#### Symbol(s) of Product



#### Signal Word

Danger

#### Possible Hazards

7% of the mixture consists of ingredient(s) of unknown acute toxicity.

#### GHS HAZARD STATEMENTS

|  |      |                                    |
|--|------|------------------------------------|
| Acute Toxicity, Inhalation, category 3 | H331 | Toxic if inhaled.                  |
| Carcinogenicity, category 1A           | H350 | May cause cancer.                  |
| Flammable Liquid, category 3           | H226 | Flammable liquid and vapour.       |
| Germ Cell Mutagenicity, category 1B    | H340 | May cause genetic defects.         |
| STOT, Single Exposure, category 3, NE  | H336 | May cause drowsiness or dizziness. |

#### GHS LABEL PRECAUTIONARY STATEMENTS

|                |  |
|----------------|--|
| P201           | Obtain special instructions before use.  |
| P210           | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.           |
| P261           | Avoid breathing dust/fume/gas/mist/vapours/spray.  |
| P271           | Use only outdoors or in a well-ventilated area.  |
| P280           | Wear protective gloves / protective clothing / eye protection / face protection.                         |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. |
| P304+P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.                               |

9800 System DTM Urethane Mastic Gloss Aluminum

|           |  |
|-----------|--|
| P308+P313 | IF exposed or concerned: Get medical advice/attention.   |
| P316      | Get emergency medical help immediately.  |
| P317      | Get medical help.  |
| P370+P378 | In case of fire: Extinguish using suitable extinguishing media.                                |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed.                               |
| P403+P235 | Store in a well-ventilated place. Keep cool.   |
| P405      | Store locked up.   |
| P501      | Dispose of contents and container in accordance with local, regional and national regulations. |

**GHS SDS PRECAUTIONARY STATEMENTS**

|      |  |
|------|--|
| P240 | Ground and bond container and receiving equipment.                           |
| P241 | Use explosion-proof electrical, ventilating, lighting, or pouring equipment. |
| P242 | Use non-sparking tools.  |
| P243 | Take action to prevent static discharges.                                    |

**3. Composition/Information On Ingredients****HAZARDOUS SUBSTANCES**

| <u>Chemical Name</u>                                  | <u>CAS-No.</u> | <u>Wt. % Range</u> | <u>GHS Symbols</u> | <u>GHS Statements</u>        |
|---|----------------|--------------------|--------------------|------------------------------|
| Methyl n-Amyl Ketone                                  | 110-43-0       | 10-25              | GHS02-GHS07        | H226-302+H332-336            |
| n-Butyl Acetate                                       | 123-86-4       | 10-25              | GHS02-GHS07        | H226-336                     |
| Mica  | 12001-26-2     | 2.5-10             | Not Available      | Not Available                |
| Ethyl 3-Ethoxypropionate                              | 763-69-9       | 1.0-2.5            | Not Available      | Not Available                |
| Titanium Dioxide                                      | 13463-67-7     | 1.0-2.5            | Not Available      | Not Available                |
| p-Toluenesulfonyl Isocyanate                          | 4083-64-1      | 0.1-1.0            | GHS06-GHS08        | H315-317-319-330-334-335-372 |
| bis(1,2,2,6,6-Pentamethyl-4-Piperidiny)l) Sebacate    | 41556-26-7     | 0.1-1.0            | GHS05-GHS06        | H317-318-330                 |
| Naphtha (Petroleum), Heavy Alkylate                   | 64741-65-7     | 0.1-1.0            | GHS06-GHS08        | H304-315-319-331-340-350-372 |
| Polymeric Benzotriazole                               | 104810-48-2    | 0.1-1.0            | GHS07              | H317                         |
| Polymeric Benzotriazole                               | 104810-47-1    | 0.1-1.0            | GHS07              | H317                         |
| Xylenes (o-, m-, p- Isomers)                          | 1330-20-7      | 0.1-1.0            | GHS02-GHS07-GHS08  | H226-304-315-319-332-335     |
| Methyl(1,2,2,6,6-Pentamethyl-4-Piperidiny)l) Sebacate | 82919-37-7     | 0.1-1.0            | Not Available      | Not Available                |

The balance of the product is Nonhazardous.

**4. First-Aid Measures**

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed. Remove contact lenses, if present and easy to do. Continue rinsing.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**FIRST AID - INGESTION:** If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cupfuls of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively. Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention. If swallowed, get medical attention.

## 5. Fire-fighting Measures

**ADG HAZCHEM CODE:** N.A.

**EXTINGUISHING MEDIA:** Aqueous Film Forming Foam, Carbon Dioxide, Dry Chemical, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Closed containers may explode when exposed to extreme heat due to buildup of steam. Vapors can travel to a source of ignition and flash back. Keep containers tightly closed. Combustible liquid and vapor.

**SPECIAL FIREFIGHTING PROCEDURES:** Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion. Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred. Evacuate area and fight fire from a safe distance. Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

## 6. Accidental Release Measures

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate all ignition sources; use explosion-proof equipment. Place material in a container and dispose of according to local, provincial, state and federal regulations. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools.

## 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Ground and bond containers when transferring material from one vessel to another. Vapor can be ignited by static discharge. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing. Do not swallow.

**STORAGE:** Store in a dry, well ventilated place. Keep container tightly closed when not in use. Keep away from heat, sparks, flame and sources of ignition. Avoid excess heat.

**Advice on Safe Handling of Combustible Dust:** No Information

## 8. Exposure Controls / Personal Protection

| Chemical Name                                       | CAS-No.     | Weight % Less Than | WHS WES TLV-TWA | WHS WES TLV-STEL |
|---|-------------|--------------------|-----------------|------------------|
| Methyl n-Amyl Ketone                                | 110-43-0    | 20.0               | 50 ppm          | N.E.             |
| n-Butyl Acetate                                     | 123-86-4    | 15.0               | 50 ppm          | 150 ppm          |
| Mica  | 12001-26-2  | 5.0                | 0.1 mg/m3       | N.E.             |
| Ethyl 3-Ethoxypropionate                            | 763-69-9    | 5.0                | N.E.            | N.E.             |
| Titanium Dioxide                                    | 13463-67-7  | 5.0                | 0.2 mg/m3       | N.E.             |
| p-Toluenesulfonyl Isocyanate                        | 4083-64-1   | 1.0                | N.E.            | N.E.             |
| bis(1,2,2,6,6-Pentamethyl-4-Piperidiny) Sebacate    | 41556-26-7  | 1.0                | N.E.            | N.E.             |
| Naphtha (Petroleum), Heavy Alkylate                 | 64741-65-7  | 1.0                | N.E.            | N.E.             |
| Polymeric Benzotriazole                             | 104810-48-2 | 1.0                | N.E.            | N.E.             |
| Polymeric Benzotriazole                             | 104810-47-1 | 1.0                | N.E.            | N.E.             |
| Xylenes (o-, m-, p- Isomers)                        | 1330-20-7   | 1.0                | 20 ppm          | N.E.             |
| Methyl(1,2,2,6,6-Pentamethyl-4-Piperidiny) Sebacate | 82919-37-7  | 1.0                | N.E.            | N.E.             |

### PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Provide general dilution of local exhaust ventilation in volume and pattern to keep TLV of hazardous ingredients below acceptable limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

**RESPIRATORY PROTECTION:** Wear an approved (or equivalent) full-facepiece airline respirator according to AS/NZS 1715-2009 and AS/NZS 1716-2012 in the positive pressure mode with emergency escape provisions. A respiratory protection program that meets AS/NZS 1715-2009 and AS/NZS 1716-2012 requirements must be followed whenever workplace conditions warrant a respirator's use. An approved air purifying respirator with organic vapor cartridge or canister according to AS/NZS 1715-2009 and AS/NZS 1716-2012 may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Users of this product in industrial/OEM applications must use one of the following forms of respiratory protection:

- AS/NZS 1715-2009 and AS/NZS 1716-2012 compliant supplied-air respirator operated in pressure demand or continuous flow mode and equipped with a tight fitting facepiece
- AS/NZS 1715-2009 and AS/NZS 1716-2012 compliant air-purifying respirator equipped with a full facepiece and organic gas/vapor cartridges
- AS/NZS 1715-2009 and AS/NZS 1716-2012 compliant powered air-purifying respirator equipped with a full facepiece and organic gas/vapor cartridges.

**SKIN PROTECTION:** Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

**EYE PROTECTION:** Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

**Engineering Measures for Combustible Dust:** No Information

## 9. Physical and Chemical Properties

|                                 |                     |   |            |
|---------------------------------|---------------------|---|------------|
| <b>Appearance:</b>              | Liquid              | <b>Physical State:</b>                              | Liquid     |
| <b>Odor:</b>                    | Solvent Like        | <b>Odor Threshold:</b>                              | N.E.       |
| <b>Specific Gravity:</b>        | 1.244               | <b>pH:</b>  | N.A.       |
| <b>Freeze Point, °C:</b>        | ND                  | <b>Viscosity:</b>                                   | N.D.       |
| <b>Solubility in Water:</b>     | Soluble             | <b>Partition Coefficient, n-octanol/<br/>water:</b> | N.D.       |
| <b>Decomposition Temp., °C:</b> | N.D.                | <b>Explosive Limits, vol%:</b>                      | 1.1 - 10.4 |
| <b>Boiling Range, °C:</b>       | 121 - 537           | <b>Flash Point, °C:</b>                             | 34         |
| <b>Flammability:</b>            | Supports Combustion | <b>Auto-Ignition Temp., °C:</b>                     | N.D.       |
| <b>Evaporation Rate:</b>        | Slower than Ether   | <b>Vapor Pressure:</b>                              | N.D.       |
| <b>Vapor Density:</b>           | Heavier than Air    |   |            |

(See "Other information" Section for abbreviation legend)

## 10. Stability and Reactivity

**Conditions to Avoid:** Avoid temperatures above 120°F (49°C). Avoid all possible sources of ignition. Avoid excess heat. Keep from freezing.

**Incompatibility:** Incompatible with strong oxidizing agents, strong acids and strong alkalis.

**Hazardous Decomposition:** When heated to decomposition, it emits acrid smoke and irritating fumes.

**Hazardous Polymerization:** Will not occur under normal conditions.

**Stability:** This product is stable under normal storage conditions.

## 11. Toxicological Information

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** Irritating, and may injure eye tissue if not removed promptly.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** May cause skin sensitization, an allergic reaction, which becomes evident upon re-exposure to this material. Low hazard for usual industrial handling or commercial handling by trained personnel.

**EFFECTS OF OVEREXPOSURE - INHALATION:** Harmful if inhaled. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. Routine handling and application does not require use of respiratory protection; however, if air monitoring demonstrates vapor, mist, or dust levels above applicable limits, wear an appropriate, properly fitted respirator (meets AS/NZS 1715-2009 and AS/NZS 1716-2012 requirements) during handling and application. Follow respirator manufacturer's directions for respirator use.

**EFFECTS OF OVEREXPOSURE - INGESTION:** Highly toxic. Substance may be harmful if swallowed. Aspiration hazard if swallowed; can enter lungs and cause damage.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis, and blurred vision) and/or damage. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Overexposure to xylene in laboratory animals has been associated with liver abnormalities, kidney, lung, spleen, eye and blood damage as well as reproductive

disorders. Effects in humans, due to chronic overexposure, have included liver, cardiac abnormalities and nervous system damage. Individuals with lung or breathing problems or prior reaction to isocyanates must not be exposed to vapor or spray mist. Vapor and spray mist harmful. Overexposure may cause lung damage. May cause allergic skin and respiratory reaction, effects may be permanent. Contains Titanium Dioxide. Titanium Dioxide is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC. No significant exposure to Titanium Dioxide is thought to occur during the use of products in which Titanium Dioxide is bound to other materials, such as in paints during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of Titanium Dioxide in the formula. (Ref: IARC Monograph, Vol. 93, 2010)

**PRIMARY ROUTE(S) OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

#### ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| <u>CAS-No.</u> | <u>Chemical Name</u>                             | <u>Oral LD50</u> | <u>Dermal LD50</u>  | <u>Vapor LC50</u>   |
|----------------|--|------------------|---------------------|---------------------|
| 110-43-0       | Methyl n-Amyl Ketone                             | 1600 mg/kg Rat   | 10300 mg/kg Rabbit  | N.E.                |
| 123-86-4       | n-Butyl Acetate                                  | 10768 mg/kg Rat  | >17600 mg/kg Rabbit | > 21 mg/L Rat       |
| 12001-26-2     | Mica   | N.E.             | N.E.                | 25000               |
| 763-69-9       | Ethyl 3-Ethoxypropionate                         | 5000 mg/kg Rat   | >9500 mg/kg Rabbit  | 25                  |
| 13463-67-7     | Titanium Dioxide                                 | >10000 mg/kg Rat | 6000                | N.E.                |
| 4083-64-1      | p-Toluenesulfonyl Isocyanate                     | 2234 mg/kg Rat   | N.E.                | >640 ppm (Rat, 1Hr) |
| 41556-26-7     | bis(1,2,2,6,6-Pentamethyl-4-Piperidiny) Sebacate | 2615 mg/kg Rat   | N.E.                | N.E.                |
| 64741-65-7     | Naphtha (Petroleum), Heavy Alkylate              | >7000 mg/kg Rat  | >2000 mg/kg Rabbit  | >5.04 mg/L Rat      |
| 1330-20-7      | Xylenes (o-, m-, p- Isomers)                     | 3500 mg/kg Rat   | >4350 mg/kg Rabbit  | 29.08 mg/L Rat      |

N.E. - Not Established

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** Product is a mixture of listed components. No ecotoxicity data was found for this product.

**TOXICITY:** The acute toxicity effects of this product have not been tested. Data on individual components are tabulated below:

#### AQUATIC ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| <u>CAS-No.</u> | <u>Chemical Name</u>                             | <u>Algae</u> | <u>Daphnia/Aquatic</u> | <u>Fish</u>    |
|----------------|--|--------------|------------------------|----------------|
| 110-43-0       | Methyl n-Amyl Ketone                             | N.E.         | N.E.                   | 126 - 137 mg/L |
| 123-86-4       | n-Butyl Acetate                                  | 674.7 mg/L   | N.E.                   | 100 mg/L       |
| 763-69-9       | Ethyl 3-Ethoxypropionate                         | N.E.         | 970 mg/L               | 62 mg/L        |
| 41556-26-7     | bis(1,2,2,6,6-Pentamethyl-4-Piperidiny) Sebacate | N.E.         | N.E.                   | 0.97 mg/L      |
| 64741-65-7     | Naphtha (Petroleum), Heavy Alkylate              | 30000 mg/L   | 2 mg/L                 | N.E.           |
| 1330-20-7      | Xylenes (o-, m-, p- Isomers)                     | N.E.         | 3.82 mg/L              | 13.4 mg/L      |

N.E. - Not Established

**PERSISTENCE AND DEGRADABILITY:** The persistence and degradability of this product have not been tested.

#### BIOACCUMULATIVE POTENTIAL:

| <u>Product/ingredient name</u>                   | <u>Octanol-water par. Coeff (log KOW)</u> | <u>Bio. Conc. Factor (BCF)</u> |
|--|---|--------------------------------|
| Methyl n-Amyl Ketone                             | 2.26                                      | N.I.                           |
| n-Butyl Acetate                                  | 1.81                                      | N.I.                           |
| Ethyl 3-Ethoxypropionate                         | 1.47                                      | N.I.                           |
| bis(1,2,2,6,6-Pentamethyl-4-Piperidiny) Sebacate | 0.37                                      | N.I.                           |
| Xylenes (o-, m-, p- Isomers)                     | 2.77 - 3.15                               | 0.6 - 15 dimensionless         |

**MOBILITY IN SOIL:** The mobility in soil of this product has not been tested.

**OTHER ADVERSE EFFECTS:** This product has not been tested for other adverse ecological effects.

## 13. Disposal Information

**DISPOSAL:** Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not incinerate closed containers.

## 14. Transport Information

|                       | <u>Domestic (USDOT)</u>              | <u>International (IMDG)</u> | <u>Air (IATA)</u> | <u>ADG</u>                           |
|-----------------------|--------------------------------------|-----------------------------|-------------------|--------------------------------------|
| UN Number:            | N.A.                                 | 1263                        | 1263              | N.A.                                 |
| Proper Shipping Name: | Paint Products in Limited Quantities | Paint                       | Paint             | Paint Products in Limited Quantities |
| Hazard Class:         | N.A.                                 | 3                           | 3                 | N.A.                                 |
| Packing Group:        | N.A.                                 | III                         | III               | N.A.                                 |
| Limited Quantity:     | Yes                                  | Yes                         | Yes               | Yes                                  |
| ADG Hazchem Code:     | N.A.                                 |                             |                   |                                      |

## 15. Regulatory Information

### Montreal Protocol

No Montreal Protocol components exist in this product.

### Stockholm Convention

No Stockholm Convention components exist in this product.

### Rotterdam Convention

No Rotterdam Convention components exist in this product.

### MARPOL

This product contains the following substances listed under the MARPOL regulations:

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|----------------------|----------------|
| Naphthalene          | 91-20-3        |

### SUSMP

This product contains the following substances classified as poisons as regulated by the Poisons Standard (SUSMP):

| <u>Chemical Name</u> | <u>Schedule Number(s)</u> |
|----------------------|---------------------------|
| Liquid Hydrocarbons  | Schedule 5                |

### Capital Territories Environmental Regulations

This product contains the following substances listed under the Australian Capital Territories Environmental Protection Regulation:

| <u>Chemical Name</u>         | <u>Schedule</u> | <u>Schedule Name</u>                 |
|------------------------------|-----------------|--------------------------------------|
| Xylenes (o-, m-, p- Isomers) | 3               | DOM - Organic Chemicals              |
| Ethylbenzene                 | 3               | Non-pesticide Anthropogenic Organics |
| Chlorobenzene                | 3               | Non-pesticide Anthropogenic Organics |
| Toluene                      | 3               | Non-pesticide Anthropogenic Organics |
| Styrene                      | 3               | DOM - Organic Chemicals              |
| Benzene                      | 3               | Non-pesticide Anthropogenic Organics |
| Zinc                         | 3               | AQUA - Inorganic Chemicals           |

**16. Other Information****SDS REVISION DATE:** 27/11/2023

**REASON FOR REVISION:** Product Composition Changed  
Substance and/or Product Properties Changed in Section(s):  
01 - Identification  
02 - Hazard Identification  
03 - Composition / Information on Ingredients  
05 - Fire-Fighting Measures  
08 - Exposure Controls / Personal Protection  
09 - Physical & Chemical Properties  
11 - Toxicological Information  
12 - Ecological Information  
Substance Hazard Threshold % Changed  
Revision Statement(s) Changed

**Legend:**

N.A. - Not Applicable    N.D. - Not Determined    N.E. - Not Established

S.T.E.L. - Short Term Exposure Limit

T.W.A. - Time Weighted Average

W.E.S. - Workplace Exposure Standard

W.H.S. - Work Health and Safety regulation

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.

