

# Safety Data Sheet

**RUST-OLEUM**  
AUSTRALIA

www.rustoleum.com.au

## 1. Identification

**Product Name:** MOTSPR 4L 4PK SPRAY PUTTY GOLD      **Revision Date:** 2/18/2020

**Name on Label:** Spray Putty Gold 4lt      **Supersedes Date:** New SDS

**Product Identifier:** SPG4

**Product Use/Class:** Ideal for the repair of nicks, scratches and minor dents.

**Supplier:** Rust-Oleum Australia & New Zealand Pty. Ltd.  
8 Lakeview Drive  
Scoresby, Melbourne, Victoria 3179  
Australia  
Ph 1 300 784 476      **Manufacturer:** Rust-Oleum Australia & New Zealand Pty. Ltd.  
73 Hallam South Rd  
Hallam, Vic 3803  
Australia  
Ph 3-9796-3400

**Preparer:** Regulatory Department

**Emergency Telephone:** 24 Hour Hotline: 1-300-366-961

## 2. Hazard Identification

This product is classified as a Dangerous Good per the Australian Code for the Transport of Dangerous Goods by Road and Rail. This product was assessed per Safe Work Australia criteria.

### Classification

#### Symbol(s) of Product



#### Signal Word

Danger

#### Possible Hazards

28% of the mixture consists of ingredient(s) of unknown acute toxicity.

#### GHS HAZARD STATEMENTS

|  |      |   |
|--|------|---|
| Acute Toxicity, Inhalation, category 4 | H332 | Harmful if inhaled.                       |
| Carcinogenicity, category 1A           | H350 | May cause cancer.                         |
| Flammable Liquid, category 1           | H224 | Extremely flammable liquid and vapor.     |
| Reproductive Toxicity, category 1A     | H360 | May damage fertility or the unborn child. |
| STOT, single exposure, category 3, NE  | H336 | May cause drowsiness or dizziness.        |
| STOT, single exposure, category 3, RTI | H335 | May cause respiratory irritation.         |
| Serious Eye Damage, category 1         | H318 | Causes serious eye damage.                |
| Skin Irritation, category 2            | H315 | Causes skin irritation.                   |

#### GHS LABEL PRECAUTIONARY STATEMENTS

|      |  |
|------|--|
| P201 | Obtain special instructions before use.  |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. NO SMOKING. |
| P261 | Avoid breathing dust/fume/gas/mist/vapors/spray.   |
| P264 | Wash hands thoroughly after handling.  |

|                |  |
|----------------|--|
| P271           | Use only outdoors or in a well-ventilated area.  |
| P280           | Wear protective gloves/protective clothing/eye protection/face protection.   |
| P302+P352      | IF ON SKIN: Wash with plenty of soap and water.  |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.                              |
| P304+P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.   |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308+P313      | IF exposed or concerned: Get medical advice/attention.   |
| P310           | If exposed immediately call a POISON CENTER or doctor/physician.   |
| P321           | For specific treatment see label.  |
| P332+P313      | If skin irritation occurs: Get medical advice/attention.   |
| P362+P364      | Take off contaminated clothing and wash it before reuse.   |
| P370+P378      | In case of fire: Use alcohol film forming foam, carbon dioxide, dry chemical, dry sand to extinguish.                            |
| P403+P233      | Store in a well-ventilated place. Keep container tightly closed.   |
| P403+P235      | Store in a well-ventilated place. Keep cool.   |
| P405           | Store locked up.   |
| P501           | Dispose of contents/container in accordance with local, regional and national regulations.                                       |

**GHS SDS PRECAUTIONARY STATEMENTS**

|      |  |
|------|--|
| P240 | Ground/bond container and receiving equipment.                 |
| P241 | Use explosion-proof electrical/ventilating/lighting/equipment. |
| P242 | Use only non-sparking tools.                                   |
| P243 | Take precautionary measures against static discharge.          |

**3. Composition/Information On Ingredients****HAZARDOUS SUBSTANCES**

| <u>Chemical Name</u>         | <u>CAS-No.</u> | <u>Wt.% Range</u> | <u>GHS Symbols</u> | <u>GHS Statements</u>        |
|------------------------------|----------------|-------------------|--------------------|------------------------------|
| Hydrous Magnesium Silicate   | 14807-96-6     | 25-50             | Not Available      | Not Available                |
| Nitrocellulose               | 9004-70-0      | 10-25             | GHS01              | H201                         |
| Toluene                      | 108-88-3       | 2.5-10            | GHS02-GHS07-GHS08  | H225-304-315-332-336-360-373 |
| Xylenes (o-, m-, p- Isomers) | 1330-20-7      | 2.5-10            | GHS02-GHS07        | H226-315-319-332-335         |
| sec-Butyl acetate            | 105-46-4       | 2.5-10            | GHS02              | H225                         |
| Methyl Ethyl Ketone          | 78-93-3        | 2.5-10            | GHS02-GHS07        | H225-319-332-335-336         |
| Isobutanol                   | 78-83-1        | 2.5-10            | GHS02-GHS05-GHS06  | H226-315-318-331-335-336     |
| Ethanol                      | 64-17-5        | 2.5-10            | GHS02-GHS07        | H225-319                     |
| Di(2-ethylhexyl) phthalate   | 117-81-7       | 2.5-10            | GHS08              | H350                         |
| 2-Propanol                   | 67-63-0        | 2.5-10            | GHS02-GHS07        | H225-302-319-336             |
| Methyl Isobutyl Ketone       | 108-10-1       | 2.5-10            | GHS02-GHS06-GHS08  | H225-319-331-335-351         |
| 1-Methoxy-2-Propyl Acetate   | 108-65-6       | 1.0-2.5           | GHS02              | H226                         |
| Titanium Dioxide             | 13463-67-7     | 1.0-2.5           | Not Available      | Not Available                |
| Ethylbenzene                 | 100-41-4       | 1.0-2.5           | GHS02-GHS07        | H225-315-319-332             |
| Crystalline Silica / Quartz  | 14808-60-7     | 0.1-1.0           | GHS08              | H350-372                     |

**The balance of the product is Nonhazardous.**

#### 4. First-Aid Measures

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**FIRST AID - INGESTION:** Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention. If swallowed, get medical attention.

#### 5. Fire-fighting Measures

**ADG HAZCHEM CODE:** .3YE

**EXTINGUISHING MEDIA:** Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Closed containers may explode when exposed to extreme heat due to buildup of steam. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. No unusual fire or explosion hazards noted.

**SPECIAL FIREFIGHTING PROCEDURES:** Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion. Evacuate area and fight fire from a safe distance. Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

#### 6. Accidental Release Measures

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

#### 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

**STORAGE:** Store in a dry, well ventilated place. Keep container tightly closed when not in use. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Do not store above 120 ° F. Store large quantities in buildings designed and protected for storage of NFPA Class II combustible liquids. Keep away from heat, sparks, flame and sources of ignition. Avoid excess heat. Product should be stored in tightly sealed containers and protected from heat, moisture, and foreign materials.

**Advice on Safe Handling of Combustible Dust:** No Information

#### 8. Exposure Controls / Personal Protection

| Chemical Name                | CAS-No.    | Weight % Less Than | WHS WES TLV-TWA | WHS WES TLV-STEL |
|------------------------------|------------|--------------------|-----------------|------------------|
| Hydrous Magnesium Silicate   | 14807-96-6 | 30.0               | 2 mg/m3         | N.E.             |
| Nitrocellulose               | 9004-70-0  | 15.0               | N.E.            | N.E.             |
| Toluene                      | 108-88-3   | 10.0               | 20 ppm          | N.E.             |
| Xylenes (o-, m-, p- Isomers) | 1330-20-7  | 10.0               | 100 ppm         | 150 ppm          |
| sec-Butyl acetate            | 105-46-4   | 10.0               | 50 ppm          | 150 ppm          |
| Methyl Ethyl Ketone          | 78-93-3    | 10.0               | 200 ppm         | 300 ppm          |
| Isobutanol                   | 78-83-1    | 5.0                | 50 ppm          | N.E.             |
| Ethanol                      | 64-17-5    | 5.0                | N.E.            | 1000 ppm         |
| Di(2-ethylhexyl) phthalate   | 117-81-7   | 5.0                | 5 mg/m3         | N.E.             |
| 2-Propanol                   | 67-63-0    | 5.0                | 200 ppm         | 400 ppm          |
| Methyl Isobutyl Ketone       | 108-10-1   | 5.0                | 20 ppm          | 75 ppm           |
| 1-Methoxy-2-Propyl Acetate   | 108-65-6   | 5.0                | N.E.            | N.E.             |
| Titanium Dioxide             | 13463-67-7 | 5.0                | 10 mg/m3        | N.E.             |
| Ethylbenzene                 | 100-41-4   | 5.0                | 20 ppm          | N.E.             |
| Crystalline Silica / Quartz  | 14808-60-7 | 1.0                | 0.025 mg/m3     | N.E.             |

**PERSONAL PROTECTION**

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or in any other circumstances where air purifying respirators may not provide adequate protection.

**SKIN PROTECTION:** Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

**EYE PROTECTION:** Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

**Engineering Measures for Combustible Dust:** No Information

## 9. Physical and Chemical Properties

|                                 |                     |   |             |
|---------------------------------|---------------------|---|-------------|
| <b>Appearance:</b>              | Liquid              | <b>Physical State:</b>                              | Liquid      |
| <b>Odor:</b>                    | Solvent Like        | <b>Odor Threshold:</b>                              | N.E.        |
| <b>Specific Gravity:</b>        | 1.240               | <b>pH:</b>  | N.A.        |
| <b>Freeze Point, °C:</b>        | N.D.                | <b>Viscosity:</b>                                   | N.D.        |
| <b>Solubility in Water:</b>     | Slight              | <b>Partition Coefficient, n-octanol/<br/>water:</b> | N.D.        |
| <b>Decomposition Temp., °C:</b> | N.D.                | <b>Explosive Limits, vol%:</b>                      | N.A. - N.A. |
| <b>Boiling Range, °C:</b>       | -18 - 537           | <b>Flash Point, °C:</b>                             | -4          |
| <b>Flammability:</b>            | Supports Combustion | <b>Auto-ignition Temp., °C:</b>                     | N.D.        |
| <b>Evaporation Rate:</b>        | Slower than Ether   | <b>Vapor Pressure:</b>                              | N.D.        |
| <b>Vapor Density:</b>           | Heavier than Air    |   |             |

(See "Other information" Section for abbreviation legend)

## 10. Stability and Reactivity

**CONDITIONS TO AVOID:** Avoid temperatures above 120°F (49°C). Avoid all possible sources of ignition.

**INCOMPATIBILITY:** Incompatible with strong oxidizing agents, strong acids and strong alkalies.

**HAZARDOUS DECOMPOSITION:** By open flame, carbon monoxide and carbon dioxide. When heated to decomposition, it emits acrid smoke and irritating fumes. Contains solvents which may form carbon monoxide, carbon dioxide, and formaldehyde.

**HAZARDOUS POLYMERIZATION:** Will not occur under normal conditions.

**STABILITY:** This product is stable under normal storage conditions. May form peroxides of unknown stability.

## 11. Toxicological Information

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** Causes Serious Eye Irritation

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** May be absorbed through the skin in harmful amounts. Causes skin irritation. Allergic reactions are possible.

**EFFECTS OF OVEREXPOSURE - INHALATION:** Harmful if inhaled. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. High vapor concentrations are irritating to the eyes, nose, throat and lungs. Prolonged or excessive inhalation may cause respiratory tract irritation.

**EFFECTS OF OVEREXPOSURE - INGESTION:** Harmful if swallowed.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** May damage fertility or the unborn child. High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis, and blurred vision) and/or damage. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Overexposure to xylene in laboratory animals has been associated with liver abnormalities, kidney, lung, spleen, eye and blood damage as well as reproductive disorders. Effects in humans, due to chronic overexposure, have included liver, cardiac abnormalities and nervous system damage. Overexposure to methyl ethyl ketone in laboratory animals has been associated with

liver abnormalities, kidney and lung damage. Fetotoxic/embryotoxic effects from inhalation have been seen in rats exposed to >1000ppm during gestation. IARC lists Ethylbenzene as a possible human carcinogen (group 2B). Contains Titanium Dioxide. Titanium Dioxide is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC. No significant exposure to Titanium Dioxide is thought to occur during the use of products in which Titanium Dioxide is bound to other materials, such as in paints during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of Titanium Dioxide in the formula. (Ref: IARC Monograph, Vol. 93, 2010) May cause genetic defects.

**PRIMARY ROUTE(S) OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

#### ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| <u>CAS-No.</u> | <u>Chemical Name</u>         | <u>Oral LD50</u> | <u>Dermal LD50</u>  | <u>Vapor LC50</u> |
|----------------|------------------------------|------------------|---------------------|-------------------|
| 14807-96-6     | Hydrous Magnesium Silicate   | 6000             | N.E.                | 30                |
| 9004-70-0      | Nitrocellulose               | >5000 mg/kg Rat  | N.E.                | N.E.              |
| 108-88-3       | Toluene                      | 2600 mg/kg Rat   | 12000 mg/kg Rabbit  | 12.5 mg/L Rat     |
| 1330-20-7      | Xylenes (o-, m-, p- Isomers) | 3500 mg/kg Rat   | >4350 mg/kg Rabbit  | 29.08 mg/L Rat    |
| 105-46-4       | sec-Butyl acetate            | 3200 mg/kg Rat   | N.E.                | N.E.              |
| 78-93-3        | Methyl Ethyl Ketone          | 2483 mg/kg Rat   | 5000 mg/kg Rabbit   | N.E.              |
| 78-83-1        | Isobutanol                   | 2460 mg/kg Rat   | 3400 mg/kg Rabbit   | >6.5 mg/L Rat     |
| 64-17-5        | Ethanol                      | 7060 mg/kg Rat   | 15,800 mg/kg Rabbit | 30,000 mg/L Rat   |
| 117-81-7       | Di(2-ethylhexyl) phthalate   | 30000 mg/kg Rat  | 25000 mg/kg Rabbit  | N.E.              |
| 67-63-0        | 2-Propanol                   | 1870 mg/kg Rat   | 4059 mg/kg Rabbit   | 72.6 mg/L Rat     |
| 108-10-1       | Methyl Isobutyl Ketone       | 2080 mg/kg Rat   | 3000 mg/kg Rabbit   | N.E.              |
| 108-65-6       | 1-Methoxy-2-Propyl Acetate   | 8532 mg/kg Rat   | >5000 mg/kg Rabbit  | N.E.              |
| 13463-67-7     | Titanium Dioxide             | >10000 mg/kg Rat | 2500 mg/kg          | N.E.              |
| 100-41-4       | Ethylbenzene                 | 3500 mg/kg Rat   | 15400 mg/kg Rabbit  | 17.4 mg/L Rat     |
| 14808-60-7     | Crystalline Silica / Quartz  | 5500 mg/kg Rat   | 5500                | 100 mg/L          |

N.E. - Not Established

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** Product is a mixture of listed components.

## 13. Disposal Information

**DISPOSAL INFORMATION:** Do not incinerate closed containers. Dispose of material in accordance to local, state, and federal regulations and ordinances.

## 14. Transport Information

|                              | <u>Domestic (USDOT)</u> | <u>International (IMDG)</u> | <u>Air (IATA)</u> | <u>ADG</u> |
|------------------------------|-------------------------|-----------------------------|-------------------|------------|
| <b>UN Number:</b>            | 1263                    | 1263                        | 1263              | 1263       |
| <b>Proper Shipping Name:</b> | Paint                   | Paint                       | Paint             | PAINT      |
| <b>Hazard Class:</b>         | 3                       | 3                           | 3                 | 3          |
| <b>Packing Group:</b>        | II                      | II                          | II                | II         |
| <b>Limited Quantity:</b>     | Yes                     | Yes                         | No                | Yes        |
| <b>ADG Hazchem Code:</b>     | .3YE                    |                             |                   |            |

## 15. Regulatory Information

**Montreal Protocol**

No Montreal Protocol components exist in this product.

**Stockholm Convention**

No Stockholm Convention components exist in this product.

**Rotterdam Convention**

No Rotterdam Convention components exist in this product.

**MARPOL**

No substances listed under the MARPOL regulations exist in this product.

**SUSMP**

This product contains the following substances classified as poisons as regulated by the Poisons Standard (SUSMP):

| <u>Chemical Name</u> | <u>Schedule Number(s)</u> |
|----------------------|---------------------------|
| Liquid Hydrocarbons  | Schedule 5                |

**Capital Territories Environmental Regulations**

This product contains the following substances listed under the Australian Capital Territories Environmental Protection Regulation:

| <u>Chemical Name</u>         | <u>Schedule</u> | <u>Schedule Name</u>                 |
|------------------------------|-----------------|--------------------------------------|
| Toluene                      | 3               | Non-pesticide Anthropogenic Organics |
| Xylenes (o-, m-, p- Isomers) | 3               | DOM - Organic Chemicals              |
| Di(2-ethylhexyl) phthalate   | 3               | Non-pesticide Anthropogenic Organics |
| Ethylbenzene                 | 3               | Non-pesticide Anthropogenic Organics |
| Chlorite Mineral             | 4               | DOM - Disinfection By-products       |

**16. Other Information**

**SDS REVISION DATE:** 2/18/2020

**REASON FOR REVISION:** No Information

Legend:

N.A. - Not Applicable N.D. - Not Determined N.E. - Not Established

S.T.E.L. - Short Term Exposure Limit

T.W.A. - Time Weighted Average

W.E.S. - Workplace Exposure Standard

W.H.S. - Work Health and Safety regulation

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.

