



## RUST-OLEUM® INDUSTRIAL ACRYLIC HARDENER

### DESCRIPTION AND USES

A clear liquid, polyfunctional aziridine additive for acrylic emulsion coatings. Improves early block resistance and mar resistance in water-based acrylic finishes.

### PRODUCT

206201 Acrylic Hardener

### PACKAGING

10 oz. plastic bottles

### COMPANION PRODUCTS

Rust-Oleum Industrial Speedy-Dry DTM Acrylic Enamel (3100 System)  
Rust-Oleum Industrial DTM Acrylic Enamel (3700 System)  
Industrial Choice DTM Acrylic (5200 System)

### PRODUCT APPLICATION

#### APPLICATION

Add 2 oz. per gallon when using with Industrial Choice™ DTM Acrylic or Rust-Oleum Industrial Speedy-Dry DTM Acrylic Enamel and just 1 oz. per gallon with Rust-Oleum Industrial DTM Acrylic Enamel. Add the Acrylic Hardener just prior to application of the coating. Mix well. Exceeding the recommended amount will not further enhance benefits. Apply the coating in the normal and recommended manner. A slight viscosity loss may occur, but not sufficient to affect application. The benefits of the additive will diminish after 24 hours. Do not repeat use of the additive.

### PHYSICAL PROPERTIES

Calculated values are shown and may vary slightly from the actual manufactured material.

#### Weight:

Per gallon: 8.9 lbs.

Per liter: 1.07 Kg

#### Shelf Life:

1 year after opening

3 years unopened

#### Safety Information:

Flash Point: 95° F (35° C) Setflash

Warning: **HANDLE WITH CARE. USE ONLY WITH ADEQUATE VENTILATION. AVOID CONTACT WITH SKIN OR EYES AND BREATHING OF SPRAY MIST. IN CASE OF SKIN OR EYE CONTACT, FLUSH THOROUGHLY WITH PLENTY OF WATER. FOR EYES, ALSO CALL PHYSICIAN. FOR INDUSTRIAL OR COMMERCIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN. SEE PRODUCT MATERIAL SAFETY DATA SHEET (MSDS) AND LABEL WARNINGS FOR ADDITIONAL SAFETY INFORMATION.**

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.