

FINISH YOUR METAL, WOOD OR FIBERGLASS DOOR WITH...



Specially formulated to protect your new door or revitalize an existing one!

Excellent coverage
and chip resistance

Standard Satin Colors



Black
238310



White
238311



Vermont Green
238316



Cranberry
238314



Dark Brown
238313

Custom Mixed Satin Colors



Vanilla



Ivory



Casual Ivory



Arabian Sands



Desert Khaki



Chateau Beige



Taupe



Tabernacle Taupe



Sedona Clay



Homestead Brown



Buckskin



Sandy Clay



Oakwood Brown



Deep Brown



Redwood



Worn Brick



Autumn Crimson



Auburn Haze



Pinot Noir



Dusty Red



Maroon



Sunset Red



Scarlet Glow



Stone Castle



Slate Gray



Iron Stone



Winter Sky



Blue Pearl



Iron Blue



Armor



Silent Indigo



Island Blue



Bold Navy



Rustic Pewter



Peddlestone Cream



Green Meadow



Far East Jade



Herb Garden



Sage



Pine Tree



Evergreen



Green Olive



Mountain Cottage



Turquoise Charm



Mint Green



Dolphin Teal

Colors shown on this printed piece may vary slightly from actual product due to aging, lighting, and printing processes.

Rust-Oleum® Oil-Based Door Paint is designed to bring great color retention and durable protection for your exterior and interior doors. Ideal for metal, wood and fiberglass doors.

This door paint can be applied over latex or oil based primer/paint.

DIRECTIONS

Preparation: For new pre-primed steel or wood doors, simply clean the surface with a lint free cloth before painting. For bare metal or wood doors, apply an even coat of primer. For repainting a painted door, remove any loose paint and rust with 120 grit sandpaper. Clean surface with soap and water, rinse and let dry.

Paint: Stir thoroughly. If thinning is necessary, thin material only with xylene. Thin no more than 5%. Recommend using a 6 1/2" shed-resistant roller with a 3/8" nap or a high quality brush with flagged ends. For optimal results, use the roller for the entire door or paint the recessed edges of raised panels with a brush then use the roller for the remaining flat surface. Dry & Recoat Times based on 70°F – 50% relative humidity. Allow more time at cooler temperatures. May recoat within 1 hour or after 24 hours. Dries to the touch in 1-2 hours, to handle in 4-6 hours, and is fully dry in 24 hours.

Clean Up: Clean brush and other tools with lacquer thinner or xylene.

Coverage: One quart of Rust-Oleum Door Paint will cover 2 coats on each side of the door.



RUST-OLEUM®
CORPORATION

11 Hawthorn Pkwy, Vernon Hills, IL 60061

800-323-3584

www.paintideas.com www.rustoleum.com