MEDICI® DECORATIVE POLYUREA FLOOR COATING





Concrete Saver® Medici® Decorative Polyurea Floor Coating is a high gloss, UV stable polyurea floor coating for use in commercial and industrial environments. The innovative Medici Roller combines two different finish colors in a simultaneous roller application to obtain a one of a kind faux stain finish.

FEATURES & BENEFITS

- ✓ High solids formula provides excellent abrasion resistance
- ✓ Quick dry time, return to service in 24 hours
- ✓ Consistent look unlike traditional concrete stains
- ✓ Easy to maintain, no waxing or upkeep needed!
- Perfect for indoor or outdoor applications and won't chalk or fade over time
- ✓ VOC compliant nationwide



"The system provides a high quality, extremely durable coating that looks great! It's easy to apply and offers the quick turn around time our clients need."

> Jamie Callaway The Paintsmiths of St Louis



MEDICI® DECORATIVE POLYUREA FLOOR COATING

QUICK FACTS

FILL WEIGHT	1 Gal.
REISIN TYPE	Polyurea
SOLIDS by VOLUME	90%
PRACTICAL COVERAGE	Up to 400 sq. ft./kit
RECOAT DRY TIME	4-6 hours
FOOT TRAFFIC	4-6 hours
HEAVY TRAFFIC	24 hours
COMPRESSION STRENGTH	12,000*
ABRASION RESISTANCE	12**
VOC	50g/L
APPLICATION METHOD	Brush, Medici Roller

Please see technical data and material safety data sheets for complete details.

COLORS



Terra Cotta 280947



Sierra Sunset 280938



Brown Slate 280939



Stone 280950

MEDICI® COMPANION PRODUCTS



Product Name Medici® Roller



Product Name Medici® Roller Tray 280959



Product Name Durability Additive 280945



Product Name FastKote UV Clear 277499

PRODUCT APPLICATION

Typical Applications: showrooms, restaurants, offices, hotels, lobbies, retail spaces and much more.





Application:



Substrates:



INFORMATION



MEDICI® Decorative Polyurea Floor Coating Video



MEDICI® Decorative Polyurea Floor Coating Technical Data Sheet



MEDICI® Decorative Polyurea Floor Coating **Material Safety Data Sheet**



Contact your Rust-Oleum representative for more information.

^{*}ASTM D695

^{**}ASTM D4060