

7769 RUSTY METAL PRIMER

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®



HIGH PERFORMANCE METAL PRIMER

MAXIMUM STRENGTH RUST INHIBITOR
FOR HEAVILY RUSTED METAL

OIL-BASED

128 FL. OZ. (1 U.S. GALLON) 3.78 LITERS

WARNING!
COMBUSTIBLE
LIQUID AND VAPOR

See other cautions on back panel.

¡ADVERTENCIA!
LIQUIDO Y VAPOR
COMBUSTIBLES

Observar otras precauciones al dorso.

NJ & PA Right to Know	
Stoddard Solvent	8052-41-3
Talc	14807-96-6
Alkyd Resin	68071-87-4
Mineral Spirits	64742-88-7
Calcium Borosilicate	59794-15-9
Iron Oxide	1309-37-1

Rust-Oleum® Professional Rusty Metal Primer provides the best base surface on heavily rusted metal for Rust-Oleum Professional Enamels. Provides more than two times the rust prevention of using the Enamels alone. Superior adhesion prevents chipping, cracking and peeling. Eliminates the need for additional topcoats and touch-ups. Start every project with a Professional Primer and finish with Professional Enamel for the best possible, longest lasting finish every time.

Painting Conditions: Use when temperature is above 32°F (0°C) and humidity is below 85% to ensure proper drying. Do not apply to surfaces that exceed 200°F (93°C) or galvanized metal. Can be used over most latex or oil paints. Rust-Oleum Professional Enamels and Primers are not recommended for water immersion.
FOR METAL SUBSTRATES ONLY.

Preparation: Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces. **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to **www.epa.gov/lead**.

Clean surface with soap and water, rinse and let dry.

Painting: Stir thoroughly. If thinning is necessary, thin with acetone only. For brush or roller, thinning is not recommended. For air spray, thin up to 1-1/2 to 2 pints per gallon. Do not thin with gasoline, lacquer thinner, turpentine, etc.

Apply with a good quality brush, roller or spray gun.

Brush: Use light, even strokes. Excessive brushing reduces film thickness and protection.

Roller: The rougher the surface, the longer the roller nap should be. Cover approximately one square yard at a time. Roll away from previously coated area and work back to it for a uniform appearance. Use a brush on crevices and sharp edges.

Spray Gun: Follow spray gun directions carefully. Always keep the gun ten to twelve inches from the surface and in motion while spraying.

Recoat Times: May recoat when fully dry, usually in 24 hours. Dries to the touch in 4-6 hours and to handle in 8-12 hours, at 70°F (21°C) – 50% relative humidity. Allow more time at cooler temperatures and higher humidity.

Clean-up: Clean brush, roller and other tools with mineral spirits.

Covers: 775 sq. ft. at 1 mil dry; 387 sq. ft. at 2 mils dry, per gallon.

WARNING: Contains Petroleum Distillates. VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Do not breathe vapors, spray mist, sanding dust or overspray. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep away from heat and flame. **Use only with adequate ventilation.** Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, do not induce vomiting. Get medical attention immediately. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. **WARNING:** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. KEEP OUT OF REACH OF CHILDREN. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Unleaded—Safe for use on children's toys, furniture, etc.

Category: Rust Preventive Coating
Max VOC: 400 g/l

We guarantee our products to conform to Rust-Oleum specifications. Due to paint application variables beyond our control, ALL WARRANTIES OF ANY KIND, EXPRESSOR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE HEREBY EXCLUDED. Liability, if any, is limited to replacement of the product or refund of the purchase price. Labor and other material costs are excluded from this limited warranty.

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact our Customer Service Department for a full refund of the purchase price. Refer to product number and batch code on top of can.

paintideas.com

©2003 Rust-Oleum Corporation

Made in USA

rustoleum.com

RUST-OLEUM®
CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061

1-800-481-4785

An RPM Company

000000 000

ADVERTENCIA:

Contiene Destilados de Petróleo. LAS EMANACIONES SON DAÑINAS. PUEDEN AFECTAR AL CEREBRO O AL SISTEMA NERVIOSO CAUSANDO MAREOS, JAQUECAS O NAUSEA. IRRITA LOS OJOS, LA PIEL, LA NARIZ Y LA GARGANTA. AVISO: En algunos estudios se ha observado que la sobreexposición ocupacional repetida y prolongada a los solventes causa daño permanente al cerebro y al sistema nervioso. Mantenga este producto alejado de fuentes caloríficas y flamas. No aspire las emanaciones, la nube del rocío, el polvo del lijado, ni el rocío. Asegúrese de que entre y circule el aire fresco durante la aplicación y el secado. Si experimenta lacrimación en los ojos, jaquecas o mareos, o si un muestreo del aire indica niveles de emanación/roció superiores a los límites correspondientes, póngase protección respiratoria adecuada (con certificación NIOSH/MSHA) durante y después de la aplicación. Evite el contacto con los ojos, piel y ropa. Lávese cuidadosamente después de cada aplicación. **Aplique el producto solamente con ventilación adecuada.** Evite la acumulación de emanaciones abriendo todas las ventanas y puertas para lograr ventilación en todas las direcciones. Vuelva a colocar la tapa después de cada uso. **PRIMEROS AUXILIOS:** Si sufre dificultad para respirar, abandone el área y respire aire fresco. Si la dificultad para respirar persiste, busque asistencia médica inmediatamente. En caso de contacto con los ojos, enjuáguelos de inmediato con suficiente agua durante un mínimo de 15 minutos y busque atención médica; en caso de contacto con la piel, lave completamente el área afectada con agua y jabón. En caso de ingestión del producto, no se induzca vómito. Llame un médico inmediato. Si el producto se derrama, encierre el material derramado y recójalo con absorbente inerte. Elimine el absorbente contaminado, el recipiente y la cantidad no utilizada de acuerdo con las leyes locales, estatales y federales. **ADVERTENCIA:** Este producto contiene químicos que son conocidos en el Estado de California porque causan cáncer y defectos de nacimiento u otros daños al sistema reproductivo. MANTENGALO FUERA DEL ALCANCE DE LOS NIÑOS. EL USO INAPROPIADO INTENCIONAL CONCENTRANDO E INHALANDO EL CONTENIDO PUEDE SER DAÑINO O MORTAL. **No contiene plomo — Puede utilizarse para los juguetes de los niños, muebles, etc. Para conseguir información emergencia sobre el producto y los posibles efectos en la salud, llame al: (847) 367-0244. PROHIBIDA SU VENTA A MENORES DE EDAD. PRODUCTO ORIGINARIO DE E.U.A.**