

• TRUSTED QUALITY SINCE 1921 •

# RUST-OLEUM®



## Epoxy Acrylic Formula

## Excellent adhesion & durability

## Refinish tubs, sinks & showers in minutes

**DANGER!** COMBUSTIBLE LIQUID AND VAPOR. VAPOR HARMFUL. EXTREMELY FLAMMABLE.

See other cautions on back panel.

**¡PELIGRO!** LIQUIDO Y VAPOR COMBUSTIBLES. VAPOR DAÑINO. EXTREMADAMENTE INFLAMMABLES.

Vea otras precauciones en el panel de atrás.

NET WT. 12 OZ. (340g)

**RUST-OLEUM® TUB & TILE AEROSOL** is a one-step solution that provides outstanding adhesion, durability and color retention in high moisture areas. This smooth, glossy, waterproof finish is perfect for tiles, sinks and tubs. **Note: Proper surface cleaning and preparation are key to a smooth, lasting finish. Follow all directions carefully and completely.**

**Painting Conditions:** Use in a well-ventilated area when the temperature is between 50°F - 100°F, and humidity is below 80% to ensure proper drying. Not for use on galvanized metal or other metal surfaces. **Preparation:** Remove metal drains. Remove any loose paint with a wire brush or sandpaper. Repair chips or cracks with a patching compound such as Liquid Steel®. Eliminate mildew from the surface by treating with a solution of bleach and water. Repeat if necessary. Rinse thoroughly with water. Scrub surface with an abrasive pad and abrasive cleaner such as Comet® to remove all dirt, grease, mold, oil, soap film and hard water deposits. Remove caulk and wipe areas with a non-oily solvent such as isopropyl alcohol. Scrub with an abrasive pad and Lime-A-Way® cleaner to create a slightly porous surface for strong adhesion. Allow to stand for 5 minutes. Scrub the entire surface again and rinse with water. Sand the surface with #40/600 grit wet/dry sandpaper. Rinse thoroughly with water to remove all residue. Allow the surface to dry for at least 90 minutes before applying paint. Wipe with a tack cloth immediately before painting to remove all dust and lint. Always test product in a small, hidden area before painting. **Painting:** Open any windows or use fans to properly ventilate the area. Shake can vigorously for one minute after mixing ball begins to rattle. If mixing ball fails to rattle, DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold can upright 10-16" from surface and spray in a steady back and forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply 2-3 light coats, spraying horizontally and vertically. **Dry Time:** Dries to touch in 15 minutes. Fully cure in 3 days. **Clean-Up:** Wipe off tip before storing. Clean up wet paint with Xyloil or mineral spirits. Throw away empty can in trash. Do not burn or place in home trash compactor. **Clogging:** If valve clogs, twist and pull off spray tip and rinse it in a solvent such as mineral spirits. Do not stick on or other object into the stem. **Coverage:** 10-15 sq. ft. for light colored tubs.

**DANGER!** Contains Acetone and Petroleum Distillates. Harmful or fatal if swallowed. Call physician immediately. Vapor harmful. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Harmful if absorbed through skin. Vapors may ignite explosively. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Use only with adequate ventilation. Ensure fresh air entry during application and drying. If a window or fan is not present in the room, place a general room fan 5 feet outside room doorway to blow fresh air into room. Apply product in 5-minute intervals, then leave room. Return after 5 minutes. If you experience eye watering, headache, or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's direction for respirator use. Close container after each use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. **First Aid:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention, for skin, wash thoroughly with soap and water. Clean up area with thinner or soap and water. Test surface in small, hidden area prior to using thinner. **WARNING:** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm. **KEEP OUT OF REACH OF CHILDREN.**

**SATISFACTION GUARANTEED:** If you are dissatisfied with this product, contact our Product Support Department at 1-800-481-4785 for a full refund of the purchase price. Refer to product number and batch code on bottom of can.



11 Hawthorn Pkwy., Vernon Hills, IL 60061  
rustoleum.com 1-800-481-4785

©2014 Rust-Oleum Corporation. Made in USA Hecho en E.U.A. 285326 0714

**RUST-OLEUM® TUB & TILE AEROSOL** es una solución de un solo paso que proporciona una excelente adherencia, durabilidad y permanencia del color en zonas de alta humedad. Este acabado impermeable y ligeramente brillante es perfecto para azulejos, lavabos y baños. **Nota: La limpieza adecuada de la superficie y su preparación son la clave para un acabado suave y duradero. Siga todas las instrucciones completa y cuidadosamente.**

For complete instructions in Spanish and additional application information, scan the QR code.

Para obtener instrucciones completas en ideas de aplicación Español y adicional, analizar el siguiente código QR:



**¡PELIGRO!**  
**CONTIENE:** Acetona y destilados del petróleo. Puede resultar dañino o fatal en caso de ingestión. Llame a un médico de inmediato. Vapor dañino. Existen informes que asocian la sobreexposición ocupacional repetida y prolongada a solventes con daños permanentes en el cerebro y en el sistema nervioso. Concentrar e inhalar deliberadamente el contenido puede ser nocivo o fatal y constituye un uso indebido intencional del producto. Puede ser perjudicial si se absorbe a través de la piel. Los vapores pueden encenderse y causar una explosión. Mantenga alejado del calor, las chispas y las llamas. No fumar. Apague todas las llamas y luces piloto, y apague estufas, calentadores, motores eléctricos y otras fuentes de ignición mientras este utilizando el producto o hasta que los vapores hayan desaparecido. Abra todas las ventanas y puertas para tener una ventilación cruzada y evitar la acumulación de vapores. **Utilice solo con la ventilación adecuada.** Asegure la entrada de aire fresco durante la aplicación y el secado. Si no hay ninguna ventana ni ventilador en la sala, coloque un ventilador a unos 5 pies de distancia de la puerta de la habitación para que sople aire fresco hacía adentro. Aplique el producto en intervalos de cinco minutos y luego, abandone la habitación. Regrese después de cinco minutos. Si le lloran los ojos, sufre de dolores de cabeza o mareos o el control del aire demuestra que los niveles de vapor o vahos son superiores a los límites aplicables, use un respirador apropiado que se ajuste adecuadamente, aprobado por el Instituto Nacional para la Seguridad y Salud Ocupacional y la Administración de Seguridad y Salud en Minas (NIOSH/MSHA) durante y después, de la aplicación. Siga las instrucciones del fabricante con respecto al uso del respirador. Cierre el recipiente luego de cada aplicación. Evite el contacto con ojos, piel y la ropa. Lávese bien después de manipular el producto. **Primeros auxilios:** Si tiene dificultades para respirar, abandone el área para obtener aire fresco. Si la dificultad persiste, busque ayuda médica de inmediato. En caso de contacto con los ojos, enjuague de inmediato con abundante agua durante al menos quince minutos y busque atención médica. En caso de contacto con la piel, lave bien con agua y jabón. Limpie el área con solvente o con jabón y agua. Pruebe la superficie en un área pequeña y oculta antes de usar solvente. **ADVERTENCIA:** Este producto contiene químicos que el Estado de California reconoce como causantes de cáncer y defectos de nacimiento u otros daños reproductivos. **MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS.**

280882 TUB AND TILE WHITE



0 20066 24720 1