

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®

CLEAR SHIMMER FLOOR TOPCOAT

INTERIOR &
EXTERIOR
DURABILITY

DRIVE ON
IN 5 DAYS

Water-Based Acrylic

Hot Tire & Chemical Resistant

Great for Garages, Driveways,
Patios & Basements

One Gallon
(128FL.OZ./3.78L)

CLEAR SHIMMER
GLOSS



COVERS
150-400 SQ. FT.

See cautions on back panel

RUST-OLEUM® CLEAR SHIMMER FLOOR TOPCOAT is a ready-to-use interior/exterior concrete clear protective coating with a decorative shimmer effect, formulated for use on garages, carpets, driveways, basements, porches, patios, walkways and pool decks. This product is designed for use over bare concrete or over one-part floor paints such as RUST-OLEUM® Concrete & Garage Floor Paint + Primer to add a protective, shimmer gloss finish that resists damage from hot tires, motor oil, grease and gasoline. The durable, UV & weather resistant finish is easy to maintain and resists fading and peeling, and can be easily cleaned up with soap & water.

LEA ATENTAMENTE TODAS LAS INSTRUCCIONES ANTES DE COMENZAR EL PROYECTO.

WHERE TO USE: Use on interior or exterior concrete surfaces such as garage floors, carpets, driveways, basements, porches, patios, walkways and pool decks. Allow newly poured concrete to cure for a minimum of 28 days prior to coating. Apply when air (ambient) temperature is 50-90°F (10-32°C) and relative humidity is below 85%. Do not paint outdoors if rain is expected within 48 hours. Not recommended for use on asphalt. For freshly painted surfaces, apply over 1-part water base paints and stains such as RUST-OLEUM® Concrete & Garage Floor Paint + Primer as a protective clear topcoat without further surface preparation. Apply topcoat after 24 hours of base coat application and within 7 days.

DÓNDE UTILIZAR: Para uso en superficies de concreto de interior o exterior, como pisos de garaje, estacionamientos, entradas, sótanos, porches, patios, pasillos y bordes de piscina. Deje que el concreto recién vertido se cure durante al menos 28 días antes de aplicar el revestimiento. Aplique cuando la temperatura del aire (ambiente) sea de 50-90°F (10-32°C) y la humedad relativa esté debajo de 85%. No aplique en el exterior si se pronostican lluvias en las siguientes 48 horas. No se recomienda para uso en asfalto. Para superficies recién pintadas: aplique sobre pinturas y tintas a base de agua de una sola parte, como el Impresor + Pintura para Cocheras y Concreto RUST-OLEUM®, como capa de acabado protector transparente sin preparación adicional. La aplicación de la superficie después de 24 horas de aplicada la capa base y en los próximos 7 días.

PREPARACIÓN DE LA SUPERFICIE: Ya sea que se aplique sobre concreto sin revestir o previamente revestido, es esencial preparar correctamente la superficie. Antes de aplicar el revestimiento, si es necesario, lífice un cepillo de alambre o una lija para quitar las partes de concreto o mampostería que están sueltas o poco firmes. Quite la grasa, el aceite, la sal y otras contaminantes con el DESENGARRASANTE DE ALTA RESISTENCIA RUST-OLEUM® O EL LIMPADOR Y DESENGARRASANTE RUST-OLEUM® (se venden por separado). Limpie profundamente las manchas con un cepillo de cerdas duras o una escoba y quite el exceso de limpiador con trapos o paños de papel para evitar que se esparsan los contaminantes. Enjuague bien con agua fresca. Repita las veces que sea necesario hasta que esté completamente limpia la superficie. Superficie de Concreto sin Revestir: Para lograr una adecuada penetración y una máxima adhesión, utilice el ácido de concreto CONCRETE ETCH DE RUST-OLEUM® O EL LIMPADOR Y ACIDO CLEAN & ETCH DE RUST-OLEUM® (se venden por separado). Siga cuidadosamente las instrucciones de la etiqueta y deje secar el piso por completo. Pase los dedos sobre la superficie limpia y seca. Si nota suciedad o polvo en los dedos, repita el enjuague y el lavado hasta que el piso quede limpio. Superficies de concreto previamente pintadas, teñidas o selladas: Utilice un cepillo de alambre para quitar toda la pintura suelta o descamada. Para garantizar una adecuada adhesión, lípe la superficie completa y limpíela con un solvente, como la acetona.

SUPERFICIE DE CONCRETO: Whether over bare or previously coated concrete, proper surface preparation is critical to performance. Before coating, if necessary, use a wire brush or sander to remove any loose or unsound concrete or masonry. Remove grease, oil, salt and other contaminants with RUST-OLEUM® HEAVY-DUTY DEGREASER or RUST-OLEUM® CLEANER & DEGREASER (sold separately). Scrub spots thoroughly with a stiff bristle brush or broom and wipe up excess cleaner with rags or paper towels to keep contaminants from spreading. Rinse thoroughly with fresh water. Repeat as necessary until completely clean. **Bare Concrete Surfaces:** For proper penetration and maximum adhesion, use RUST-OLEUM® CONCRETE ETCH or RUST-OLEUM® CLEAN & ETCH (sold separately). Follow label instructions carefully and allow the floor to dry completely. Wipe your fingers over the clean, dry surface. If you see any dust or powder on your fingers, repeat rinsing and scrubbing until the floor is clean. **Previously Painted, Stained or Sealed Concrete Surfaces:** Use a wire brush to remove any loose or peeling paint, stain or sealer. To ensure proper adhesion, scuff sand the entire surface and clean with a solvent such as acetone.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN YOUNG CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Spot check all exposed concrete surfaces using RUST-OLEUM® CONCRETE ETCH or RUST-OLEUM® CLEAN & ETCH. Rinse thoroughly and allow to dry completely.

APPLICATION: RUST-OLEUM® CLEAR SHIMMER FLOOR TOPCOAT is ready to use. Do not thin. If using more than one gallon, mix all cans of the same product to ensure gloss uniformity. Stir thoroughly before applying. Note: Painted floors may be slippery when wet. If desired, mix in RUST-OLEUM® ANTI-SKID ADDITIVE (sold separately).

Use a brush or edger to trim the perimeter and hard-to-reach areas. Use a long handled roller and a high-quality, 3/8" nap roller cover to apply an even coat of RUST-OLEUM® CLEAR SHIMMER FLOOR TOPCOAT onto the surface. Apply in 4'x4' sections, and maintain a wet edge to prevent lap marks and gloss differences. Continue applying in 4'x4' sections until complete. Only one coat is necessary. If a second coat is desired, wait 4 hours before applying the second coat in a direction perpendicular to the first. Occasional touch-up may be necessary for areas subject to heavy vehicle traffic.

DRY TIME: Surface should be ready for light foot traffic in 24 hours. FOR FULL CURE AND VEHICLE TRAFFIC, ALLOW 5 DAYS. Dry times increase at cooler temperatures.

CLEAN UP: Wash tools and equipment with warm water and a mild detergent. Properly dispose of all soiled rags and protect unused product from freezing.

COVERAGE: Each gallon contains enough surface treatment to cover approximately 150-250 square feet over bare concrete and 300-400 square feet over coated concrete. Additional product may be required depending on surface conditions.

PRECAUTIONS. Do not take internally. Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. Close container after each use. Avoid contact with skin and eyes. Wash thoroughly after handling. **First Aid:** If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of contact, immediately flush skin with soap and water and eyes with plenty of water. If swallowed, get medical attention immediately. KEEP OUT OF REACH OF CHILDREN. For emergency, call your physician, local poison control center or local emergency room. For product health information, call: (800)481-4785.

WARNING. Cancer and reproductive Harm - www.P65Warnings.ca.gov.

PRECAUCIÓN. No lo ingiera. Utilice el producto solo con la ventilación adecuada. No respire el polvo ni los vapores. Asegúrese de que entre aire puro durante la aplicación y el secado. Cierre el envase después de cada uso. Evite el contacto con la piel y los ojos. Lávese bien después de manipular el producto. **Primeros Auxilios:** Si tiene dificultades para respirar, abandone el área en busca de aire puro. Si la dificultad persiste, busque asistencia médica de inmediato. En caso de contacto, enjuague la piel de inmediato con agua y jabón, si tiene contacto con los ojos, lave con abundante agua. En caso de ingestión, busque atención médica de inmediato. MANTENGA EL PRODUCTO ALEJADO DEL ALCANCE DE LOS NIÑOS. En caso de emergencia, llame a su médico, al centro de toxicología o al servicio local de emergencias. Para obtener información sanitaria del producto, llame: (800)481-4785.

ADVERTENCIA. Cáncer y daños reproductivos - www.P65Warnings.ca.gov.

VOC: Max VOC 50 g/L

COV: Máximo COV 50 gramos/Litro

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Technical Support at 1-888-NUFLOR (1-888-683-5667) for a full refund of the purchase price.

SATISFACCIÓN GARANTIZADA: Si no está satisfecho(a) con este producto, póngase en contacto con el Apoyo Técnico de Rust-Oleum marcando 1-888-NUFLOR (1-888-683-5667) para obtener un reembolso completo del precio de la compra.

RUST-OLEUM
CORPORATION



11 Hawthorn Pkwy.
Vernon Hills, IL 60061

rustoleum.com

0 20066 44490 7

©2018 Rust-Oleum Corporation
350178 1218