



**AUTOMOTIVE  
WAX & TAR REMOVER**

**DESCRIPTION AND USES**

Rust-Oleum® Wax & Tar Remover is an effective, fast-acting remover for many automotive surfaces, including metal, plastic and fiberglass. It should be used prior to sanding to prolong the life of sandpaper and again after sanding as a clean-up agent prior to applying top coats. Wax & Tar Remover removes old wax build-up before re-application of new wax to promote an even, mirror-like finish. It is also great for removing grease, silicone and road film.

**PRODUCTS**

SKU (32 oz. Quart)	Description
2514757	Wax & Tar Remover

**PRODUCT APPLICATION**

**APPLICATION**

Protect hands with solvent-resistant gloves and eyes with chemical splash goggles.

Saturate a clean, lint-free cloth with Wax & Tar Remover. Thoroughly cover area to be cleaned. Apply to a small area (3' x 3') at a time. Allow to stand as long as possible without drying, normally 4 to 6 minutes. Wipe dry with a clean, lint-free white cloth. Turn cloth frequently to ensure a clean side contacts surface. Replace cloth as it becomes damp and soiled to prevent re-depositing of contaminants.

**NOTE:** This product may not be compatible with all surfaces and all conditions surrounding application. Before applying to any surface, always test product in a small, inconspicuous area to ensure no damage will result. Do not use on freshly painted surfaces. Ensure paint has cured in accordance with paint manufacturer's instructions. Do not use on metal or plastic surfaces that are hot to the touch. For best results, apply at temperatures between 65-90°F (18-32°C) and avoid direct sunlight or strong breezes.

**PHYSICAL PROPERTIES**

Physical Properties	WAX & TAR REMOVER
Composition	Ethoxylated Alcohols and Water
Weight per Gallon	8.33 lbs.
Volatile Organic Compounds	677 g/l
Shelf Life	5 years
Flash Point	>200°F (93°C)
Safety Information	For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.