



**AUTOMOTIVE
AIRCRAFT REMOVER**

DESCRIPTION AND USES

Rust-Oleum® Aircraft Remover is a fast acting remover that strips finishes from metal automotive surfaces. Use Aircraft Remover to quickly remove acrylics, lacquers, polyurethane and baked enamels from automobiles and trucks in 10 minutes which leaves a bare surface that is ready to be primed or painted. Not recommended for use on fiberglass, plastics, or any other synthetic surface. This product is non-corrosive to all common metals under normal exposure time

PRODUCTS

SKU	Description
255447	1-Gallon Aircraft Remover
248874	1-Gallon Aircraft Remover
255448	1-Quart Aircraft Remover
248873	1-Quart Aircraft Remover

PRODUCT APPLICATION

SURFACE PREPARATION

Remove or protect any portions of the vehicle not being stripped. Mask seams and trim openings as this will prevent bleed-back stripping of new finish. Spread a solvent resistant drop cloth covered in newspaper around work area in case of drips or spills. . Protect hands with solvent-resistant gloves and eyes with chemical splash goggles.

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

APPLICATION

Use outdoors or in a well-ventilated area such as an open garage. Apply when temperature is between 65-90°F (18-32°C). Pour remover into a metal or glass container and apply a thick coat with a chemical resistant brush. If applying to a vertical surface, begin the application at the bottom, as vapors are heavier than air and can accumulate near the floor. Apply to one section at a time up to 9 square inches. Brush in one direction only. Allow the remover to work until the finish is blistered or softened completely, generally within 5-15 minutes. Remove paint with a flexible plastic scraper and then flush with solvent or water to remove any residue. Allow surface to dry before applying a new finish. The metal should be primed as soon as possible to prevent flash rust.

NOTE: This product may not be compatible with all surfaces and all conditions surrounding the application. Before applying to any surface, always test product in a small inconspicuous area to ensure no damage will result. This product is not recommended for use on fiberglass, plastics or any other synthetic surface.

CLEAN UP

Tools and brushes should be cleaned with soap and water immediately after use.

**TECHNICAL DATA****AUTOMOTIVE AIRCRAFT REMOVER****PHYSICAL PROPERTIES**

		AIRCRAFT REMOVER
Solvents		Blend of Methanol, Ethanol and Methylene Chloride
Weight	Per Gallon	9.81 lbs.
	Per Liter	1.17 kg
VOC		150 g/l
Shelf Life		5 years
Flash Point		>200°F (93°C)
Safety Information		For additional Information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.