



# RUST STRIPPER

## DESCRIPTION AND USES

Rust-Oleum® Rust Stripper is an acid based formula that safely strips metal clean and helps to restore them to an original finish. It is suitable for use on tools, automobiles, patio furniture, iron railings and doors, mailboxes, bicycles, swing sets, lawn equipment and most other metal, steel, and iron products. **DO NOT** use Rust Stripper on aluminum, chrome or galvanized steel.

## PRODUCTS

SKU (8 ounce bottle)	Description
248660	Rust Stripper

## PRODUCT APPLICATION

### SURFACE PREPARATION

Wear rubber gloves and safety glasses when using this product. Prepare by having a towel, drop cloth and soapy water available to clean up spills. Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove all loose rust, scale, and previous coatings with a wire brush, scraper, or putty knife. Power tool clean to remove severe rust and corrosion and deteriorated coatings.

**WARNING!** If you scrape, sand or remove old paint from any surface, you may release lead paint dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## PRODUCT APPLICATION (cont.)

### APPLICATION

Shake the bottle to ensure the contents are well mixed. Apply Rust Stripper to rusted surfaces directly from the bottle or pour the needed amount into a non-metal bowl and apply using a brush. Wait 10 minutes. Rinse with fresh water. Use the enclosed stripper pad to loosen rust from the surface and dry with a clean towel. Repeat as necessary.

For best results, prime and paint the clean metal surface within 24 hours of using Rust Stripper. If a clean metal surface will not be painted, oil the surface immediately using a light coat of rust preventive oil. For maximum rust prevention, prime the metal surface with a Rust-Oleum Automotive Primer and apply one of the Automotive finish coats. Recommended primers include 249319 Clean Metal Primer, 249321 Primer Sealer, 249410 Engine Primer, or one of the Stops Rust® primers.

### CLEAN-UP

Clean pad and any spills with warm, soapy water while the Rust Stripper is still wet.



## TECHNICAL DATA

# RUST STRIPPER

## PHYSICAL PROPERTIES

		RUST STRIPPER
Composition		Hydrochloric acid, Phosphoric acid
Solvent		Water
Weight	Per Gallon	9.8 lbs.
	Per Liter	1.17 kg
Shelf Life		5 years
Flash Point		NA
Warning!		<b>CORROSIVE! CONTAINS HYDROCHLORIC ACID</b>
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.