



**JOMAX<sup>®</sup>**  
**MOLD & MILDEW STAIN REMOVER**

**DESCRIPTION AND USES**

JOMAX<sup>®</sup> Mold & Mildew Stain Remover removes tough mold & mildew stains on drywall and wood prior to painting. Ideal for use on fiberglass, tile, grout, vinyl, plastic and more. Use weekly around bath and shower stalls to prevent mold and mildew stains & soap scum buildup.

**PRODUCT**

DESCRIPTION	SKU
32 Oz. Bottle	60118

**PRODUCT APPLICATION**

**DIRECTIONS FOR USE**

Remove all loose dirt, oil, grease, and other contaminants. Rotate the nozzle to spray position for large areas. Rotate the nozzle to stream for a concentrated jet spray on hard to reach areas. Apply directly to soiled areas. Wait 5 to 10 minutes for stains to disappear and then rinse thoroughly with water. For difficult stains, some scrubbing may be necessary. Wipe dry, using a clean cellulose sponge, cloth or paper towel. For sensitive skin, wear gloves.

**PRODUCT APPLICATION (cont.)**

**NOTE:** This product may not be compatible with all surfaces and all conditions surrounding the application. Before applying to any surface, always test product in a small inconspicuous area to ensure no damage will result. Use with adequate ventilation at all times. During use, a NIOSH approved respirator is advised. **\*Do not mix this product with other chemicals and do not use on varnished surfaces, granite, marble, silver, brass or leather.**

**CAUTION!** Avoid contact with eyes and skin. If eye contact occurs, flush with water for at least 15 minutes. If irritation persists, seek medical attention. Do not take internally. **KEEP OUT OF REACH OF CHILDREN.**

**DISPOSAL**

The empty container can be recycled. If recycling is not available, discard in trash.

**PHYSICAL PROPERTIES**

		MOLD & MILDEW STAIN REMOVER
<b>Composition</b>		Sodium Hypochlorite, Surfactants, Water
<b>Weight</b>	<b>Per Gallon</b>	8.38 lbs.
	<b>Per Liter</b>	1.0 kg
<b>pH</b>		9-10
<b>Practical Coverage</b>		50-75 sq.ft./32 oz. bottle
<b>Shelf Life</b>		5 Years
<b>Flash Point</b>		145°F (63°C)
<b>Safety Information</b>		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.