

<b>ADDITIVE</b>	<b>TECHNICAL DATA</b>	<b>PPA-02</b>
<b>PaintPlus™</b> Paint Additive	<b>PAINT PLUS™</b> <b>SOLAR REFLECTIVE PAINT ADDITIVE</b>	

**DESCRIPTION AND USES**

Paint Plus™ Solar Reflective Paint Additive is an innovative way to turn any exterior paint into a solar reflective coating. It is ideal for use in any exterior latex or oil-based paint or primer. It can be applied to painted or bare wood, composite or vinyl siding, stucco or hardy board. For best results use with a pastel base, flat sheen exterior paints.

**PERFORMANCE CHARACTERISTICS**

- Turns exterior paint into a solar reflective barrier
- Saves up to 20% in cooling costs

**PRODUCTS**

SKU	Description
262483	10 ounce Package

**PRODUCT APPLICATION**

**SURFACE PREPARATION**

Follow paint manufacturer's directions for surface preparation.

**PRODUCT APPLICATION (cont.)**

**DIRECTIONS FOR USE**

Make sure all surfaces are clean before painting. Pour 1 gallon of paint into a clean 2 gallon container. Slowly pour the entire contents of the Solar Reflective Additive (10 oz.) into the paint while stirring. Continue stirring until an even consistency is reached. Follow the application instructions of the exterior paint manufacturer being used. Two coats are required for maximum solar reflection.

**Note:** Paint Plus Solar Reflective paint Additive may add a slight texture to the coating surface and can slightly dull the sheen on semi-gloss paints.

**CAUTION:** Keep out of reach of children and pets. Not for human consumption. If swallowed, do not induce vomiting. Call a physician. May cause eye irritation. If contact with eyes occurs, flush with water for 15 minutes. If irritation persists, seek medical attention.

**PHYSICAL PROPERTIES**

		<b>SOALR REFLECTIVE</b>
<b>Composition</b>		Crystalline Silica, Aluminum Oxide, Nepheline Syenite
<b>Weight</b>	<b>Per Gallon</b>	50.0 lbs.
	<b>Per Liter</b>	6.0 kg
<b>Solids</b>	<b>By Weight</b>	100%
<b>Volatile Organic Compounds</b>		0 g/l
<b>Practical Coverage</b>		Will depend on type of paint, method of application and surface type
<b>Shelf Life</b>		5 years
<b>Safety Information</b>		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation  
11 Hawthorn Parkway  
Vernon Hills, Illinois 60061  
An RPM Company

Phone: 877-385-8155  
www.rustoleum.com

Form: GDH-986  
Rev.: 103015